Word View

$$w = \{a\}\{a,b\}\{\}\ldots$$
, $\varphi = a \cup (\neg a \wedge b)$

- ▶ The subformulae of φ are $\{\varphi, a, \neg a \land b, \neg a, b\}$
- At each position i of w, some (sub)formulae of φ or their negation are true. Consider maximally consistent such sets wrt φ , call them B_i .
- $B_0 = \{\neg \varphi, \neg b, a, \neg(\neg a \land b)\},$
- $B_1 = \{a, b, \neg(\neg a \land b), \neg \varphi\},$
- $B_2 = \{ \neg a, \neg b, \neg (\neg a \land b), \neg \varphi \}.$
- $\psi \in B_i \text{ iff } A_i A_{i+1} A_{i+2} \ldots \models \psi.$

1/6

Consistent Sets

- \triangleright B_i is consistent wrt propositional logic subformulae:
 - $\varphi_1 \land \varphi_2 \in B_i \Leftrightarrow \varphi_1 \in B_i \land \varphi_2 \in B_i$
 - $\psi \in B_i \Leftrightarrow \neg \psi \notin B_i$
- ▶ B_i is consistent wrt until subformulae:
 - $\varphi_2 \in B_i \Rightarrow \varphi_1 \cup \varphi_2 \in B_i$
 - $\varphi_1 \cup \varphi_2 \in B_i, \varphi_2 \notin B_i \Rightarrow \varphi_1 \in B_i$
- ▶ B_i is maximal : for any subformula ψ , $\psi \in B_i \Leftrightarrow \neg \psi \notin B_i$


LTL φ to GNBA G_{φ}

- States of G_φ are sets B_i
- For a word $w = A_0 A_1 A_2 \dots$ the sequence of states $\sigma = B_0 B_1 B_2 \dots$ will be a run for w
- σ will be accepting iff $w \models \varphi$ iff $\varphi \in B_0$
- ▶ In general, a run B_iB_{i+1} ... for A_iA_{i+1} ... is accepting iff A_iA_{i+1} ... $\models \psi$ for all $\psi \in B_i$.

LTL to GNBA

- ▶ Let $\varphi = \bigcirc a$.
- ▶ Subformulae of φ : $\{a, \bigcirc a\}$. Let $A = \{a, \bigcirc a, \neg a, \neg \bigcirc a\}$.
- Possibilities at each state: a maximally consistent subset of A holds
 - ► {a, ○a}
 - {¬a, ○a}
 - ► {*a*,¬ () *a*}
 - $\blacktriangleright \{ \neg a, \neg \bigcirc a \}$
- ▶ Our initial state(s) must guarantee truth of $\bigcirc a$. Thus, initial states: $\{a, \bigcirc a\}$ and $\{\neg a, \bigcirc a\}$

LTL to GNBA



5/6

LTL to GNBA

- Claim: Runs from a state labelled set B indeed satisfy B
- No good states. All words having a run from a start state are accepted.
- ▶ Automaton for ¬ a same, except for the start states.