

CS 228 : Logic in Computer Science

Krishna. S

Moving On : Temporal Logics

- ▶ Starting Linear Temporal Logic (LTL)

Transition Systems

A **Transition System** is a tuple $(S, Act, \rightarrow, I, AP, L)$ where

- ▶ S is a set of **states**
- ▶ Act is a set of **actions**
- ▶ $s \xrightarrow{\alpha} s'$ in $S \times Act \times S$ is the **transition relation**
- ▶ $I \subseteq S$ is the **set of initial states**
- ▶ AP is the set of **atomic propositions**
- ▶ $L : S \rightarrow 2^{AP}$ is the **labeling function**

Traces of Transition Systems

- ▶ Labels of the locations represent values of all observable propositions $\in AP$
- ▶ Captures system state
- ▶ Focus on sequences $L(s_0)L(s_1)\dots$ of labels of locations
- ▶ Such sequences are called **traces**
- ▶ Assuming transition systems have no terminal states,
 - ▶ Traces are infinite words over 2^{AP}
 - ▶ Traces $\in (2^{AP})^\omega$

Traces of Transition Systems

Given a transition system $TS = (S, Act, \rightarrow, I, AP, L)$ without terminal states,

- ▶ All maximal executions/paths are infinite

Traces of Transition Systems

Given a transition system $TS = (S, Act, \rightarrow, I, AP, L)$ without terminal states,

- ▶ All maximal executions/paths are infinite
- ▶ Path $\pi = s_0 s_1 s_2 \dots$, $trace(\pi) = L(s_0)L(s_1)\dots$

Traces of Transition Systems

Given a transition system $TS = (S, Act, \rightarrow, I, AP, L)$ without terminal states,

- ▶ All maximal executions/paths are infinite
- ▶ Path $\pi = s_0 s_1 s_2 \dots$, $trace(\pi) = L(s_0)L(s_1)\dots$
- ▶ For a set Π of paths, $Trace(\Pi) = \{trace(\pi) \mid \pi \in \Pi\}$

Traces of Transition Systems

Given a transition system $TS = (S, Act, \rightarrow, I, AP, L)$ without terminal states,


- ▶ All maximal executions/paths are infinite
- ▶ Path $\pi = s_0 s_1 s_2 \dots$, $trace(\pi) = L(s_0)L(s_1)\dots$
- ▶ For a set Π of paths, $Trace(\Pi) = \{trace(\pi) \mid \pi \in \Pi\}$
- ▶ For a location s , $Traces(s) = Trace(Paths(s))$

Traces of Transition Systems


Given a transition system $TS = (S, Act, \rightarrow, I, AP, L)$ without terminal states,

- ▶ All maximal executions/paths are infinite
- ▶ Path $\pi = s_0 s_1 s_2 \dots$, $trace(\pi) = L(s_0)L(s_1)\dots$
- ▶ For a set Π of paths, $Trace(\Pi) = \{trace(\pi) \mid \pi \in \Pi\}$
- ▶ For a location s , $Traces(s) = Trace(Paths(s))$
- ▶ $Traces(TS) = \bigcup_{s \in I} Traces(s)$

Example Traces




Example Traces



$AP = \{p, q, r, t\}$

► $\{p, q\} \emptyset \{q, r\}^\omega$


Example Traces



$AP = \{p, q, r, t\}$

- ▶ $\{p, q\} \emptyset \{q, r\}^\omega$
- ▶ $(\{p, q\} \emptyset \{r\})^\omega$

Example Traces



$AP = \{p, q, r, t\}$

- ▶ $\{p, q\} \emptyset \{q, r\}^\omega$
- ▶ $(\{p, q\} \emptyset \{r\})^\omega$
- ▶ $(\{p, q\} \emptyset \{r\})^* \{p, q\} \emptyset \{q, r\}^\omega$


Linear Time Properties

- ▶ Linear-time properties specify traces that a TS must have
- ▶ A LT property P over AP is a subset of $(2^{AP})^\omega$
- ▶ TS over AP satisfies a LT property P over AP


$$TS \models P \text{ iff } \text{Traces}(TS) \subseteq P$$

- ▶ $s \in S$ satisfies LT property P (denoted $s \models P$) iff $\text{Traces}(s) \subseteq P$

Specifying Traces




Specifying Traces




- Whenever p is true, r will eventually become true

Specifying Traces




- ▶ Whenever p is true, r will eventually become true
 - ▶ $\{A_0A_1A_2\cdots \mid \forall i \geq 0, p \in A_i \rightarrow \exists j \geq i, r \in A_j\}$

Specifying Traces




- ▶ Whenever p is true, r will eventually become true
 - ▶ $\{A_0A_1A_2\cdots \mid \forall i \geq 0, p \in A_i \rightarrow \exists j \geq i, r \in A_j\}$
- ▶ q is true infinitely often

Specifying Traces




- ▶ Whenever p is true, r will eventually become true
 - ▶ $\{A_0 A_1 A_2 \dots \mid \forall i \geq 0, p \in A_i \rightarrow \exists j \geq i, r \in A_j\}$
- ▶ q is true infinitely often
 - ▶ $\{A_0 A_1 A_2 \dots \mid \forall i \geq 0, \exists j \geq i, q \in A_j\}$

Specifying Traces



- ▶ Whenever p is true, r will eventually become true
 - ▶ $\{A_0A_1A_2\cdots \mid \forall i \geq 0, p \in A_i \rightarrow \exists j \geq i, r \in A_j\}$
- ▶ q is true infinitely often
 - ▶ $\{A_0A_1A_2\cdots \mid \forall i \geq 0, \exists j \geq i, q \in A_j\}$
- ▶ Whenever r is true, so is q

Specifying Traces



- ▶ Whenever p is true, r will eventually become true
 - ▶ $\{A_0A_1A_2\cdots \mid \forall i \geq 0, p \in A_i \rightarrow \exists j \geq i, r \in A_j\}$
- ▶ q is true infinitely often
 - ▶ $\{A_0A_1A_2\cdots \mid \forall i \geq 0, \exists j \geq i, q \in A_j\}$
- ▶ Whenever r is true, so is q
 - ▶ $\{A_0A_1\cdots \mid \forall i \geq 0, r \in A_i \rightarrow q \in A_i\}$

Syntax of Linear Temporal Logic

Given AP , a set of propositions,

Syntax of Linear Temporal Logic

Given AP , a set of propositions,

- ▶ Propositional logic formulae over AP
 - ▶ $a \in AP$ (atomic propositions)
 - ▶ $\neg\varphi, \varphi \wedge \psi, \varphi \vee \psi$

Syntax of Linear Temporal Logic


Given AP , a set of propositions,

- ▶ Propositional logic formulae over AP
 - ▶ $a \in AP$ (atomic propositions)
 - ▶ $\neg\varphi, \varphi \wedge \psi, \varphi \vee \psi$
- ▶ Temporal Operators
 - ▶ $\bigcirc\varphi$ (Next φ)
 - ▶ $\varphi \mathbf{U}\psi$ (φ holds until a ψ -state is reached)
- ▶ LTL : Logic for describing LT properties

Semantics

LTL formulae over AP interpreted over words over Σ^ω , $\Sigma = 2^{AP}$



This is not an automaton, but a word over Σ



Semantics

LTL formulae over AP interpreted over words over Σ^ω , $\Sigma = 2^{AP}$




This is not an automaton, but a word over Σ



Semantics

LTL formulae over AP interpreted over words over Σ^ω , $\Sigma = 2^{AP}$





This is not an automaton, but a word over Σ



Semantics

LTL formulae over AP interpreted over words over Σ^ω , $\Sigma = 2^{AP}$






This is not an automaton, but a word over Σ



Semantics

LTL formulae over AP interpreted over words over Σ^ω , $\Sigma = 2^{AP}$

This is not an automaton, but a word over Σ



Derived Operators

- ▶ $true = \varphi \vee \neg\varphi$
- ▶ $false = \neg true$
- ▶ $\diamond\varphi = true \text{ U } \varphi$ (Eventually φ)
- ▶ $\Box\varphi = \neg\diamond\neg\varphi$ (Forever φ)

Precedence

- ▶ Unary Operators bind stronger than Binary
- ▶ \bigcirc and \neg equally strong
- ▶ U takes precedence over $\wedge, \vee, \rightarrow$
 - ▶ $a \vee b \text{ U } c \equiv a \vee (b \text{ U } c)$
 - ▶ $\bigcirc a \text{ U } \neg b \equiv (\bigcirc a) \text{ U } (\neg b)$