

Skeptik [System Description]

Joseph Boudou¹ *, Andreas Fellner^{2,3} **, and Bruno Woltzenlogel Paleo³ ***

¹ IRIT, Université de Toulouse, France
`joseph.boudou@irit.fr`

² Free University of Bolzano, Italy
`fellner.a@gmail.com`

³ Vienna University of Technology, Austria
`bruno@logic.at`

Abstract. This paper introduces **Skeptik**: a system for checking, compressing and improving proofs obtained by automated reasoning tools.

1 Introduction

There are various reasons why it is desirable that automated reasoning tools output not only a *yes* or *no* answer to a problem but also *proofs/refutations* or *(counter)models*.

Firstly, state-of-the-art tools are complex and often heavily optimized. Their code is hard to understand and difficult to automatically verify. Therefore, it is reasonable to distrust their answers. But if proofs or (counter)models are produced, they can serve as independently checkable certificates of correctness for the provided answers.

Secondly, for most applications, a *yes/no* is inherently insufficient. We often already know in advance whether a problem is expected to be satisfiable or unsatisfiable, and we want more than just a confirmation of this expectation. For satisfiable formulas, the desired information is encoded in the model; for valid formulas, it is contained in the proof. In case the expectation was wrong, refutations and countermodels can be very helpful to explain issues in the encoding of the problem, in order to correct and refine it.

Proofs and refutations can be used, for example, to extract unsatisfiable cores [?], interpolants [?], Herbrand disjunctions [?], linguistic implicatures [?]
...

Although current automated deduction tools are very efficient at finding proofs, they do not necessarily find the best proofs. **Skeptik**¹ aims precisely at efficiently analyzing proofs, in order to compress and improve them by eliminating their redundancies.

* Supported by the Google Summer of Code 2012 program.

** Supported by the Google Summer of Code 2013 program.

*** Supported by the Austrian Science Fund, project P24300.

¹ <http://github.com/Paradoxika/Skeptik/>

Related Work: CERes² [?] is another proof transformation system, specialized in cut-elimination for classical first-order sequent calculus. It was replaced by GAPT³ [?], extended with cut-introduction techniques [?]. MINLOG⁴ [?] extracts functional programs from proofs, employing a refined A-translation for functional proofs.

2 Installation

Skeptik is implemented in Scala and runs on the java virtual machine (JVM). Therefore, Java⁵ must be installed. The easiest way to download Skeptik is via git⁶, by executing `git clone git@github.com:Paradoxika/Skeptik.git` in the folder where Skeptik should be downloaded. It is helpful to install SBT⁷, a build tool that automatically downloads all compilers and libraries on which Skeptik depends. To compile, build and package Skeptik, run `sbt one-jar` in Skeptik's home folder. This generates a jar file that can be executed like any other Java jar file.

SBT and Scala programs may need a lot of memory for compilation and execution. If out-of-memory problems occur, the JVM's maximum available memory can be increased by executing `export JAVA_TOOL_OPTIONS='-Xmx1024m'` in the terminal.

3 Usage

The command `java -jar skeptik.jar --help` displays a help message explaining how to use Skeptik. For example, to compress the proof “eq_diamond9.smt2” using the algorithm RPI and write the compressed proof using the ‘smt2’ proof format, the following command should be executed: `java -jar skeptik.jar -a RPI -f smt2 examples/proofs/VeriT/eq_diamond9.smt2`.

Skeptik can be called with an arbitrary number of algorithms and proofs. The following command would compress the proofs “p1.smt2” and “p2.smt2” with two algorithms each (RP and a sequential composition of DAGify, RPI and LU): `java -jar skeptik.jar -a RP -a (DAGify*RPI*LU) p1.smt2 p2.smt2`

4 Supported Proof Formats

ToDo: RUP

² <http://www.logic.at/ceres>

³ <http://code.google.com/p/gapt/>

⁴ <http://www.mathematik.uni-muenchen.de/logik/minlog/>

⁵ <https://www.java.com/>

⁶ <http://git-scm.com/>

⁷ <http://www.scala-sbt.org/>

4.1 TraceCheck Format

ToDo (Andreas)

4.2 The SMT-Lib Proof Format

veriT

ToDo (Bruno)

4.3 Skeptik's own Proof Format

ToDo (Joseph)

5 Available Proof Compression Algorithms

5.1 RecyclePivots and RecyclePivotsWithIntersection

In [9], Tseitin outlines a first kind of proof redundancy with the concept of *irregular proof*. A proof is irregular if some pivot is resolved more than once on some path from the root to a leaf. But Goerdt [7] proved that the corresponding regular proof of an irregular proof may be exponentially bigger than the original. Therefore, only *partial* regularisation algorithm can compress a proof.

RecyclePivots (RP) [1,2] and **RecyclePivotsWithIntersection** (RPI) [5] are such partial regularisation algorithms. They both compute for each node a set of *safe literals* and then delete a premise iff its auxiliary literal is safe. The set of safe literals is constructed recursively from the root of the proof by adding the dual of the auxiliary literal. The two algorithms only differs for nodes which are premises of more than one resolution. In that case, RP resets the safe literals to the empty set whereas RPI computes the intersection of the safe literals corresponding to each incoming edge.

5.2 LowerUnits

Another kind of proof redundancy happens when a node η appears as premise of many resolutions on the same pivot p . In that case, it would be better to resolve η on p only once. The **LowerUnits** (LU) algorithm [5] reduces this kind of redundancy by lowering *units* down to the root of the proof. Units are subproofs whose conclusion consists in a single literal. Such a subproof can always be lowered down the proof.

LowerUnits is of linear time complexity in the length of the proof. It is a very fast algorithm which perform good compression ratio.

5.3 LowerUnivalents

The **LowerUnivalents** algorithm [3] (**LUniv**) generalizes **LowerUnits** by exploiting the information of the already lowered subproofs and their pivots. Then, it becomes possible to lower a non-unit node if all its conclusion's literals but one can be deleted by the already lowered subproofs. Moreover, the lowered pivots are safe literals and thus some partial regularization can be achieved simultaneously.

In **Skeptik**, **LUniv** has been implemented as a replacement for the **fixProof** function used by some algorithms to reconstruct a proof after deletions. Therefore, non-sequential combinations of those algorithms with **LUniv** are easy to implement. For instance, **LUnivRPI** is a non-sequential combination of **LUniv** after **RPI**. This latter algorithm is currently one the best trade-off between compression time and compression ratio [3].

5.4 RPI[3]LU and RPI[3]LUniv

RPI[3]LU and **RPI[3]LUniv** are non-sequential combinations of **RPI** after **LU** and **LUniv**. They consist in three traversals. The first traversal collects subproofs to be lowered down the proof. The second traversal computes the sets of safe literals for each node, taking into account the subproofs marked for being lowered. The last traversal actually compress the proof by removing redundant branches and lowering subproofs.

These algorithm are optimizations of the corresponding sequential compositions, achieving the same compression ratio in less time.

5.5 ReduceAndReconstruct

The **ReduceAndReconstruct** (**RedRec**) approach consists in applying local transformation rules to each node. The set of local rules presented in [8] are sufficient to emulate any other compression algorithm. Unfortunately, the proposed heuristic only consists in trying to apply each rule (with given priorities) to each node in a top-down traversal. For this heuristic to be efficient, the process has to be repeated many times. The resulting algorithm can achieve very good compression ratio if run long enough.

As this algorithm allows experimentations in the local transformation rules, the heuristic to apply them and the termination conditions, its implementation in **Skeptik** is very modular. Each component is defined independently and a convenient framework allows to combine them as desired. A handful of alternative local transformation rules and termination conditions have been implemented too.

5.6 Split

The **Split** [4] algorithm is a technique to lower pivot variables in a proof. From a proof with conclusion C , two proofs with conclusion $v \vee C$ and $\neg v \vee C$

are constructed, where the variable v is chosen heuristically.

In a first step the positive/negative premises of resolvents with pivot v are removed from the proof. Afterwards the proof is fixed, by traversing it top-down and fixing each proof node. A proof node is fixed by either replacing it by one of or resolving the fixed premises.

The roots of the resulting proofs are resolved, using v as pivot, to obtain a new proof of C .

The time-complexity of this algorithm is linear in the proof length and it suits very well for repeated application. This can be done iteratively or recursively. Also multiple variables can be chosen in advance. All these variants are implemented into Skeptik.

5.7 TautologyElimination

5.8 StructuralHashing

5.9 DAGification

5.10 Subsumption

Subsumption based algorithms use, as the name implies, the subsumption relation on clauses for compressing a proof. A clause C_1 subsumes a clause C_2 *iff* every literal occurring in C_1 also occurs in C_2 . The general goal is to replace a clause C by another clause D , used elsewhere in the proof, that are such that C subsumes D . There are three subsumption based compression algorithms implemented into Skeptik.

Top-down Subsumption searches for subsumed clauses among all clauses visited earlier in a top-down traversal. The time-complexity of this algorithm is worst case quadratic in the number of proof nodes.

Bottom-up Subsumption searches for subsumed clauses among all clauses visited earlier in a bottom-up traversal. A subsumed clause D can only replace a clause C , if D is not an ancestor of C in the graph representing the proof. Bottom-up Subsumption has the same time-complexity as Top-down Subsumption, but the additional ancestor-check makes it slower in practise.

RecycleUnits [2] is a special case of Bottom-up Subsumption that only searches for subsumed clauses that are unit (i.e. contain only one literal). This algorithm has a worst case time-complexity that is quadratic in the number of unit clauses.

5.11 Pebbling

Pebbling algorithms compress proofs in the **space measure**, as opposed to the usual length compression. The space measure of a proof indicates how many proof nodes maximally have to be kept in memory, while reading the proof, simultaneously.

This measure is closely related to the **Black Pebbling Game** [6], which lends its name to the algorithms described here. A strategy for this game directly corresponds to a topological node ordering, i.e. an ordering of nodes such that

every premise of each node is lower than the node itself, combined with deletion information, i.e. extra lines in the proof output indicating that a node can be deleted from memory. An optimal strategy for the Black Pebbling Game would therefore result in optimal space compression of the proof. However, as shown in [6], finding the optimal solution is PSPACE-complete and therefore not a feasible approach for this program.

To obtain algorithms that have an acceptable runtime greedy heuristics for finding a good node ordering are used.

Top-down pebbling directly corresponds to playing the game with limited information on how the proof looks. At every point there are nodes which can be pebbled (initially these are only the axioms). Using information from these nodes and their children nodes, it is decided which node to pebble next, which can make other nodes pebbleable. This is done until the root node is pebbled. Unfortunately the lack of knowledge about the structure of the proof often results in bad space compression.

Bottom-up pebbling constructs a node ordering by visiting proof nodes and their premises recursively, starting from the root node. At every node it is chosen heuristically in what order its premises are visited. After all premises are visited, the node is added to the order.

6 Implementation Details

ToDo: statistics about the code

6.1 Organization of the Code

ToDo: brief description of the package structure

6.2 Data Structures for Formulas

6.3 Data Structures for Proofs

immutable

7 Conclusions and Future Work

ToDo: limitation: memory consumption in Scala underlying symbols are strings

New proof formats on demand

extension to first-order

contextual natural deduction

cut-introduction

References

1. Bar-Ilan, O., Fuhrmann, O., Hoory, S., Shacham, O., Strichman, O.: Linear-time reductions of resolution proofs. In: Chockler, H., Hu, A.J. (eds.) Haifa Verification Conference. Lecture Notes in Computer Science, vol. 5394, pp. 114–128. Springer (2008)
2. Bar-Ilan, O., Fuhrmann, O., Hoory, S., Shacham, O., Strichman, O.: Reducing the size of resolution proofs in linear time. *STTT* 13(3), 263–272 (2011)
3. Boudou, J., Paleo, B.W.: Compression of propositional resolution proofs by lowering subproofs. In: Galmiche, D., Larchey-Wendling, D. (eds.) *TABLEAUX*. Lecture Notes in Computer Science, vol. 8123, pp. 59–73. Springer (2013)
4. Cotton, S.: Two techniques for minimizing resolution proofs. In: Strichman, O., Szeider, S. (eds.) *Theory and Applications of Satisfiability Testing SAT 2010*, Lecture Notes in Computer Science, vol. 6175, pp. 306–312. Springer (2010)
5. Fontaine, P., Merz, S., Woltzenlogel Paleo, B.: Compression of propositional resolution proofs via partial regularization. In: Bjørner, N., Sofronie-Stokkermans, V. (eds.) *CADE*. Lecture Notes in Computer Science, vol. 6803, pp. 237–251. Springer (2011)
6. Gilbert, J.R., Lengauer, T., Tarjan, R.E.: The pebbling problem is complete in polynomial space. *SIAM Journal on Computing* 9(3), 513–524 (1980)
7. Goerdt, A.: Comparing the complexity of regular and unrestricted resolution. In: Marburger, H. (ed.) *GWAI. Informatik-Fachberichte*, vol. 251, pp. 181–185. Springer (1990)
8. Rollini, S.F., Bruttomesso, R., Sharygina, N.: An efficient and flexible approach to resolution proof reduction. In: Barner, S., Harris, I., Kroening, D., Raz, O. (eds.) *Hardware and Software: Verification and Testing*, Lecture Notes in Computer Science, vol. 6504, pp. 182–196. Springer (2011)
9. Tseitin, G.S.: On the complexity of derivation in propositional calculus. In: Siekmann, J., Wrightson, G. (eds.) *Automation of Reasoning: Classical Papers in Computational Logic 1967-1970*, vol. 2. Springer-Verlag (1983)