

Selector	Example
*	<code>\$("*")</code>
#id	<code>\$("#lastname")</code>
.class	<code>\$(".intro")</code>
.class,.class	<code>\$(".intro,.demo")</code>
element	<code>\$("p")</code>
el1,el2,el3	<code>\$("h1,div,p")</code>
:first	<code>\$("p:first")</code>
:last	<code>\$("p:last")</code>
:even	<code>\$("tr:even")</code>
:odd	<code>\$("tr:odd")</code>
:first-child	<code>\$("p:first-child")</code>
:first-of-type	<code>\$("p:first-of-type")</code>
:last-child	<code>\$("p:last-child")</code>
:last-of-type	<code>\$("p:last-of-type")</code>
:nth-child(n)	<code>\$("p:nth-child(2)")</code>
:nth-last-child(n)	<code>\$("p:nth-last-child(2)")</code>
:nth-of-type(n)	<code>\$("p:nth-of-type(2)")</code>
:nth-last-of-type(n)	<code>\$("p:nth-last-of-type(2)")</code>
:only-child	<code>\$("p:only-child")</code>
:only-of-type	<code>\$("p:only-of-type")</code>
parent > child	<code>\$("div > p")</code>
parent descendant	<code>\$("div p")</code>
element + next	<code>\$("div + p")</code>
element ~ siblings	<code>\$("div ~ p")</code>
:eq(index)	<code>\$("ul li:eq(3)")</code>
:gt(no)	<code>\$("ul li:gt(3)")</code>
:lt(no)	<code>\$("ul li:lt(3)")</code>
:not(selector)	<code>\$("input:not(:empty)")</code>
:header	<code>\$(":header")</code>
:animated	<code>\$(":animated")</code>
:focus	<code>\$(":focus")</code>
:contains(text)	<code>\$(":contains('Hello'))"</code>
:has(selector)	<code>\$("div:has(p)")</code>
:empty	<code>\$(":empty")</code>
:parent	<code>\$(":parent")</code>
:hidden	<code>\$("p:hidden")</code>
:visible	<code>\$("table:visible")</code>
:root	<code>\$(":root")</code>
:lang(language)	<code>\$("p:lang(de)")</code>
[attribute]	<code>\$("[href]")</code>

[attribute=value]	<code>\$("[href='default.htm']")</code>
[attribute!=value]	<code>\$("[href!='default.htm']")</code>
[attribute\$=value]	<code>\$("[href\$='.jpg']")</code>
[attribute =value]	<code>\$("[title ='Tomorrow']")</code>
[attribute^=value]	<code>\$("[title^='Tom']")</code>
[attribute~=value]	<code>\$("[title~='hello']")</code>
[attribute*=value]	<code>\$("[title*='hello']")</code>
:input	<code>\$(":input")</code>
:text	<code>\$(":text")</code>
:password	<code>\$(":password")</code>
:radio	<code>\$(":radio")</code>
:checkbox	<code>\$(":checkbox")</code>
:submit	<code>\$(":submit")</code>
:reset	<code>\$(":reset")</code>
:button	<code>\$(":button")</code>
:image	<code>\$(":image")</code>
:file	<code>\$(":file")</code>
:enabled	<code>\$(":enabled")</code>
:disabled	<code>\$(":disabled")</code>
:selected	<code>\$(":selected")</code>
:checked	<code>\$(":checked")</code>

Selects

All elements

The element with id="lastname"

All elements with class="intro"

All elements with the class "intro" or "demo"

All <p> elements

All <h1>, <div> and <p> elements

The first <p> element

The last <p> element

All even <tr> elements

All odd <tr> elements

All <p> elements that are the first child of their parent

All <p> elements that are the first <p> element of their parent

All <p> elements that are the last child of their parent

All <p> elements that are the last <p> element of their parent

All <p> elements that are the 2nd child of their parent

All <p> elements that are the 2nd child of their parent, counting from the last child

All <p> elements that are the 2nd <p> element of their parent

All <p> elements that are the 2nd <p> element of their parent, counting from the last child

All <p> elements that are the only child of their parent

All <p> elements that are the only child, of its type, of their parent

All <p> elements that are a direct child of a <div> element

All <p> elements that are descendants of a <div> element

The <p> element that are next to each <div> elements

All <p> elements that appear after the <div> element

The fourth element in a list (index starts at 0)

List elements with an index greater than 3

List elements with an index less than 3

All input elements that are not empty

All header elements <h1>, <h2> ...

All animated elements

The element that currently has focus

All elements which contains the text "Hello"

All <div> elements that have a <p> element

All elements that are empty

All elements that are a parent of another element

All hidden <p> elements

All visible tables

The document's root element

All <p> elements with a lang attribute value starting with "de"

All elements with a href attribute

All elements with a href attribute value equal to "default.htm"
All elements with a href attribute value not equal to "default.htm"
All elements with a href attribute value ending with ".jpg"
All elements with a title attribute value equal to 'Tomorrow', or starting with 'Tomorrow' followed by a hyphen
All elements with a title attribute value starting with "Tom"
All elements with a title attribute value containing the specific word "hello"
All elements with a title attribute value containing the word "hello"

All input elements
All input elements with type="text"
All input elements with type="password"
All input elements with type="radio"
All input elements with type="checkbox"
All input elements with type="submit"
All input elements with type="reset"
All input elements with type="button"
All input elements with type="image"
All input elements with type="file"
All enabled input elements
All disabled input elements
All selected input elements
All checked input elements