

EXPERIMENTS

```
mysql>
mysql> CREATE TABLE numbers (
  ->   num INT
  -> );
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE case_example(IN n INT)
  -> BEGIN
  ->   CASE
  ->     WHEN n = 1 THEN
  ->       SELECT 'One' AS Result;
  ->     WHEN n = 2 THEN
  ->       SELECT 'Two' AS Result;
  ->     WHEN n = 3 THEN
  ->       SELECT 'Three' AS Result;
  ->     ELSE
  ->       SELECT 'Other Number' AS Result;
  ->   END CASE;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL case_example(2);
+-----+
| Result |
+-----+
| Two    |
+-----+
1 row in set (0.00 sec)

Query OK, 0 rows affected (0.00 sec)

mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE loop_example()
  -> BEGIN
  ->   DECLARE i INT DEFAULT 1;
  ->
  ->   my_loop: LOOP
  ->     INSERT INTO numbers VALUES (i);
  ->     SET i = i + 1;
  ->
  ->     IF i > 5 THEN
  ->       LEAVE my_loop;
  ->     END IF;
  ->   END LOOP my_loop;
  -> END //
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL loop_example();
Query OK, 1 row affected (0.02 sec)
```

```
mysql>
mysql> SELECT * FROM numbers;
```

num
1
2
3
4
5

```
5 rows in set (0.00 sec)
```

```
mysql> |
```