

EXPERIMENTS

```
mysql> CREATE TABLE student (  
-> student_id INT,  
-> student_name VARCHAR(50),  
-> department VARCHAR(30),  
-> marks INT  
-> );  
Query OK, 0 rows affected (0.05 sec)  
  
mysql>  
mysql> INSERT INTO student VALUES  
-> (101, 'Arun', 'CSE', 85),  
-> (102, 'Karthik', 'ECE', 78),  
-> (103, 'Rahul', 'CSE', 92),  
-> (104, 'Vijay', 'IT', 88),  
-> (105, 'Ajay', 'CSE', 76);  
Query OK, 5 rows affected (0.01 sec)  
Records: 5 Duplicates: 0 Warnings: 0  
  
mysql>  
mysql> DELIMITER //  
mysql>  
mysql> CREATE PROCEDURE display_students()  
-> BEGIN  
-> SELECT * FROM student;  
-> END //  
Query OK, 0 rows affected (0.01 sec)  
  
mysql>  
mysql> DELIMITER ;  
mysql>  
mysql> CALL display_students();  
+-----+-----+-----+-----+  
| student_id | student_name | department | marks |  
+-----+-----+-----+-----+  
| 101 | Arun | CSE | 85 |  
| 102 | Karthik | ECE | 78 |  
| 103 | Rahul | CSE | 92 |  
| 104 | Vijay | IT | 88 |  
| 105 | Ajay | CSE | 76 |  
+-----+-----+-----+-----+  
5 rows in set (0.00 sec)  
  
Query OK, 0 rows affected (0.02 sec)  
  
mysql>  
mysql> DELIMITER //  
mysql>  
mysql> CREATE PROCEDURE get_student(IN sid INT)  
-> BEGIN  
-> SELECT *  
-> FROM student  
-> WHERE student_id = sid;  
-> END //  
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE get_department(IN dept VARCHAR(30))
-> BEGIN
->     SELECT *
->     FROM student
->     WHERE department = dept;
-> END //
```

Query OK, 0 rows affected (0.01 sec)

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL get_department('CSE');
```

student_id	student_name	department	marks
101	Arun	CSE	85
103	Rahul	CSE	92
105	Ajay	CSE	76

3 rows in set (0.00 sec)

Query OK, 0 rows affected (0.01 sec)

```
mysql> |
```