

EXPERIMENTS

```
mysql>
mysql> CREATE TABLE numbers (
  ->   num INT
  -> );
Query OK, 0 rows affected (0.05 sec)

mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE while_example()
  -> BEGIN
  ->   DECLARE i INT DEFAULT 1;
  ->
  ->   WHILE i <= 5 DO
  ->     INSERT INTO numbers VALUES (i);
  ->     SET i = i + 1;
  ->   END WHILE;
  -> END //
Query OK, 0 rows affected (0.03 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL while_example();
Query OK, 1 row affected (0.04 sec)

mysql>
mysql> SELECT * FROM numbers;
+-----+
| num |
+-----+
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
+-----+
5 rows in set (0.00 sec)

mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE repeat_example()
  -> BEGIN
  ->   DECLARE i INT DEFAULT 6;
  ->
  ->   REPEAT
  ->     INSERT INTO numbers VALUES (i);
  ->     SET i = i + 1;
  ->   UNTIL i > 10
  ->   END REPEAT;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
```

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL repeat_example();
Query OK, 1 row affected (0.02 sec)
```

```
mysql>
mysql> SELECT * FROM numbers;
```

num
1
2
3
4
5
6
7
8
9
10

```
10 rows in set (0.00 sec)
```