

EXPERIMENTS

```
mysql> CREATE TABLE student (  
-> student_id INT,  
-> student_name VARCHAR(50),  
-> department VARCHAR(30),  
-> marks INT  
-> );  
Query OK, 0 rows affected (0.06 sec)  
  
mysql>  
mysql> INSERT INTO student VALUES  
-> (101, 'Arun', 'CSE', 85),  
-> (102, 'Karthik', 'ECE', 78),  
-> (103, 'Rahul', 'CSE', 92),  
-> (104, 'Vijay', 'IT', 88),  
-> (105, 'Ajay', 'CSE', 76),  
-> (106, 'Suresh', 'ECE', 82);  
Query OK, 6 rows affected (0.01 sec)  
Records: 6 Duplicates: 0 Warnings: 0  
  
mysql>  
mysql> SELECT *  
-> FROM student  
-> WHERE marks > (  
-> SELECT AVG(marks)  
-> FROM student  
-> );  
  
+-----+-----+-----+-----+  
| student_id | student_name | department | marks |  
+-----+-----+-----+-----+  
| 101 | Arun | CSE | 85 |  
| 103 | Rahul | CSE | 92 |  
| 104 | Vijay | IT | 88 |  
+-----+-----+-----+-----+  
3 rows in set (0.01 sec)
```

```
mysql>
mysql> SELECT *
-> FROM student
-> WHERE marks = (
->     SELECT MAX(marks)
->     FROM student
-> );
```

student_id	student_name	department	marks
103	Rahul	CSE	92

1 row in set (0.00 sec)

```
mysql>
mysql> SELECT *
-> FROM student
-> WHERE department IN (
->     SELECT department
->     FROM student
->     GROUP BY department
->     HAVING COUNT(*) > 1
-> );
```

student_id	student_name	department	marks
101	Arun	CSE	85
102	Karthik	ECE	78
103	Rahul	CSE	92
105	Ajay	CSE	76
106	Suresh	ECE	82

5 rows in set (0.00 sec)

```
mysql>
mysql> SELECT s1.*
-> FROM student s1
-> WHERE s1.marks > (
->     SELECT AVG(s2.marks)
->     FROM student s2
->     WHERE s2.department = s1.department
-> );
```

student_id	student_name	department	marks
101	Arun	CSE	85
103	Rahul	CSE	92
106	Suresh	ECE	82

3 rows in set (0.02 sec)