

EXPERIMENTS

```
mysql> CREATE DATABASE college_exp17;
Query OK, 1 row affected (0.03 sec)

mysql> USE college_exp17;
Database changed
mysql>
mysql> DELIMITER //
mysql> CREATE FUNCTION get_grade(mark INT)
  -> RETURNS VARCHAR(10)
  -> DETERMINISTIC
  -> BEGIN
  ->   DECLARE grade VARCHAR(10);
  ->
  ->   IF mark >= 90 THEN
  ->     SET grade = 'A+';
  ->   ELSEIF mark >= 80 THEN
  ->     SET grade = 'A';
  ->   ELSEIF mark >= 70 THEN
  ->     SET grade = 'B';
  ->   ELSEIF mark >= 60 THEN
  ->     SET grade = 'C';
  ->   ELSE
  ->     SET grade = 'D';
  ->   END IF;
  ->   RETURN grade;
  -> END //
Query OK, 0 rows affected (0.01 sec)

mysql>
mysql> DELIMITER ;
mysql>
mysql> SELECT get_grade(95);
+-----+
| get_grade(95) |
+-----+
| A+            |
+-----+
1 row in set (0.01 sec)

mysql> SELECT get_grade(85);
+-----+
| get_grade(85) |
+-----+
| A             |
+-----+
1 row in set (0.00 sec)
```

```
mysql> SELECT get_grade(72);
+-----+
| get_grade(72) |
+-----+
| B             |
+-----+
1 row in set (0.00 sec)

mysql>
mysql> CREATE TABLE student (
  ->     student_id INT,
  ->     student_name VARCHAR(50),
  ->     marks INT
  -> );
Query OK, 0 rows affected (0.04 sec)

mysql>
mysql> INSERT INTO student VALUES
  -> (101, 'Arun', 95),
  -> (102, 'Karthik', 85),
  -> (103, 'Rahul', 72),
  -> (104, 'Vijay', 65),
  -> (105, 'Ajay', 55);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql>
mysql> SELECT student_id,
  ->     student_name,
  ->     marks,
  ->     get_grade(marks) AS grade
  -> FROM student;
+-----+-----+-----+-----+
| student_id | student_name | marks | grade |
+-----+-----+-----+-----+
| 101 | Arun | 95 | A+ |
| 102 | Karthik | 85 | A |
| 103 | Rahul | 72 | B |
| 104 | Vijay | 65 | C |
| 105 | Ajay | 55 | D |
+-----+-----+-----+-----+
5 rows in set (0.00 sec)
```