

EXPERIMENTS

```
mysql> USE college_exp18;
Database changed
mysql>
mysql> CREATE TABLE student (
->     student_id INT,
->     student_name VARCHAR(50),
->     marks INT
-> );
Query OK, 0 rows affected (0.05 sec)

mysql>
mysql> INSERT INTO student VALUES
-> (101, 'Arun', 85),
-> (102, 'Karthik', 78),
-> (103, 'Rahul', 92),
-> (104, 'Vijay', 88),
-> (105, 'Ajay', 76);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0

mysql>
mysql> DELIMITER //
mysql>
mysql> CREATE PROCEDURE cursor_example()
-> BEGIN
->     DECLARE done INT DEFAULT 0;
->     DECLARE sname VARCHAR(50);
->     DECLARE smarks INT;
->
->     DECLARE student_cursor CURSOR FOR
->         SELECT student_name, marks FROM student;
->
->     DECLARE CONTINUE HANDLER FOR NOT FOUND SET done = 1;
->
->     OPEN student_cursor;
->
->     read_loop: LOOP
->         FETCH student_cursor INTO sname, smarks;
->
->         IF done = 1 THEN
->             LEAVE read_loop;
->         END IF;
->
->         SELECT sname AS Student_Name, smarks AS Marks;
->
->     END LOOP;
->
->     CLOSE student_cursor;
-> END //
Query OK, 0 rows affected (0.01 sec)
```

```
mysql>
mysql> DELIMITER ;
mysql>
mysql> CALL cursor_example();
+-----+-----+
| Student_Name | Marks |
+-----+-----+
| Arun         | 85    |
+-----+-----+
1 row in set (0.02 sec)

+-----+-----+
| Student_Name | Marks |
+-----+-----+
| Karthik      | 78    |
+-----+-----+
1 row in set (0.02 sec)

+-----+-----+
| Student_Name | Marks |
+-----+-----+
| Rahul       | 92    |
+-----+-----+
1 row in set (0.02 sec)

+-----+-----+
| Student_Name | Marks |
+-----+-----+
| Vijay       | 88    |
+-----+-----+
1 row in set (0.02 sec)

+-----+-----+
| Student_Name | Marks |
+-----+-----+
| Ajay        | 76    |
+-----+-----+
1 row in set (0.03 sec)

Query OK, 0 rows affected (0.03 sec)
```