

EXP-05

```
mysql> USE college_exp8;
Database changed
mysql>
mysql> CREATE TABLE student (
    ->     student_id INT,
    ->     student_name VARCHAR(50),
    ->     department VARCHAR(30),
    ->     marks INT
    -> );
Query OK, 0 rows affected (0.05 sec)
```

```
mysql>
mysql> INSERT INTO student VALUES
    -> (101, 'Arun', 'CSE', 85),
    -> (102, 'Karthik', 'ECE', 78),
    -> (103, 'Rahul', 'CSE', 92),
    -> (104, 'Vijay', 'IT', 88),
    -> (105, 'Ajay', 'CSE', 76);
Query OK, 5 rows affected (0.01 sec)
Records: 5  Duplicates: 0  Warnings: 0
```

```
mysql>
mysql> SELECT * FROM student
    -> WHERE marks BETWEEN 80 AND 90;
```

student_id	student_name	department	marks
101	Arun	CSE	85
104	Vijay	IT	88

```
2 rows in set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM student
    -> WHERE marks NOT BETWEEN 80 AND 90;
```

student_id	student_name	department	marks
102	Karthik	ECE	78
103	Rahul	CSE	92
105	Ajay	CSE	76

```
3 rows in set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM student
    -> WHERE department IN ('CSE', 'ECE');
```

student_id	student_name	department	marks
101	Arun	CSE	85
102	Karthik	ECE	78
103	Rahul	CSE	92
105	Ajay	CSE	76

```
4 rows in set (0.00 sec)
```

```
mysql>
mysql> SELECT * FROM student
    -> WHERE department NOT IN ('CSE', 'ECE');
```

student_id	student_name	department	marks
104	Vijay	IT	88

```
1 row in set (0.00 sec)
```

```
mysql>
mysql> SELECT COUNT(*) AS total_students
    -> FROM student;
```

total_students
5

```
1 row in set (0.02 sec)
```

```
mysql>
mysql> SELECT SUM(marks) AS total_marks
    -> FROM student;
```

total_marks
419

```
1 row in set (0.00 sec)
```

```
mysql> SELECT AVG(marks) AS average_marks  
-> FROM student;
```

```
+-----+  
| average_marks |  
+-----+  
|          83.8000 |  
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql>  
mysql> SELECT MAX(marks) AS highest_marks  
-> FROM student;
```

```
+-----+  
| highest_marks |  
+-----+  
|           92 |  
+-----+
```

```
1 row in set (0.00 sec)
```

```
mysql>  
mysql> SELECT MIN(marks) AS lowest_marks  
-> FROM student;
```

```
+-----+  
| lowest_marks |  
+-----+  
|           76 |  
+-----+
```

```
1 row in set (0.00 sec)
```