

Week 6 – 1:

ROLL NO.:240801142

Name : Kadhiroliselvan R D

<b>Status</b>	Finished
<b>Started</b>	Monday, 23 December 2024, 5:33 PM
<b>Completed</b>	Sunday, 8 December 2024, 12:32 PM
<b>Duration</b>	15 days 5 hours

Q1) Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that  $A[i] - A[j] = k$ ,  $i \neq j$ .

Input Format

1. First line is number of test cases T. Following T lines contain:
2. N, followed by N integers of the array
3. The non-negative integer k

Output format

Print 1 if such a pair exists and 0 if it doesn't.

Sample Input:

```
1
3 1 3 5
4
```

Sample Output:

```
1
```

Code:

```
1 #include<stdio.h>
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while(t-->0)
7     {
8         int n;
9         scanf("%d",&n);
10        int a[n];
11        for(int i=0;i<n;i++)
12        {
13            scanf("%d",&a[i]);
14        }
15        int k;
16        scanf("%d",&k);
17        int flag =0;
18        for(int i =0;i<n;i++)
19        {
20            for(int j=i+1;j<n;j++)
21            {
22                if(a[i] - a[j] ==k || a[j] -a[i] ==k){
23                    flag =1;
24                    break;}
25            }if(flag)
26                break;
27        } printf("%d\n",flag);
28    }
29 }
```

OUTPUT:

	Input	Expected	Got	
✓	1 3 1 3 5 4	1	1	✓
✓	1 3 1 3 5 99	0	0	✓

Passed all tests! ✓

Q2) Sam loves chocolates and starts buying them on the 1st day of the year. Each day of the year,  $x$ , is numbered from 1 to  $Y$ . On days when  $x$  is odd, Sam will buy  $x$  chocolates; on days when  $x$  is even, Sam will not purchase any chocolates.

Complete the code in the editor so that for each day  $N_i$  (where  $1 \leq x \leq N \leq Y$ ) in array  $arr$ , the number of chocolates Sam purchased (during days 1 through  $N$ ) is printed on a new line. This is a function-only challenge, so input is handled for you by the locked stub code in the editor.

Input Format

The program takes an array of integers as a parameter.

The locked code in the editor handles reading the following input from `stdin`, assembling it into an array of integers ( $arr$ ), and calling `calculate(arr)`.

The first line of input contains an integer,  $T$  (the number of test cases). Each line  $i$  of the  $T$  subsequent lines describes the  $i$ th test case as an integer,  $N_i$  (the number of days).

Constraints

$$1 \leq T \leq 2 \times 10^5$$

$$1 \leq N \leq 2 \times 10^6$$

$$1 \leq x \leq N \leq Y$$

Output Format

For each test case,  $T_i$  in  $arr$ , your `calculate` method should print the total number of chocolates Sam purchased by day  $N_i$  on a new line.

Sample Input 0

3

1

2

3

Sample Output 0

1

1

4

Code:

```
1 #include<stdio.h>
2 int main()
3 {
4     int t;
5     scanf("%d",&t);
6     while(t-->0)
7     {
8         int n,c=0;
9         scanf("%d",&n);
10        for(int i=0;i<=n;i++)
11        {
12            if(i%2!=0)
13                c=c+i;
14
15
16
17        }
18        printf("%d\n",c);
19
20
21    }
22 }
```

OUTPUT:

	Input	Expected	Got	
✓	3 1 2 3	1 1 4	1 1 4	✓
✓	10 71 100 86 54 40 9 77 9 13 98	1296 2500 1849 729 400 25 1521 25 49 2401	1296 2500 1849 729 400 25 1521 25 49 2401	✓

Passed all tests! ✓

Q3) The number of goals achieved by two football teams in matches in a league is given in the form of two lists. Consider:

- Football team A, has played three matches, and has scored { 1 , 2 , 3 } goals in each match respectively.
- Football team B, has played two matches, and has scored { 2, 4 } goals in each match respectively.
- Your task is to compute, for each match of team B, the total number of matches of team A,
- where team A has scored less than or equal to the number of goals scored by team B in that match.

In the above case:

- For 2 goals scored by team B in its first match, team A has 2 matches with scores 1 and 2.
- For 4 goals scored by team B in its second match, team A has 3 matches with scores 1, 2 and 3. Hence, the answer: {2, 3}.

Complete the code in the editor below. The program must return an array of  $m$  positive integers, one for each  $maxes[i]$  representing the total number of elements  $nums[j]$  satisfying  $nums[j] \leq maxes[i]$  where  $0 \leq j < n$  and  $0 \leq i < m$ , in the given order.

It has the following:

`nums[nums[0],...nums[n-1]]`: first array of positive integers

maxes[maxes[0],...maxes[n-1]]: second array of positive integers

Constraints:

$2 \leq n, m \leq 105$ ,  $1 \leq \text{nums}[j] \leq 109$ , where  $0 \leq j < n$ ,  $1 \leq \text{maxes}[i] \leq 109$ , where  $0 \leq i < m$ .

Input Format For Custom Testing

Input from stdin will be processed as follows and passed to the function.

The first line contains an integer  $n$ , the number of elements in `nums`.

The next  $n$  lines each contain an integer describing `nums[j]` where  $0 \leq j < n$ .

The next line contains an integer  $m$ , the number of elements in `maxes`.

The next  $m$  lines each contain an integer describing `maxes[i]` where  $0 \leq i < m$ .

Sample Input

4

1

4

2

4

2

3

5

Sample Output

2

4

Code:

```

1  #include<stdio.h>
2  int main()
3  {
4      int s1,s2,ans;
5      scanf("%d",&s1);
6      int ta[s1];
7      for(int i =0;i<s1;i++)
8      {
9          scanf("%d",&ta[i]);
10     }
11     scanf("%d",&s2);
12
13     int tb[s2];
14     for(int i=0;i<s2;i++)
15     {scanf("%d",&tb[i]);
16     }
17     for(int j=0;j<s2;j++)
18     {
19         ans=0;
20         for(int i=0;i<s1;i++)
21         {
22             if(tb[j]>=ta[i])
23                 ans++;
24         }printf("%d\n",ans);
25     }
26
27 }
28 }

```

OUTPUT:

	Input	Expected	Got	
✓	4	2	2	✓
	1	4	4	
	4			
	2			
	4			
	2			
	3			
	5			
✓	5	1	1	✓
	2	0	0	
	10	3	3	
	5	4	4	
	4			
	8			
	4			
	3			
	1			
	7			
	8			

Passed all tests! ✓