





















Performance

Accessibility

Best Practices

SEO

Progressive Web App



0-49

50-89

90-100



Performance

First Contentful Paint

 $0.7 \, s$

Metrics

Speed Index

1.2 s

Largest Contentful Paint

0.9 s

Time to Interactive

 $0.8 \, s$

Total Blocking Time

 $0 \, \mathrm{ms}$

Cumulative Layout Shift

0.026

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

View Original Trace















 \equiv

Show audits relevant to: All FCP LCP TBT CLS



Opportunities — These suggestions can help your page load faster. They don't <u>directly affect</u> the Performance score.

Eliminate render-blocking resources

Opportunity

0.44 s ^

Estimated Savings

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn more. (FCP) (LCP)

· · · · · · · · · · · · · · · · · · ·		
	Show 3rd party re	esources (6)
URL	Transfer Size	Potentia Saving
css/bootstrap.min.css (cdn.jsdelivr.net)	24.8 KiB	360 ms
css/hover-min.css (cdnjs.cloudflare.com)	5.7 KiB	230 ms
/0030311fd7.js (kit.fontawesome.com)	4.0 KiB	230 ms
/jquery-3.6.0.min.js (code.jquery.com)	30.4 KiB	350 ms
js/bootstrap.min.js (stackpath.bootstrapcdn.com)	16.2 KiB	300 ms
/v3/ (js.stripe.com)	66.4 KiB	400 ms
Reduce unused JavaScript		0.2 s
Reduce unused JavaScript and defer loading scripts until they are required to decrease Learn more. LCP	se bytes consumed by netw	ork activity.
	Show 3rd party re	esources (2)
URL	Transfer Size	Potentia Saving
/v3/ (js.stripe.com)	66.4 KiB	51.6 KiB
/jquery-3.6.0.min.js (code.jquery.com)	30.4 KiB	20.2 KiB
erformance score. Image elements do not have explicit width and height		/
Set an explicit width and height on image elements to reduce layout shifts and improv	e CLS. <u>Learn more</u> CLS	
	Show 3rd-party re	e sources (0)
URL	Failing Elements	
		img. w-
/media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)		100.i mg-
		fluid
Serve static assets with an efficient cache policy — 7 resources found		
A long cache lifetime can speed up repeat visits to your page. <u>Learn more</u> .		
	✓ Show 3rd-party re	esources (3)
URL	Cache TTL	Transfer Siz
/media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)	None	197 KiB
,, o ()		•

URL	Cache TTL	Transfer Size
css/base.css (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)	None	14 KiB
js/back_to_top.js (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)	None	1 KiB
css/contact.css (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)	None	0 KiB
/v3/ (js.stripe.com)	1 m	66 KiB
js/m-outer-35486fbjs (js.stripe.com)	1 m	1 KiB
/out-4.5.41.js (m.stripe.network)	5 m	16 KiB

Avoid chaining critical requests — 15 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. <u>Learn more</u>. (FCP) (LCP)

Maximum critical path latency: 1,940 ms

Initial Navigation

/contact/ (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)

...css/bootstrap.min.css (cdn.jsdelivr.net) - 50 ms, 24.76 KiB

...css/base.css (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)

/css2?family=Pacifico&display=swap (fonts.googleapis.com)

...v17/FwZY7-Qmy....woff2 (fonts.gstatic.com) - 30 ms, 20.62 KiB

/css2? family = Oswald: wght @200; 300; 400; 500; 600; 700 & display = swap ~~ (fonts. googleap is.com)

...v40/TK3iWkUHH....woff2 (fonts.gstatic.com) - 20 ms, 24.83 KiB

...css/hover-min.css (cdnjs.cloudflare.com) - 60 ms, 5.74 KiB

...css/contact.css (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) - 90 ms, 0.19 KiB

/0030311fd7.js (kit.fontawesome.com) - 60 ms, 4.00 KiB

/jquery-3.6.0.min.js (code.jquery.com) - 110 ms, 30.40 KiB

...umd/popper.min.js (cdn.jsdelivr.net) - 110 ms, 7.57 KiB

...js/bootstrap.min.js (stackpath.bootstrapcdn.com) - 80 ms, 16.18 KiB

...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) - 120 ms, 22.78 KiB

/v3/ (js.stripe.com) - 80 ms, 66.45 KiB

...js/back_to_top.js (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) - 50 ms, 0.81 KiB

...webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com) - 260 ms, 75.76 KiB

...webfonts/free-fa-regular-400.woff2 (ka-f.fontawesome.com) - 240 ms, 13.73 KiB

...webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com) - 270 ms, 77.16 KiB

Keep request counts low and transfer sizes small — 29 requests • 662 KiB

To set budgets for the quantity and size of page resources, add a budget.json file. Learn more.

Resource Type Requests Transfer Size

Total 29 662.4 KiB

Resource Type			
	Requests		Transfer Size
Font	5		212.1 KiB
Image	1		197.0 KiB
Script	9		164.5 KiB
Stylesheet	6		45.7 KiB
Document	3		22.5 KiB
Other	5		20.5 KiB
Media	0		0.0 KiB
Third-party	23		428.3 KiB
Largest Contentful Paint element — 1 element found			/
This is the largest contentful element painted within the	e viewport. <u>Learn More</u> <u>LCP</u>		
Element			
p.text-center			
ised audits (32)			
ssed audits (32)			/
Properly size images — Potential savings of 88 KiB			
	lular data and improve load time. <u>Learn r</u>	nore.	
Properly size images — Potential savings of 88 KiB	lular data and improve load time. <u>Learn r</u>	more. Show 3rd-party re	
Properly size images — Potential savings of 88 KiB	lular data and improve load time. <u>Learn r</u>	Show 3rd-party re	esources (0) Potentia
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell	lular data and improve load time. <u>Learn r</u>	Show 3rd-party re	esources (0) Potentia
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell		Show 3rd-party re	esources (0) Potentia Saving
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell URL		Show 3rd-party re Resource Size	Potentia Saving 88.2 KiB
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell URL /media/contactskate.jpg (8000-turquoise-fish-	-a9gcw8ki.ws-eu27.gitpod.io)	Resource Size 196.9 KiB	Potentia Saving 88.2 KiB
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell URL /media/contactskate.jpg (8000-turquoise-fish- Defer offscreen images Consider lazy-loading offscreen and hidden images at	-a9gcw8ki.ws-eu27.gitpod.io)	Resource Size 196.9 KiB	esources (0) Potentia Saving 88.2 KiB
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell URL /media/contactskate.jpg (8000-turquoise-fish- Defer offscreen images Consider lazy-loading offscreen and hidden images at interactive. Learn more.	-a9gcw8ki.ws-eu27.gitpod.io) fter all critical resources have finished loa	Resource Size 196.9 KiB	esources (0) Potentia Saving: 88.2 KiB
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell URL /media/contactskate.jpg (8000-turquoise-fish- Defer offscreen images Consider lazy-loading offscreen and hidden images at interactive. Learn more. Minify CSS — Potential savings of 5 KiB	-a9gcw8ki.ws-eu27.gitpod.io) fter all critical resources have finished loa	Resource Size 196.9 KiB	esources (0) Potentia Saving: 88.2 KiB
Properly size images — Potential savings of 88 KiB Serve images that are appropriately-sized to save cell URL /media/contactskate.jpg (8000-turquoise-fish- Defer offscreen images Consider lazy-loading offscreen and hidden images at interactive. Learn more. Minify CSS — Potential savings of 5 KiB	-a9gcw8ki.ws-eu27.gitpod.io) fter all critical resources have finished loa	Resource Size 196.9 KiB	Potentia Savings 88.2 KiB

Minify JavaScript		
Minifying JavaScript files can reduce payload sizes and script parse time. <u>Learn more</u> . [FCP LCP	
Reduce unused CSS — Potential savings of 36 KiB		
Reduce unused rules from stylesheets and defer CSS not used for above-the-fold contenetwork activity. <u>Learn more</u> . <u>FCP</u> <u>LCP</u>	ent to decrease bytes con	sumed by
	Show 3rd-party r	esources (1)
URL	Transfer Size	Potenti Saving
css/bootstrap.min.css (cdn.jsdelivr.net)	24.8 KiB	23.6 KiE
/*! * Font Awesome Free 5.15.4 by @fontawesome - https://fontawesome.com * License https://fonta	12.0 KiB	11.9 KiE
Efficiently encode images — Potential savings of 25 KiB		•
Optimized images load faster and consume less cellular data. <u>Learn more</u> .		
	Show 3rd party r	esources (0)
URL	Resource Size	Potenti Saving
/media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)	196.9 KiB	24.9 KiE
/media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) Serve images in next-gen formats — Potential savings of 118 KiB	196.9 KiB	24.9 KiB
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC		wnloads
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC	G, which means faster do	wnloads
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC and less data consumption. Learn more.	G, which means faster do Show 3rd party r Resource	wnloads esources (0 Potenti Savinç
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC and less data consumption. Learn more. URL	G, which means faster do Show 3rd party r Resource Size	wnloads resources (0 Potenti Savino 117.6 KiE
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC and less data consumption. Learn more. URL /media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io)	G, which means faster do Show 3rd party r Resource Size 196.9 KiB	wnloads resources (0 Potenti Savino 117.6 KiE
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC and less data consumption. Learn more. URL /media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) Enable text compression — Potential savings of 26 KiB Text-based resources should be served with compression (gzip, deflate or brotli) to mini	G, which means faster do Show 3rd party r Resource Size 196.9 KiB	wnloads esources (0 Potenti Saving 117.6 KiE
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC and less data consumption. Learn more. URL /media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) Enable text compression — Potential savings of 26 KiB Text-based resources should be served with compression (gzip, deflate or brotli) to mini	Show 3rd party r Resource Size 196.9 KiB	wnloads resources (0 Potenti Savino 117.6 KiE
Serve images in next-gen formats — Potential savings of 118 KiB Image formats like WebP and AVIF often provide better compression than PNG or JPEC and less data consumption. Learn more. URL /media/contactskate.jpg (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) Enable text compression — Potential savings of 26 KiB Text-based resources should be served with compression (gzip, deflate or brotli) to minimore. FCP LCP	Show 3rd party r Resource Size 196.9 KiB Show 3rd-party r Transfer	wnloads esources (0 Potenti Saving 117.6 KiE

Consider adding 'preconnect' or 'dns-prefetch' resource hints to establish early connections to important third-party origins. Learn more. [FCP] [LCP] Initial server response time was short — Root document took 250 ms Keep the server response time for the main document short because all other requests depend on it. Learn more. [FCP] LCP Show 3rd-party resources (0) **URL** Time Spent /contact/ (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io) 250 ms Avoid multiple page redirects Redirects introduce additional delays before the page can be loaded. Learn more. [FCP] [LCP] Preload key requests Consider using `<link rel=preload>` to prioritize fetching resources that are currently requested later in page load. Learn more. FCP [LCP] Use HTTP/2 HTTP/2 offers many benefits over HTTP/1.1, including binary headers and multiplexing. Learn more. Use video formats for animated content Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more [LCP] Remove duplicate modules in JavaScript bundles — Potential savings of 13 KiB Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. TBT Show 3rd party resources (0) Source Transfer Size **Potential Savings** 0ther 3.10 KiB ...js/bootstrap.min.js (stackpath.bootstrapcdn.com) ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) 2.85 KiB ../../js/src/tooltip.js ...js/bootstrap.min.js (stackpath.bootstrapcdn.com) 2.85 KiB ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) 2.85 KiB ../../js/src/carousel.js 2.00 KiB ...js/bootstrap.min.js (stackpath.bootstrapcdn.com) 2.10 KiB ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) 2.00 KiB 1.85 KiB ../../js/src/dropdown.js ...js/bootstrap.min.js (stackpath.bootstrapcdn.com) 1.80 KiB 1.85 KiB ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) ../../js/src/modal.js 1.55 KiB 2.45 KiB ...js/bootstrap.min.js (stackpath.bootstrapcdn.com)

Source	Transfer Size	Potential Savings	
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	1.55 KiB		
//js/src/collapse.js		1.25 KiB	
js/bootstrap.min.js (stackpath.bootstrapcdn.com	1.35 KiB		
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)	1.25 KiB		
Avoid serving legacy JavaScript to modern browser	rs — Potential savings of 0 KiB	^	
Polyfills and transforms enable legacy browsers to	use new JavaScript features. However, many are	n't necessary for	
modern browsers. For your bundled JavaScript, add			
detection to reduce the amount of code shipped to More (TBT)	modern browsers, while retaining support for lega	cy browsers. <u>Learn</u>	
	Show	w 3rd-party resources (2)	
URL		Potential Savings	
Preload Largest Contentful Paint image		^	
Preload the image used by the LCP element in order	er to improve your LCP time. <u>Learn more</u> . <u>LCP</u>		
Avoids enormous network payloads — Total size v	vas 662 KiB	^	
Large network payloads cost users real money and	are highly correlated with long load times. <u>Learn</u>	more. (LCP)	
	✓ Show	w 3rd-party resources (8)	
URL		Transfer Size	
/media/contactskate.jpg (8000-turquoise-fish-a9gcw8	3ki.ws-eu27.gitpod.io)	197.0 KiB	
webfonts/free-fa-solid-900.woff2 (ka-f.fontawesor	ne.com)	77.2 KiB	
webfonts/free-fa-brands-400.woff2 (ka-f.fontawes	some.com)	75.8 KiB	
/v3/ (js.stripe.com)		66.4 KiB	
/jquery-3.6.0.min.js (code.jquery.com)		30.4 KiB	
v40/TK3iWkUHHwoff2 (fonts.gstatic.com)		24.8 KiB	
css/bootstrap.min.css (cdn.jsdelivr.net)		24.8 KiB	
js/bootstrap.bundle.min.js (cdn.jsdelivr.net)		22.8 KiB	
v17/FwZY7-Qmywoff2 (fonts.gstatic.com)		20.6 KiB	
/contact/ (8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpo	d.io)	20.6 KiB	
Avoids an excessive DOM size — 216 elements		^	
A large DOM will increase memory usage, cause lo	nger <u>style calculations</u> , and produce costly <u>layout</u>	reflows. <u>Learn more</u> .	
Statistic	Element	Value	
Total DOM Elements		216	
Maximum DOM Depth	i.fas.fa-search	13	

Statistic Element Value body Maximum Child Elements 10 User Timing marks and measures Consider instrumenting your app with the User Timing API to measure your app's real-world performance during key user experiences. Learn more. JavaScript execution time Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. Learn more. [TBT] Minimizes main-thread work — 0.0 s Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn more [TBT] Category Time Spent Other 20 ms Script Evaluation 0 ms All text remains visible during webfont loads Leverage the font-display CSS feature to ensure text is user-visible while webfonts are loading. Learn more. FCP [CCP] Minimize third-party usage — Third-party code blocked the main thread for 0 ms Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. Learn more. [TBT] Show 3rd-party resources (0) Third-Party Transfer Size Main-Thread Blocking Time FontAwesome CDN 189 KiB 0 ms 77 KiB ...webfonts/free-fa-solid-900.woff2 (ka-f.fontawesome.com) 0 ms ...webfonts/free-fa-brands-400.woff2 (ka-f.fontawesome.com) 76 KiB 0 ms ...webfonts/free-fa-regular-400.woff2 (ka-f.fontawesome.com) 14 KiB 0 ms ...css/free.min.css?token=0030311fd7 (ka-f.fontawesome.com) 13 KiB 0 ms **Stripe** 85 KiB 0 ms /v3/ (js.stripe.com) 66 KiB 0 ms /out-4.5.41.js (m.stripe.network) 16 KiB 0 ms 55 KiB JSDelivr CDN 0 ms ...css/bootstrap.min.css (cdn.jsdelivr.net) 25 KiB 0 ms ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) 23 KiB $0 \, \text{ms}$

...umd/popper.min.js (cdn.jsdelivr.net)

0 ms

8 KiB

	Third-Party	Transfer Size	Main-Thread Blocking Time
	Google Fonts	47 KiB	0 ms
	v40/TK3iWkUHHwoff2 (fonts.gstatic.com)	25 KiB	0 ms
	v17/FwZY7-Qmywoff2 (fonts.gstatic.com)	21 KiB	0 ms
	jQuery CDN	30 KiB	0 ms
	/jquery-3.6.0.min.js (code.jquery.com)	30 KiB	0 ms
	Bootstrap CDN	16 KiB	0 ms
	js/bootstrap.min.js (stackpath.bootstrapcdn.com)	16 KiB	0 ms
	Cloudflare CDN	6 KiB	0 ms
	css/hover-min.css (cdnjs.cloudflare.com)	6 KiB	0 ms
0	Lazy load third-party resources with facades		^
	Some third-party embeds can be lazy loaded. Consider replacing them TBT	with a facade until they a	are required. <u>Learn more</u> .
0	Largest Contentful Paint image was not lazily loaded		^
	Above-the-fold images that are lazily loaded render later in the page life <u>Learn more</u> .	ecycle, which can delay t	he largest contentful paint.
0	Avoid large layout shifts		^
	These DOM elements contribute most to the CLS of the page. CLS		
	Uses passive listeners to improve scrolling performance		^
	Consider marking your touch and wheel event listeners as 'passive' to	improve your page's scro	oll performance. <u>Learn more</u> .
	Avoids document.write()		^
	For users on slow connections, external scripts dynamically injected via seconds. <u>Learn more</u> .	a `document.write()` can	delay page load by tens of
0	Avoid long main-thread tasks		^
	Lists the longest tasks on the main thread, useful for identifying worst of	contributors to input delay	. <u>Learn more</u> (TBT)
0	Avoid non-composited animations		^
	Animations which are not composited can be janky and increase CLS.	Learn more CLS	
	Has a <meta name="viewport"/> tag with width or initial-scale		^
	A ` <meta name="viewport"/> ` not only optimizes your app for mobile sci to user input. Learn more. [TBT]	reen sizes, but also preve	ents <u>a 300 millisecond delay</u>



These checks highlight opportunities to improve the accessibility of your web app. Only a subset of accessibility issues can be automatically detected so manual testing is also encouraged.

	ditional items to manually check (10) — These items address areas which an automated testing tool cannot cover. Learn re in our guide on conducting an accessibility review.	۱ ^
0	The page has a logical tab order	^
	Tabbing through the page follows the visual layout. Users cannot focus elements that are offscreen. <u>Learn more</u> .	
0	Interactive controls are keyboard focusable	^
	Custom interactive controls are keyboard focusable and display a focus indicator. <u>Learn more</u> .	
0	Interactive elements indicate their purpose and state	^
	Interactive elements, such as links and buttons, should indicate their state and be distinguishable from non-interactive elements. <u>Learn more</u> .	
0	The user's focus is directed to new content added to the page	^
	If new content, such as a dialog, is added to the page, the user's focus is directed to it. <u>Learn more</u> .	
0	User focus is not accidentally trapped in a region	^
	A user can tab into and out of any control or region without accidentally trapping their focus. <u>Learn more</u> .	
0	Custom controls have associated labels	^
	Custom interactive controls have associated labels, provided by aria-label or aria-labelledby. <u>Learn more</u> .	
0	Custom controls have ARIA roles	^
	Custom interactive controls have appropriate ARIA roles. <u>Learn more</u> .	
0	Visual order on the page follows DOM order	^
	DOM order matches the visual order, improving navigation for assistive technology. <u>Learn more</u> .	
0	Offscreen content is hidden from assistive technology	^
	Offscreen content is hidden with display: none or aria-hidden=true. <u>Learn more</u> .	
0	HTML5 landmark elements are used to improve navigation	^
	Landmark elements (<main>, <nav>, etc.) are used to improve the keyboard navigation of the page for assistive technology Learn more.</nav></main>	y .
Pas	ssed audits (20)	^
	[aria-*] attributes match their roles	^
	Each ARIA `role` supports a specific subset of `aria-*` attributes. Mismatching these invalidates the `aria-*` attributes. <u>Learn.</u> <u>more.</u>	1

[aria-hidden="true"] is not present on the document <body>

Assistive technologies, like screen readers, work inconsistently when `aria-hidden="true"` is set on the document `<body>`. Learn more. [aria-hidden="true"] elements do not contain focusable descendents Focusable descendents within an `[aria-hidden="true"]` element prevent those interactive elements from being available to users of assistive technologies like screen readers. Learn more. [aria-*] attributes have valid values Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid values. Learn more. [aria-*] attributes are valid and not misspelled Assistive technologies, like screen readers, can't interpret ARIA attributes with invalid names. Learn more. Buttons have an accessible name When a button doesn't have an accessible name, screen readers announce it as "button", making it unusable for users who rely on screen readers. Learn more. The page contains a heading, skip link, or landmark region Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more. Background and foreground colors have a sufficient contrast ratio Low-contrast text is difficult or impossible for many users to read. Learn more. Document has a <title> element The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more. [id] attributes on active, focusable elements are unique All focusable elements must have a unique 'id' to ensure that they're visible to assistive technologies. Learn more. ARIA IDs are unique The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn more. Heading elements appear in a sequentially-descending order Properly ordered headings that do not skip levels convey the semantic structure of the page, making it easier to navigate and understand when using assistive technologies. Learn more. <html> element has a [lang] attribute If a page doesn't specify a lang attribute, a screen reader assumes that the page is in the default language that the user chose when setting up the screen reader. If the page isn't actually in the default language, then the screen reader might not announce the page's text correctly. Learn more. <html> element has a valid value for its [lang] attribute Specifying a valid BCP 47 language helps screen readers announce text properly. Learn more. Image elements have [alt] attributes

Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more. Form elements have associated labels Labels ensure that form controls are announced properly by assistive technologies, like screen readers. Learn more. Links have a discernible name Link text (and alternate text for images, when used as links) that is discernible, unique, and focusable improves the navigation experience for screen reader users. Learn more. Lists contain only elements and script supporting elements (<script> and <template>). Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more. List items () are contained within or parent elements Screen readers require list items ('') to be contained within a parent '' or '' to be announced properly. Learn more. [user-scalable="no"] is not used in the <meta name="viewport"> element and the [maximum-scale] attribute is not less than 5. Disabling zooming is problematic for users with low vision who rely on screen magnification to properly see the contents of a web page. Learn more. Not applicable (24) [accesskey] values are unique Access keys let users quickly focus a part of the page. For proper navigation, each access key must be unique. Learn more. button, link, and menuitem elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA input fields have accessible names When an input field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA meter elements have accessible names When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. ARIA progressbar elements have accessible names When a 'progressbar' element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more. [role]s have all required [aria-*] attributes Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more. Elements with an ARIA [role] that require children to contain a specific [role] have all required children.

	Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. <u>Learn more</u> .	
0	[role]s are contained by their required parent element	^
	Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. <u>Learn more</u> .	
0	[role] values are valid	^
	ARIA roles must have valid values in order to perform their intended accessibility functions. <u>Learn more</u> .	
0	ARIA toggle fields have accessible names	^
	When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .	
0	ARIA tooltip elements have accessible names	^
	When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .	
0	ARIA treeitem elements have accessible names	^
	When an element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. <u>Learn more</u> .	
0	<pre><dl>'s contain only properly-ordered <dt> and <dd> groups, <script>, <template> or <div> elements.</pre></td><td>^</td></tr><tr><td></td><td>When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td>Definition list items are wrapped in <d1> elements</td><td>^</td></tr><tr><td></td><td>Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td>No form fields have multiple labels</td><td>^</td></tr><tr><td></td><td>Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td><frame> or <iframe> elements have a title</td><td>^</td></tr><tr><td></td><td>Screen reader users rely on frame titles to describe the contents of frames. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td><pre><input type="image"> elements have [alt] text</pre></td><td>^</td></tr><tr><td></td><td>When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. <u>Learn more</u>.</td><td>></td></tr><tr><td>0</td><td>The document does not use <meta http-equiv="refresh"></td><td>^</td></tr><tr><td></td><td>Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td><object> elements have [alt] text</td><td>^</td></tr><tr><td></td><td>Screen readers cannot translate non-text content. Adding alt text to `<object>` elements helps screen readers convey meaning to users. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td>No element has a [tabindex] value greater than 0</td><td>^</td></tr></tbody></table></script></dd></dt></dl></pre>	

A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. <u>Learn more</u>.

Cells in a element that use the [headers] attribute refer to table cells within the same table.

Screen readers have features to make navigating tables easier. Ensuring `` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more.

elements and elements with [role="columnheader"/"rowheader"] have data cells they describe.

Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. <u>Learn more</u>.

O [lang] attributes have a valid value

Specifying a valid <u>BCP 47 language</u> on elements helps ensure that text is pronounced correctly by a screen reader. <u>Learn more</u>.

<video> elements contain a <track> element with [kind="captions"]

When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more.



Best Practices

Trust and Safety

Ensure CSP is effective against XSS attacks

A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn more

Description Directive Severity

No CSP found in enforcement mode High

General

Detected JavaScript libraries

All front-end JavaScript libraries detected on the page. Learn more.

Name Version

Bootstrap 5.0.2

jQuery 3.6.0

Passed audits (16)

Avoids deprecated APIs

Deprecated APIs will eventually be removed from the browser. Learn more.

Uses HTTPS All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more. Links to cross-origin destinations are safe Add `rel="noopener"` or `rel="noreferrer"` to any external links to improve performance and prevent security vulnerabilities. Learn more. Avoids requesting the geolocation permission on page load Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more. Avoids requesting the notification permission on page load Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more. Avoids front-end JavaScript libraries with known security vulnerabilities Some third-party scripts may contain known security vulnerabilities that are easily identified and exploited by attackers. Learn more. Allows users to paste into password fields Preventing password pasting undermines good security policy. Learn more. Displays images with correct aspect ratio Image display dimensions should match natural aspect ratio. Learn more. Serves images with appropriate resolution Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn more. Page has the HTML doctype Specifying a doctype prevents the browser from switching to quirks-mode. Learn more. Properly defines charset A character encoding declaration is required. It can be done with a '<meta>' tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more. Avoids unload event listeners The 'unload' event does not fire reliably and listening for it can prevent browser optimizations like the Back-Forward Cache. Consider using the 'pagehide' or 'visibilitychange' events instead. Learn more Avoids Application Cache Application Cache is deprecated. Learn more.

No browser errors logged to the console

Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. <u>Learn more</u>

Page has valid source maps

Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. <u>Learn more</u>.

Show 3rd-party resources (3)

URL Map URL

- ...js/bootstrap.min.js (stackpath.bootstrapcdn.com) ...js/bootstrap.min.js.map (stackpath.bootstrapcdn.com)
- ...umd/popper.min.js (cdn.jsdelivr.net) ...umd/popper.min.js.map (cdn.jsdelivr.net)
- ...js/bootstrap.bundle.min.js (cdn.jsdelivr.net) ...js/bootstrap.bundle.min.js.map (cdn.jsdelivr.net)

No issues in the Issues panel in Chrome Devtools

Issues logged to the 'Issues' panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

Not applicable (1)

Fonts with font-display: optional are preloaded

Preload 'optional' fonts so first-time visitors may use them. Learn more



SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on

Core Web Vitals. Learn more.

Additional items to manually check (1) — Run these additional validators on your site to check additional SEO best practices.

Structured data is valid

Run the Structured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more.

Passed audits (10)

	Has a <meta name="viewport"/> tag with width or initial-scale	^
	A ` <meta name="viewport"/> ` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond delay</u> to user input. <u>Learn more</u> . TBT	y _
	Document has a <title> element</th><th>^</th></tr><tr><th></th><th>The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. <u>Learn more</u>.</th><th></th></tr><tr><td></td><td>Document has a meta description</td><td>^</td></tr><tr><td></td><td>Meta descriptions may be included in search results to concisely summarize page content. <u>Learn more</u>.</td><td></td></tr><tr><td></td><td>Page has successful HTTP status code</td><td>^</td></tr><tr><td></td><td>Pages with unsuccessful HTTP status codes may not be indexed properly. <u>Learn more</u>.</td><td></td></tr><tr><td></td><td>Links have descriptive text</td><td>^</td></tr><tr><td></td><td>Descriptive link text helps search engines understand your content. <u>Learn more</u>.</td><td></td></tr><tr><td></td><td>Links are crawlable</td><td>^</td></tr><tr><td></td><td>Search engines may use 'href' attributes on links to crawl websites. Ensure that the 'href' attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn More</td><td>3</td></tr><tr><td></td><td>Page isn't blocked from indexing</td><td>^</td></tr><tr><td></td><td>Search engines are unable to include your pages in search results if they don't have permission to crawl them. <u>Learn more</u>.</td><td></td></tr><tr><td></td><td>Image elements have [alt] attributes</td><td>^</td></tr><tr><td></td><td>Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. <u>Learn more</u>.</td><td></td></tr><tr><td></td><td>Document has a valid hreflang</td><td>^</td></tr><tr><td></td><td>hreflang links tell search engines what version of a page they should list in search results for a given language or region. <u>Learn more.</u></td><td></td></tr><tr><td></td><td>Document avoids plugins</td><td>^</td></tr><tr><td></td><td>Search engines can't index plugin content, and many devices restrict plugins or don't support them. <u>Learn more</u>.</td><td></td></tr><tr><td>No</td><td>t applicable (4)</td><td>^</td></tr><tr><td>0</td><td>robots.txt is valid</td><td>^</td></tr><tr><td></td><td>If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td>Document has a valid rel=canonical</td><td>^</td></tr><tr><td></td><td>Canonical links suggest which URL to show in search results. <u>Learn more</u>.</td><td></td></tr><tr><td>0</td><td>Document uses legible font sizes</td><td>^</td></tr></tbody></table></title>	

Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. <u>Learn more</u>.

Tap targets are sized appropriately

Interactive elements like buttons and links should be large enough (48x48px), and have enough space around them, to be easy enough to tap without overlapping onto other elements. <u>Learn more</u>.



Progressive Web App

These checks validate the aspects of a Progressive Web App. Learn more.

Installable

▲ Web app manifest or service worker do not meet the installability requirements — 1 reason

Service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. With proper service worker and manifest implementations, browsers can proactively prompt users to add your app to their homescreen, which can lead to higher engagement. <u>Learn more</u>.

Failure reason

No manifest was fetched

PWA Optimized

▲ Does not register a service worker that controls page and start_url

The service worker is the technology that enables your app to use many Progressive Web App features, such as offline, add to homescreen, and push notifications. <u>Learn more</u>.

Redirects HTTP traffic to HTTPS

If you've already set up HTTPS, make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. <u>Learn more</u>.

▲ Is not configured for a custom splash screen Failures: No manifest was fetched.

A themed splash screen ensures a high-quality experience when users launch your app from their homescreens. <u>Learn more</u>.

Does not set a theme color for the address bar.

Failures: No manifest was fetched, No `<meta name="theme-color">` tag found.

The browser address bar can be themed to match your site. Learn more.

Content is sized correctly for the viewport

If the width of your app's content doesn't match the width of the viewport, your app might not be optimized for mobile screens. <u>Learn more</u>.

Has a <meta name="viewport"> tag with width or initial-scale

A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents <u>a 300 millisecond delay to user input</u>. <u>Learn more</u>. <u>TBT</u>

Provides a valid apple-touch-icon

For ideal appearance on iOS when users add a progressive web app to the home screen, define an `apple-touch-icon`. It must point to a non-transparent 192px (or 180px) square PNG. <u>Learn More</u>.

Manifest doesn't have a maskable icon No manifest was fetched

A maskable icon ensures that the image fills the entire shape without being letterboxed when installing the app on a device. Learn more.

Additional items to manually check (3) — These checks are required by the baseline <u>PWA Checklist</u> but are not automatically checked by Lighthouse. They do not affect your score but it's important that you verify them manually.

Site works cross-browser

To reach the most number of users, sites should work across every major browser. Learn more.

Page transitions don't feel like they block on the network

Transitions should feel snappy as you tap around, even on a slow network. This experience is key to a user's perception of performance. <u>Learn more</u>.

Each page has a URL

Ensure individual pages are deep linkable via URL and that URLs are unique for the purpose of shareability on social media. <u>Learn more</u>.

Runtime Settings

URL https://8000-turquoise-fish-a9gcw8ki.ws-eu27.gitpod.io/contact/

Fetch Time Jan 16, 2022, 3:03 PM GMT+1

Device Emulated Desktop

Network throttling 40 ms TCP RTT, 10,240 Kbps throughput (Simulated)

CPU throttling 1x slowdown (Simulated)

Channel devtools

User agent (host) Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like

Gecko) Chrome/97.0.4692.71 Safari/537.36

Mozilla/5 0 (Macintosh: Intel Mac OS X 10 15 7) AppleWebKit/537 36 (KHTMI

1/16/22, 3:04 PM

User agent (network)

like Gecko) Chrome/94.0.4590.2 Safari/537.36 Chrome-Lighthouse

CPU/Memory Power 287

Axe version 4.2.3

Generated by **Lighthouse** 8.5.0 | File an issue