

### 3.4 THE BASIC DECISION TREE LEARNING ALGORITHM

Most algorithms that have been developed for learning decision trees are variations on a core algorithm that employs a top-down, greedy search through the space of possible decision trees. This approach is exemplified by the ID3 algorithm (Quinlan 1986) and its successor C4.5 (Quinlan 1993), which form the primary focus of our discussion here. In this section we present the basic algorithm for decision tree learning, corresponding approximately to the ID3 algorithm. In Section 3.7 we consider a number of extensions to this basic algorithm, including extensions incorporated into C4.5 and other more recent algorithms for decision tree learning.

Our basic algorithm, ID3, learns decision trees by constructing them top-down, beginning with the question "which attribute should be tested at the root of the tree?" To answer this question, each instance attribute is evaluated using a statistical test to determine how well it alone classifies the training examples. The best attribute is selected and used as the test at the root node of the tree. A descendant of the root node is then created for each possible value of this attribute, and the training examples are sorted to the appropriate descendant node (i.e., down the branch corresponding to the example's value for this attribute). The entire process is then repeated using the training examples associated with each descendant node to select the best attribute to test at that point in the tree. This forms a greedy search for an acceptable decision tree, in which the algorithm never backtracks to reconsider earlier choices. A simplified version of the algorithm, specialized to learning boolean-valued functions (i.e., concept learning), is described in Table 3.1.

#### 3.4.1 Which Attribute Is the Best Classifier?

The central choice in the ID3 algorithm is selecting which attribute to test at each node in the tree. We would like to select the attribute that is most useful for classifying examples. What is a good quantitative measure of the worth of an attribute? We will define a statistical property, called *information gain*, that measures how well a given attribute separates the training examples according to their target classification. ID3 uses this information gain measure to select among the candidate attributes at each step while growing the tree.

##### 3.4.1.1 ENTROPY MEASURES HOMOGENEITY OF EXAMPLES

In order to define information gain precisely, we begin by defining a measure commonly used in information theory, called *entropy*, that characterizes the (im)purity of an arbitrary collection of examples. Given a collection  $S$ , containing positive and negative examples of some target concept, the entropy of  $S$  relative to this boolean classification is

$$\text{Entropy}(S) \equiv -p_{\oplus} \log_2 p_{\oplus} - p_{\ominus} \log_2 p_{\ominus} \quad (3.1)$$