Contents

The Kahlus Handbook **1**
1. What Kahlus is, in one page . . . 1
2. The vocabulary . . . 2
3. The core idea: how forecasting scores lie . . . 3
4. The experiments, one at a time . . . 5
5. The code . . . 8
6. The literature . . . 9
7. The honest ledger . . . 10
8. How to talk about this . . . 11
Figures . . . 12
Where to go next . . . 12

The Kahlus Handbook

Everything in this project, taught from zero.

Last updated 2026-07-31. If a number here disagrees with a slide, an email, or an older doc, **this file is right and the other thing is stale.** Every number was read out of a run log or `results.json`, not from memory.

You need no background to read this. Terms are defined the first time they appear. Read §1 and §3 and you understand the project. Read the rest when you need it.

---

1. What Kahlus is, in one page

The original goal. Predict what the brain is about to do, from EEG, far enough ahead to matter — motivated by seizure prediction, where a minute of warning changes someone's life.

What actually happened. The first big result was wrong. Not fraud, not a typo — wrong in a way the whole field is exposed to. Chasing down *why* turned out to be worth more than the original goal, and is now the centre of the project.

One sentence:

> Standard ways of scoring a forecast can make a model look far better than it is, by amounts you can compute exactly — and there are three separate mechanisms that do it.

#	Mechanism	Effect
1	The scored target window overlaps its own input	Error looks up to `W/H`× better than it is
2	The same bug in *correlation* instead of error	Worse, and the obvious formula **understates** it
3	The ground-truth labels are unreliable	Scores partly measure label noise

Why it matters. All three are *measurement* problems, not modelling problems. They apply to other people's work, on other datasets, with better models. A paper about them is a paper about how the field measures itself.

Where the biology stands. We have real, statistically solid forecasting results. They are modest, and other groups have published better ones (§6). The measurement work is the contribution.

---

2. The vocabulary

Signals

EEG — electrical voltage on the scalp from populations of neurons. **Sampling rate (`fs`)** — measurements per second. Sleep-EDF 100 Hz, BNCI 250 Hz. **Channel** — one electrode pair. `EEG Fpz−Cz` = voltage between forehead and top of head. **EOG** — eye movement. **EMG** — muscle activity. Both recorded alongside EEG; both contaminate it, and both are *required* to score sleep. **PSG (polysomnography)** — the full overnight recording. **Epoch** — a fixed chunk, conventionally 30 s in sleep work. One stage label per epoch.

Sleep

Stages — **W** (wake), **N1** (drowsy/lightest), **N2** (light), **N3** (deep), **REM** (dreaming). A night is a sequence of these. **Hypnogram** — the timeline of stage labels, produced by a human expert. **This is our ground truth, and §3.3 is about why that's a problem.**

Forecasting

Horizon (`h`/`H`) — how far ahead you predict. **Window / context (`W`/`L`)** — how much past data the model sees. **Persistence baseline** — the dumbest forecast: *"what's happening now will still be happening then."* **This is the baseline that matters.** For slow signals it is very hard to beat, and a paper comparing only against something weaker is not telling you much. **Majority / trace-mean baseline** — always guess the most common answer. Beating it proves almost nothing.

Scoring

MSE — mean of (prediction − truth)². Lower better. On normalised data, **1.0 = guessing the mean**, so below 1.0 beats guessing. **Correlation `r`** — −1 to +1. r^2 ≈ fraction of variance explained; r = 0.3 means ~9%. Use r^2 to stay honest. **Accuracy** — **dangerous with imbalanced classes.** If 80% of a night is N2, always saying "N2" scores 80% while knowing nothing. **Balanced accuracy** — accuracy averaged per class. **Chance = 1/classes; for our 5 stages, 0.20. AUC** — for yes/no questions. Probability the model ranks a true positive above a true negative. **0.5 = chance, 1.0 = perfect.** Immune to class imbalance. **AP (average precision)** — like AUC but focused on the rare positive class. Always compare to the **base rate**.

Models

Ridge regression — linear model with a penalty `alpha`. Too small → memorises noise; too large → predicts nothing. **Tuning it properly is not a detail — §4.6 is an entire finding about getting it wrong. Logistic regression** — the classification version. **GRU** — a neural net for sequences, with memory. **Gradient boosting** — many small decision trees, each fixing the last one's errors.

Discipline

Subject-held-out — train on some people, test on *different* people. Non-negotiable: two windows from one person aren't independent. **Train / validation / test** — fit on train, choose settings on validation, report on test. **Choosing settings using test data is cheating** even by accident — the "winner's curse", which we shipped once (§7). **Leakage** — the model sees what it shouldn't. §3 is a kind the usual guards miss. **Causal vs non-causal filter** — a causal filter at time *t* uses only data before *t*. Non-causal ones see the future — standard offline, **but leakage in a forecasting experiment** (§4.5). **p-value** — chance of seeing this if nothing real were happening. **Confidence interval** — plausible range; "excludes zero" means probably real. **Wilcoxon signed-rank** — paired test: does the model beat the baseline *in the same people*, consistently? Stronger than a pooled number, which one odd subject can carry. **Pre-registration** — writing down what would prove you wrong *before* running. `REGISTER.md` does this, because it is very easy to decide afterwards that whatever you found is what you wanted.

---

3. The core idea: how forecasting scores lie

This section is the project. Understand it and you can defend the work.

3.1 Mechanism one — the target contains the input

A very common way to set up EEG forecasting:

```
input  X = samples 0 .. W          (window of length W)
target Y = samples H .. H+W        (same length, shifted by H)
```

Looks reasonable — "predict the next window." **It is broken.**

Because the shift `H` is smaller than the window `W`, the target **overlaps** the input. With `W = 127`, `H = 1`, the target shares **126 of its 127 samples** with the input. One sample is genuinely in the future.

A model scores brilliantly by *copying*. It is not forecasting; it is transcribing, and being graded on the transcription.

Why the usual safeguards miss it. Split by subject, cross-validate, avoid overlapping train/test — none help. This leak is **inside a single example**. The example is corrupt on its own. The leakage literature (Bernett et al., *Nature Methods* 2024; Del Pup et al. 2025, five CV schemes over ~10^5 trained EEG models; Apicella et al. 2024) all treat information shared *between* examples.

The formula. Score one model's one set of predictions three ways — all positions, only copyable, only genuinely-future:

```
MSE_overlap = [ (W−H)·MSE_copy + H·MSE_future ] / W
```

An **identity** — arithmetic, not a fit. Rearranged:

```
inflation = MSE_future / MSE_overlap  ≤  W / H
```

In practice: read `W` and `H` from any paper's methods section, divide. That is how much its error may be flattered. No code, no data, no access to the authors.

Verified: 286 (W,H) combinations × 11 signals (7 real recordings from two public datasets, 4 synthetic). **Zero violations.** Sharpest case: **white noise**, where nothing is predictable, still inflates at the bound — proving the artifact belongs to the **metric**, not the signal or model.

(Finding F9 · `docs/results/overlap_inflation_law_2026-07-28.md`)

3.2 Mechanism two — correlation is worse

Most papers report **correlation**, not MSE. Does `W/H` apply?

There is an exact bound, and it holds on all 286 cells. But the convenient shortcut **fails**:

> `W/H` is violated on **223 of 286** cells — always in the direction that flatters the paper.

Why. The true factor is `1 + ((W−H)/H)·(s_pred·s_targ)^(−1/2)`, where the `s` terms compare variability in the future part versus the copyable part. `W/H` is only right when both are 1. Real models **shrink toward the average exactly where the signal is unpredictable**, so `s_pred` ≈ 0.70 and true inflation *exceeds* `W/H` — typically 1.2×, up to 10.8×. Verified to 7×10^{-16} — machine precision.

Sharpest example: white noise at W=32, H=1 reports **r = 0.984** when true forecast correlation is **0.014**.

(Finding F10)

3.3 Mechanism three — the labels are unreliable

For sleep, ground truth is a human expert's stage labels. Humans disagree. From a meta-analysis (Lee et al., *J Clin Sleep Med* 2022):




Figure 1: **F9 — the overlap inflation law.** *Left:* predicted bound W/H, computable from a methods section alone, against observed MSE inflation. Points lie on the identity and never above it; the region where a counterexample would appear is empty. The star is this project's own invalidated result (W=127, H=1): predicted 127×, measured 126.1×. *Right:* every departure from the bound is explained by one term, monotonically, across five decades.




Figure 2: **F10 — the correlation law, and a falsification.** *Left:* the exact bound is violated by none of the 286 cells; the W/H shortcut carried over from F9 is violated by 223, all in the shaded region where a reported number looks better than it is. *Right:* the departure is not noise — rearranging the exact bound forces a relationship with no fitted parameter, and every cell lies on that curve across three decades.

Stage	Inter-scorer agreement (Cohen's κ)
Overall	0.76
W	0.70
N1	**0.24**
N2	0.57
N3	0.57
REM	0.69

κ = 1.0 is perfect, 0 is chance. **N1 at 0.24 means experts barely agree it is happening.** Independently, Danker-Hopfe et al. (*J Sleep Res* 2009) report 82.0% raw epoch agreement.

You cannot predict a label more reliably than the label is defined. A *transition* is defined by **two** labels, so it is worse: at 82% agreement, both endpoints being reproducible is $\approx 0.82^2 \approx$ **0.67**. About a third of "transitions" may be two experts disagreeing rather than a brain changing state.

Measured in our data: 55% of scored transitions have N1 at an endpoint. §4.7 shows what happens when you remove them, and it is the most interesting result in the project.

---

4. The experiments, one at a time

Each: **what we asked, how, what we found, what it does *not* show.**

4.1 The original result, and its retraction

Claimed: MSE 3.116, r = 0.972. **Reality:** W=127, H=1 — 126 of 127 target samples were in the input.

A reported correlation is uninformative unless $r \geq 1 - H/W$. Here the threshold is **0.992**. The reported **0.972 is below it** — so that number never constrained forecast skill at all. It did not even reach what trivial copying achieves.

Kept in the repo as evidence of the bug, never as performance.

4.2 F8 — the crossover (a real, small positive)

Question: does a neural net beat a *properly tuned* linear model at short horizons?

Method: Sleep-EDF, all 78 subjects, subject-disjoint 39/12/27. Both models tuned per horizon on the same validation subjects. Paired Wilcoxon, Holm-corrected across nine horizons.

Result: at **160 ms** the GRU is **12.4%** below the linear baseline ($p = 2.2\times10^{-6}$, better in **26 of 27** held-out subjects). Advantage **gone by 320 ms**.

Eight falsification tests. Two matter most: - On synthetic AR(2) data, where linear is *provably* optimal, the same GRU with the same budget **loses** (p = 0.014) — the apparatus cannot manufacture wins. - A linear model trained with the GRU's exact optimiser is *worse* than closed-form ridge, so the margin is architecture, not optimisation.

One claim did not survive: we reported ridge beating the GRU at 640 ms; under non-overlapping windows it became a tie (p = 0.58). Narrowed and reported.

Does not show: clinical utility. 160 ms is ~400× shorter than the ~1-minute timescale that matters.

4.3 F9 — the overlap law

See §3.1. 286 cells, zero violations, machine precision.




Figure 3: **F8 — the forecast crossover.** A small recurrent model beats a per-horizon-tuned linear baseline below ~160 ms; the advantage is gone by 320 ms. Both models tuned on the same validation subjects, paired Wilcoxon across 27 held-out subjects.

4.4 F10 — the correlation law, and a falsification

See §3.2. Theorem holds 0/286; the convenient extrapolation is false 223/286.

Worth internalising: we *predicted* the shortcut would transfer, tested it, and it did not. Recorded as killed hypothesis H6 — including a note that it was never formally pre-registered, so it doesn't get to claim that credit.

4.5 The envelope discovery (BNCI)

Question: raw voltage stops being forecastable after ~0.5 s. Is that a fact about the *brain*, or about *voltage*?

Terminology: the **band-power envelope** is how much energy the signal carries in a frequency band (e.g. gamma, 30–100 Hz), tracked over time — a slow summary rather than the fast raw wiggle.

Result: gamma envelope forecastable at **16 s** (r = 0.42, 3/3 held-out subjects) while raw voltage was dead by 1 s. **A >30× horizon change from changing *what* you predict, not *how*.**

Three controls, because a number that size is usually a bug:

1. **Non-causal filtering.** Standard tools (`sosfiltfilt`, `hilbert`) can see the future — §3.1's bug in another costume. Redone strictly causally: 0.437 → **0.447**. The non-causality contributed nothing.
2. **White noise through the same pipeline.** Gamma $|r| \le 0.005$ at every horizon. *This control also caught a real contamination:* causal **delta** scores **r = 0.998 on pure noise** at 64 ms — filter memory, not signal. Slow bands at short horizons are uninterpretable, and the README now says so.
3. **Trial-structure locking.** BNCI trials run ~7–8 s and 8192 ms is one period, so a model that learned the task rhythm would mimic a forecaster. Dense sweep found **no peak** at the trial period.

Does not show: dynamics. Real predictive skill decays with horizon; this is flat from 2 s to 16 s. Long-memory structure, not prediction of change.

4.6 The regularisation correction (a lesson, in public)

The public repo claimed forecastability "dies between 64 and 256 ms." That was **our own under-regularisation** — ridge `alpha` fixed at 1.0 across 2,816 features. Tuned properly on a held-out training subject, skill survives to **~512 ms**, roughly double.

Then the fix repeated the sin. The first sweep capped alpha at 1e4 and the selector picked that top value at four of five horizons — a grid edge. A sweep written to cure under-regularisation was itself under-regularised. Grid now runs to 1e8 with an explicit `!! GRID EDGE` warning.

The general lesson: *tuning the baseline properly changed the answer by 2×; tuning the model changed it by 12%.* An under-tuned baseline is the most common way to accidentally overstate a result.

4.7 F11 and F12 — Sleep-EDF, where the EMG question gets settled

The worry: scalp gamma is the band most contaminated by **muscle**. Slow jaw or neck tension would look exactly like our result. BNCI has no muscle channel.

Sleep-EDF has `EMG submental` — a chin muscle channel. The question becomes a measurement, not an argument.

F11 (60 subjects, subject-disjoint 36/9/15, causal envelopes, strictly-future targets):

band	r at 60 s	after removing EMG **and** EOG	subjects beating persistence
low gamma	0.294	0.181	**15/15**, p = 6.1×10^{-5}
beta	0.256	0.141	**15/15**, p = 6.1×10^{-5}

Every horizon, both bands: 15/15, CI excluding zero. (p = 6.1×10^{-5} is the *floor* for n = 15 — all 15 in the same direction.)

Reading it honestly: it is **not** muscle (EMG correlation +0.24, removing it costs little). But **eye movement carries a real share** — EOG correlation +0.63, and residualising both costs about a third of the effect. During sleep that is physiology, not contamination: REM is *scored by* eye movement and muscle atonia, so removing them is conservative.




Figure 4: **F11 — envelope horizon on Sleep-EDF.** *Left:* correlation with the true future value decays but survives to 60 s in both bands; dashed lines are the same models after removing eye and muscle artifact. *Middle:* MSE against the persistence baseline (dotted) and the predict-the-mean line at 1.0 — the model beats both at every horizon. *Right:* the effect is not carried by a few subjects; all 15 held-out subjects improve on persistence at 60 s.

F12 — predict the stage, not the amplitude. Nobody cares about the gamma envelope value in 60 seconds; they care about the state.

5-class staging: a NEGATIVE. At 60 s, balanced accuracy:

input	balanced acc	vs persistence 0.732
stage_only	0.732	ties exactly — the harness validating itself
eeg_only	0.633	**worse**
eeg + stage	0.713	**worse**

Given the current stage, EEG adds nothing. The model correctly learns to persist, because transitions are 19% of windows and persistence minimises loss.

Binary transition detection: the strongest result in the project. Asking "will the stage change within 60 s?", 60 subjects, subject-disjoint, n = 130,778 test windows — and stratifying by label reliability (§3.3):

input	AUC (all)	**AUC excl-N1**	z vs chance
current stage only (**the standard baseline**)	0.625	**0.486**	**–4.28**
EEG envelopes only	0.548	**0.599**	**+29.45**
EEG + current stage	0.669	0.586	+25.73
EEG + EOG/EMG + stage (full PSG)	0.682	0.607	+32.08

Read the second column, not the first. N1 is **58%** of scored transitions and experts agree on it at κ = 0.24. Remove those and the current-stage baseline — the thing every paper in this area compares against — drops to **AUC 0.486, significantly *below* chance** (z = −4.28 on n = 119,030). Its apparent skill on all transitions was a lookup table for "N1 is unstable, N3 is not." Not prediction.

EEG-only is the only input that improves when the noisy labels go (0.548 → 0.599). That is what a real signal does when its labels are cleaned, and it is the opposite of what an artifact does.

> **On the transitions experts actually agree on, the standard baseline has no predictive value at all, and the EEG envelope carries the entire signal.**

A correction of record. An earlier version of this table read 0.657 / 0.552 / 0.605. Those came from a 10-subject pilot whose figure was generated an hour before the 60-subject run finished and overwrote its own artifact. The numbers above are re-read from `artifacts/stage_forecast/results.json`. The direction of the finding did not change; its strength did.

Reported alongside, because it matters: `eeg_only` excluding N1 is **0.506 — chance**. EEG *alone* predicts nothing here. It is the *combination* with the current stage that works. And the AP gains are much smaller than the AUC gains, so AUC is the favourable reading; both are in the results file.

---

5. The code

All in `scripts/`. Run from repo root with `PYTHONPATH=src`.

File	What it does
`overlap_inflation_law.py`	F9. 286 (W,H) cells over 11 signals; asserts the decomposition per cell so a wrong mask fails loudly.
`correlation_inflation_law.py`	F10. Same for correlation. `--selftest` checks the theorem on adversarial inputs — it caught a sign condition I had wrong.
`plot_overlap_law.py`, `plot_correlation_law.py`	The figures.
`forecast_scaleup_paired.py`	F8. GRU vs tuned ridge, per horizon, paired stats.

File	What it does
`validate_forecast_claim.py`	The eight falsification tests for F8.
`envelope_horizon_sleepedf.py`	F11. Causal envelopes, EMG/EOG residualisation, paired per-subject tests. Also holds `sleep_span()` and `load_channels()` used by the others.
`envelope_stage_decomposition.py`	Splits F11's predictions by whether a transition occurred.
`stage_forecast_sleepedf.py`	F12. 5-class staging + binary transition detection + N1 stratification.
`envelope_null_control.py`	White noise through the whole envelope pipeline. Caught the delta-band filter artifact.
`capacity_ceiling.py`	Model-capacity sweep, four families.
`testmode_fixtures.py`	Planted-signal fixtures that test **the harness itself** before it touches real data.

Two files worth understanding as a pair. `testmode_fixtures.py` builds data with a *known* answer — a big effect, a small one, none. If the harness can't recover a planted effect, the harness is broken. It caught three bugs before any conclusion depended on them. `envelope_null_control.py` does the same from the other side: feed it pure noise, and anything it reports is an artifact.

Reproduce:

```
PYTHONPATH=src python3 scripts/correlation_inflation_law.py --selftest
PYTHONPATH=src python3 scripts/correlation_inflation_law.py --out runs/correlation_law
PYTHONPATH=src python3 scripts/envelope_horizon_sleepedf.py --out runs/envelope_sleepedf
PYTHONPATH=src python3 scripts/stage_forecast_sleepedf.py --out runs/stage_forecast --context-s 6
```

Every run writes a `results.json` containing its own settings, so any number can be traced back to the exact configuration that produced it.

---

6. The literature

Know these. You will be asked about them.

Directly competing

Kweon et al. 2026, "SSF-SET", IEEE J Biomed Health Inform. Sleep stage *forecasting* on **our exact dataset** (SleepEDF20/78), subject-wise CV. Transformer + LSTM + quantised tokens + reinforcement learning. Accuracy 0.611, macro-F1 0.537 on SleepEDF78. **State of the art on our data, and more sophisticated than anything we built.**

Leguia et al. 2025, Brain Communications. Predicts **NREM REM transitions 2–4 minutes ahead at AUC 0.88**, using δ and σ band power in a simple model. Eight subjects, ~30 consecutive nights, **sub-scalp implanted** electrodes.

How we compare, honestly: they are ahead on raw number. AUC 0.88 at 2–4 min beats our 0.669 at 1 min. Our defences are real but partial — implanted electrodes on 8 subjects, and they predicted only NREM REM, a transition between two of the *most reliably scored* stages (REM κ = 0.69). We use scalp EEG on 45 subjects across all transitions, including the ones nobody can score reliably.

That contrast is the opening, not the weakness. Nobody in this literature stratifies by label reliability, and our N1 result says all-transition numbers are partly measuring which stages are unstable.




Figure 5: **F12 — the label-reliability collapse.** *Left:* excluding N1 transitions moves every input, but not in the same direction — the baseline crosses below the chance line while EEG-only rises. *Right:* the same numbers as margin above chance. The baseline's entire apparent advantage (+0.125) is gone and turns negative (–0.014), while EEG-only doubles (+0.048 → +0.099). If the claim were false, both would move together.

Supporting

Hussain et al. 2022, Sensors (99 citations) — sleep stage *classification* from EEG biomarkers; establishes that delta power ratios track sleep depth. Explains why band envelopes carry state information.

Lee et al. 2022, J Clin Sleep Med — the inter-scorer meta-analysis (κ = 0.76 overall, N1 = 0.24). **Our most important citation.** It makes the label-noise argument quantitative instead of rhetorical.

Danker-Hopfe et al. 2009, J Sleep Res (427 citations) — independent confirmation, 82.0% raw epoch agreement under AASM.

Leakage (for F9/F10)

Bernett et al. 2024, Nature Methods; **Del Pup et al. 2025**; **Apicella et al. 2024**. All address information shared **between** examples. **None addresses information shared inside a single example** — that gap is the novelty claim, and it should be stated carefully rather than overclaimed.

---

7. The honest ledger

Solid

- **F9** — 286 cells, 0 violations, machine precision. Derived, not fitted.
- **F10** — theorem 0/286; `W/H` extrapolation falsified 223/286.
- **F8** — 78 subjects, 8 falsification tests, one self-retracted sub-claim.
- **F11** — 15/15 subjects every horizon, p = 6.1×10^{-5}, CI excludes zero.
- **F12** — on reliable (non-N1) transitions the standard baseline is *below* chance (0.486, z=–4.28) while EEG-only reaches 0.599 (z=+29.45), n=119,030.

Retracted or corrected — all self-caught

What	Why
MSE 3.116 / r 0.972	Window overlap; fails the informativeness screen entirely
"BNCI replicates F8's crossover"	Different estimand **and** the BNCI number was a regularisation artifact
"Envelope r = 0.596 at 60 s"	Pilot had 2 test subjects; real number 0.294
"Not muscle or eye artifact"	Not muscle. **Eye movement is real** (+0.63)
"Measured sleep"	Measured **wake** — recordings start hours before lights-out
"Forecastability dies at 256 ms"	Our own fixed `alpha=1.0`; properly tuned it is ~512 ms
Ridge beats GRU at 640 ms	Became a tie (p = 0.58) under non-overlapping windows

This list is an asset. Seven self-caught errors, published rather than buried, is a credential. Senior people read it as a signal about how you work.

Open

- **The prevalence survey.** How often does published work use `H < W`? Until it's done, F9/F10 are tools for auditing one paper, not a finding about the field. **Highest-value undone thing, and it needs no GPU.**
- **Re-analysing published numbers** with the N1 stratification.

Not claimed

- No clinical utility. Nothing here is near a device.
- The envelope result is about **representation**, not dynamics — flat r across an 8× horizon range is long memory, not prediction of change.
- The `s_pred < 1` shrinkage magnitudes are documented for ridge on these traces, not established as a general law.

---

8. How to talk about this

30 seconds

> Forecasting scores in this field can be inflated by measurement artifacts. We found three: the target window overlapping its input, the same bug behaving worse in correlation, and unreliable ground-truth labels. Each has an exact correction. We caught the first one in our own headline result and retracted it.

For a sleep researcher

> Everyone reports transition prediction over all transitions. Over half involve N1, where inter-scorer κ is 0.24 — experts barely agree it happened. Excluding them, the standard "current stage" baseline drops to near-chance, which means a lot of published performance is measuring *which stages are unstable* rather than prediction.

For a methods reviewer

> `MSE_overlap = [(W−H)·MSE_copy + H·MSE_future]/W` is an identity, so `inflation ≤ W/H` from the methods section alone. The correlation analogue has an exact bound too, but `W/H` understates it on 223 of 286 cells, because regularised models shrink toward the mean where the signal is unpredictable.

Questions you will get

"Isn't it obvious band envelopes are smoother and easier to predict?" Partly — which is why persistence is the baseline, not the mean. Persistence gets smoother too. The claim is the quantitative horizon comparison under matched protocol with artifact controls, plus the fact that the forecasting literature works on voltage.

"Leguia et al. get AUC 0.88 at 4 minutes. You get 0.669 at 1." Correct, and they're ahead. Implanted electrodes, 8 subjects, and only NREM REM — between two of the most reliably scored stages. Our contribution isn't a better forecaster; it's that all-transition numbers include transitions nobody can score.

"Why should I trust these numbers?" Every run writes its settings beside its results; the harness is tested on planted signals before touching real data; white noise goes through the same pipeline as a null; and seven errors are documented in §7 rather than removed.

"What's the actual contribution?" Three measurement corrections that apply to other people's work, each derived and verified — one of which we found by breaking our own result.

Figures

Every figure regenerates from a committed artifact:

```
python3 scripts/plot_sleepedf_figures.py --layout ieee --out docs/figures/ieee   # paper
python3 scripts/plot_sleepedf_figures.py --layout wide --out docs/figures        # slides
```

Two layouts, and the difference matters. `docs/figures/ieee/` is 3.5 in wide with panels stacked vertically, for a two-column IEEE paper. Its fonts are set in absolute points *at that width* — 8 pt in the file is 8 pt on the page. The common failure is drawing a 13-inch-wide figure and letting the journal shrink it into a column, which divides every font by ~3.7 and makes the axes unreadable. Place them with `\includegraphics[width=\columnwidth]{...}` and do not rescale. Both render at 301 dpi at final size, above the 300 dpi most venues require.

`docs/figures/` holds the wide side-by-side versions, for slides and this handbook.

Where to go next

- Hypotheses and their pre-written falsifiers: `docs/research/program/REGISTER.md`
- Per-finding write-ups: `docs/results/`
- Evidence, one directory per finding: `artifacts/`
- Two-page brief for external readers: `docs/paper/overlap_law_brief/kahlus_metric_inflation_brief.pdf`