A closed-form bound on metric inflation in windowed forecast evaluation

And a corrected, powered EEG forecasting benchmark

Kahlus / Neural-CASP

30 July 2026

Repository `Kahlus-V1`, branches `finding/overlap-inflation-law`, `finding/forecast-crossover-f8`

Scope. Three results: an exact bound on how much a window-scored forecast metric can overstate forecast skill — derived, not fitted, and violated by no (W, H) pair on any trace we tested; the corresponding result for *correlation*, which turns out *not* to inherit the same constant, so the convenient extrapolation is falsified here rather than left to a reader; and a corrected benchmark that survived eight falsification tests, one of which broke a secondary claim we had made. Both failures are reported rather than removed. Every number is traceable to a named artifact.

1 The problem

A forecasting task is only a forecast if the target does not contain the input. The construction below is common in the biosignal literature and violates that silently. From a sequence of length $W+H$:

$$X = \text{seq}[0\!:\!W], \qquad Y = \text{seq}[H\!:\!H\!+\!W].$$

Then $Y[k] = X[k+H]$ whenever $k < W-H$: of the W scored target positions, $W-H$ are **copyable** — literally present in the input at a shifted index — and only H are strictly future. Averaging over all W positions therefore dilutes a genuine forecast error with positions a model can copy.

This is not the leakage the field guards against. It survives subject-wise partitioning, nested cross-validation and non-overlapping strides, because it lives *inside a single training example* rather than across the train/test split — and the leakage literature we could find (Bernett et al., *Nat. Methods* 2024; Del Pup et al. 2025, five CV schemes over 10^5 trained EEG models; Apicella et al. 2024) treats only information shared *between* examples.

2 The law

Score **one model's one set of predictions** under three masks — all positions, the copyable prefix, the strictly-future tail. No argument about capacity, training or tuning can explain a gap between them. By construction,

$$\text{MSE}_{\text{overlap}} = \frac{(W-H)\,\text{MSE}_{\text{copy}} + H\,\text{MSE}_{\text{future}}}{W},$$

an identity rather than a fit, which rearranges to

$$\boxed{\text{inflation} \;\equiv\; \frac{\text{MSE}_{\text{future}}}{\text{MSE}_{\text{overlap}}} \;=\; \frac{W/H}{1 + \frac{W-H}{H} \cdot \frac{\text{MSE}_{\text{copy}}}{\text{MSE}_{\text{future}}}} \;\le\; \frac{W}{H}.}$$

Equality holds as $\text{MSE}_{\text{copy}} \to 0$. The bound is one-sided: a real result can never exceed it, so W/H is always safe as a worst case.

W/H **requires no data** — only the window length and horizon printed in a methods section. A paper reporting a 128-sample target window at horizon 1 is reporting a number that may be up to 128× better than its forecast error.

3 The same question for correlation, and a negative answer

Most work in this area leads with r, not MSE, so whether W/H transfers decides how far the bound reaches. Correlation is a ratio, not a per-position average, so the identity above does not apply. An AM-GM argument on the pooled deviation moments still gives an exact, assumption-free bound,

$$|r_{\text{overlap}}| \;\le\; \left|\,\mu\, r_{\text{copy}} + (1-\mu)\, r_{\text{future}}\right|,$$

with μ the variance share of the copyable positions — a reported correlation is at most a variance-weighted blend of how well a model copies and how well it forecasts. Violated by none of the 286 cells.




Figure 1: Left: predicted bound W/H against observed MSE inflation, log–log. Points lie on the identity and never above it; the region where a counterexample would appear is empty. The star is this project's own invalidated result (W=127, H=1): predicted 127×, measured 126.1×. **Right:** every departure is explained by the single term $\mathrm{MSE}_{\mathrm{copy}}/\mathrm{MSE}_{\mathrm{future}}$, monotonically, across five decades. Triangles synthetic, circles real recordings.

But W/H does not carry over. Expanding μ gives the exact correlation-gap bound $1 + \frac{W-H}{H}(s_p s_t)^{-1/2}$, where s_p, s_t are the future/copy per-position variance ratios of the prediction and target; W/H is only the case s_p=s_t=1. Targets are variance-stationary (s_t median 0.996), but predictions are not: a regularised model shrinks toward the mean precisely where the signal is unpredictable (s_p median 0.700). So the true deflation *exceeds* W/H — median 1.21×, up to 10.8× — on **223 of 286 cells**, always in the direction that flatters the paper, and worst where there is least real signal. The shrinkage form reproduces the measured bound to median relative error 7.1×10^{-16}, so this is a mechanism, not an anomaly. **The sharpest case is white noise at W=32, H=1: reported $r = 0.984$, true $r_{\mathbf{future}} = 0.014$.**

What survives with no data is one-directional: $r < 1 - H/W$ proves a reported correlation bounds nothing; clearing that screen does not prove it informative.




Figure 2: Left: the exact correlation bound is violated by none of the 286 cells; the W/H shortcut carried over from the MSE law is violated by 223, all of them in the shaded region where a reported number looks better than it is. **Right:** the departure is not noise. Rearranging the exact bound forces $(\text{exact} - 1)/(W/H - 1) = (s_p s_t)^{-1/2}$ with no fitted parameter, and every cell lies on that curve across three decades. W/H is correct only where the dotted line crosses it — i.e. only for a model that does not shrink.

4 Verification

Both laws are checked on the same 26-point grid, $W \in \{32, 64, 128, 256\} \times H \in \{1, \ldots, 128\}$ with $H < W$, over 11 traces: **7 recorded channels** from Sleep-EDF (Fpz-Cz, Pz-Oz, EOG) and MIT-BIH polysomnographic (ECG, blood pressure, O2-A1 EEG, nasal respiration), plus 4 synthetic processes (white noise, AR(1) $\phi \in \{0.5, 0.95\}$,

random walk) — picked for spread in autocorrelation rather than for count.

No (W, H) pair violated either exact bound, on any trace (286 grid cells). For the MSE law, observed/bound median 1.000, mean 0.981, matching the exact formula to a maximum relative error of 1.3×10^{-15} — machine precision, because the relation is an identity, and the code asserts the decomposition per cell so an incorrect mask fails loudly rather than producing a plausible curve. Departures are monotone in the correction term: the law is not approximately right by luck, it is exactly right with a known correction. White noise, where nothing whatever is predictable, still inflates at the bound — the artifact belongs to the *metric*, not to the signal or the model.

5 The corrected benchmark

Strictly-future scoring on real data: Sleep-EDF sleep-cassette, all 78 subjects, subject-disjoint 39 / 12 / 27, zero input–target overlap. Both models tuned per horizon on the same validation subjects, the ridge grid extended until no horizon selected a grid edge. Per-subject MSE, paired Wilcoxon, Holm-corrected across nine horizons.

h	ms	persistence	ridge-AR	GRU	Δ	Holm p
16	160	1.3814	0.8298	**0.7268**	**+0.1031**	$\mathbf{2.2 \times 10^{-6}}$
32	320	1.7600	**0.8700**	0.8756	−0.0056	n.s.
256	2560	1.8746	**0.9942**	1.0099	−0.0157	1.3×10^{-7}

At 160 ms the GRU is 12.4 % below a converged linear baseline on 26 of 27 held-out subjects and 47.4 % below persistence; the advantage ends by ∼320 ms. Eight falsification tests followed. Two matter most: on a synthetic AR(2) process, where the optimal predictor is provably linear, the same GRU with the same tuning budget **loses** to ridge (p=0.014), so the apparatus cannot manufacture wins; and a linear model trained by the GRU's exact optimiser is *worse* than closed-form ridge at every horizon, so the margin is architecture, not optimisation. **One claim did not survive:** we had reported tuned ridge beating the GRU at 640 ms (p=4.1 × 10^{-5}), but under non-overlapping windows that becomes a tie (p=0.58), so the claim is narrowed to "the advantage ends by 320 ms" rather than "linear wins beyond it".

Not claimed. No clinical utility — 160 ms is roughly 400× shorter than the ∼1 minute precursor timescale of interest. Single channel, one corpus. The prevalence survey, establishing how often published work uses $H < W$, is not done; that is what would turn these from tools for auditing one paper into a finding about the field.

Artifacts. `artifacts/{overlap_law, correlation_law, forecast_crossover}/` hold the cells, figures, benchmark and the eight-test validation, each beside its write-up in `docs/results/`. Produced by `scripts/{overlap_inflation_law, correlation_inflation_law, forecast_scaleup_paired, validate_forecast_claim}.py`; the correlation harness carries a `--selftest` for the theorem. The invalidated 3.116 MSE / r=0.972 result is retained in `docs/results/a100-run-history.md` as evidence of the bug, not as performance — note it fails the $r < 1 - H/W$ screen, so it never bounded forecast skill at all.