Yaesu FT-2D Files

Overview

This folder contains Programming files for the FT-2D

Release: Draft Feb 16

The files were prepared using the RT-Systems FT-2D software with Data extracted from the WIA data set.

Files

- VKBV2D.rsf – basic settings file options

- VKBV2D.FT2D – template used to import more memories, includes the bank names.

- VKBVyymondd.FT2D – most recent RT Systems file

- BACKUP.dat – generated SD card file.

Radio Load Steps

backup.dat can be copied to a sd card and loaded to the radio.

- Insert and format an SD card in the radio.
- Use the 1. BACKUP> Write to SD> Write OK.
- Power off handset and unload card, insert into PC.
- The standard format on the radio sometimes sets a read only flag on files and directories.
- Right click/Properties on the FT2D Folder on the drive just mounted and unset the Read-Only Attribute
- The file just created will be x:\FT2D\BACKUP\BACKUP.dat copy or rename this file as a backup and move the provided backup.dat to the same folder. Eject the card and load to radio.
- Load the backup SD CARD> Backup > Read from SD> Read OK. [Sometimes this comes back straight away and it hasn't loaded. Repeat and it seems to load properly.. you will see the flashing Waiting message and SDSymbol]
- Configure your call sign and APRS
    - Both menus (Callsign and APRS) available from the DISP
    - [For some reason the callsign field is filled with spaces and you first have to go

one rightarrow to wrap to the beginning of line.]

- APRS call sign is APRS>23 CALLSIGN.
- Testing APRS – the preconfigured manual position in "24 MY Position" is the Opera House.

The source files for RT Systems are VK2_yymondd.FT2D and VKBVFT2D.rsf.