

CW300 SPRING CHANGE PROCEDURE.**DRG. No. CW300SCP.****Spring Change Kit Part No. CW300SK:-**

Spring, Release Lever	CW 314/P9	1 off
Spring, Back Release	CW 315/P1	1 off
Bolt, Shear	AN4-13A (Mod)	2 off
Nut, Shear (Thin)	AN316-4	2 off
Distance Piece/Bush	CW 304	2 off

1. GENERAL.


- 1.1 Although not essential in the interest of reliability and to avoid repetitive maintenance it is recommended that both the Back Release and Release Lever Springs are changed at the same time. Lubricate both bushes with GP grease before installation. Use **Aeroshell 3** or its equivalent for general lubrication.
- 1.2 Although it is possible to change both springs without the use of special tools the procedure is made simpler and quicker if the tools shown in the attached Drg. No. CW3400TK are locally manufactured or purchased from Cair Aviation Ltd..

2. PROCEDURE.**IMPORTANT NOTE.**

TO ENSURE THAT THE ISU DATUM IS NOT DISTURBED UNIT SUB - ASSEMBLIES MUST NOT BE EXCHANGED FOR SUB-ASSEMBLIES FROM OTHER UNITS AND UNDER NO CIRCUMSTANCES SHOULD THE ADJUSTER BE RE-SET OR TAMPERED WITH.

IF THE UNIT FAILS THE TESTS GIVEN IN PARA. 3 BELOW THE UNIT SHOULD BE RETURNED FOR OVERHAUL.

- 2.1 Remove the unit from the glider, thoroughly clean with lead free petrol or kerosine and dry with an air blast.
- 2.2 Remove the Lever Carriage 1/4" UNF pivot bolt, nut and washer. Discard nut and bolt.
- 2.3 Withdraw the Lever Carriage, complete with bush and shims, from the Casing. Discard the bush.
- 2.4 Using the 3/16" Drift remove the the 3/16" Cross tube which locates the Release Lever spring legs from the Casing.

Amdt P.11.
February 2004