

CW400 SPRING/BUSH CHANGE PROCEDURE. (Drg. No. CW400SCP)

Spring Change Kit Part No. CW400SK:-

Spring, Release Lever	CW 414/P9	1 off
Bolt, Shear	AN4-13A(M)	1 off
Nut, Shear (Thin)	AN316-4	1 off
Distance Piece/Bush	CW 304	1 off

Spring Change Kit Part No. CW400SKFE (Bocian only).

Spring, Release Lever	OM 123/14	1 off
Bolt, Shear	AN4-13A	1 off
Nut, Shear (Thin)	AN316-4	1 off

1. GENERAL.

- 1.1 Although it is possible to change the spring without the use of special tools the procedure is made simpler and quicker by using the 3/8" Drift and Bullet Guide shown in Drg. No. CW3400TK which can be locally manufactured or purchased from Cair Aviation Ltd. The bush should be lubricated with GP grease before installation. Use **Aeroshell 3** or its equivalent for general lubrication.

PROCEDURE.

IMPORTANT NOTE.

TO ENSURE THAT THE ISU DATUM IS NOT DISTURBED UNIT SUB-ASSEMBLIES MUST NOT BE CHANGED FOR SUB-ASSEMBLIES FROM OTHER UNITS AND UNDER NO CIRCUMSTANCES SHOULD THE ADJUSTER BE RE-SET OR TAMPERED WITH.

IF THE UNIT FAILS THE TESTS GIVEN IN PARA. 3 BELOW THE UNIT SHOULD BE RETURNED FOR OVERHAUL.

- 2.1 Remove the Unit from the glider and thoroughly clean with lead free petrol or kerosine and dry with an air blast. Where fitted, remove the 2BA Countersunk Stop bolt and retain.(CW417 Lever only).
- 2.2 Remove the 1/4" UNF lever pivot bolt, nut and washer. Discard the bush, nut and bolt.
- 2.3 Withdraw the Lever/Lever Carriage assembly, complete with bush and shim washers. Discard the Release Lever spring.
- 2.4 Using the 3/8" Drift remove the 3/8" Cross Tube which locates the spring legs in the top of the Casing.
- DOK 1*