

INSTALLATION DATA.

DRG.No. CW3400INS.

CW 300.

The CW300 is a Centre of Gravity positioned unit utilising three standard M6 8.8 mounting bolts. Using a two bolt mounting the unit can be positioned at three angles relative to its Longitudinal Datum i.e. 0° , $+10^\circ$ and $+20^\circ$. In the interest of cost only the rear and 0° mounting holes are bushed, however if required the unit can be supplied with bushes fitted in all five mounting holes.

The Longitudinal Datum is shown on DRG No. CW3400INS Sht. 1.

The unit is driven by a five hole Lever Carriage and to accommodate varying installation requirements eight types of operating lever are provided. Where space is at a premium the aircraft operating system may also be connected direct to the Lever Carriage.

Levers are supplied in two formats namely, solid and fork ended. Connection of the solid levers to the aircraft system is effected by two adjustable Link Plates which can be fitted on to the lever in five positions, all Lever Carriage/Lever /Link Plate attachments are standardised at 5mm diameter.

Lever/Link Plate/Direct Drive information is shown in DRG No. CW3400INS

The standard long straight lever (Part No. CW302 and 302FE) provides an operating radius of 68.5mm and is the lever used for pre-delivery test purposes. This lever can be connected direct to the cockpit release control but should the installation utilise any of the shorter levers or have the aircraft operating system connected direct to the Lever Carriage, the operating loads will increase proportionally and some form of multiplier must be incorporated in the aircraft system.

Automatic Back Release occurs at $85^\circ \pm 5^\circ$ relative to the Longitudinal Datum at a cable load of 20 daN. The angle relative to the unit datum at which each unit back releases is recorded in the Unit Log Book.

Unit Weight = 0.666 Kg. (1.5 lbs)