

CW 400.

The CW400 is a nose positioned aerotow unit utilising two or more standard M6 8.8 mounting bolts. Four mounting holes are provided, three being bushed. If required bushing can also be fitted to the fourth mounting hole. The unit is not adjustable relative to its Longitudinal Datum which is shown on Drg. No. CW3400INS Sht. 2

The unit is supplied with two lever options.

The first has a three hole Lever Carriage drive which accepts all the Lever/Link Plate/Direct Drive options provided with the CW300. Connection to the solid levers is effected by the same two adjustable Link Plates provided with the CW300. As before all Lever Carriage/Link/Link Plate attachments are standardised at 5mm diameter.

The second is fitted with a fixed fork ended operating lever, the fork being 6mm wide. The lever has an operating radius of 52mm and requires the installation of a multiplier. This unit although designed specifically for the SZD Bocian can be utilised in other types.

The Part No. for the Fork ended unit is CW400FE.

Lever/Link Plate/Direct Drive information is shown in DRG CW3400INS

As the Lever Carriage Drive and operating Lever dimensions are identical to those employed with the CW300 and similar test parameters apply, the comments regarding operating loads and the need for the inclusion of some form of multiplier when using the Direct Drive or shorter operating levers are also applicable to the CW400 installation.

Unit weight = 0.585 Kg. (1.36 lbs)