


Project Management Report

1. Project Timeline & Milestones

Project: NoCode_Bench
Start Date: November 1, 2025
End Date: January 31, 2026
Total Duration: 90 Days
Key Milestone: January 15, 2026 (Mid-Project Review)

Date	Tasks
2025.11.01 - 2025.11.10	Project Initiation & Requirement Analysis
2025.11.11 - 2025.11.20	System Architecture & Design
2025.11.21 - 2025.12.20	Core Development - Backend & Frontend & Agent
2025.12.21 - 2025.12.31	Integration
2026.01.01 - 2026.01.15	Testing & Evaluation
2026.01.16 - 2026.01.31	Documentation & Deployment




2. System Architecture

The NoCode-bench system is built on a distributed, asynchronous architecture designed to handle documentation-driven code generation and containerized validation. The architecture consists of four primary layers:

- Web & API Layer:** A Django-based backend provides RESTful endpoints for task specification, allowing users to submit either verified benchmark tasks or custom GitHub repository URLs.
- Task Orchestration Layer:** Utilizes Celery with a Redis message broker to manage long-running evaluation tasks asynchronously. This ensures the web interface remains responsive while the agent processes complex code changes.

- **AI Agent Core:** This component integrates the Gemini-2.5-Flash model for efficient file retrieval and the Gemini-2.5-Pro model for sophisticated code generation. It manages a self-correction loop by maintaining a history of failed attempts and error logs to refine subsequent code patches.
- **Isolated Execution Layer:** A Docker-based environment where generated patches are applied to cloned repositories. It executes pre-configured test suites (Fail-to-Pass and Pass-to-Pass) within specialized containers to verify the functional correctness of the AI-generated code.



3. Method

Component	Choice	Rationale
File Retrieval	LLM-based Semantic Filtering (Gemini-2.5-Flash) with Path Scanning	Uses high-speed LLM reasoning to identify core files from a large codebase (up to 3000 paths) before fetching full content, ensuring the context remains relevant and within token limits.
Code Generation	Full-file Rewrite Strategy via Gemini-2.5-Pro	Avoids the complexities of parsing diffs by generating entire file contents with structured delimiters, ensuring code consistency and easier application to the workspace.
Docker Validation	Isolated Containerized Testing (F2P & P2P)	Provides a reproducible and safe environment to verify patches by running existing tests (Pass-to-Pass) and new feature tests (Fail-to-Pass) to ensure functional correctness without regressions.

Component	Choice	Rationale
Self-Correction Loop	Iterative Error-Feedback Loop (Attempt-based)	Captures execution failures and test logs to feed back into the model's context, allowing the agent to analyze logic errors and refine its implementation in subsequent attempts.

4. Team Roles & Responsibilities

Name	Role	Key Contributions
Kai-Hao, Yang	Project Lead & AI Architect	Led the overall project direction and system design; architected and orchestrated agentic workflows across the platform.
Hao Lin	Backend & Evaluation Engineer	Test and engineered the automated evaluation pipeline.
Han Hu	Infrastructure & DevOps Engineer	Built Docker sandboxes and automated benchmark environment deployment.
Kaihui, You	Frontend & UI/UX Designer	Design and implement UI components and page layouts, Handle styling and responsive design.
Hsuan Lien	Frontend & API Integration Engineer	Integrate frontend with backend APIs, Handle routing, and error handling.

5. Future Plans

To enhance the performance and versatility of the NoCode-bench platform, several key technical improvements are planned based on the current system's architecture:

- Dynamic Multi-Attempt Self-Correction:** The current system is limited to a single generation attempt per task (`MAX_ATTEMPTS = 1`). Future versions will implement a dynamic budget for self-correction, allowing the agent to perform multiple iterative fixes based on more granular feedback from test failure logs.
- Enhanced Retrieval for Large-Scale Codebases:** Currently, the file retrieval component scans a maximum of 3,000 files and is restricted by a 200,000-character context limit. We plan to implement a more scalable RAG (Retrieval-Augmented Generation) approach or a hierarchical directory-traversal agent to handle enterprise-level repositories.
- Broadening Framework and Language Support:** The system is currently optimized for Python-based repositories like Django and scikit-learn. Future updates will include specialized Docker environments and configuration mappings for other ecosystems such as JavaScript (Node.js), Go, and Java to evaluate cross-language documentation-driven coding.
- Advanced Multi-Agent Collaboration:** The architecture currently uses a two-stage sequential pipeline (Flash for search, Pro for coding). We aim to transition to a multi-agent

framework where specialized agents (e.g., a 'Reviewer Agent' and a 'Debugger Agent') collaborate to verify code quality and security before the final execution in Docker.

- **Integration of Real-Time Evaluation Metrics:** Beyond the existing Fail-to-Pass (F2P) and Pass-to-Pass (P2P) metrics, we plan to incorporate code complexity analysis and token efficiency tracking directly into the results dashboard to provide deeper insights into the agent's implementation efficiency.