


CONTAINERIZED STEAM BOILER PLANT

Steam boiler plant

1000 kg/h

Gas / oil burner · output 1000 kg/h · operating pressure up to 13 barg

MAIN FEATURES

- Dual-fuel burner gas / oil
- Two feedwater pumps
- Chimney
- Flash vessel
- Power & control switchgear
- Condensate tank
- Safety equipment, 72-hour unattended operation

PARAMETERS

Maximum output [kg/h]	1000
Maximum operating pressure [barg]	13

CONNECTIONS

Pump supply	DN 50 PN 16
Gas connection	DN 100 PN 16
Light heating oil supply	½" quick coupling
Light heating oil return	½" quick coupling
Condensate return	DN 50 PN 16
Steam connection	DN 40 PN 16
Feedwater connection (after water treatment)	¾" male thread

REQUIRED POWER SUPPLY

Electrical voltage [V]	400
Power [kW]	7,5
Current protection [A]	32

MAX. FUEL CONSUMPTION

Natural gas [Nm³/h]	79
Light heating oil [l/h]	73

TECHNICAL PARAMETERS

Transport dimensions (L × W × H) [mm]	6150 × 2438 × 2790
Operating dimensions with chimney [mm]	6150 × 2438 × 3500
Transport weight [kg]	7500
Operating weight [kg]	9500