


CONTAINERIZED STEAM BOILER PLANT

Steam boiler plant

350 kg/h

Gas / oil burner · output 350 kg/h · operating pressure up to 10 barg

MAIN FEATURES

- Dual-fuel burner gas / oil
- Two feedwater pumps
- Chimney
- Flash vessel
- Power & control switchgear
- Condensate tank
- Safety equipment, 72-hour unattended operation

PARAMETERS

Maximum output [kg/h]	350
Maximum operating pressure [barg]	10

CONNECTIONS

Pump supply	DN 50 PN 16
Gas connection	DN 100 PN 16
Light heating oil supply	½" quick coupling
Light heating oil return	½" quick coupling
Condensate return	DN 40 PN 16
Steam connection	DN 32 PN 16
Feedwater connection (after water treatment)	1" male thread

REQUIRED POWER SUPPLY

Electrical voltage [V]	400
Power [kW]	6
Current protection [A]	25

MAX. FUEL CONSUMPTION

Natural gas [Nm ³ /h]	30
Light heating oil [l/h]	29

TECHNICAL PARAMETERS

Transport dimensions (L × W × H) [mm]	6150 × 2438 × 2790
Operating dimensions with chimney [mm]	6150 × 2438 × 3500
Transport weight [kg]	7000
Operating weight [kg]	8500