


CONTAINERISED STEAM BOILER PLANT

STEAM BOILER PLANT

1000 KG/H

Gas / oil burner · output 1000 kg/h · working pressure up to 13 barg


KEY FEATURES

- ✓ Dual-fuel gas / oil burner
- ✓ Chimney
- ✓ Power & control switchgear
- ✓ Safety fittings for 72 h attended operation
- ✓ Two feedwater pumps
- ✓ Flash vessel
- ✓ Condensate tank

PARAMETERS

Maximum output [kg/h]	1000
Maximum working pressure [barg]	13

CONNECTIONS

Pump supply	DN 50 PN 16
Gas connection	DN 100 PN 16
Light fuel oil supply	½" quick coupler
Light fuel oil return	½" quick coupler
Condensate return	DN 50 PN 16
Steam connection	DN 40 PN 16
Feedwater connection after WTS	¾" ext. thread

REQUIRED POWER SUPPLY PARAMETERS

Voltage [V]	400
Power [kW]	7,5
Circuit protection [A]	32

MAXIMUM FUEL CONSUMPTION

Natural gas [Nm³/h]	79
Light fuel oil [l/h]	73

TECHNICAL PARAMETERS

Transport dimensions (L × W × H) [mm]	6150 × 2438 × 2790
Working dimensions with chimney [mm]	6150 × 2438 × 3500
Transport weight [kg]	7500
Working weight [kg]	9500