

CONTAINERISED DUAL-FUEL BOILER PLANT

WATER BOILER PLANT 2000 KW

Gas / oil burner · 2000 kW · working pressure up to 14 barg



KEY FEATURES

- ✓ Power & control switchgear
- ✓ Dual-fuel gas / oil burner
- ✓ Boiler pump
- ✓ Diaphragm expansion vessel
- ✓ Chimney
- ✓ Safety fittings for 72 h attended operation
- ✓ Optional equipment: fuel tank up to 16 m³

PARAMETERS

Maximum output [kW]	2000
Maximum working pressure [barg]	14

CONNECTIONS

Supply	DN 125 PN 16
Return	DN 125 PN 16
Oil supply (external tank)	½" quick coupler
Supply from heat exchanger	DN 80 / DN 100 PN 16
Return from heat exchanger	DN 25
Boiler water drain	DN 32 PN 40

REQUIRED POWER SUPPLY PARAMETERS

Voltage [V]	400
Power [kW]	16,5
Circuit protection [A]	63

MAXIMUM FUEL CONSUMPTION

Natural gas [Nm ³ /h]	219
Light fuel oil [l/h]	217

TECHNICAL PARAMETERS

Transport dimensions (L x W x H) [mm]	6150 / 6610* x 2541 x 2850
Working dimensions with chimney [mm]	6150 / 6610* x 2541 x 3750
Transport weight [kg]	9000
Working weight [kg]	12000

* Dimension for the natural-gas version.