

CONTAINERISED DUAL-FUEL BOILER PLANT

WATER BOILER PLANT

2500 KW

Gas / oil burner · 2500 kW · working pressure up to 14 barg


KEY FEATURES

- ✓ Power & control switchgear
- ✓ Dual-fuel gas / oil burner
- ✓ Boiler pump
- ✓ Chimney
- ✓ Safety fittings for 72 h attended operation
- ✓ Optional equipment: fuel tank up to 16 m³

PARAMETERS

Maximum output [kW]	2500
Maximum working pressure [barg]	14

CONNECTIONS

Supply	DN 150 PN 16
Return	DN 150 PN 16
Oil supply & return (external tank)	1" / 1" quick coupler
Return from heat exchanger	DN 80 / DN 100 PN 16
Boiler water drain	DN 32 PN 40

REQUIRED POWER SUPPLY PARAMETERS

Voltage [V]	400
Power [kW]	32
Circuit protection [A]	78

MAXIMUM FUEL CONSUMPTION

Natural gas [Nm³/h]	278
Light fuel oil [l/h]	275

TECHNICAL PARAMETERS

Transport dimensions (L × W × H) [mm]	6150 / 6610* × 2541 × 3050
Working dimensions with chimney [mm]	6150 / 6610* × 2541 × 3700
Transport weight [kg]	10 300
Working weight [kg]	13 500

* Dimension for the natural-gas version.