

CONTAINERISED STEAM BOILER PLANT

STEAM BOILER PLANT 350 KG/H

 Gas / oil burner · output 350 kg/h · working
 pressure up to 10 barg

KEY FEATURES

- ✓ Dual-fuel gas / oil burner
- ✓ Power & control switchgear
- ✓ Two feedwater pumps
- ✓ Condensate tank
- ✓ Chimney
- ✓ Safety fittings for 72 h attended operation
- ✓ Flash vessel

PARAMETERS

Maximum output [kg/h]	350
Maximum working pressure [barg]	10

CONNECTIONS

Pump supply	DN 50 PN 16
Gas connection	DN 100 PN 16
Light fuel oil supply	½" quick coupler
Light fuel oil return	½" quick coupler
Condensate return	DN 40 PN 16
Steam connection	DN 32 PN 16
Feedwater connection after WTS	1" ext. thread

REQUIRED POWER SUPPLY PARAMETERS

Voltage [V]	400
Power [kW]	6
Circuit protection [A]	25

MAXIMUM FUEL CONSUMPTION

Natural gas [Nm³/h]	30
Light fuel oil [l/h]	29

TECHNICAL PARAMETERS

Transport dimensions (L x W x H) [mm]	6150 x 2438 x 2790
Working dimensions with chimney [mm]	6150 x 2438 x 3500
Transport weight [kg]	7000
Working weight [kg]	8500