

CONTAINERISED OIL-FIRED BOILER PLANT

WATER BOILER PLANT 250 KW

Oil-fired · output 250 kW · working pressure up to 5 barg



KEY FEATURES

- ✓ Power & control switchgear
- ✓ Oil burner
- ✓ Boiler pump
- ✓ Diaphragm expansion vessel
- ✓ Chimney
- ✓ Fuel tank 1500 litres
- ✓ Flexible connections 2 x 10 m
- ✓ Safety fittings for 72 h attended operation

PARAMETERS

Maximum output [kW]	250
Maximum working pressure [barg]	5

CONNECTIONS

Heating (CH) connection	2" fire coupling
DHW connection	2" fire coupling
Oil supply (external tank)	½" quick coupler

REQUIRED POWER SUPPLY PARAMETERS

Voltage [V]	230
Power [kW]	4,1
Circuit protection [A]	B25

MAXIMUM FUEL CONSUMPTION

Max. consumption — light fuel oil [l/h]	27
---	-----------

TECHNICAL PARAMETERS

Transport dimensions (L x W x H) [mm]	3000 x 2438 x 2770
Working dimensions with chimney [mm]	3000 x 2438 x 3100
Transport weight [kg]	2000
Working weight [kg]	3550