


CONTAINERIZED DUAL-FUEL BOILER PLANT

Water boiler plant 2000 kW

Gas / oil burner · 2000 kW · operating pressure up to 14 barg

MAIN FEATURES

- Power & control switchgear
- Dual-fuel burner gas / oil
- Boiler pump
- Expansion vessel
- Chimney
- Safety equipment, 72-hour unattended operation
- Optional: fuel tank up to 16 m³

PARAMETERS

Maximum output [kW]	2000
Maximum operating pressure [barg]	14

CONNECTIONS

Supply (flow)	DN 125 PN 16
Return	DN 125 PN 16
Oil supply (external tank)	½" quick coupling
Supply from heat exchanger	DN 80 / DN 100 PN 16
Return from heat exchanger	DN 25
Boiler water drain	DN 32 PN 40

REQUIRED POWER SUPPLY

Electrical voltage [V]	400
Power [kW]	16,5
Current protection [A]	63

MAX. FUEL CONSUMPTION

Natural gas [Nm ³ /h]	219
Light heating oil [l/h]	217

TECHNICAL PARAMETERS

Transport dimensions (L × W × H) [mm]	6150 / 6610* × 2541 × 2850
Operating dimensions with chimney [mm]	6150 / 6610* × 2541 × 3750
Transport weight [kg]	9000
Operating weight [kg]	12000

* Dimension for the natural-gas version.