


CONTAINERIZED DUAL-FUEL BOILER PLANT

Water boiler plant 2700 kW

Gas / oil burner · 2700 kW · operating pressure up to 14 barg

MAIN FEATURES

- Power & control switchgear
- Dual-fuel burner gas / oil
- Boiler pump
- Chimney
- Safety equipment, 72-hour unattended operation
- Optional: fuel tank up to 16 m³

PARAMETERS

Maximum output [kW]	2700
Maximum operating pressure [barg]	14

CONNECTIONS

Supply (flow)	DN 150 PN 16
Return	DN 150 PN 16
Oil supply & return (external tank)	1" / 1" quick coupling
Return from heat exchanger	DN 80 / DN 100 PN 16
Boiler water drain	DN 32 PN 40

REQUIRED POWER SUPPLY

Electrical voltage [V]	400
Power [kW]	32
Current protection [A]	78

MAX. FUEL CONSUMPTION

Natural gas [Nm ³ /h]	300
Light heating oil [l/h]	295

TECHNICAL PARAMETERS

Transport dimensions (L × W × H) [mm]	6150 / 6610* × 2541 × 3150
Operating dimensions with chimney [mm]	6150 / 6610* × 2541 × 3700
Transport weight [kg]	11 200
Operating weight [kg]	14 200

* Dimension for the natural-gas version.