Hw 3　　107033056 - 資工三 - 徐宏宇

(1.) X (∵ ① ~~propagation delay ⇒ different nodes may detect the channel idle at slightly different time ⇒ simultaneous transmission ⇒ collision~~ 2 nodes set the same countdown value

② the ACK packets themselves may collide)

(2.) X (WIFI adjusts random backoff range (0, W) based on K (# of send attempts))

(3.) O (Human hearing range : 20 Hz ~ 20 kHz, & 44100 Hz > 2×20 kHz)

(4.) X (FM (analog modulation)'s resistance to noise is due to its frequency modulation technique. This has nothing to do with OFDM, which is a digital transmission method that provides robustness through its use of multiple orthogonal sub-carriers.)

(5.)

	d_1	d_2	d_3	d_4
• dataword :	0	0	0	1

$p1 = d_1 + d_2 + d_4 = 0 + 0 + 1 = 1$

$p2 = d_1 + d_3 + d_4 = 0 + 0 + 1 = 1$

$p3 = d_2 + d_3 + d_4 = 0 + 0 + 1 = 1$

	P_1	P_2	d_1	P_3	d_2	d_3	d_4
• codeword :	1	1	0	1	0	0	1

$((011)_2 = (3)_{10})$ ↓ introduce an 1-bit error

	b_1	b_2	b_3	b_4	b_5	b_6	b_7
• received :	1	1	1	1	0	0	1

$c_1 = b_1 + b_3 + b_5 + b_7 = 1 + 1 + 0 + 1 = 1$

$c_2 = b_2 + b_3 + b_6 + b_7 = 1 + 1 + 0 + 1 = 1$

$c_3 = b_4 + b_5 + b_6 + b_7 = 1 + 0 + 0 + 1 = 0$

Ans: 1 1 1 1 0 0 1

(Starts w/ a valid codeword. Error at bit $(011)_2 = 3$)

6.

$$
\begin{array}{r|l}
 & 1\ 1\ 1 \\
\hline
1\,0\,0\,0\,1 & 1\ 1\ 1\ 0\ 1\ 0\ 0 \\
 & 1\ 0\ 0\ 0\ 1 \\
\hline
 & 1\ 1\ 0\ 0\ 0 \\
 & 1\ 0\ 0\ 0\ 1 \\
\hline
 & 1\ 0\ 0\ 1\ 0 \\
 & 1\ 0\ 0\ 0\ 1 \\
\hline
 & 0\ 0\ 1\ 1
\end{array}
$$

codeword $c(x) = d(x)\,x^{5-1} + r(x)$

$= \underline{\underline{1\ 1\ 1\ 0\ 1\ 0\ 0\ 0\ 0\ 1\ 1}}$ #

7.

$$
\begin{cases}
c_1 = 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0 \\
c_2 = 0\ 1\ 1\ 1\ 1\ 1\ 1\ 0\ 0\ 0\ 0\ 0\ 0\ 0\ 0 \\
c_3 = 1\ 0\ 0\ 0\ 0\ 0\ 0\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1 \\
c_4 = 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1\ 1
\end{cases}
$$

$d(c_1, c_2) = 6$, $d(c_1, c_3) = 6$

$d(c_1, c_4) = 12$, $d(c_2, c_3) = 12$

$d(c_2, c_4) = 6$, $d(c_3, c_4) = 6$

(8) ?

dataword 差 1 bit ⇒ Hamming distance = 3

" 2 " ⇒ " = 4

3 ⇒ = 4

Two-Dimensional Parity Check

- 點



d. Three errors affect four parities

無法 detect

⇒ Min. Hamming dist. = 3

(9.)

	d_1	d_2	d_3	d_4
• dataword :	0	0	1	0

$p1 = d_1 + d_2 + d_4 = 0 + 0 + 0 = 0$

$p2 = d_1 + d_3 + d_4 = 0 + 1 + 0 = 1$

$p3 = d_2 + d_3 + d_4 = 0 + 1 + 0 = 1$

	P_1	P_2	d_1	P_3	d_2	d_3	d_4
• codeword :	1	1	0	1	0	1	0
	b_1	b_2	b_3	b_4	b_5	b_6	b_7

decode

$c_1 = b_1 + b_3 + b_5 + b_7 = 1 + 0 + 0 + 0 = 1$

$c_2 = b_2 + b_3 + b_6 + b_7 = 1 + 0 + 1 + 0 = 0$

$c_3 = b_4 + b_5 + b_6 + b_7 = 1 + 0 + 1 + 0 = 0$

$(001)_2 = 1 \Rightarrow$ indicates that there's an error at bit 1

bad conclusion

$\Rightarrow$ result = 1 0 1 0 #

(10.) $X^{10} + 1$

① len (generator) - len (burst err.)

② even # of terms $\Rightarrow$ detects odd # of errs

11.



Ans: 1 0 1 1 0 0 0

12. 3 Parties: A (attacker), B, C

1° A $\xrightarrow{Tx1}$ B, Tx1 is broadcast to the bitcoin network and await confirmation.

2° Before Tx1 is confirmed, A $\xrightarrow{Tx2}$ C (using the same Bitcoins, privately)

3° A starts mining a new block with Tx2 instead of Tx1 (high prob. ∵ A controls the majority of the computational resources) ⇒ making chain longer

4° Broadcast the private chain to the entire Bitcoin network

5° As a result, the block Tx1 is invalidated and dropped from the Bitcoin Network.

(51% Attack)