CRSG-DX53D



Description: cold rolled slit galvanized

Properties	Typical Values	Units	Test Methods
Width Range	75-800	MM	EN 10142: 2000
Width Range	75-800	MM	EN 10346: 2009
Thickness Range	0.4-2	MM	EN 10142: 2000
Thickness Range	0.5-2	MM	EN 10346: 2009

Disclaimer

Any sale by Hadeed and its subsidiary (each a "seller"), is made exclusively under seller's standard conditions of sale (available upon request) unless agreed otherwise in writing and signed on behalf of the seller. While the information contained herein is given in good faith, SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND NONINFRINGEMENT OF INTELLECTUAL PROPERTY, NOR ASSUMES ANY LIABILITY, DIRECT OR INDIRECT, WITH RESPECT TO THE PERFORMANCE, SUITABILITY OR FITNESS FOR INTENDED USE OR PURPOSE OF THESE PRODUCTS IN ANY APPLICATION. Each customer must determine the suitability of seller materials for the customer's particular use through appropriate testing and analysis. No statement by seller concerning a possible use of any product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right.