

Text data types

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jake Roach
Field Data Engineer

Data types and functions in Snowflake



Snowflake is used by more than 10,000 organizations globally

Data Types

Manipulating Data

Advanced Techniques

¹ <https://www.snowflake.com/en/company/overview/about-snowflake/>

Snowflake text data

Text data is one of the most popular data types in Snowflake

- Categorical values
- Messages
- Phone numbers
- Unstructured text

```
-- Text data might be categorical  
'Software Engineer'
```

```
-- Messages are also text data  
'Hello, World!'
```

```
-- As well as phone numbers  
'931-663-0164'
```

```
-- And even things like this!  
'Taylormade, Titleist, Ping'
```

Text data types

```
CREATE TABLE TABLE_NAME (  
  message VARCHAR(100),  
  phone_number TEXT,  
  brands STRING  
);
```

Define column with `VARCHAR(...)`

- `TEXT`
- `STRING`

message	phone_number	brands
-----	-----	-----
Hello, World!	931-663-0164	Taylormade, Titleist, Ping
Goodnight!	617-256-3086	Apple, Windows, Linux

Columns that store text data can look quite different!

Describing a Snowflake table

```
DESCRIBE TABLE <SCHEMA>.<table_name>;
```

- Outputs information about each column in the table
- `name` , `type` , `default` , ...

name	type	kind?	...
r_id	VARCHAR(16777216)	COLUMN	...
cuisine	VARCHAR(16777216)	COLUMN	...
price	VARCHAR(16777216)	COLUMN	...

Text data in queries

SELECT

```
<field>,  
<another-field>,  
-- Can be used in a SELECT  
'<value>'
```

```
FROM SCHEMA.TABLE_NAME;
```

SELECT

```
*
```

```
FROM SCHEMA.TABLE_NAME
```

```
-- Can be used in a WHERE clause
```

```
WHERE FIELD = '<value>';
```

- Text values can be used in different parts of a SQL query
- SELECT
- WHERE
- CASE

'...' Single Quotes

- Case-sensitive

Manipulating text data

Function	Description
LENGTH	Find the number of characters in a text value.
TRIM	Remove a sequence of characters at the beginning or end of a string.
RTRIM	Same functionality as TRIM , only applied to right-side of the string.
LTRIM	Same functionality as TRIM , only applied to left-side of the string.
SPLIT	Split a string using some delimiter, like a comma.
SEARCH	Search a string for a certain value.
CAST , ::	Convert other data types into a VARCHAR data type.

Let's practice!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE

Numeric data types

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jake Roach
Field Data Engineer

Numeric data types

NUMBER

- Control the size of numeric values
- `DECIMAL` , `INTEGER` are synonymous with `NUMBER`

```
126          -- Integers
7.99         -- Dollar amounts
.000191      -- Decimals
-46.88       -- Negative values
563719100    -- ID's

...

1.234E+2     -- Numeric constants
```

Precision and scale

```
NUMBER(<precision>, <scale>)
```

Precision is the **total number** of digits in the number

Scale is the number of digits **after** the decimal point

```
-- Precision: 4, Scale: 2
```

```
NUMBER(4, 2)
```

```
1.75      -- Good!
```

```
624.99    -- Won't fit
```

Precision and scale

```
-- Precision: 3, Scale: 0  
NUMBER(3, 0)
```

```
42      -- Good!
```

```
1000    -- Won't fit
```

```
41.99   -- Won't fit
```

- Default `NUMBER` is `NUMBER(38, 0)`

Defining numeric data types

```
CREATE TABLE sales (  
  id NUMBER,           -- Traditional numeric data  
  price NUMBER(5, 2),  -- Dollar values up to $999.99  
  quantity NUMBER(4, 0) -- Integer values less than 10,000  
);
```

```
DESCRIBE TABLE schema.table;
```

name		type		kind		...
-----		-----		-----		---
id		NUMBER(38,0)		COLUMN		...
price		NUMBER(5,2)		COLUMN		...
quantity		NUMBER(4,0)		COLUMN		...

FLOAT data type

- Used in Scientific and statistical calculations
- "Approximate" numeric type
- Possibility of rounding errors
- **Fast and can handle extreme scale!**

```
0.00000000120056
```

```
CREATE TABLE metrics (  
    id NUMBER,  
    accuracy FLOAT  
);
```

```
DESCRIBE TABLE schema.table;
```

name		type		...
-----		-----		---
id		NUMBER(38,0)		...
accuracy		FLOAT		...

Manipulating numeric data

- Numeric data can be manipulated in a number of different ways
- Comparing values using tools such as `=` , `!=` , `<` , or `>` .
- Performing arithmetic operations, such as `+` , `-` , `/` , or `*` .
- Aggregating data with `SUM` , `AVG` , or `COUNT` .
- Calculating summary statistics with `MEDIAN` , `STDDEV` , and `CORR` .
- ... and tons more!

Let's practice!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE

Datetime data types

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jake Roach
Field Data Engineer

DATE data types

- Date values store the day on which something occurred

2023-04-01

YYYY-MM-DD

```
CREATE TABLE sales (  
    transaction_date DATE -- Define a column of type `DATE`  
);
```

DATE data types

```
SELECT
```

```
    TO_DATE('2023-04-01') AS the_date, -- Convert a string into a DATE
```

```
    '2023-04-01'::DATE AS casted_date -- Casted using <value>::DATE
```

```
;
```

the_date		casted_date
-----		-----
2023-04-01		2023-04-01

Time data types

- Captures the hours, minutes, and seconds that some event occurred

08:24:08

HH:MM:SS

```
CREATE TABLE sales (  
    transaction_time TIME -- Create a column with the `TIME` keyword  
);
```

- Define a `TIME` column

Time data types

```
SELECT
```

```
    TO_TIME('08:24:04') AS the_time,
```

```
    '08:24:04'::TIME AS casted_time
```

```
;
```

	the_time		casted_time	
	-----		-----	
	08:24:08		08:24:08	

- `TO_TIME` function
- Cast using `::`

Timestamp data types

- `TIMESTAMP` captures both date and time

2023-04-01 08:24:04

YYYY-MM-DD HH:MM:SS

```
CREATE TABLE (  
    transaction_timestamp TIMESTAMP  
);
```

Timestamp data types

```
SELECT
```

```
    TO_TIMESTAMP('2023-04-01 08:24:04') AS the_timestamp,  
    '2023-04-01 08:24:04'::TIMESTAMP AS casted_timestamp  
;
```

- Convert a string to a timestamp using `TO_TIMESTAMP` or `<value>::TIMESTAMP`
- Most common way to store datetime data

the_timestamp	casted_timestamp
2024-04-01 08:24:08	2024-04-01 08:24:08

Examples

SELECT

TO_DATE('2021-05-14') **AS** the_date,

TO_TIME('06:13:00') **AS** the_time,

TO_TIMESTAMP('2021-05-14T06:13:00') **AS** the_timestamp,

-- Extract the DATE from a TIMESTAMP, we could do the same with TIME!

transaction_timestamp::DATE **AS** casted_date

;

the_date		the_time		the_timestamp		casted_date
-----		-----		-----		-----
2021-05-14		06:13:00		2021-05-14T06:13:00		2021-05-14

Timezones

By default, `DATE` , `TIME` , and `TIMESTAMP` 's are stored without a timezone

`TIMESTAMP_NTZ`

- Default implementation of `TIMESTAMP`
- No timezone is stored

`TIMESTAMP_LTZ`

- Relies on **local** timezone

`TIMESTAMP_TZ`

- User **specifies** timezone

¹ <https://docs.snowflake.com/en/sql-reference/data-types-datetime#timestamp-ltz-timestamp-ntz-timestamp-tz>

Let's practice!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE