

Flattening Semi-Structured Data

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jake Roach
Field Data Engineer

Structured data

school_id	school_name	street_number	street_name	suffix	city	zip_code
s_19219	West Aurora HS	879	Main	St.	West Aurora	25041
s_77465	Springtown HS	1645	Cherry	Rd.	Springtown	14556

school_id	address_info
s_19219	{ "school_name": "West Aurora HS", "address": { "street_number": 879, "street_name": "Main", "suffix": "St.", "city": "West Aurora", "zip_code": 25041 } }

Semi-structured data

Data stored with braces in key-values pairs takes the data type `VARIANT`

```
{
  "school_name": "West Aurora HS",
  "address": { -- Nested object
    "street_number": 879,
    "street_name": "Main",
    "suffix": "St.",
    "city": "West Aurora",
    "zip_code": 25041
  }
}
```

- Like a Python dictionary or JSON object
- Allows data to be stored in "raw" format
- Nest objects, like `address`
- Retrieve data in two different ways

Dot-notation

```
my_column
-----
{
  "my_first_key": 2025,
  "my_second_key": {
    "a": "alpha",
    "b": "bravo"
  }
}
```

SELECT

```
my_column:my_first_key      -- Top-level
my_column:my_second_key.a   -- Nested
my_column:my_second_key.b   -- Nested
...
```

Makes it easy to retrieve top-level and nested values from `VARIANT` data

- Colon separates
`<column-name>:<top-level-key>`
- Add a `.` followed by the nested field,
`<column-name>:<top-level-key>.<nested-key>`
- Retrieve deeply-nested values

Dot-notation

SELECT

```
address_info:school_name,           -- Top-level, dot-notation

address_info:address.street_number AS street_number,  -- Nested, dot-notation
address_info:address.street_name AS street_name,
address_info:address.suffix AS suffix
```

```
FROM SCHOOLS.school_info;
```

school_name	street_number	street_name	suffix
-----	-----	-----	-----
West Aurora HS	879	Main	St.
Springtown HS	1645	Cherry	Rd.

Bracket-notation

Provides an additional technique for retrieving top-level and nested values

- `<column-name>['<top-level-key>']['...']`
- Many nested layers
- Like retrieving data from a Python dictionary
- Make sure to use **single quotes** (`'`)!

```
my_column
-----
{
  "my_first_key": 2025,
  "my_second_key": {
    "a": "alpha",
    "b": "bravo"
  }
}
```

SELECT

```
my_column['my_first_key'],           -- Top-level
my_column['my_second_key']['a']      -- Nested
my_column['my_second_key']['b']      -- Nested
...
```

Bracket-notation

SELECT

```
address_info['school_name'],           -- Top-level, bracket-notation
```

```
address_info['address']['city'] AS city,      -- Nested, bracket-notation
```

```
address_info['address']['zip_code'] AS zip_code
```

FROM SCHOOLS.school_info;

school_name	city	zip_code
-----	-----	-----
West Aurora HS	West Aurora	25041
Springtown HS	Springtown	14556

Transforming semi-structured data

SELECT

school_id,

address_info:school_name **AS** school_name, -- Top-level, dot-notation

address_info:address.street_number **AS** street_number, -- Nested, dot-notation

address_info:address.street_name **AS** street_name,

address_info:address.suffix **AS** suffix,

address_info['address']['city'] **AS** city, -- Nested, bracket-notation

address_info['address']['zip_code'] **AS** zip_code

FROM SCHOOLS.school_info;

Transforming semi-structured data

school_id	address_info
-----	-----
s_19219	{ "school_name": "West Aurora HS", "address": { "street_number": 879, "street_name": "Main", "suffix": "St.", "city": "West Aurora", "zip_code": 25041 } }

school_id	school_name	street_number	street_name	suffix	city	zip_code
-----	-----	-----	-----	-----	-----	-----
s_19219	West Aurora HS	879	Main	St.	West Aurora	25041
s_77465	Springtown HS	1645	Cherry	Rd.	Springtown	14556

Let's practice!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE

Multiple common table expressions

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jacob Roach
Field Data Engineer

Common table expressions (CTEs)

```
WITH seniors AS (  
    SELECT  
        student_id,  
        first_name  
    FROM STUDENTS.personal_info  
    WHERE graduation_year = 2025  
)  
  
SELECT  
    ...  
FROM seniors
```

CTEs temporarily store the results of a query to eventually be used within another query

- Used to organize queries
- More readable and modular
- Not limited to a single CTE

Defining multiple CTEs

Multiple temporary results can be defined using a single `WITH` statement

- `...), <another-cte-name> AS (...)`
- Make table filtering and manipulation easier to understand
- `JOIN` multiple temporary result sets together
- Subqueries within another CTE

```
WITH <cte-name> AS (  
  
    <query>  
  
) , <another-cte-name> AS (  
  
    -- Add another query!  
    <another-query>  
)  
  
-- These CTE's could be JOIN'd  
SELECT ... ;
```

Joining temporary result sets

```
-- First common table expression
WITH seniors AS (
    SELECT student_id, first_name FROM STUDENTS.personal_info WHERE graduation_year = 2025

-- Second common table expression
), final_exam_grades AS (
    SELECT student_id, course_name, exam_score FROM STUDENTS.grades WHERE exam_type = 'Final'
)

SELECT
    seniors.first_name, final_exam_grades.course_name, final_exam_grades.exam_score
FROM final_exam_grades

-- Join the temporary result sets together
JOIN seniors ON final_exam_grades.student_id = seniors.student_id
```

Joining temporary result sets

first_name	course_name	exam_score
-----	-----	-----
Ryan	Calculus I	97
Tatiana	Biology	98
Pankaj	English III	92
Taylor	Python	71
Iris	Finance	89
Charles	Marketing	88
...		

Using a temporary result in a CTE

```
WITH ny_schools AS (  
    SELECT school_id, school_name, district FROM SCHOOL.school_info WHERE school_state = 'NY'  
) , ny_teachers AS (  
    SELECT  
        teacher_id, teacher_name, tenure, specialty  
    FROM SCHOOLS.teachers  
    WHERE school_id IN (SELECT school_id FROM ny_schools) -- Filter by records in ny_schools  
)  
  
SELECT  
    ny_teachers.teacher_name, ny_teachers.course_name, previous_courses.term  
FROM SCHOOLS.previous_courses  
JOIN ny_teachers ON previous_courses.teacher_id = ny_teachers.teacher_id AND  
    previous_courses.course_area = ny_teachers.specialty  
;
```


Using a temporary result in a CTE

```
WITH ny_schools AS (  
  SELECT  
    school_id,  
    ...  
  WHERE school_state = 'NY'  
) , ny_teachers AS (  
  SELECT  
    ...  
  FROM SCHOOLS.teachers  
  
  -- Filter by school_id in records above  
  WHERE school_id IN (  
    SELECT school_id FROM ny_schools  
  )  
)
```

- First, only filter for `school_id`'s in `NY`
- Temporary result stored in `ny_schools`
- In `ny_teachers`, filter records by `school_id` in `ny_schools`
- Could also `JOIN`, etc.

Matching teachers workloads to their specialties

```
...  -- Building the ny_teachers CTE

SELECT
    ny_teachers.teacher_name,
    ny_teachers.course_name,
    previous_courses.term
FROM  SCH00LS.previous_courses

-- Finally, join the CTE with the previous_courses table
JOIN  ny_teachers ON
    previous_courses.teacher_id = ny_teachers.teacher_id AND
    previous_courses.course_area = ny_teachers.specialty
;
```

Matching teachers workloads to their specialties

teacher_name	course_name	term
-----	-----	-----
Marcus Lee	U.S. History	H1'22
Priya Desai	Algebra II	H2'22
Elena Rodríguez	Environmental Science	H1'25
Jamal Thompson	English I	H2'21
Mei-Ling Chen	World History	H1'23
Gregory O'Malley	Calculus II	H2'24

...

Let's practice!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE

Pivoting Data

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jake Roach
Field Data Engineer

Aggregated table

course_name	exam_type	avg_exam_score
-----	-----	-----
Calculus I	Exam 1	81.78
Calculus I	Exam 2	83.55
Calculus I	Final	80.93
Finance	Exam 1	89.47
Finance	Exam 2	90.39
Finance	Final	89.69
Marketing	Exam 1	94.11
Marketing	Exam 2	93.29
Marketing	Final	93.81

"Pivoted" table

course_name	"Exam 1"	"Exam 2"	"Final"
-----	-----	-----	-----
Calculus I	81.78	83.55	80.93
Finance	89.47	90.39	89.69
Marketing	94.11	93.29	93.81

Creating a pivoted table

```
SELECT
  *
FROM SCHEMA.TABLE

PIVOT(
  -- Aggregation function
  SUM(<1>)

  -- Specify rows to pivot to columns
  FOR <2> IN (ANY ORDER BY <2>)

  -- No need to GROUP BY!
);
```

`PIVOT` offers a different way to output aggregated data by "pivoting" values into columns

- `SELECT *`, can use `EXCLUDE`
- `PIVOT` goes after `FROM ...`
- `ANY` values in `<2>`

`<1>` : field to aggregate

`<2>` : row values to turn into columns

CTE's and pivoted data

```
WITH exam_grades AS (  
    SELECT  
        ..., exam_score, exam_type  
    FROM SCHEMA.TABLE  
    WHERE ...  
)  
  
SELECT  
    *    -- Could also use EXCLUDE  
FROM exam_grades  
PIVOT(  
    AVG(exam_score)  
    FOR exam_type IN (ANY ORDER BY exam_type)  
);
```

First, define a CTE before using **PIVOT** !

```
SELECT * FROM <cte>
```

exam_score : field to aggregate

exam_type : row values to turn into columns

Comparing exam grades by type

```
WITH exam_grades AS (  
    SELECT  
        course_name, course_abbreviation, exam_score, exam_type  
    FROM STUDENTS.grades  
    WHERE course_level = '101'  
)  
  
SELECT  
    * EXCLUDE course_abbreviation -- Remove course_abbreviation from the result set  
FROM exam_grades  
PIVOT(  
    AVG(exam_score)  
    FOR exam_type IN (ANY ORDER BY exam_type)  
);
```

Comparing exam grades by type

course_name	exam_type	avg_exam_score
-----	-----	-----
Calculus I	Exam 1	81.78
Calculus I	Exam 2	83.55
Calculus I	Final	80.93
Finance	Midterm 1	89.47
...		

course_name	"Exam 1 "	"Exam 2"	"Final"
-----	-----	-----	-----
Calculus I	81.78	83.55	80.93
Finance	89.47	90.39	89.69
Marketing	94.11	93.29	93.81

Let's practice!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE

Congratulations!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE



Jake Roach
Field Data Engineer

Thank you!

DATA TYPES AND FUNCTIONS IN SNOWFLAKE