

KairoX ERP — Production & Traceability

System, Business & Module Guide

Modules covered: Users · Employees · Clients · Imports · Barcode · Materials · **Cutting** · Production · **Store** (*replaces Drawers*) · **Inspections** · **Job Work** · Attendance · Wages · Analytics · Dashboard

Audience: this one document is written for three readers at once.

If you are...	Read	You will be able to
The client / business owner (non-technical)	Part A and Part B	Understand exactly what the software does on the factory floor, who touches it, and what happens to one garment from order to export
A frontend developer	Part A, Part B, Part C	Design and build every screen without needing live data or a backend engineer
A backend developer	Part B, Part D, Appendices	Review the code with full context — you will know what each file is for before you open it

Companion document: *KairoX Production-Event API Reference* — every endpoint with request/response examples and mock data.

Scope note. This document covers **Phase 1** — the system of record and the tracking layer, from the order sheet landing to the garment leaving the building. The Phase-2 procurement engine (BOM, procurement, inventory, supplier PO, intelligence) is documented separately in **KAIROX PROCUREMENT SYSTEM GUIDE** and **KAIROX PROCUREMENT API REFERENCE**.

Updated 2026-09-21. Two things changed since the last revision, and both are written up where they belong rather than only here:

- List reads are paged.** Twenty endpoints now return 50 rows by default instead of the whole table, behind one `Page` envelope. Why, and the counting rule that is easy to get wrong, are in **\$25.6**; the per-endpoint contract is in the API Reference **\$3.1**.
- Four routes were removed** on 2026-09-19: `POST /users/clients` (\$6.3), `GET /attendance/me/status`, and `GET / PATCH /attendance/config` (\$30.1). All four are commented out in their routers with the reason, not deleted. Nothing they governed stopped working — shift policy still applies on every punch — only the API for it is gone.

Table of Contents

PART A — THE PLAIN-ENGLISH STORY 1. What this system is, in one page 2. The problem it solves 3. One garment's journey 4. Who does what 5. What "done" looks like at each step

PART B — THE BUSINESS FLOW IN DETAIL 6. Identity and access — who can log in at all 7. People — employees, cards, and the no-login rule 8. Clients, orders, styles and SKUs 9. Import and the release gate — where garments are born 10. The barcode system — the spine 11. Materials, lots and the style recipe 12. Production — one log, two doors, four gates 13. Cutting — the grid that replaced the spreadsheet 14. The store and the merge gate 15. Inspections — reject and rework 16. Job work — garments that leave the building 17. Attendance 18. Wages 19. Analytics and the manager dashboards

PART C — FOR FRONTEND DEVELOPERS

20. The screen inventory

21. State machines you must render

22. Scan-driven UX — the patterns that matter

23. The error contract

24. Badges, chips and status vocabulary

PART D — FOR BACKEND DEVELOPERS

25. Architecture and the layering rules

26. Module map — every file and what it is for

27. The data model

28. Cross-module choreography

29. The key algorithms

30. Configuration and migration notes

31. A code-review checklist

APPENDICES

A. Glossary

B. Complete enum reference

C. Audit log actions

PART A — THE PLAIN-ENGLISH STORY

1. What this system is, in one page

This is a production-management ERP for a **leather garment factory**. It manages the order-to-production lifecycle and gives **per-piece traceability**.

In one sentence: *every individual garment carries its own barcode from the moment its breakdown sheet is released, and every action anyone performs on it — cutting, stitching, storing, inspecting, exporting — is scanned and permanently logged against that barcode.*


That single idea is what everything else hangs off.

What "per-piece" actually means

Most factory systems track **batches**: "200 jackets went to stitching today." This one tracks **pieces**: "garment PC-004821 — a size-50 black CLERMONT, the 17th of its SKU — was cut by Ramesh on the 4th from leather lot A-338 across nine named hides, stored and released from the store, line-stitched by Farid on the 9th, and is currently waiting for final inspection."

Every question a client, a manager or an auditor can ask about one garment has an exact answer, months later.

The five things the system does



Alongside those five, three supporting systems run continuously: **attendance** (who is on the floor today — production logging requires it), **materials** (what leather and accessories exist and what each garment consumed), and **dashboards** (what every manager needs to see about their own line).

2. The problem it solves

Before

1. An order sheet arrives. Someone types it into a spreadsheet.
2. Cutting happens. Someone writes "200 cut" on a whiteboard.

3. A bundle of parts moves to stitching in a plastic crate with a paper docket.
4. The docket gets wet, or swapped, or the crate gets split across two tables.
5. A client asks *"which hide did the jacket in this complaint come from?"* — nobody knows.
6. Payroll is worked out from tally marks in a notebook, two weeks late.
7. A stage runs out of work and nobody notices for a day.

After

Problem	How the system fixes it
Batches lose their identity when split	The piece is the tracked unit. There are no bundles. Each garment has its own barcode, so splitting a batch costs nothing
Someone logs the wrong stage	The caller never picks a stage. The login screen fixes the cut path; every other stage is inferred from the piece's own history
Work gets logged out of order	The sequence gate. A piece cannot be pasted before it is fused
A jacket reaches stitching with no lining	The merge gate. Line-stitching is blocked until the garment holds everything it needs and the store has released it
The wrong worker is credited	The skill gate warns when a cutter is logged on a pasting job, and every event names the worker whose card was scanned
Someone logs work for a person who is not in the building	Production logging requires today's attendance
Leather consumption is guesswork	The two cut stages capture actual consumption per piece , decrementing a named lot
Payroll is a separate re-count	Wages are computed from the same production events . Nothing is counted twice
A whole batch is lost because one piece is wrong	Partial accept everywhere. One blocked piece never loses the thirty-nine good ones scanned with it
Workers need logins the factory cannot manage	Shop-floor workers have no login at all. They have a card. An operator scans it

The design principles behind all of it

Six rules run through every module. They explain most of the decisions in this document.

1. **The piece is the unit.** Not the bundle, not the batch, not the SKU.
2. **The scanner tells the server who and what — never what stage.** Stage is derived. A screen that lets someone pick a stage is a screen that eventually records the wrong one.
3. **Partial accept.** A batch operation reports per-item outcomes and commits the good ones. One bad scan never wastes a manager's whole tray.
4. **You retire codes, never people or records.** A worker leaving retires their card. Their employee row, every production event and every wage line stay intact for ever.
5. **Approval gates are hard, audited state transitions** — never a boolean someone can flip quietly.
6. **When the system is unsure, it asks.** Ambiguous material lots, undeclared lining, unconfirmed recipes — the system stops and surfaces the choice rather than guessing.

3. One garment's journey

Follow a single jacket — a size-50 black **CLERMONT** — end to end.

Step 1 — The order arrives

The client's order becomes a **ClientOrder** with a unique order number, holding **Styles** (CLERMONT), each holding **SKUs** (a colour + size combination with a quantity ordered).

```
Client — BOGGI MILANO
└─ ClientOrder — BOG-SS27-001
    └─ Style — CLERMONT (article A-4471, thickness 0.7mm)
        └─ SKU — BLACK · 50 · qty 20
            └─ Piece — seq 17 of 20 ← our jacket
```

Step 2 — The breakdown sheet is uploaded

The Direct Manager uploads the breakdown workbook. It is parsed and **previewed** first — nothing is written. When they commit, the styles and SKUs land as **DRAFT** rows.

Nothing is minted yet. No barcodes and no pieces. The DM can now see the whole breakdown as an editable table and correct what the sheet got wrong — article numbers, thickness, colours, quantities, prices. Breakdown sheets are hand-made from a client order and a spec sheet, and the first pass is routinely wrong in small ways.

Step 3 — Release: the mint

When the breakdown is correct, the DM **releases** the styles. For each style they must answer one question that cannot be answered later:

Does this garment need a lining?

This is not optional and it is not inferred. `null` is rejected — "*we never asked*" is a real state and the system will not proceed from it. The answer is stamped on the style, copied onto every piece it mints, and from that moment decides two things: whether the garment has a lining-cutting stage at all, and whether **both** parts must reach the store before line-stitching.

Release then creates, atomically: - the **Piece** rows — one per ordered unit, numbered 1..N within the SKU, - each piece's **barcode** — a compact `PC-...` code that gets printed, plus a long human-readable alias, - each piece's **store state** — `WAITING`, meaning it exists but no part of it has reached the store yet.

Our jacket now exists. It is piece seq 17, barcode `PC-004821`.

Nothing is allocated and nothing can run out. Release used to assign each piece a physical drawer from a finite pool of 200, and a release that outran the pool left garments minted but unstorable. The store is now a state on the garment itself, so `pieces_waiting_for_drawer` is gone from the release response — along with the shortage it counted.

Step 4 — Cutting

The **Cutting Manager** logs in. Their login is their screen — a cutting manager is pinned to the LEATHER_CUT screen and cannot be anywhere else.

At the table they scan: **the worker's card**, then **the piece barcodes** — a tray of thirty at a time. They choose the leather lot (or type article + colour and let the system resolve it) and enter the dcm consumed.

The server: 1. Checks the **role** may log leather cutting. ✅ 2. Checks the worker's **designation** — a CUTTER, correct for this stage. ✅ 3. Checks the **sequence** — cutting starts a chain, so nothing to check. ✅ 4. Checks the worker is **present today**. ✅ 5. Writes one ProductionEvent per piece, links the leather lot, and **decrements stock once for the whole batch**.

The lining is cut in parallel, by a different manager, on a different screen, against the same pieces.

Step 5 — Fusing and pasting

The **Stitching Manager** scans the same pieces at the next stages. They do not pick a stage — the server infers it. Piece `PC-004821` has completed LEATHER_CUTTING, so the next chain stage is FUSING. Scan it again tomorrow and the server infers PASTING.

If someone scans a piece for pasting that has not been fused, that one piece comes back `sequence_blocked` with the reason. The other twenty-nine in the tray still log.

Step 6 — The store

The cut parts go to the store. The scan is **employee, then piece** — two scans, not three. The drawer scan is gone, because the piece barcode already says which garment it is and the drawer only ever said where it happened to be sitting.

The system infers whether the part arriving is leather or lining from the piece's own cut history. Once the garment holds everything it needs — leather, and lining if the style declared one — it **automatically reaches RECEIVED**. Nobody presses a button to assert a fact the server already computed.

A part cannot be parked before it has been made: storing a lining on a garment nobody has cut a lining for is a **409**. The store is where a finished part is put down, not where an unfinished one waits.

Accessories are different. Scanning `part=ACCESSORY` issues the garment's whole accessory kit from the style's recipe and **spends stock**. It is never inferred — a wrongly guessed kit would move money nobody asked to move.

Step 7 — Send

The Store Manager opens the store list, filters to the **send queue**, ticks the garments that are ready, and sends them as one batch. Sending sets each piece's store state to **SENDED** — and that is exactly what the production merge gate reads.

Our jacket is sent. `PC-004821` is now eligible for line-stitching.

Step 8 — Line stitching onward

The Stitching Manager scans it. This time the **merge gate** applies: has the store sent this garment? Yes. The piece logs.

Then SHELL_STITCHING → FINAL_FINISH → FINAL_INSPECTION → PACKAGE_EXPORT. The last two are **approvals**, not floor work: no manager role owns them, so only DM/MD/HR can log them.

When PACKAGE_EXPORT is logged, the garment's store flags are **cleared** — there is no pool to return it to, because there is no pool.

Step 9 — Payroll

At the end of the fortnight, a **piece-rate run** is computed for the CLERMONT style. It reads the same ProductionEvent rows that were written on the floor, prices each against the rate in force **on the day the work happened**, and produces one line per employee.

The run is closed and **frozen**. It is the document the cash was counted against, and from that moment it is never silently recomputed.

Step 10 — Forever

Six months later a client complaint arrives about one jacket. Scanning its barcode returns: every stage, who worked it, on what date, whether it was reworked, which leather lot it was cut from, which individual hides went into it, how much was consumed, and what accessories it was issued.

4. Who does what

Role	Value	What they do
Managing Director	<code>managing_director</code>	Superuser. Bypasses every role gate. Final authority on payroll changes and deletions
Direct Manager	<code>direct_manager</code>	The operational lead. Uploads and releases breakdowns, manages clients and users, sets rates, runs payroll, sends garments to outside factories. Also bypasses stage gates
Cutting Manager	<code>cutting_manager</code>	Logs leather cutting only . Pinned to the LEATHER_CUT screen. Creates material lots when leather arrives
Lining Manager	<code>lining_manager</code>	Logs the lining-cut path . Pinned to the LINING_CUT screen
Stitching Manager	<code>stitching_manager</code>	Logs every post-cut floor stage — fusing, pasting, line-stitching, shell-stitching, final finish. Also releases garments from the store
Store Manager	<code>store_manager</code>	Runs the store hub: scans parts onto garments, reads the store list, sends batches onward, records off-spec material issues. Store functions only — this role cannot log a production stage
Supervisor	<code>supervisor</code>	Reads the floor roster and dashboards. No attendance writes, no user creation
HR	<code>hr</code>	Employees, wages visibility, designation backfill, attendance operator
Security	<code>security</code>	Gate operator . Scans employee cards in and out. Nothing else
Merchandiser	<code>merchandiser</code>	Client-facing coordinator. Can log in; no route grants them anything yet
Client	<code>client</code>	External login, scoped to their own orders only
Viewer	<code>viewer</code>	Read-only office staff
~~Employee e~~	~~ employee e ~~	LEGACY — never minted . See below

The rule that shapes everything: workers get no login

A shop-floor worker has no login and no `app_user` row.

Creating one therefore needs no phone, no email and no password — just a name, a designation and a wage type. They are identified on the floor by their **employee barcode**, and their attendance is entered *for* them by an operator: **Security, HR, MD or DM**.

Why this matters: - The factory does not have to manage hundreds of passwords for people who do not own smartphones. - There is no "worker forgot their password" support burden. - Attendance is done by a gate operator scanning cards, which is faster and more honest than self-service.

The `employee` role value still exists in the enum only because `app_user.role` is a native Postgres enum and values cannot be dropped — historical rows may still carry it. Nothing mints it any more.

Two separations worth understanding

The store manager cannot log production. The person who owns the store is not the person who owns the line. Store access and stage access are two different questions, and the code keeps them apart deliberately.

A cutting manager cannot log a lining cut. Each cut manager is pinned to their own screen by their role. The login is the screen. That is what makes "no stage buttons" possible.

5. What "done" looks like at each step

Step	Done when	Where you see it
Order exists	A ClientOrder row with a unique order number	GET /imports/orders — <code>breakdown_status: NOT_UPLOADED</code>
Breakdown committed	Styles and SKUs land as DRAFT	<code>breakdown_status: DRAFT</code> , <code>pieces_minted: 0</code>
Breakdown corrected	Article, thickness, colours, quantities all right	The breakdown table shows what you expect
Recipe confirmed	The style's material spec is signed off	<code>material_spec_confirmed_at</code> is set
Released	Pieces exist, barcodes minted	<code>production_status: RELEASED</code> , <code>minted_pieces > 0</code>
Cut sheet approved	The hides for each garment are named and frozen	The cutting row's <code>status: APPROVED</code>
Cut	An event at LEATHER_CUTTING (and LINING_CUTTING if lined)	The piece's completed stages
Stored	The garment holds everything it needs	Store state <code>received</code> , <code>can_send: true</code>
Sent	Store state is SENDED	The piece is eligible for line-stitching
Finished	An event at PACKAGE_EXPORT	The store flags are cleared
Paid	A frozen wage run covering the work	Run status <code>closed</code>

PART B — THE BUSINESS FLOW IN DETAIL

6. Identity and access — who can log in at all

Module: `app/modules/users/` · **URL prefix:** `/api/v1/auth` and `/api/v1/users`

6.1 One table for every login

A single `app_user` table authenticates everyone — managers, HR, security, clients, viewers. Authorisation is then a matter of the `role` column.

Why one table and not one per role: authentication logic lives in exactly one place. Adding a role never means a new login flow or a new table — just a new enum value. And every "who did this" foreign key points at one column.

```
app_user
├─ phone          the LOGIN identifier (unique)
├─ email          optional, also unique
├─ password_hash  bcrypt
├─ role           the native PG enum
├─ is_active
├─ must_change_password
├─ employee_id    → this login IS a person on the payroll
├─ client_id      → this login is an external client, scoped to their orders
```

The two optional links are what let one table serve very different kinds of user without extra login tables. A manager who is also on the payroll has `employee_id` set. A client login has `client_id` set, and every read they perform is scoped to it.

`client_id` is currently unreachable. The column, the scoping and the `CLIENT` role all still exist, but the only route that could mint a `CLIENT` login was removed on 2026-09-19 (\$6.3). No live row can carry the role, so nothing exercises the scoping today. It is kept, not deleted, because Phase 2 may want a client portal.

6.2 The two gates

`require_roles(...)` — the per-route gate. MD and DM are **superusers** and bypass every one of them.

A note on that bypass: the spec target is for MD alone to be the superuser and DM to be operational-only. DM still bypasses during the MD rollout so the existing seeded god-account does not lose access. Drop DM from that set once an MD owner is confirmed in every environment.

`block_employees` — a deny-list dependency applied at the **router level** in `main.py`, so a *new* route is closed to the legacy employee role unless someone opens it deliberately. Most read routes use bare `get_current_user`; retrofitting an allow-list to every one of them is not realistic, and any route missed is a leak.

Three router groups stay **unlocked**: auth, users, and attendance — plus `/barcode/resolve`, which must stay reachable from the attendance screen so a gate operator can resolve a card.

6.3 Who may create whom

- **`POST /users`** admits DM, HR and MD at the door — but *which* role may be granted is decided in the service against the caller's own authority.
- **`POST /users/clients` was removed on 2026-09-19.** It provisioned a client login bound to a `client_id`, so a buyer could log in and watch their own orders. Phase 1 is the factory floor's system of record, and the buyer is not a user of it: they send an order sheet and they receive a BOM, both by hand, and the costing they approve is approved off-system before production starts. A client login had nothing to do inside the app that a person was not already doing for them outside it.

Why removing it was worth doing rather than leaving it unused. It was the *only* door that could mint a `CLIENT` login. Every `if user.role == UserRole.CLIENT` branch in `clients/`, `analytics/`, `dashboard/`, `production/` and `bom/` is a cross-tenant scoping check, and each one is a place a buyer could be shown another buyer's styles, prices or order book if the scoping were ever got wrong. With no door to mint the role, that surface cannot be reached at all. The branches stay where they are — they cost nothing, and Phase 2 may well want a client portal — but nothing can hold the role until the route is deliberately put back. `UserService.create_client_user()` and `schemas.ClientUserCreate` are left in place so that is an uncommitment, not a rewrite.

`POST /clients` is a different thing and still exists. It creates the client *record* — the buyer the orders hang off. It mints no login.

7. People — employees, cards, and the no-login rule

Module: `app/modules/employees/` · **URL prefix:** `/api/v1/employees`

7.1 Creating a worker

The common case is deliberately tiny:

```
{ "name": "Ramesh Kumar", "designation": "CUTTER", "wage_type": "piece_rate" }
```

No phone, no email, no password, no role. What comes back includes an **employee barcode** — minted in the same transaction so the card can be printed immediately.

7.2 Creating staff

Passing an explicit **staff** role mints a login alongside the employee row. That path *does* need a phone and a password.

Permitted here: **HR, Supervisor, Cutting/Lining/Stitching Manager, Security, Merchandiser**. Excluded: **DM and MD** (created via user-creation) and **employee** (workers get no login at all).

A rule that used to be wrong: a MONTHLY wage type used to auto-mint an `employee` login. It no longer does. Wage type is a payroll fact and says nothing about system access.

7.3 Designations — a controlled vocabulary

Designations are **always uppercase**, normalised on write: `" shell tailor "` and `"Shell-Tailor"` both become `SHELL_TAILOR`.

Why it is controlled and not free text: the moment it is free text, `Cutter`, `cutter` and `CUTTTER` become three different skills and the skill gate is decorative.

Unknown designations are **kept, not rejected** — seeded data carries job titles nobody has catalogued, and failing employee creation on an unrecognised title would block HR. The skill gate treats an uncatalogued designation as unknown and **passes** it (fail-open), tightening as HR backfills the vocabulary.

7.4 Names are unique

A collision is prefixed `IN-CHAL`. Two people called Ramesh Kumar are two rows, and the floor can tell them apart.

7.5 Leaving

Deleting an employee is a **soft delete**: `is_active: false`, and their barcode is retired. DM/MD only — **HR can edit but not remove**.

The employee row, every production event and every wage line stay intact. You delete the scannable code, never the person or their record. Scanning the retired card returns **410 Gone** — distinguishable from *"never existed"*, so the screen can say *"this card was deactivated"* rather than *"invalid barcode"*.

7.6 Reading one worker

`GET /employees/{employee_id}` is the single-worker read — what the edit screen and the worker card open on. Before it existed, the only way to show one person was to fetch the whole roster and filter it in the browser, which meant every screen showing one worker downloaded every worker's phone number.

An inactive worker is a normal 200, not a 404. Someone who has left is still readable, because their production events and wage lines reference them and a name that stops resolving turns last quarter's payroll into an unanswerable question. Only the **card** stops working.

7.7 Salary is redacted

The roster returns salary **only** to HR, DM and MD. And the roster itself is internal — a CLIENT or VIEWER token is refused outright, because the row carries phone and email too.

8. Clients, orders, styles and SKUs

Module: `app/modules/clients/` · **URL prefix:** `/api/v1/clients`

8.1 The hierarchy

```
Client          name, country, code (KJ, GGZ...), currency, size system
├── ClientOrder order_number (unique), dates, sea cut-off, ship mode
│   └── Style    name, article, thickness, code (unique), season, refs, price
│       └── SKU   colour + size + qty_ordered; code unique per style
│           └── Piece ONE physical garment; seq 1..N within the SKU
```

Piece is the tracked unit. Its **code** is the parent barcode.

8.2 Two dates that matter commercially

- **delivery_deadline** — when the client expects it.
- **sea_cutoff_date** — the last day to make sea freight.

Missing the sea cut-off means air freight, which is the single biggest margin event in the business. That is why it is an **alert** on every manager dashboard, not a report line.

8.3 Style-level production state

Each style carries its own release lifecycle:

Field	Meaning
production_status	DRAFT → RELEASED → CANCELLED
released_at / released_by	Who minted the pieces, and when
needs_lining	The DM's declaration. Nullable — null means unanswered
material_spec_confirmed_at / _by	The recipe sign-off
material_spec_no_accessories	The explicit " <i>this garment takes none</i> "

8.4 Tenancy

A CLIENT login is pinned to its own **client_id** on **every** client-facing read — the client list, the styles list, orders, analytics, production reads. A cross-tenant id resolves to 404 rather than 403, because **existence itself is information**.

Dormant since 2026-09-19. These checks are correct and they stay in the code, but no login can hold the **CLIENT** role any more — the one route that minted it is gone (§6.3). Treat this section as the contract Phase 2 re-enables, not as a live surface. If the route comes back, every branch described here comes back with it and must be re-tested; that is the point of leaving them in place rather than deleting them.

8.5 Delete vs deactivate

DELETE /clients/{id} works only on a client with **no orders** — a mistyped or duplicate row. A client *with* orders is a **409**, because the cascade would take their orders, styles, SKUs, and every piece, production event and wage line hanging off them. The error names the exact call to make instead: **PATCH** with **{ "is_active": false }**.

9. Import and the release gate — where garments are born

Module: `app/modules/imports/` · **URL prefix:** `/api/v1/imports`

This module is where a spreadsheet becomes real garments. It is the highest-consequence surface in Phase 1, and it is deliberately a **two-phase commit**.

9.1 Preview, then commit

```
POST /imports/preview — parse the workbook, return a summary + warnings. WRITES NOTHING.
POST /imports/commit  — parse again, then write SKUs into the named order. Idempotent.
```

The order number is validated **first** — the endpoint 404s rather than create an order, so a typo cannot silently spawn a phantom order.

The upload itself is guarded three ways: extension, a hard **size cap** streamed rather than read into memory, and a **zip-container check** (an `.xlsx` is a zip; anything renamed to `.xlsx` that is not a valid zip is rejected before it reaches the parser).

9.2 Commit mints nothing

This is the change that matters most.

```
POST /imports/commit writes DRAFT styles and SKUs. It creates no pieces and no barcodes. The response says
so explicitly: release_required: true, pieces_minted: 0.
```

The sheet lands as an editable table. The DM reviews it and corrects what is wrong.

9.3 The breakdown table

`GET /imports/breakdown/{order_number}` is the screen between upload and production: styles with their SKUs, each row carrying its `production_status`.

- **DRAFT** rows are editable and have minted nothing.
- **RELEASED** rows have real barcoded garments behind them and are read-only.

Corrections are made through three doors: - `PATCH /breakdown/skus/{id}` — the table row. **Can edit the SKU and its parent style in one call**, in one transaction, so the screen can never end up with the colour saved and the article not. - `PATCH /breakdown/styles/{id}` — the style header, which has no SKU to hang off. - `DELETE /breakdown/skus/{id}` — drop a line the sheet should not have had. DRAFT with zero minted pieces only.

All of them **409 once the style is RELEASED**: its pieces carry printed barcodes, and rewriting the breakdown behind a garment already on the floor is how a factory loses traceability.

9.4 The release — the mint

`POST /imports/breakdown/{order_number}/release` is the moment garments come into existence. Atomically, and only now:

1. **Piece** rows — one per ordered unit.
2. **Per-piece barcodes** — the compact `PC-XXXXXX` that gets printed, plus the long alias so older labels still resolve.
3. **The store state** — each piece starts at `WAITING`; nothing is allocated and nothing can run out.
4. The style stamped RELEASED with the actor and time, plus an `audit_log` row.

9.5 The lining declaration

Every style must declare whether it needs a lining. Three shapes are accepted:

Shape	Meaning
<code>{"styles": [{"style_id": ..., "needs_lining": true}, ...]}</code>	The contract. Each style carries its own answer
<code>{"style_ids": [...], "needs_lining": true}</code>	Broadcast. One human answer covering the whole list — still a declaration

Shape	Meaning
<code>{"style_ids": [...]}</code> alone	Deprecated. Falls back to <i>inferring</i> the lining requirement from the style name

A per-style answer **overrides** the broadcast, so the common case can be sent once and the exceptions named.

Three things make this worth the friction:

- **null is rejected.** "*We never asked*" is a real and different state from "*no*", and release will not proceed from it.
- **The declaration outranks the system's own guess, in both directions** — including declaring a style named "...KNIT" as leather-only. That is the point of asking: inference off a style name cannot know that a particular wool shell has no lining, and the DM holding the spec sheet can.
- **It cannot be changed after release.** Pieces are minted against it and their barcodes are printed.

The request body uses `extra="forbid"`, so a misspelt or misplaced field is a 422 naming it — rather than a silent no-op on the one field this endpoint exists to capture.

9.6 Partial accept

An already-released style comes back in `rejected` with its reason; the rest still release. **Read `minted`, not the HTTP status.**

9.7 There is no longer a pool to run out of

`minted.pieces_waiting_for_drawer` **is gone from the release response**, and `grow_drawer_pool` on the release body is ignored.

It used to count the garments a release had minted beyond the 200 free drawers — real barcodes with nowhere to be stored, and therefore unable to pass the merge gate until a drawer freed up. The store is now a state on the garment, so the shortage cannot happen and the banner that reported it should come off the upload screen.

9.8 The order index

`GET /imports/orders` is the index every breakdown screen opens from, with a rolled-up status per order:

breakdown_status	Meaning
<code>NOT_UPLOADED</code>	The order exists; no breakdown committed yet
<code>DRAFT</code>	Sheet uploaded, nothing released, nothing minted
<code>PARTIALLY_RELEASED</code>	Some styles in production, some still editable
<code>RELEASED</code>	Every live style released and minting pieces
<code>CANCELLED</code>	Every style on the order was cancelled

Ordered **most-recently-worked-on first** — the newest of the order's creation and its last-written style. The client's `order_date` says nothing about what the factory is handling now.

10. The barcode system — the spine

Module: `app/modules/barcode/` · **URL prefix:** `/api/v1/barcode`

10.1 One registry, one front door

`barcode_registry` is the single table every scan resolves through. Each printed code — a piece, a material lot, an individual leather hide, an employee card — has exactly one row carrying its `type`, its `status`, and a nullable foreign key to the domain row it names.

`GET /barcode/resolve?code=...` is one indexed lookup:

Outcome	Meaning
404	Unknown code
410 Gone	Retired code — <i>"this was deactivated; the record and history are intact"</i>
200	The code's <code>type</code> plus a live payload for that type

That 404/410 split is the whole point. A retired employee card and a typo are different facts, and the screen should say different things.

Retirement applies to every barcode type, not just employee cards. A retired lot label and a deactivated piece must not silently resolve either.

10.2 The types

Type	Minted when	Editable?
PIECE	Release	No — permanent garment identity
LEATHER_LOT / LINING_LOT / ACCESSORY_LOT	Material lot created	No
DRAWER	<i>(withdrawn)</i>	Historical rows only — the drawer module is unrouted
LEATHER_SHEET	A hide is received or added to a cutting row	No — one label per physical hide
EMPLOYEE	Employee created	Yes — reissue / deactivate

10.3 One piece, two codes

Since the compact code arrived, a piece has **two** active registry rows:

- the small `PC-004821` that is printed and scanned — the primary,
- its old long `KJ2451-CLERMONT-57-M-017` code, kept alive so labels printed before the change still resolve — flagged `is_alias: true`.

`is_alias` is a stored flag, not inferred from the prefix. Every per-order count and the whole history list select `type=PIECE` rows; with two rows per piece and no discriminator, `minted` doubles, `balance` goes negative, the duplicates integrity proof reads as broken, and the history table shows each garment twice. Those queries need to name the rule they mean — *"the code happens to start with PC-"* is not that rule.

A resolve on a legacy code still works and returns `is_alias: true`, so the screen can nudge the operator to reprint the label.

10.4 The employee card lifecycle — history is sacred

Reissue (lost or damaged card): retire the old code, mint a new one. **History untouched.**

Deactivate (worker leaves): flip the registry status to RETIRED → resolve returns 410. **The employee row, all production events, and all wage lines stay intact.**

Both are audited. `PATCH /employees/{id}/barcode` is where they live — mounted under `/employees` because that is where the frontend expects it, but owned by the barcode module because employee barcodes are a barcode concern.

10.5 Resolve answers the next question too

A scan does not just say *what* the code is. It also carries:

Field	Meaning
<code>next_expected_scan</code>	"PIECE" / null — which code to present next. Answered for every type, including EMPLOYEE, which is the first scan of every workflow. A PIECE returns null : the garment is the end of the scan, not the middle of it
<code>next_stage + next_stage_label</code>	The production stage this piece is due at, derived by the same helper the write path uses
<code>next_stage_blocked_reason</code>	Set when that stage cannot be logged yet — e.g. the store has not released the garment

That last pair matters: the stage is **still reported** even when blocked. The screen shows where the piece is going *and* what is holding it there.

Why one shared helper: `next_chain_stage()` is pure and takes a set of completed operation codes. Both the write path (which decides what a scan logs) and the read paths (which tell the screen what is coming) call it. Two copies of that loop would drift, and the drift is invisible until a screen offers a stage the log then refuses.

10.6 Printing

`POST /barcode/print` returns a Code128-ready payload for a set of codes, or for every piece of a SKU or order. Each label carries the `code` to encode plus a `label_line` — the order number, article, style, colour, size and serial, pre-joined and ready to typeset underneath.

There is also a **material barcode screen** (`GET /barcode/materials`), which exists because lots minted a code at creation and nobody could reprint it once the first label was lost.

10.7 The order-level integrity proof

`GET /barcode/orders/{id}/analytics` reports planned vs generated vs balance, per order and per style, plus:

- **duplicates** — should always be 0. It is the proof that minting stayed idempotent.
- **half_minted** — some pieces exist but not all.
- **fully_generated** — the order is complete.

11. Materials, lots and the style recipe

Module: `app/modules/materials/` · **URL prefixes:** `/api/v1/materials`, `/api/v1/suppliers`, `/api/v1/styles`

Two related things live here: **what the factory HAS** (lots), and **what a garment NEEDS** (the recipe). They meet at six identity columns and nowhere else.

11.1 Three categories, strict fields

Every lot must carry exactly its category's fields, or the API rejects it with a 422. Creating a lot **mints a child barcode** — that is how material formally enters inventory.

Category / subtype	Required attributes	Quantity field	UOM	Filters
Leather	thickness, dcm	dc ^m	dcm	article, colour, thickness
Lining / plain	thickness, mtrs	m ^{tr} s	mtrs	article, colour, thickness
Lining / ribs	kg	kg	kg	article, colour
Lining / knit	pcs	pcs	pcs	article, colour
Accessory / button	size, count	count	pcs	article, colour, size
Accessory / zip	size, count	count	pcs	article, colour, size
Accessory / thread	thickness, mtrs	m ^{tr} s	mtrs	article, colour, thickness
Accessory / other	description, count	count	pcs	article, colour

article and colour are required for every material. GET /materials/spec?category=&subtype= returns this list at runtime, so the frontend renders the right form and the right filter boxes without hard-coding anything.

A (category, subtype) pair not in that table is **rejected** — the system does not invent a shape for a material class it was not told about.

11.2 Three stored numbers

```

on_hand    a real column – physically in the building
reserved   a reservation ledger – committed to a required quantity
available  on_hand – reserved ← DERIVED, never stored

```

available is never stored, **so the two can never drift**.

Category-specific attributes live in a JSON column rather than twenty mostly-null columns. The four the queries actually filter on — article, colour, thickness, size — are promoted to real indexed columns.

11.3 The lot picker

GET /materials/lots is the endpoint the cut screen uses to turn "black sheep glass, 0.7mm" into a lot id.

Three material GETs, three different jobs — worth keeping straight:

Endpoint	Returns
/materials/spec	The form definition — which boxes to render
/materials/lots	The rows , with lot ids
/materials/stock	Aggregate totals , with the lot ids summed away

The picker also does two helpful things: last_used_for_sku pre-selects the lot this SKU was last cut from (and shows that it did), and passing required makes each lot report covers_required — so a lot that cannot cover the batch is greyed out **before** the cut instead of warning after it.

Exhausted lots are returned, not hidden. A manager searching for a lot they know exists must find it, with available: 0 explaining itself.

11.4 Editing a lot — three different operations

The stock screen deliberately splits what looks like one action into three:

Operation	What it changes	Why separate
PATCH /lots/{id}	Identity — article, colour, thickness, size, supplier	

Operation	What it changes	Why separate
PATCH <code>/lots/{id}/adjust</code>	Quantity , as a <code>delta</code> with a mandatory reason, audited	It records a movement , so the ledger still adds up and someone can ask a year later why 40 dcm disappeared
DELETE <code>/lots/{id}</code>	Retires the lot and its barcode	Never a hard delete — cut events point at this lot and are the consumption history the costing screens are built on

Category, subtype, UOM and `on_hand` are not patchable. Moving LEATHER→LINING would leave a lot measured in dcm claiming to be metres, and every cut event already pointing at it would silently re-denominate. Setting `on_hand` directly would make the stock and the movement history disagree with no record of who changed it.

Retiring is presented as "*retire*", not "*delete*". A scan of the old label returns **410 Gone** ("*this lot was retired*"), not 404 ("*invalid barcode*").

11.5 Receiving

POST `/materials/receive` records **approved and rejected quantities separately**.

- Approved quantity is **added to stock**.
- Rejected quantity is **logged** — supplier quality history.
- A PO mismatch is a **409** unless a DM/MD sends `approve_mismatch: true`, which receives it into a **new substitute lot** rather than quietly re-labelling the old one.

11.6 Supplier orders

A simple two-state manual flow: **ORDERED** → **ARRIVED**. Raising an order validates the requested article against the chosen or suggested supplier's catalogue. GET `/materials/stock` suggests a supplier when short.

11.7 The style material spec — the recipe

Mounted at `/api/v1/styles/{style_id}/material-spec`. This is what one garment of a style needs: its leather, its lining, and every accessory.

```
StyleMaterialSpec (one row per line)
├─ style_id
├─ sku_id           null = the style-wide default; set = a per-SKU override
├─ category / subtype / article / colour / thickness / size
├─ qty_per_piece
├─ uom              DERIVED from (category, subtype) – never taken from the client
├─ material_lot_id  optional explicit binding
```

The UOM is derived, not accepted. Buttons are pcs, thread is mtrs — the unit is a property of the material kind. `uom` stays in the request contract only so a client can round-trip a GET without stripping fields.

11.8 Confirming the recipe unlocks release

POST `/styles/{id}/material-spec/confirm` is the sign-off, and it is a **separate call from release** on purpose: the DM can finish the recipe days earlier, and the release screen can render `release_blockers` **before** the button is pressed rather than explaining a rejection afterwards.

`no_accessories: true` is the DM stating "*this garment takes none*". It is the only thing that lets a style with an empty accessory list through the release gate — **an empty list on its own is ambiguous** (nobody entered them yet?), and releasing that silently is how a whole order reaches the store with no kit. Sending `true` while accessory lines exist is a 422, not a precedence rule.

11.9 The requirement screen

GET /styles/{id}/material-spec/requirement is qty_ordered × per-piece against what is on the shelf, per line.

This is the screen that should stop an order, and the moment to read it is before release. Afterwards the garments exist and a shortfall is a stoppage rather than a purchase order. short_by and suggested_supplier feed straight into POST /suppliers/orders.

11.10 The frozen recipe and its escape hatch

Once a style is RELEASED, its recipe **cannot be edited** — its garments are already being issued against it.

A wrong article is corrected by recording **what was actually handed over**: POST /materials/issues records a material issued to one garment outside its spec, and spends stock.

It is **repeatable on purpose**: three corrections on one garment are three real events, and none of them makes the kit checklist think a spec line was satisfied.

The store manager can call it — waiting for a DM to record a swapped button is how the correction stops being made at all.

12. Production — one log, two doors, four gates

Module: app/modules/production/ · **URL prefix:** /api/v1/production

12.1 The pipeline

```
LEATHER_CUTTING ┌
                  └─ parallel cut paths, per piece
LINING_CUTTING  ┌
                  └─
    → FUSING → PASTING → [ MERGE GATE ] → LINE_STITCHING → SHELL_STITCHING
    → FINAL_FINISH → FINAL_INSPECTION → PACKAGE_EXPORT
```

Two entry stages, one join. Leather and lining are cut independently, by different managers, on different screens. They have **no predecessor**. Everything after the store merge is a single linear chain.

That breaks the naive "one linear predecessor" model, so the code is explicit about it: predecessor() returns the leather-side predecessor for the leather chain, and **None for LINE_STITCHING** — because line-stitching's precondition is not "pasting done" but "leather and lining both in the store, and the store has released it", which the **completeness gate** enforces, not the sequence gate.

This is why the completeness gate is load-bearing rather than decorative. It is the *only* gate on LINE_STITCHING. Remove it and a garment can be stitched before it was ever cut, with nothing in the system to contradict the record.

Why stage order is in code, not config. The operation table stays the source of truth for labels and rates. But the stage **order**, the two parallel cut paths, the **role** → **stage** map and the **designation** → **stage** map are business law. Encoding order against operation.sequence alone would mean a stray UPDATE to a sequence number silently reorders the factory. Codes are stable; sequence numbers are not.

12.2 One endpoint, two doors, no stage buttons

POST /production/log is the whole floor's logging surface. The caller sends an **actor** (an employee, by barcode or id) and **targets** (pieces, by barcode or sku + seqs).

The caller never sends a stage.

- A **cut screen** (LEATHER_CUT / LINING_CUT) fixes the cut stage.

- Otherwise the stage is **inferred** from each piece's own history — the next chain stage after the furthest one it has completed.

"Furthest completed, plus one" rather than "first not completed": a piece that was reworked or logged out of order should advance from how far it has actually got, not stall at the earliest gap.

The **screen context is derived from the role**. A cutting manager is pinned to LEATHER_CUT; a lining manager to LINING_CUT; a stitching manager or supervisor to PIPELINE. Any value they send is ignored. Only DM/MD/HR — who legitimately log any stage — may pass an explicit override.

Both doors POST the same shape. The router resolves barcodes to ids; the service sees ids only.

12.3 The four gates

Cheapest and most-likely-to-fail first.

#	Gate	Scope	On failure
1	ROLE — may this role log this stage?	Whole request	403
2	SKILL — may this designation work this stage?	Per piece	Warning, still logged
3	SEQUENCE — has the piece completed the previous chain stage?	Per piece	sequence_blocked
4	MERGE — for LINE_STITCHING only: has the store sent this garment?	Per piece	merge_blocked

Gate 1 is whole-request because the role is wrong for the whole batch — there is nothing per-piece about it. **Gates 2–4 are per-piece** so that one bad piece never loses the thirty-nine good ones a manager scanned with it.

MD and DM bypass the role gate. HR does too (`_STAGE_BYPASS_ROLES` in `production/service.py`).

Gate 1 in full — which role logs which stage

`STAGE_ROLE_ACCESS` in `core/enums_barcode.py` . This is the whole map:

Stage	Role that may log it
LEATHER_CUTTING	cutting_manager
LINING_CUTTING	lining_manager
FUSING	stitching_manager
PASTING	stitching_manager
LINE_STITCHING	stitching_manager
SHELL_STITCHING	stitching_manager
FINAL_FINISH	stitching_manager
FINAL_INSPECTION	— none —
PACKAGE_EXPORT	— none —

THE LAST TWO STAGES HAVE NO MANAGER ROLE, AND THAT IS DELIBERATE. Only MD, DM and HR can log final inspection and package-and-export, because those are the two stages that decide a garment is *finished* and *gone*. The stitching manager's authority stops at `FINAL_FINISH`.

This is the 403 that looks like a bug and is not. A stitching manager scanning a garment at final inspection gets "*The final inspection stage is logged by its own manager (direct_manager, managing_director)*" — the message falls back to naming DM/MD precisely because the allow-list is empty. Do not "fix" it by adding `stitching_manager` to the map.

The escape hatch is per-operation, not per-stage. `operation_access` is a real table: an MD can grant one role one operation without a deploy, and Gate 1 checks it (`repo.operations_for_role`) after the enum map says no. That is how a factory that genuinely wants its stitching manager to close out garments does it — as an audited grant, not by rewriting business law.

Gate 2 in full — which designation is ordinary for which stage

`STAGE_DESIGNATIONS`. A designation **outside** its stage's set produces a warning in `skill_warnings[]` and **still logs the piece**.

Stage	Ordinary designations
<code>LEATHER_CUTTING</code>	<code>CUTTER</code>
<code>LINING_CUTTING</code>	<code>CUTTER</code> · <code>LINING_CUTTER</code>
<code>FUSING</code>	<code>CUTTER</code> · <code>FUSER</code>
<code>PASTING</code>	<code>PASTER</code> · <code>TAILOR</code>
<code>LINE_STITCHING</code>	<code>LINE_TAILOR</code> · <code>TAILOR</code>
<code>SHELL_STITCHING</code>	<code>SHELL_TAILOR</code> · <code>TAILOR</code>
<code>FINAL_FINISH</code>	<code>FINISHER</code> · <code>TAILOR</code>
<code>FINAL_INSPECTION</code>	<code>FINISHER</code> · <code>INSPECTOR</code>
<code>PACKAGE_EXPORT</code>	<code>FINISHER</code> · <code>PACKER</code>

The floor is cross-trained, and the map says so. `CUTTER` appears at the lining cut and at fusing; `TAILOR` appears at four stages. That is the factory, not a loose gate — widen it only when the floor genuinely cross-trains a role, never to silence a warning.

`MULTI_STAGE_DESIGNATIONS` — `HELPER` and `SUPERVISOR` — are exempt everywhere: they never raise a skill warning at any stage, because covering any stage is what they are for. An **unknown** designation fails open the same way, so an HR backfill gap never blocks the floor.

Gate 2 is a warning, not a block. A cutter logged on a pasting job still records the work; the anomaly comes back in `skill_warnings` with the employee, their designation, the stage and a note. Blocking it would mean a helper covering a shift cannot be recorded at all.

Rework is permissive and bypasses gates 3 and 4. A piece returning to a stage it already passed is legitimate — flagged, never blocked.

12.4 The door gate

`POST /production/log` also carries a **role dependency at the door**, in front of the per-stage gate.

The route deliberately had none for a while, on the reasoning that the role gate is stage-specific. That is true for a piece with a resolvable stage — and it left a gap for one without. A piece that has not been cut yet resolves to *no* stage on the PIPELINE screen, so Gate 1 never runs and the request comes back 201 with everything in the `not_cut` bucket, for **any** authenticated token.

Nothing was ever written on that path, so it was not a data leak. It was worse as an **answer**: a store login was told "*nothing logged, cut it first*", implying it may log once the piece is cut — when in fact its scan will 403 the moment a stage resolves. The role that cannot log anything is now told so at the door, once.

STORE_MANAGER is deliberately absent from the logger set.

12.5 Consumption

The two cut stages only capture material consumption per piece and **decrement stock once per batch**, in the same transaction as the events.

The lot link lives on the event — the act of cutting — never on the piece.

Three doors supply the lot:

1. **Lot id** — the screen already picked one.
2. **Article + colour + optional thickness** — the cutting manager types what is on the hide, and the router resolves it through the same lot picker the UI uses.
3. **use_style_spec: true** — take the dcm from the style's recipe.

Two of those refuse to guess:

- **No lot matches** → 404 naming the spec and telling you to add the delivery first.
- **Several lots match** → **409 naming up to five candidates** with their availability. Silently taking the first would decrement stock from a lot the manager never chose — a wrong number in the one ledger the factory reconciles against, and invisible.
- **A batch whose pieces disagree on the spec dcm** → 422 naming both values. Pieces from two SKUs with different overrides have no single number, and picking one would write the wrong consumption against half the garments.

use_style_spec is **off by default**, deliberately: omitting both dcm and the flag still returns today's 422, so no existing client silently changes behaviour on the one branch that guards the leather ledger. The recipe is normally reached the other way round — /production/piece-state returns suggested_dcm_per_piece and the screen prefills the field, so the operator still confirms the number that reaches the ledger.

A cut that consumes more than the lot has available is still recorded. Stock drifts and the garment is physically cut; the shortfall comes back in stock_warning rather than silently driving on_hand negative.

12.6 The scan-time read

GET /production/piece-state is what a barcode scan should return: **one piece**, not a SKU.

Send code + employee_barcode and read three fields:

Field	Meaning
current_stage	Where the piece is now
next_stage	What this scan would log — never chosen by hand
ready_to_log	true → POST the log immediately. false → show blockers. null → no employee was sent, so the question is unanswered — which is not the same as blocked, and must not be rendered as one

It exists because stage inference and all three per-piece gates used to run only at **write** time, so the UI had to guess: it made the operator pick a stage by hand, and it left later stage cards scannable before their predecessor was done. This answers both from the server, **using the very same predicates the log enforces** — so a card the UI opens is a card the log will accept.

It also carries the piece's store state, its `stages[]` cards (each `completed` / `next` / `locked` / `not_applicable`, with the gate and reason for a locked one), the `actor` block (name, designation, whether they are checked in, any skill anomaly), the `material_requirement` kit checklist, and `sku` progress.

12.7 The response

`POST /production/log` returns a rich per-piece result, because a batch of forty is forty separate outcomes:

Field	Meaning
<code>stage</code>	The stage logged. "MIXED" when a PIPELINE batch spanned several; <code>null</code> only when nothing resolved
<code>stage_by_piece</code>	The truth for a mixed batch
<code>logged</code> / <code>rework</code> / <code>not_found</code> / <code>completed</code>	The classic buckets
<code>sequence_blocked</code> / <code>skill_blocked</code> / <code>merge_blocked</code> / <code>role_blocked</code>	Per-piece refusals
<code>blocked[]</code>	Every rejection with its cause — <code>{piece, stage, gate, reason}</code>
<code>skill_warnings[]</code>	Gate-2 anomalies that still logged
<code>stock_warning</code>	A cut that went short
<code>sku_progress</code>	<code>{total, done, remaining, closed}</code> for the stage just logged. closed: true means stop offering this style for scanning
<code>drawer_by_piece</code>	Each piece's store state. The key keeps its old name so existing clients do not break; read it as the garment's store state
<code>kit_by_piece</code>	Deliberately lean — <code>kit_required</code> , <code>kit_status</code> , <code>outstanding</code> . A forty-piece batch carrying full requirement blocks would dwarf the rest of the response
<code>message</code>	One sentence for the scan screen

preview: true runs the whole thing as a dry run: computes every bucket, writes nothing.

12.8 The retired routes

`POST /production/cutting` and `POST /production/scan` return **410 Gone** with a message pointing at `/log`. A deleted route 404s, and a 404 on a screen that worked yesterday reads as *"the server is broken"*. 410 says the removal was deliberate.

13. Cutting — the grid that replaced the spreadsheet

Module: `app/modules/cutting/` · **URL prefix:** `/api/v1/cutting`

13.1 The problem


The cutting manager kept the real record in Excel: which hides went to which garment, the DCM on each one, what came back, what was adjusted. Then he typed the finished bundle into the ERP a second time. **Two systems, double work, and the ERP could not answer the one question the whole module exists for — how much leather did this jacket actually cost?** V1 only started recording once the bundle was already cut, by which time the hides were gone.

13.2 A hide is a thing, and it has a barcode

One leather sheet is one physical hide. You cannot make a garment from one — it takes **seven to twelve** — so the lot-level barcode could never say which skins went into which jacket. **Every hide now gets its own printed label** (`BarcodeType.LEATHER_SHEET`), which is the MD's requirement and the thing that makes per-piece leather cost real rather than an average.

<code>material_lot</code>	"NAPPA-77 / PINE GREEN / 1.2mm"	← what the material IS
└─ <code>material_sheet</code>	LS-000123, 44 dcm, IN_STOCK	← one physical hide

A sheet's status is a fact about where it is, not a balance:



A sheet is fully consumed by the row it is issued to — it never spans two garments. That is why a status is enough and no per-hide balance is kept.

`lot.on_hand` stays the leather stock figure in dcm and remains what production decrements. Sheets are the detail beneath it. The consistency check ($\sum \text{IN_STOCK sheet dcm} == \text{on_hand}$) is **reported, never enforced** — a mismatch is something a human needs to see, not a reason to refuse a delivery.

13.3 One row is one garment

<code>cutting_row</code>	<code>piece · style · colour · article · size · rc_no</code>
	<code>cutter_employee_id · work_date</code>
<code>target_dcm</code>	what the allocator aimed at
<code>total_dcm</code>	DERIVED from its sheets – never typed
<code>status</code>	DRAFT → APPROVED → LOGGED

Sheets attach by `material_sheet.cutting_row_id` , so "*the hides on this row*" is one indexed read **and a hide can never be on two rows**.

13.4 How many hides — the size baseline

The DM is not asked for a per-piece DCM, so the system needs a defensible default. `app/core/leather_norms.py` holds a pure size → DCM table, validated against the factory's own sheets (six rows averaging **46 dcm per hide**) and against the leather trade's 45–55 sq ft per jacket:

Size	Target dcm	≈ hides @46
XS	340	7
S	370	8
M	400	9
L	430	9
XL	465	10
XXL	500	11
XXXL	540	12

Italian numeric sizes ride the same ladder (46=XS, 48=S, 50=M, 52=L, 54=XL, 56=XXL, 58+=XXXL).

It is explicitly an estimate. The style's own `style_material_spec.leather.qty_per_piece` wins whenever it exists, and `target_source` on every row says which number was used — "`style_spec`" (somebody measured it and signed it off) or "`size_baseline`" (this system's estimate) — so the manager knows whether to expect to correct it.

13.5 The grid, and why every cell is editable

`POST /cutting/rows/generate` creates one DRAFT row per un-cut piece of the chosen style + colour and allocates hides nearest-fit first until the running total reaches the target. Allocated hides move to `ALLOCATED` so two rows cannot claim the same skin.

Then **the manager edits every cell** — cutter, size, rc_no, article, colour — because that is what he was doing in Excel, and the grid has to be at least as good as the thing it replaces. Adding and removing hides is the flow he named directly: *the cutter came back and needed one more skin*.

- `POST /cutting/rows/{id}/sheets` — scan it, pick it, or create it
- `DELETE /cutting/rows/{id}/sheets/{sheet_id}` — **returns it to IN_STOCK**
- `PATCH /cutting/rows/{id}/sheets/{sheet_id}` — correct a hide's DCM

All of it free and unaudited **while the row is DRAFT**. Nothing has been claimed yet, so there is nothing to protect.

13.6 Approval is a wall, not a checkbox

`POST /cutting/rows/{id}/approve` freezes the row: these hides, this total, this cutter. Sheets move `ALLOCATED` → `ISSUED`, `total_dcm` is frozen, and any further edit is a **409**. Undoing it is a `reopen`, and both are audited (`CUTTING_ROW_APPROVED` / `CUTTING_ROW_REOPENED`).

`AuditLog.actor_user_id` is an `app_user.id` — the **LOGIN**. The row's `cutter_employee_id` is a **worker**, in a different table, with no login at all. Passing the scanned employee id here is the mistake that produced a 500 in the old store scan. The worker belongs in the audit `after` payload, as data.

13.7 What the cutter's scan does with it

`POST /production/log` is unchanged in shape. When a cut scan resolves a piece that has an **APPROVED** row, the router pulls `article`, `colour`, `lot` and `total_dcm` from that row instead of demanding them on the request — `consumption_source: "CUTTING_ROW"` in the response says so.

The operator types nothing. It was entered once, on the grid, and signed off.

On success the row goes `APPROVED` → `LOGGED` and its hides `ISSUED` → `CONSUMED`. Stock timing is **unchanged**: approve reserves, logging consumes, and the single per-batch decrement is the same one production always did.

A piece with no approved row keeps the old typed path exactly, so nothing on the floor breaks mid-migration.

13.8 Attendance is on this screen for a reason

The grid shows who is **present today**, from `AttendanceService.today_roster()`. The manager must not be able to pick a name that cannot legally be logged against — production refuses an absent worker, and a grid that offers one is a grid that produces a 400 an hour later with no explanation attached to it.

14. The store and the merge gate

Module: `app/modules/store/` · **URL prefix:** `/api/v1/store`

Drawers are withdrawn. `/api/v1/drawers/*` is unrouted — not renamed, not deprecated. This chapter describes what replaced it, and why.


14.1 Why the drawer had to go

There were **200 physical drawers**. A style releases a hundred-plus garments, the run stalls mid-chain, the next fifty have nowhere to go — and re-allocating by hand was too complicated for the DM to actually do. The drawer was a **bottleneck that earned nothing**: it was a place to put a thing, and the system was modelling the place instead of the thing.

The store is now a state on the garment. It has no capacity, nothing runs out, and `pieces_waiting_for_drawer` has disappeared from every screen it used to appear on — because the shortage it counted no longer exists.

14.2 The state, and where it lives

Five columns on `piece`: `store_state`, `leather_in`, `lining_in`, `accessories_in`, `store_entered_at`. The same seven states the drawer had, minus the pool:



The migration copied each drawer's state onto the piece it was holding, so nothing in flight was lost. The drawer tables remain, **unwritten, for audit**.

14.3 The scan: employee, piece, enter

Two scans, not three. The drawer scan is gone, and that is the whole "make merging easy" fix — the piece barcode already says which garment it is, and the drawer only ever said where it happened to be sitting.

`POST /store/scan` takes an **employee** and a **piece**. Both are mandatory:

- **The employee scan is not optional.** The store scan used to accept no actor at all — the one door on the floor where "who did this" was unanswerable. A rule only the frontend enforces is a rule that disappears the moment anything else calls the API.
- **Who may stand at this screen:** Store Manager, Stitching Manager, DM, MD. Managers scan too, not only workers — the store is not always staffed.

`part` is **optional**. The server infers LEATHER vs LINING from the piece's own cut history and what the garment is still missing. Send it only to override.

`part=ACCESSORY` is **explicit-only and never inferred**. The worst a wrong LEATHER/LINING guess can do is set a boolean a human can flip back. An inferred ACCESSORY would **spend stock** — it decrements every accessory lot on the style's spec — so a mis-inference would move money nothing on the floor asked to move. The accessory scan is **idempotent**: a second tap issues nothing and returns the same 200.

A part cannot be parked before it has been made. Storing a lining on a garment with no `LINING_CUTTING` event is a **409**: the store is where a *finished* part is put down, not where an unfinished one waits.

Every scan returns the kit block, cut parts included, so the person at the screen sees what the garment still needs without leaving it.

14.4 Completeness, not sequence

- A **lined** jacket needs leather **and** lining before it is complete.
- A **leather-only** piece (`needs_lining: false`) is complete on leather alone.

RECEIVED is reached automatically the moment a garment holds everything it needs. The old flow — press RECEIVED, then press SEND, one drawer at a time — is gone, because RECEIVED asserted a fact the server had already computed.

`needs_lining` on every store row is the **EFFECTIVE requirement**, resolved from the style, the SKU and the cut history — **not** the stored `piece.needs_lining` flag, which is written once at release and is wrong for most of a live order. When the two disagree, `lining_reason` says why.

14.5 Send — the decision that stayed

SEND is a **decision**, so it stayed, and it is **plural**, because the store never releases one garment at a time.

POST `/store/send` takes piece ids or piece barcodes and nothing else. **There is no destination to pick**: lining is upstream of the store, so a complete garment has exactly one way forward.

Sending sets `store_state = SENDED`, which is exactly what the production merge gate reads. The whole selected bunch becomes eligible for LINE_STITCHING in one action.

Partial accept: a garment that is not yet complete comes back in `not_ready` with its reason; the rest are still sent. **Check count_sent**, not the HTTP status.

Who may send: MD, DM, Store Manager — **and the Stitching Manager**. That last one is deliberate: sending is what releases a batch into line-stitching, and on the floor the stitching manager is the one who walks to the store and takes the garments. Requiring a DM to press the button made the store a bottleneck on a decision the stitching manager was already making physically. It is a **role grant on the store surface, not a production permission** — `STAGE_ROLE_ACCESS` is untouched. Cutting and lining managers are still excluded: they put parts **in**; they do not decide what leaves.

14.6 THE GATE — and why this chapter matters most

`_merge_ok` is the **ONLY** gate on LINE_STITCHING.

`_sequence_ok` returns `True` early for that stage, because `LINE_STITCHING` has no chain predecessor by design — the two cut paths run in parallel and converge here. So if the store state ever stops gating line-stitching, **a garment could be stitched before it was ever cut, and nothing in the system would contradict it**.

That is why the piece-level gate was written and tested *before* a single line of drawer code was removed, and why the end-to-end flow asserts the refusal by name.

14.7 The store list

GET `/store/pieces` is the store's working screen — filter by `state`, `style_id`, or a piece code. GET `/store/pieces/{piece_code}` is one garment, and it is reachable by **every floor-facing role**, so the person physically placing pieces can look one up without DM access.

There is no pool screen, no shortfall, and no "allocate waiting pieces". Those endpoints existed to manage a scarcity that no longer exists.

15. Inspections — reject and rework

Module: `app/modules/production/inspection.py` · **URL prefix**: `/api/v1/inspections`

15.1 The gap this closed

Rework was **refused on the write path and counted on the read path** — the dashboards reported a number the API would not let anybody produce. And a defect found at final inspection had nowhere to go: the garment was simply logged again, so the record said the work was done twice and never said it was done *wrong*.

15.2 A defect names a stage, and a stage names a person

`POST /inspections` records a **reject** or a **rework** against a piece, with the stage **responsible** for the defect — not the stage it was found at. A seam that opens at final finish is a line-stitching defect, and the difference is the whole point: `GET /inspections/responsibility` is the report that says where defects are actually being created.

`Designation.QC_INSPECTOR` already existed in the vocabulary, unused. It is now this module's designation.

15.3 The DM approves the re-walk

A rejection is a **decision about money** — somebody's work is being sent back — so it is proposed and then approved:

<code>POST /inspections</code>	an inspector records it
<code>POST /inspections/{id}/approve</code>	DM agrees – the piece re-walks from the responsible stage
<code>POST /inspections/{id}/decline</code>	DM disagrees – nothing moves

On approval the piece's position moves back to the responsible stage, and the stages after it are invalidated so they must be logged again.

15.4 The re-walk is counted, not timestamped

The obvious implementation compares `created_at` against `resolved_at`. It cannot work here: `created_at` is **naive, with one-second resolution**, and `resolved_at` is **timezone-aware, with microseconds** — so the comparison is never true and a re-walked garment stalls forever.

The working implementation **counts**: `event_counts_by_stage` against `resolved_redo_spans`. A stage is satisfied when it has been logged more times than it has been sent back.

And the span is bounded — `index[target] < here <= index[found]` — because invalidating every stage after the defect would demand re-logging stages the garment had never reached, which is how `SHELL_STITCHING` came to be logged twice.

16. Job work — garments that leave the building

Module: `app/modules/jobwork/` · **URL prefix:** `/api/v1/jobwork`

16.1 The gap

When a deadline is short, tailoring — or cutting, or lining — goes to another factory. Nothing modelled it. The garments stopped moving, nobody could say where they were, and **the money paid for the work was recorded nowhere**.

16.2 Three tables

<code>vendor</code>	<code>name · contact · is_active</code>
<code>job_work</code>	<code>vendor · stage · dispatched_at · expected_back · returned_at · status</code>
<code>job_work_piece</code>	<code>job_work · piece · status (OUT BACK SHORT REJECTED)</code>

Registering the same vendor name twice **returns the first one**. A duplicate is not a mistake worth blocking with a 409.

16.3 GATE 7 — a garment that is away cannot be scanned here

`POST /jobwork/dispatch` sends garments out, and they stop being scannable in-house until they return. Otherwise the system records line-stitching done *here* on a jacket sitting twenty miles away, and nothing would ever contradict it.

The refusal **names the vendor** — `offsite_blocked`, with a `blocked[]` reason carrying the vendor's name — because "this piece is blocked" is not actionable and "this piece is at SUNRISE TAILORS" is: somebody can go and get it.

One garment at a vendor does not lose the tray. Like every other per-piece gate, the good pieces scanned alongside it still log.

A piece already out at another vendor is **skipped and reported**, never double-booked: two open records claiming one garment would each look satisfied by the other's return.

16.4 The vendor's work IS the stage

`POST /jobwork/{id}/receive` books garments back in **and logs the stage the vendor performed**. The work really happened, so the garment must advance and the progress counts must include it.

But it is logged with `employee_id = NULL` and `vendor_id` set. Nobody on our payroll did it, so **no wage line may be generated** — and because the wage query inner-joins Employee, the event drops out of payroll on its own rather than by a special case somebody has to remember to write.

Receiving twice does not log the stage twice.

16.5 Only what came back is paid for

"Even when we give it to the outside factory we are paying for each piece, so we have to track that."

`rate_per_piece` is **optional** — some work is quoted per piece, some is settled another way, and demanding a number nobody has yet means the dispatch does not get recorded at all. A job with no rate reports `cost: null`, **not 0**, because zero reads as free.

SHORT and REJECTED are kept apart because they lead to different conversations: a missing garment is a loss to chase with the vendor, a badly-made one is a quality matter. **Neither is work delivered, and neither is paid for.**

A return where some pieces are still out is `PARTIAL` — *"the job is back"* is a different statement from *"every piece is back"*.

16.6 Overdue is the alert

`expected_back` goes on the dispatch, and `GET /jobwork?overdue=true` is the chase list. **A dispatch nobody chases is how garments go missing.**

17. Attendance

Module: `app/modules/attendance/` · **URL prefix:** `/api/v1/attendance`

17.1 Every write comes from an operator

Only four roles may write attendance: SECURITY, HR, MD, DM.

Nobody else on the floor has a login, so there is nothing else it could be. Both doors share **one dependency**, so the barcode door and the manual door can never drift apart.

17.2 Two doors

The barcode door (primary): `POST /attendance/scan-check-in` with the card code and a direction of `"in"` or `"out"`. The operator standing at the gate scans every card — monthly or daily, including their colleagues'.

The manual door (fallback): `POST /attendance/proxy/check-in` and `/proxy/check-out` when a card fails or is forgotten. Takes a list of employee ids. Any wage type.

`/attendance/check-in` and `/check-out` are now an **operator recording their own** arrival and departure — their login is linked to an employee row. The body is optional; identity comes from the token and the timestamp is set server-side to block client-side clock manipulation.

17.3 One row per person per day

`work_date` uniqueness is enforced **at the database level**, so a duplicate check-in is physically impossible rather than merely discouraged. Check-in is **idempotent** — a re-tap is a no-op.

`recorded_by_user_id` names the operator on every proxy entry. Accountability, and a fraud trail.

Three flags are computed **at write time** so dashboards never recompute on read: `is_late`, `is_short`, `is_overtime`.

17.4 Shift policy is data, not code

A single `shift_config` row holds the start time, shift length, grace minutes and the factory timezone — so HR can change them without a redeploy. The timezone is the single source of truth for interpreting wall-clock policy and for deciding which calendar day a punch belongs to. Storage stays UTC; the timezone is applied only at the business-logic and display boundaries.

17.5 Location tracking is removed

No route asks for, validates or stores a position. Check-in succeeds on identity alone.

`lat` and `lon` are still **accepted and ignored** on the bodies that used to require them, so a client that still sends coordinates gets a 201 rather than a 422. The geofence columns remain mapped on the model because they are NOT NULL in Postgres with no server default — removing them for real is a migration, not a comment-out.

17.6 It gates production

Production logging requires the employee to be present today. That is the link between the two modules: work cannot be recorded for someone who is not in the building.

17.7 Correcting a punch — and why it is re-allocation, not deletion

The real mistake on the floor is not "nobody was here".

Security scans a card at the gate. The card said MAJID; the worker who actually did the day's cutting was SALIM. By the time anybody notices, MAJID has twelve cutting events against his name — **and the wage for them, because wages are computed from the events, not from the attendance.**

So the correction the floor needs is not *"delete the attendance"*. It is **re-allocate it to the right person, and take the day's work with it.** The work happened; it was simply filed under the wrong name, and the name is on both records.

`PATCH /attendance/{id}` with a new `employee_id` moves the punch **and every production event that worker has on that date**, in one action, under one reason, with one audit row. The response says how many events moved, so the operator sees the size of what they just did.

Why they move in the same action. Leaving them behind splits one mistake into two jobs, and the second is the one nobody remembers to do: attendance would say SALIM was here while the cutting log still paid MAJID. The money would follow the wrong worker no matter how many times the attendance was corrected.

Only that day moves. A swapped card is one day's mistake; yesterday's events stay where they are.

Correcting a time recomputes the flags. A corrected punch still claiming `is_short` from the old times would be worse than not correcting it at all.

17.8 Delete is narrower than edit

Operation	Roles	Why
<code>PATCH</code> — correct / re-allocate	SECURITY · HR · MD · DM	a gate operator who mis-scans must be able to fix it without going to find anybody
<code>DELETE</code> — remove the record	HR · MD · DM only	it decides whether somebody is paid for the day at all

A reason is mandatory on delete (422 without it) — it is the only thing that makes the removal reviewable afterwards.

And a delete is refused when the worker has production events that day (409), with the refusal naming the better operation. The work was really done, so the cause is a swapped card rather than an absent worker — and deleting would leave those events dated to a day the worker was never marked present, a state **the production log's own presence gate would have refused to create**.

17.9 A closed payroll run is a wall

Both operations refuse with **409** when the day falls inside a **CLOSED** wage run — the same rule production events follow, and for the same reason. A closed run is the document the cash was counted against and is **never recomputed**, so a change underneath it would leave the payroll disagreeing with the days it claims to summarise. The fix there is a payroll adjustment, not a quiet edit.

An OPEN run does not block anything — nothing has been paid yet, so the recompute picks the correction up.

17.10 One punch per worker per day, said in words

`work_date` uniqueness is a **database constraint**, so re-allocating onto somebody who was already marked present that day would collide. The service checks first and returns a **409 naming the person** — *"PADMA is already marked present on 2026-09-18"* — rather than letting an `IntegrityError` surface as a 500 the operator cannot act on.

18. Wages

Module: `app/modules/wages/` · **URL prefix:** `/api/v1/wages`

18.1 Rates are date-effective

A rate is `(style, operation, rate, effective_from)`. A mid-period rate change prices **each day at the rate in force that day**. Nothing is retroactively re-priced.

The rate screens never show or accept a UUID — `style_code` and `operation_code` go in, and the service resolves them.

`GET /wages/styles` carries `rated_operations / total_operations` per style, so **unpriced styles are visible before payroll runs and silently pays zero for them**.

18.2 Two payrolls, not one

This is the central idea of the module. The fork is on the **employee population**, and it exists because the two populations are priced by incompatible facts.

run_kin d	Pays	Scope	Why
<code>piece</code>	PIECE_RATE workers	<code>style_code</code> or <code>order_number</code> REQUIRED	A piece wage is earned on a specific garment, so the style is the run, not a filter on it
<code>monthl y</code>	MONTHLY salaried staff	None required	A salary is a fact about a person for a period. There is no honest way to say what share of a fitter's month belongs to CLERMONT rather than CARNABY
<code>~~ comb ined ~~</code>	Both	—	Legacy only. Never created any more

The scope requirement on a piece run is the guardrail. Dates alone used to be accepted, and that is how a manager pays the whole factory's piece work under a window they meant to narrow. It is enforced at the schema (so it appears in the OpenAPI contract and the frontend can grey out the button before the round trip) **and repeated in the service** — because a rule only the HTTP layer knows is a rule that vanishes the moment anything else calls compute.

A monthly run **may** carry an order or style as a **label** for the payroll screen ("*the month we ran CLERMONT*"). The response echoes `scope_is_label: true` to say it did not narrow anything. **The screen must not print "CLERMONT payroll" over a sheet that paid every salaried person in the building.**


A piece run and a monthly run over the same window do not conflict. Their populations are disjoint, and together they are one complete payroll for that fortnight — compute both.

18.3 One line per employee per run

PIECE_RATE and MONTHLY are **mutually exclusive** — never both on one line. `pieces` is always 0 for monthly.

Behind each summary line sits a `wage_line_detail` row per `(employee, style, operation)` cell, carrying the pieces, the rate applied and the amount. That is what makes the three breakdown folds possible.

18.4 The run lifecycle



Status	Meaning
OPEN	A draft . Lines exist and can be recomputed freely — nothing has been paid against them, so rewriting them costs nothing
CLOSED	Frozen . The document the cash was counted against. Never silently recomputed

Recompute discards the lines and rebuilds them from current production events and rates, for the same window and the same scope. The run keeps its id; `recompute_count` increments and the actor is stamped — so a payslip reprinted afterwards is **identifiably a different document** from the one paid against.

Reopen is the only door out of CLOSED, requires a **reason**, and is DM/MD only. It is deliberately a separate call from recompute: a manager who must press reopen, type why, then press recompute cannot rewrite a paid payslip by mistyping a run id. The reason is stored and belongs on every reissued payslip for that period.

`confirm_closed: true` on recompute is a one-call escape hatch. It works, it stamps the recompute, and it **records no reason** — which is exactly why the reopen door exists.

Close is idempotent (a double-click changed nothing) and **refuses to freeze a run with no lines** — locking a window in which nobody is paid is never what was meant.

Delete exists because the overlap guard has always named it. `create_run` commits an OPEN run **before** any line is written, so a compute that died halfway left a committed empty run permanently occupying that window, blocking every later run over those dates, with no way to clear it. It refuses a CLOSED run unless explicitly confirmed: deleting a frozen run destroys the record of a payment that actually happened. **To change a frozen run, reopen and recompute** — that keeps the audit trail. Deleting is for runs that should never have existed.

18.5 The overlap guard

Two runs that would pay the same money twice is a **409 naming the run that blocks you** and what to do about it.

Before paying anyone, check two fields on the response:

- `unrated_operations` — stages with no rate in force. They pay **zero**, silently, unless you look.
- `gap_days` — days in the window that no run covers.

18.6 The result screens

Endpoint	What it gives
<code>/runs/{id}/breakdown</code>	One frozen run folded three ways : per style (stages and workers nested), per stage factory-wide, and per employee
<code>/runs/{id}/pieces</code>	Per-piece detail — which garment, which stage, which worker, their employee barcode, and what that one piece paid
<code>/ledger</code>	Every computed run, latest computed first , searchable

All three breakdown folds come off the **same frozen row set**, so the three tabs cannot disagree with each other or with the run total — which they will if the frontend sums them itself.

Per-piece amounts come from the run's **frozen** rate for that cell. Nothing is re-priced, so a rate corrected after the run closed does not change what this says the run paid. A row with `amount: null` carries a `note` explaining why (a monthly worker, or the stage was unrated at run time) — **deliberately not a zero**, which would read as work worth nothing.

The ledger is ordered by **when a run was computed**, not by its period: the question the ledger answers is "*what did we just run*".

18.7 Who may see it

Wages are visible only to **HR, DM and MD**.

Every other read endpoint in this codebase uses bare `get_current_user`. These do not, because CLIENT is a real role with a real login, and **per-piece labour rates are the factory's cost structure**. A client who can see that cutting pays 12.50/pc on their own style is holding your margin during the next price negotiation.

HR **reads** payroll. DM and MD **authorise changes** to it — recompute, reopen, close and delete are all DM/MD.

19. Analytics and the manager dashboards

Modules: `app/modules/analytics/` and `app/modules/dashboard/` · **Prefixes:** `/api/v1/analytics`, `/api/v1/dashboard`

Both are **read-only** and **own no tables**. Every query reads other modules' models.

19.1 What moved, and why

The standalone **Analytics Overview** and **Risk Alerts** screens have been **removed** — they return **410 Gone** with a message naming the replacement.

The reasoning: the bottleneck and the alerts were the only parts of those pages anyone acted on, and **a manager should not have to know a separate screen exists to find out their line is blocked**. They moved onto the surface every manager already opens — `GET /dashboard/alerts` — readable by every manager role rather than the DM alone.

They are 410 rather than deleted for the same reason the old production routes are: a 404 on a screen that worked yesterday reads as "*the server is broken*".

19.2 Analytics — the drill-down

```
/explorer → /orders/{id}/tree → /styles/{id}/detail → /pieces/detail
```

Plus two features that stand on their own:

- **The piece life story** (`/pieces/{code}/story`) — every stage a piece passed, who worked it, when, the rework flag, leather consumption at cutting, its current stage and what it is waiting on.

- **Consumption vs stock** (`/consumption`) — leather consumed per style, summed from cut events.

Analytics is a **live** view. Payroll of record stays the frozen wage run, and the two legitimately differ mid-period.

19.3 The five dashboards

Each is a **composite** — one call returns a whole screen.

Dashboard	For	Contains
Cutting	Cutting Manager	KPIs, current order, per-cutter performance, leather lots, per-order progress, 14-day trend
Lining	Lining Manager	The same shape for the lining leg, plus upcoming work — leather-cut pieces not yet lining-cut
Stitching	Stitching Manager	Top KPIs, the pre-store (fusing/pasting) and post-store (line/shell/final) blocks, the store handoff, the running style's funnel, per-stage employee performance
Store	Store Manager	Store KPIs, current styles in store, the filterable garment list, what is held and what is ready to send
Cutting grid	Cutting Manager	One row per garment, the hides on each, the present-cutters picker, approve / reopen
Inspection s	QC Inspector, DM	Record a reject or rework against the responsible stage; the DM's approval queue
Job work	DM, MD	Dispatch to a vendor, the overdue chase list, book returns and see what they cost
Direct Manager	DM / MD	The factory-wide control panel — composed from the four stage dashboards' own aggregates , so this screen and the four can never disagree

19.4 The alerts

`GET /dashboard/alerts` returns three blocks, most-actionable first:

Block	What it is
<code>bottleneck</code>	The deepest queue — the stage with the most work waiting in front of it. Deliberately <i>not</i> "the first unfinished stage": the first unfinished stage is wherever the line happens to have got to, which is not a constraint and not actionable
<code>stage_spread</code>	Where each downstream stage lags the leather cut. The gap is true WIP in flight
<code>freight_risk</code>	Orders approaching their sea cut-off. Missing it means air freight — the single biggest margin event in the business

`alert_count` is what a badge should render. **Empty lists are a good day, not a missing feature.**

19.5 Piece tracking — one handler, six URLs

A piece's history is the same history whichever screen is asking. `/dashboard/pieces/{code}` is canonical; five per-stage aliases exist so each dashboard keeps its own URL namespace.

Separate per-stage implementations would drift the moment one of them gained a field.

Three neighbouring reads answer genuinely different questions — worth keeping straight:

Endpoint	Answers
<code>/production/piece-state</code>	What happens next , and which stage cards to lock
<code>/dashboard/pieces/{code}</code>	The full stage history with the STORE overlay and consumption

Endpoint	Answers
<code>/analytics/pieces/{code}/story</code>	The analytics life story

19.6 Two honesty features

The **consumption grid is one stage per response**. It previously returned both cut stages while joining the leather lot, so lining-cut events appeared with a blank lot and their quantities counted toward leather totals. Asking for a consumption grid on any non-cut stage is a **422**, not a silently empty list — it is a question with no answer.

`meta.unsupported` on the **DM dashboard** names the figures that are null **by design** because no table backs them yet. Several quality and costing numbers fall into this. It is better to say so than to render a confident zero.

PART C — FOR FRONTEND DEVELOPERS

Everything here can be built against the mock payloads in the companion *API Reference*. You do not need a running backend.

20. The screen inventory

20.1 The single most important UI rule

The scan screen never asks the operator to pick a stage.

Send the piece barcode and the worker card to `GET /production/piece-state`, read `next_stage` and `ready_to_log`, and either post the log or render the blockers. An operator choosing a stage from a dropdown is an operator who will eventually choose the wrong one.

20.2 Import & release

Screen: Order index — `GET /imports/orders`. A searchable table with the rolled-up `breakdown_status` badge, `pieces_minted`, and a `breakdown_url` per row. Ordered most-recently-worked-on first.

Screen: Breakdown table

BOG-SS27-001 · BOGGI MILANO				DRAFT · 0 minted	
▼ CLERMONT	art A-4471	0.7mm	season SS27	[edit style]	
BLACK · 46 · 10	BLACK · 48 · 20	BLACK · 50 · 20			
COGNAC · 48 · 10	COGNAC · 50 · 10				
needs_lining: ⚠ NOT DECLARED					
▼ CARNABY	art A-4482	0.9mm		RELEASED · 40 ✓	
(read-only – pieces minted)					
[Release selected styles]					

Build: - **DRAFT rows editable, RELEASED rows read-only**. Drive it off `production_status`; do not let the user discover the 409. - Use the **combined PATCH** (`style: {...}` nested inside the SKU patch) so a row saves in one transaction. Two calls means a 200 on the SKU and a 409 on the style leaves the screen half-saved with no way to tell which half. - Surface

`needs_lining` per style **on this screen**, before the release dialog — a DM who spots it mid-review should be able to fix it there.

Screen: Release dialog — the highest-consequence dialog in the product.

Release 2 styles into production

This mints barcodes. It cannot be undone.

CLERMONT	60 pieces	Needs lining?	☐ Yes	☐ No	⚠
CARNABY	40 pieces	Needs lining?	☒ Yes	☐ No	

[Cancel]

[Release] ← disabled

Build: - **Disable Release until every style has an explicit yes/no.** Never default the radio. `null` is a real state and the server rejects it. - Offer a **"same answer for all"** control that maps to the top-level `needs_lining` — that is a declaration, not a guess. - **Delete the drawer-pool banner and the "grow the pool" checkbox.** There is no pool: `pieces_waiting_for_drawer` is gone from the response and `grow_drawer_pool` on the body is ignored. Release can no longer outrun anything. - On the response, render `minted` per style. - `rejected[]` entries are per-style with reasons. **Read `minted`, not the HTTP status.**

20.3 The scan screens

Screen: Cut screen (Cutting / Lining Manager)

LEATHER CUT

Ramesh Kumar ✓ in

1. Scan worker card

✓ Ramesh Kumar · CUTTER · present

2. Material

Article [SHEEP GLASS ▼] Colour [BLACK ▼]
Thickness [0.7 ▼] → lot A-338
Available 3,400 dcm ✓ covers this batch

3. dcm per piece

[34.5] ⓘ style recipe says 34.5

4. Scan pieces

29 scanned

[Log 29 pieces]

Build: - **The screen is fixed by the role.** Do not render a stage picker or a screen selector for a cutting or lining manager. Only DM/MD/HR get an override. - Drive the material dropdowns off `GET /materials/lots` — `options` fills the cascading selects; the row with `last_used_for_sku: true` is pre-selected, **and you should show that you pre-selected it**. - Pass `required` (dcm × piece count) so lots report `covers_required` and you can grey out a lot that cannot cover the batch **before** the cut. - Prefill the dcm from `suggested_dcm_per_piece` on the piece-state read. **A suggestion, never a substitution** — the operator confirms the number that reaches the ledger. - Handle the **409 with candidates**: several lots match the typed spec. Render the named candidates and let the operator pick.

Screen: Pipeline scan (Stitching Manager)

Scan piece ...

PC-004821 CLERMONT · BLACK · 50 · #017
Now: PASTING ✓ Next: LINE_STITCHING
Store: leather + lining ✓ · SENDED ✓

✓ Ready to log [Log]

Blocked variant:

Now: PASTING ✓ Next: LINE_STITCHING
Store: leather only · waiting for LINING

🔒 Blocked
merge - the store has not released this garment
Ask the store to complete and send it.

Build: - **ready_to_log** is the one boolean an automatic screen needs. `true` → post immediately. `false` → show blockers. `null` → **no employee was scanned, so the question is unanswered — do not render it as blocked.** - Render `stages[]` as cards with four visual states: `completed`, `next`, `locked` (with its gate and reason), `not_applicable` (a lining cut on an unlined piece). - Show the `actor` block — name, designation, checked-in status, any skill anomaly. **Skill is a warning, so it never appears in blockers.** - `can_log_next: false` means this login's role cannot log the stage. Say "ask the stitching manager" rather than letting the scan come back 403.

Screen: Batch result — the most under-built screen in most implementations.

PASTING · 29 logged · 1 blocked

✓ 29 pieces logged
⚠ PC-004833 sequence - not yet fused
⚠ skill: Ramesh Kumar is a CUTTER, logged on PASTING (recorded)
① SKU progress: 29 of 30 done · 1 remaining

Build: - **Never present a partial batch as a failure.** 29 logged and 1 blocked is a good outcome. - `blocked[]` carries `{piece, stage, gate, reason}` — render the reason, not just the code. - `skill_warnings[]` are logged, not blocked. Style them differently from blockers. - **`sku_progress.closed: true` means stop offering this style for scanning.** - Handle `stage: "MIXED"` — read `stage_by_piece`. - Offer **`preview: true`** as a "check before logging" affordance.

20.4 The store screens

Screen: Store list — GET /store/pieces

This replaces the 200-cell drawer grid, and it is a net deletion. The old screen rendered a fixed board of boxes and asked the operator to find the right one. This one is a filterable list of garments. There is no capacity bar, no free-drawer count and no shortfall, because none of those things exist any more.

Store [search: PC-0048] ☒ ready to send only state: all ▼					
PIECE	STATE	HOLDING	GARMENT	CAN SEND	SINCE
PC-004821	received	leather + lining ✓	CLERMONT	☒	2m
PC-004822	holding	leather only	CLERMONT	☐	14m
PC-004901	waiting	nothing yet	CARNABY	☐	—
☒ 1 selected			[Send selected]		

Build: - **store_state** and **holding** are different questions. The state is the lifecycle; holding is what has physically arrived. They stop agreeing at **received** and **sended**. Render both. - Drive the Send checkbox off **can_send** — it applies the same rule the server enforces, so the queue can never offer a row the server refuses. - Use **needs_lining** from the row (the **effective** requirement, resolved from the style, the SKU and the cut history), and show **lining_reason** when present. Do not read the piece's stored flag. - Search accepts the compact **PC-...** code and the long alias. Scanning a garment should jump straight to its row.

Screen: Store scan — employee, then piece. Two fields, not three. The drawer step is gone, and removing it is the whole "make merging easy" change: the piece barcode already identifies the garment.

Render the **kit** block on **every** scan, not just accessory ones — the person holding the leather is the one who also has to find the buttons. **status: NOT_REQUIRED** means **hide the checklist**, not render an empty one. "*No accessories declared*" and "*accessories declared but none issued*" are different facts.

On an accessory scan, show **issued_now**, **already_issued**, **outstanding** and — importantly — **unresolved**, where a line could not be matched to a lot (**reason: NONE** or **AMBIGUOUS** with candidate lot ids).

auto_received: true deserves a visible confirmation: "*This garment is now complete and ready to send.*"

A **409** on a lining scan means the lining has not been cut yet. Say that, and offer the lining-cut screen — the operator is holding a part the system has no record of anybody making.

sent: false **plus** **next_action** exists because scanning is **not** completion. Say so explicitly.

20.5 Attendance

The gate screen is one input and two buttons: scan a card, in or out. Show the resolved worker's name and photo-less identity card immediately, then the result — late flag, whether this was a re-tap (idempotent no-op).

Keep the manual door one click away for a failed card. **/attendance/today** is the roster.

20.6 Wages

Screen: Order cards → style cards → rate sheet. Three levels. The **n of m** **priced** badge at each level is the point — unpriced styles pay zero silently.

Screen: Compute run — this dialog decides which of two incompatible pricing rules applies.

Compute payroll

Kind (•) Piece rate () Monthly salary

Scope Style [JP-CLERMONT_VEST ▼] ← REQUIRED for piece

Window [2026-09-01] → [2026-09-15]

☒ Freeze on compute

ⓘ A piece run and a monthly run over the same window do not conflict. Compute both for a full payroll.

- **Grey out Compute for a piece run with no scope.** The schema rejects it; do not make the user find out.
- For a monthly run, if they set a scope, label it "*for reference only*" and echo `scope_is_label: true` on the result.
- On the response, **surface `unrated_operations` and `gap_days` before anyone approves a payment.**
- The 409 overlap error **names the blocking run** — link to it.

Screen: Run detail — three tabs from `/breakdown` (style / stage / employee) plus a per-piece tab. All four come off the same frozen rows; **never sum them client-side.**

`scope_is_label: true` must render differently from a genuine narrowing. `recompute_count > 0` or `reopen_count > 0` should be visible on the header — a rebuilt run is a different document from the one paid against.

20.7 Dashboards

Each is one call. Render the composite. Read `meta.unsupported` and render those figures as "*not tracked*" rather than as zero.

The alerts block belongs on **every** manager dashboard, with `alert_count` as a badge.

21. State machines you must render


Style production status

From	Action	To	Guard
DRAFT	release	RELEASED	Every style must declare <code>needs_lining</code> . Mints pieces + barcodes
DRAFT	cancel	CANCELLED	
RELEASED	(nothing)	—	Frozen. Re-release only tops up quantity

Store state (on the piece — formerly the drawer's)

From	Trigger	To
waiting	release merges a piece	merged
merged	leather scanned	holding_leather
merged	lining scanned	holding_lining
holding_leather	lining scanned	holding_both
any holding	completeness reached	received (automatic)
received	send	sended
sended	PACKAGE_EXPORT logged	waiting

Production stage chain — forward-only, except rework which is always permitted.



Wage run

From	Action	To	Guard
—	compute	open closed	freeze decides. Piece runs need a scope
open	recompute	open	Free
open	close	closed	Refuses an empty run. Idempotent
closed	reopen	open	DM/MD + a reason
closed	recompute	closed	Only with confirm_closed — no reason recorded
open	delete	—	
closed	delete	—	Only with confirm_closed

Barcode status — active → retired . One way. Resolve returns 410 after.

22. Scan-driven UX — the patterns that matter

22.1 The resolve-first pattern

Every workflow starts with a scan of unknown type. Call GET /barcode/resolve?code=... and branch on type :

```
const r = await resolve(code);
switch (r.type) {
  case "EMPLOYEE":    return setActor(r.employee);           // next_expected_scan tells you what's
next
  case "PIECE":       return setPiece(r.piece);
  case "LEATHER_SHEET": return setSheet(r.sheet);  // one physical hide
  // case "DRAWER":    withdrawn - historical codes only
  case "LEATHER_LOT":
  case "LINING_LOT":
  case "ACCESSORY_LOT": return setLot(r.lot);
}
```

Handle the three outcomes distinctly:

Status	Say
404	"Unknown barcode."
410	" This card was deactivated. " — never "invalid"
200 + is_alias: true	Works, but "this is an old label — reprint it."

Use next_expected_scan to drive the wizard. It is answered for every type, including EMPLOYEE — the first scan of every workflow.

22.2 The state-then-log pattern

```
scan piece + scan worker
  |
  v
GET /production/piece-state?code=...&employee_barcode=...
  |
  ├── ready_to_log: true   → POST /production/log immediately
  ├── ready_to_log: false → render blockers[], offer no Log button
  └── ready_to_log: null   → "scan the worker's card" (NOT "blocked")
```

The read uses the same predicates as the write, so **a card the UI opens is a card the log will accept**.

22.3 Batch accumulation

Cut and pipeline screens accumulate scans, then post once. Show a running count, allow removal, and offer `preview: true` before committing a large tray.

22.4 Never poll

Nothing in Phase 1 is asynchronous. Every write is synchronous and returns its full result. There is no 202, no task id, no SSE. Post and render.

(The Phase-2 procurement engine does use 202-and-poll and SSE. Do not carry those patterns over.)

23. The error contract

23.1 The shape

FastAPI's `detail` wrapper, containing either a plain string or a structured object:

```
{ "detail": "No piece with code 'PC-9999'." }
```

```
{ "detail": { "error": "stale_revision", "current_revision": 7 } }
```

Handle both.

```
function errorMessage(body) {
  const d = body?.detail;
  if (typeof d === "string") return d;
  if (Array.isArray(d)) return d.map(e => `${e.loc?.join(".")}: ${e.msg}`).join("; ");
  return d?.message ?? d?.error ?? "Something went wrong.";
}
```

Validation failures from Pydantic come back as an **array** of `{loc, msg, type}`. Several of this codebase's most useful 422s are Pydantic messages written as full sentences — render them verbatim.

Every 500 carries a `request_id`. **Show it** — support traces the failure by it.

23.2 Status codes

Code	Means	Do
200 / 201	OK	
204	No content	Password change, client delete
400	Bad upload	Not an <code>.xlsx</code> , or not a valid zip

Code	Means	Do
401	Unauthenticated	Redirect to login
403	Wrong role	The message usually names who can
404	Not found	Also: unknown barcode
409	State conflict	See below
410	Gone	A retired barcode, or a removed endpoint
413	File too large	Show the cap
422	Validation	Field-level, or a domain sentence
500	Server error	Show <code>request_id</code>

23.3 The 409s and 410s worth handling individually

Situation	Meaning	UI response
Released style edited	Frozen — barcodes printed	Drive editability off <code>production_status</code>
Lining stored before it was cut	The store holds finished parts, not pending ones	<i>"Log the lining cut first"</i>
Ambiguous material lot	Several lots match the typed spec	Render the named candidates and let them pick
Lot retire with stock reserved	Reservations outstanding	Say what is holding it
Lot spec collision	Two lots a cutter cannot tell apart	Offer the existing lot
Wage run overlap	Would pay the same money twice	Link to the blocking run
Recompute a closed run	Frozen	Offer Reopen (with a reason field)
Delete a closed run	Destroys a payment record	Require explicit confirmation
Client delete with orders	Cascade would take everything	Offer deactivate instead
410 on a barcode	Retired card / lot / piece	<i>"This was deactivated"</i>
410 on an endpoint	Removed deliberately	The message names the replacement

23.4 The 422s that are really business rules

Where	Message
Release	<i>"N styles have no lining answer... it cannot be changed after release"</i>
Piece wage run	<i>"A piece-rate run must name the work it pays for"</i>
Spec confirm	<code>no_accessories: true</code> while accessory lines exist
Consumption	<i>"The pieces in this batch have different consumption in their style specs"</i>
Employee create	<i>"password is only accepted when a staff login is created"</i>
Consumption grid	<i>"stage must be one of [LEATHER_CUTTING, LINING_CUTTING]"</i>

Render these verbatim. They are written to be read by the operator, and they explain the rule as well as the failure.

24. Badges, chips and status vocabulary

Family	Value	Colour	Note
Style production	DRAFT	grey	Editable
	RELEASED	green	Frozen; barcodes exist
	CANCELLED	red, struck	
Breakdown rollup	NOT_UPLOADED grey · DRAFT amber · PARTIALLY_RELEASED blue · RELEASED green · CANCELLED red		
Store state	waiting grey · merged blue · holding_leather / holding_lining amber · holding_both teal · received green · sendd purple		Purple: it has left the store
Store holding	EMPTY · HOLDING LEATHER · HOLDING LINING · HOLDING BOTH		Different question from state
Sheet status	IN_STOCK grey · ALLOCATED blue · ISSUED amber · CONSUMED green · RETURNED / SCRAPPED red		One physical hide
Cutting row	DRAFT grey · APPROVED green · LOGGED teal · CANCELLED red		APPROVED is read-only
Job work	OUT amber · PARTIAL blue · BACK green · SHORT / REJECTED red		Overdue overrides with red
Stage card	completed green ✓ · next blue, prominent · locked grey 🔒 · not_applicable faint		
Log outcome	logged green · rework amber ʘ · not_found grey · completed teal		
	sequence_blocked / merge_blocked / role_blocked red		
	skill_warnings amber — logged anyway		Never red
Barcode	active green · retired grey struck · is_alias amber "reprint"		
Kit	NOT_REQUIRED hidden · PENDING grey · PARTIAL amber · ISSUED green		Hidden, not empty
Attendance	present green · is_late amber · is_short amber · is_overtime blue · absent grey		
Wage run	open amber "draft" · closed green 🔒 "frozen"		
	scope_is_label: true → "label only" chip		
	recompute_count > 0 → "rebuilt" chip		
Stock	available > required green · 0 < available < required amber · available = 0 red		
Freight	past sea cut-off red · within 7 days amber · else green		The biggest margin event

PART D — FOR BACKEND DEVELOPERS


25. Architecture and the layering rules

25.1 A modular monolith

One deployable FastAPI app and **twenty** module packages under `app/modules/`: **fifteen** Phase-1 (`analytics`, `attendance`, `barcode`, `clients`, `cutting`, `dashboard`, `drawers`, `employees`, `imports`, `jobwork`, `materials`, `production`, `store`, `users`, `wages`) plus **five** Phase-2 (`bom`, `intelligence`, `inventory`, `procurement`, `supplier_po`). Cross-module calls go **through services**, never repositories or models.

Fifteen packages, fourteen live surfaces. `drawers/` is a package with no router — it is commented out in `main.py` (§26.8). It counts here because its tables still hold audit rows and its code still compiles; it does not count as a thing you can call. Inspections have no package of their own: they live inside `production/` (§26.12).

25.2 The three layers



Barcode resolution happens in the router. That is deliberate and load-bearing: the service then sees ids only, so the barcode door and the manual door converge before any business logic runs and cannot behave differently.

25.3 Where business law lives

Four things are **code, not config**, and `core/enums_barcode.py` is where they live:

1. **Stage order.**
2. **The two parallel cut paths.**
3. **Role → stage access.**
4. **Designation → stage access.**

The `operation` table remains the source of truth for **labels and rates** — the MD edits those. But encoding order against `Operation.sequence` would mean a stray UPDATE silently reorders the factory. Codes are stable; sequence numbers are not.

`operation_access` is a runtime **escape hatch** on top of the enum default, so an MD can grant an exception without a deploy.

25.4 One helper, both paths

`next_chain_stage(completed_codes)` is pure — a set of codes in, a stage out, no database.

It exists so the **write** path (which decides what a scan logs) and the **read** paths (`/barcode/resolve`, `/production/piece-state`) cannot answer the same question differently. Two copies of that loop would drift, and the drift is invisible until a screen offers a stage the log then refuses.

When you add a stage, add it here and both sides move together.

25.5 Async discipline

Every blocking call goes through `run_in_threadpool` — openpyxl parsing and the sync bulk loader. The event loop is never blocked.

The import path deliberately keeps the **proven sync loader** and runs it in a worker thread rather than rewriting it as async.

25.6 One page envelope, one way to ask for a page

Module: `app/core/pagination.py`

The problem it fixed. Five routers — production, clients, cutting, dashboard, users — declared no `limit`, `offset` or `page` parameter at all. Those endpoints returned the whole table. `production_event` gains a row per piece per stage and never shrinks, so `GET /production/events` with no filter meant "*serialise the whole production history*": survivable after a few weeks of running, fatal after a year. The cost is not the response size. It is the request that times out, the worker holding hundreds of megabytes, and **the pooled database connection held open for the whole of it** — and the pool, not CPU, is this service's real concurrency ceiling. One unbounded list read degrades every other request on the box.

The routers that *did* paginate had each invented their own shape — `{total, count, items}` in wages, `{page, page_size, total, pages, items}` in barcode — so a frontend special-cased each one and there was nowhere to fix a paging bug once.

The three pieces.

- **PageParams** — a FastAPI dependency (`params: PageParams = Depends()`), not two loose `Query` arguments, so every paginated route declares the same two parameters with the same bounds and the same documentation, and a later change lands in one place. `limit` defaults to **50** and is capped at **200**; the cap is what stops a caller asking for the whole table with `?limit=999999` and reintroducing exactly the problem paging solves.
- **Page[T]** — `items, total, limit, offset, count, has_more`. `total` is the whole result set, because that is what a list screen renders as "*101–150 of 3,184*"; it costs a second `COUNT`, which is the price of a pager and far cheaper than shipping every row. `has_more` is derived server-side rather than left to the caller, because `offset + len(items) < total` is the off-by-one every client otherwise reimplements.
- **paginate(db, stmt, params)** — runs the page and counts the match **from the same statement**, wrapped as a subquery. Hand-writing a separate `COUNT` is how a pager ends up claiming 40 rows over 3 pages while the filters actually match 12 — silently, because both queries succeed. The `ORDER BY` is stripped from the count (it cannot change how many rows match, and sorting a set you will only count is wasted work), and **the slice happens in SQL**: fetching everything and slicing in Python would shrink the response but not the query, leaving the expensive part exactly where it was.

Offset, not cursor — for now. Offset paging is what a jump-to-page list screen needs, and that is what every one of these surfaces renders. It degrades on very deep offsets because the database still walks the skipped rows. None of these surfaces page tens of thousands deep; a cursor API that nothing needs is a contract to maintain for nothing.

What it deliberately did not do. It did not retrofit the older shapes. `RunPiecePage`, `LedgerPage` and the rest are published contracts a frontend is reading today, and quietly changing a response shape breaks a screen without breaking a test. New and newly-paginated endpoints use `Page`; the older ones migrate when their consumer is ready. The API Reference §3.1 lists which is which.

The rule that is easy to get wrong. A count that describes the *collection* must not be recomputed per page. `GET /production/skus/{id}/pieces` returns `SKU-wide total / done / pending / closed` beside a 50-row page, because `closed` withdraws a style from the scan screen — deriving it from one page would tell a manager sitting on page 1 that a 900-piece SKU was finished. `blocked` genuinely *is* a page figure, because eligibility depends on the previous stage per piece and cannot be summarised without re-running the whole gate for the SKU; so it is reported as a page figure and **named** one, via `blocked_scope`. Reporting a page figure honestly beats reporting a whole-SKU figure that is actually a page figure.

26. Module map — every file and what it is for

26.1 `users/` — 502 lines

File	Lines	Purpose
<code>service.py</code>	200	Login, user creation with authority checks, password change
<code>deps.py</code>	108	<code>get_current_user</code> , <code>require_roles</code> , <code>block_employees</code> — the whole auth surface
<code>router.py</code>	97	6 endpoints across two routers
<code>schemas.py</code>	68	Token, <code>UserRead</code> , the two create shapes
<code>repository.py</code>	66	
<code>models.py</code>	63	<code>app_user</code> — the one login table

Why `deps.py` is in `users` and not `core`: it depends on the concrete `User` model, and `core` must not import modules (enforced by `import-linter`). `core/security.py` keeps only the model-agnostic primitives.

26.2 `employees/` — 642 lines

File	Lines	Purpose
<code>service.py</code>	279	Create (with optional staff login), update, soft-delete, barcode lookup
<code>schemas.py</code>	134	The login-role validation rules live here
<code>router.py</code>	97	4 endpoints
<code>repository.py</code>	80	
<code>models.py</code>	52	

26.3 `clients/` — 1,116 lines

File	Lines	Purpose
<code>repository.py</code>	360	
<code>models.py</code>	310	Client → Order → Style → SKU + <code>StyleComponent</code> + <code>SkuOrderLine</code>
<code>service.py</code>	228	Including <code>create_order_with_breakdown</code> (called by Phase 2)
<code>router.py</code>	173	8 endpoints. Route order is load-bearing
<code>schemas.py</code>	136	
<code>utlis.py</code>	85	(sic)

26.4 imports/ — 3,234 lines

File	Lines	Purpose
<code>breakdown.py</code>	834	The breakdown table, edits, cancel, and RELEASE
<code>premint.py</code>	579	The mint — pieces and barcodes. The four-phase flush collapsed to two when the pool went: phases 1 and 3 existed only for the piece↔drawer FK cycle
<code>router.py</code>	536	9 endpoints. Also holds the release-request validation
<code>load_to_db.py</code>	423	The idempotent bulk loader
<code>_size_band.py</code>	398	Size-band parsing
<code>parse_orders.py</code>	299	
<code>excel_reader.py</code>	186	
<code>import_engine.py</code>	168	<code>build_preview</code>
<code>parse_production.py</code>	160	

26.5 barcode/ — 1,957 lines

File	Lines	Purpose
<code>repository.py</code>	724	Every read. No SQL lives in the service
<code>service.py</code>	642	<code>resolve</code> , print payloads, employee-card lifecycle, order analytics
<code>models.py</code>	468	<code>barcode_registry</code> , <code>drawer</code> , <code>material_lot</code> , reservations, receipts, suppliers, supplier orders, style spec, issue ledger
<code>router.py</code>	178	10 endpoints
<code>schemas.py</code>	145	

26.6 materials/ — 2,855 lines

File	Lines	Purpose
<code>style_spec_service.py</code>	1097	The recipe — CRUD, confirm, copy, requirement, manual issue
<code>service.py</code>	832	Lots, stock, receiving, supplier orders, the decrement
<code>router.py</code>	424	Three routers — <code>/materials</code> , <code>/suppliers</code> , <code>/styles</code>
<code>repository.py</code>	212	
<code>style_spec_repository.py</code>	199	
<code>schemas.py</code>	200	
<code>style_spec_schemas.py</code>	91	

26.7 production/ — 2,287 lines

File	Lines	Purpose
service.py	1109	log_batch and the four gates; piece_state
router.py	377	9 endpoints. Resolves barcodes and lots to ids
repository.py	336	
schemas.py	327	The rich LogResult and PieceState
models.py	130	operation, operation_access, style_operation, piece, production_event

26.8 drawers/ — 1,844 lines · WITHDRAWN

Not mounted. app/main.py keeps the import and the include_router call commented out with the reason beside them, and the files stay on disk so the history of how the store used to work is readable. Nothing calls into them. Its replacement is store/ — see chapter 14.

File	Lines	Purpose
service.py	1193	Store scan, part inference, completeness, auto-receive, batch send, the kit issue
router.py	406	9 endpoints
schemas.py	245	

No models.py — the drawer table lives in barcode/models.py.

26.9 cutting/ — the grid

models.py cutting_row · schemas.py the grid contract · repository.py all DB access · service.py the allocator, the sheet add/remove, approve and reopen · router.py HTTP only.

The allocator is the only interesting algorithm here: nearest-fit hides from IN_STOCK, matching the article and colour, until the running dcm reaches the size's target. It moves what it takes to ALLOCATED, so two rows can never claim the same skin. app/core/leather_norms.py holds the size → dcm table it aims at — a pure module with no imports, beside kit_rules.py and lining_rules.py.

26.10 store/ — what replaced drawers/

No models.py: **the store's state lives on piece**, which is the whole point of the change. service.py carries store_scan, send, list_pieces, piece_row, needs_lining and release_nocommit.

needs_lining and _needs_lining_map were **relocated here, not deleted** — production calls them from three places and would have broken silently.

26.11 jobwork/ — garments at an outside factory

models.py vendor, job_work, job_work_piece · service.py dispatch, receive, the cost roll-up and current_job_for_piece (which is what the production gate calls) · router.py HTTP only.

production_event.vendor_id FKs to vendor, which is why app/main.py imports jobwork.models near the top — the shared MetaData has to see the table before the production models resolve their FK.

26.12 Inspections — inside `production/`

`inspection.py`, `inspection_router.py` and `inspection_schemas.py` sit in `production/` rather than in a module of their own, because a rejection is a statement about a production event and the re-walk is a production concept. Its sibling is `corrections.py` — reassign and delete for an event that named the wrong worker.

26.13 `attendance/` — 1,063 lines

File	Lines	Purpose
<code>service.py</code>	471	<code>_open_or_reject</code> / <code>_close</code> primitives, shared by both doors
<code>router.py</code>	209	12 endpoints
<code>schemas.py</code>	164	
<code>models.py</code>	101	<code>shift_config</code> singleton, <code>attendance_log</code>
<code>repository.py</code>	61	
<code>geofence.py</code>	44	Vestigial — the feature is removed

26.14 `wages/` — 3,074 lines

File	Lines	Purpose
<code>service.py</code>	1241	Rates, the two run kinds, the overlap guard, recompute/reopen/close/delete, the folds
<code>repository.py</code>	742	
<code>schemas.py</code>	423	RunRequest carries the scope rules in the contract
<code>router.py</code>	387	16 endpoints. Route order is load-bearing
<code>models.py</code>	175	<code>rate</code> , <code>wage_run</code> , <code>wage_line</code> , <code>wage_line_detail</code>
<code>proration.py</code>	68	Monthly calendar pricing

26.15 `analytics/` — 1,365 lines · `dashboard/` — 4,425 lines

File	Lines	Purpose
<code>analytics/service.py</code>	1056	Explorer, drill-downs, life story, consumption, alerts
<code>analytics/router.py</code>	153	10 endpoints — 3 of them 410 Gone
<code>analytics/barcode_ext.py</code>	149	
<code>dashboard/repository.py</code>	1944	Every grouped query
<code>dashboard/service.py</code>	1209	Five composites
<code>dashboard/schemas.py</code>	760	The typed dashboard shapes
<code>dashboard/router.py</code>	493	22 endpoints

Neither module owns a table.

26.16 `core/` — the shared floor every module stands on

`core` owns no tables and no routes. **It must not import a module** — the rule is enforced by import-linter, and it is why `deps.py` lives in `users/` (it needs the concrete `User` model) while `core/security.py` keeps only the model-agnostic primitives.

File	Purpose
<code>enums.py</code>	<code>UserRole</code> , wage types, attendance sources. <code>app_user.role</code> is a native PG enum — adding a member here is not enough (§30.2)
<code>enums_barcode.py</code>	Stage order, the two cut paths, role → stage, designation → stage. Business law as code (§25.3)
<code>pagination.py</code>	<code>PageParams</code> , <code>Page[T]</code> , <code>paginate()</code> — one page envelope and one way to ask for a page (§25.6)
<code>security.py</code>	JWT issue/verify, bcrypt. Model-agnostic on purpose
<code>database.py</code>	Async engine, session factory, <code>GUID</code> and <code>JSON_VARIANT</code> portability shims
<code>config.py</code>	Settings. What is <i>not</i> here matters: shift policy and page size are not settings (§30.1)
<code>leather_norms.py</code>	How much hide one garment takes, by size. A default table exists so the cutting sheet opens with sheets already allocated — otherwise the manager is back to picking ten hides by hand per garment, which is the Excel work the grid replaced
<code>kit_rules.py</code>	The four accessory-kit predicates, as pure functions . They are asked from five places — the release gate, the store scan, the store list, the scan payloads and the production log — three of them hot paths that must not import a service
<code>store_display.py</code>	STORE as a derived display stage , not an enum value. The overlay the user-facing pipeline shows, computed in one place so two screens cannot caption the same garment differently
<code>throttle.py</code>	A rate limit on login and nowhere else . Rate-limiting the floor would be actively harmful — a barcode terminal doing two scans a second is the system working
<code>cache.py</code>	A read cache for the 32 dashboard and analytics routes that recompute large aggregates
<code>singleflight.py</code>	Runs a periodic job once across every replica . The sweepers start as asyncio tasks inside the API process, so without this each replica would run them
<code>celery.py</code>	The worker wiring for the Phase-2 background jobs

27. The data model

27.1 Conventions

`UUIDMixin` (portable `GUID`) + `TimestampMixin` on every table. Money `Numeric(12,2)` ; quantities `Numeric(12,3)` or `(14,3)` ; semi-structured data `JSON_VARIANT` .

Status columns are `VARCHAR` storing a `str-Enum's .value` — with one exception.

27.2 The one native enum

`app_user.role` is a native Postgres enum (`user_role`). Everything else in Phase 1 is `VARCHAR`.

That has a sharp migration consequence — see §30.2.

27.3 The tables

IDENTITY	
app_user	one login table for everyone
PEOPLE	
employee	name, designation, wage_type, salary, is_active
COMMERCIAL	
client	name, country, code, currency, size system
client_order	order_number, dates, sea_cutoff, ship_mode
style	+ production_status, needs_lining, spec confirmation
style_component	VEST, FUR DETACH, KNIT, NYLON add-ons
sku	colour + size + qty_ordered
sku_order_line	per-date order lines under a SKU
PRODUCTION	
operation	code, label, sequence (labels + rates = config)
operation_access	role → operation runtime override
style_operation	which operations a style actually uses
piece	★ ONE GARMENT. (sku_id, seq) unique. needs_lining, store_state, leather_in, lining_in, accessories_in, store_entered_at (drawer_id retained, unwritten)
production_event	★ THE CENTRAL TABLE. one worker, one op, ONE PIECE, one day + leather_lot_id / lining_lot_id / consumption_qty at cuts
BARCODE & STORE	(all in barcode/models.py)
barcode_registry	★ every scannable code. type, status, is_alias, 7 nullable FKs
drawer	static code, recycling state – FROZEN, audit only
material_sheet	★ ONE PHYSICAL HIDE. dcm, status, cutting_row_id
material_lot	category/subtype/article/colour/thickness/size, on_hand, attributes
material_reservation	soft allocation
material_receipt	approved / rejected quantities
material_supplier	the vendor directory
supplier_order	ORDERED → ARRIVED
style_material_spec	★ THE RECIPE. style or SKU-scoped lines
piece_material_issue	★ THE ISSUE LEDGER. what was actually given to one garment
CUTTING	
cutting_row	★ ONE GARMENT'S CUT SHEET. target/total dcm, status, cutter, rc_no (its hides join by material_sheet)
QUALITY & OUTSOURCING	
piece_inspection	reject / rework + the stage RESPONSIBLE for the defect
vendor	an outside factory
job_work	a dispatch: vendor, stage, dates, status, rate
job_work_piece	one garment on that dispatch (OUT BACK SHORT REJECTED)
ATTENDANCE	
shift_config	singleton policy row
attendance_log	one row per (employee, work_date) – DB-enforced
WAGES	
rate	(style, operation, rate, effective_from)
wage_run	window + status + run_kind + scope + audit counters
wage_line	one per employee per run
wage_line_detail	per (employee, style, operation) cell
CROSS-CUTTING (core/models.py)	
audit_log	every hard transition
document / notification	shared with Phase 2

27.4 The piece ↔ drawer cycle (*historical*)

The store no longer uses either end of this link — `piece.store_state` replaced it. Both columns survive so in-flight data and the audit trail stay readable, and the FK rules below still govern them. It is documented because the `onDelete` reasoning applies to every 1:1 cycle in the schema, not because the drawer is still in use.

`piece.drawer_id` and `drawer.current_piece_id` are the same 1:1 link read from opposite ends — and they are **not interchangeable**:

- The **drawer's** pointer is the **live claim**. A store scan moves state and the leather/lining flags on the row that claims the piece; releasing nulls it when the garment ships.
- The **piece's** pointer is the piece's **own assignment**.

Every card query in barcode/dashboard/production reads through the **claim**; every analytics store query reads through the **assignment**.

The cycle is deliberate. What was missing was a rule for what happens when one end is deleted. Both sides now carry `onDelete="SET NULL"`, which is not a concession — it is already a legal, handled state. A piece with `drawer_id IS NULL` is the "waiting for a drawer" case the pool allocator and the `no_drawer` analytics bucket already speak about. **Deleting a drawer returns its piece to the waiting list rather than deleting the garment's record.**

`use_alter=True` sits on the **drawer** side, and that placement is about DDL ordering, not delete semantics. A cycle means `create_all` cannot topologically sort `{piece, drawer}`; SQLAlchemy silently resolved it by moving **every** foreign key on **both** tables out to `ALTER TABLE`. SQLite cannot execute those, so on the test harness `piece` was created with **no FKs at all** — `sku_id` included. Marking this one back-pointer as the alterable edge lets the sort succeed, `piece` keeps its constraints inline, and the integration test that runs `PRAGMA foreign_keys=ON` can still catch a bad insert order.

27.5 SET NULL on the registry

Every nullable FK on `barcode_registry` carries SET NULL, so a parent row can actually be deleted instead of being pinned forever.

On this table that is the least comfortable rule, because a registry row exists **in order to** name a domain row. It is still right, for two reasons:

- `resolve()` already guards every branch on the FK being present, so a widowed code degrades to "known code, no payload" — it does not crash the scan screen.
- **CASCADE is the alternative, and CASCADE would mean deleting a piece silently destroys its printed label's only record.** That is the exact opposite of "you delete the scannable code, never the person or their record".

The real point: deleting a piece, drawer or employee **row** is not a workflow this system has. Workers are retired, pieces deactivated, drawers recycled. These delete rules exist for administrative cleanup — a mis-imported order, a test batch. If you do use them, sweep the registry for rows whose type-appropriate FK went NULL, or they will keep inflating the per-order minted/balance counts the factory reconciles against.

28. Cross-module choreography

```
ClientService.create_client / add_order
  ▼
ImportService: build_preview → load_preview_into_order      [threadpool, sync loader]
  ▼
BreakdownService.get_table / update_sku / update_style      [DRAFT only]
  ▼
StyleSpecService.confirm                                    ← unlocks release
  ▼
BreakdownService.release_styles                             ★ THE MINT
  ├──> premint: Piece rows
  ├──> premint: barcode_registry (compact + long alias)
  ├──> premint: drawer merge
  └──> audit_log
  ▼
AttendanceService.barcode_scan                               ← gates production
  ▼
ProductionService.log_batch                                 ★ THE FLOOR
  ├── Gate 1 ROLE      → 403 whole request
  ├── Gate 2 SKILL     → per-piece warning
  ├── Gate 3 SEQUENCE  → per-piece block
  ├── Gate 4 MERGE     → per-piece block (LINE_STITCHING only)
  ├──> EmployeeService: present today?
  ├──> MaterialService: decrement stock (cut stages, once per batch)
  └──> StyleSpecService: suggested dcm
  ▼
DrawerService.store_scan                                    ← employee → drawer → piece
  ├──> infer part from cut history
  ├──> completeness → auto RECEIVED
  └──> ACCESSORY: issue the kit, spend stock, write the issue ledger
  ▼
DrawerService.send_batch                                    ← unlocks LINE_STITCHING
  ▼
ProductionService.log_batch (PACKAGE_EXPORT)
  └──> drawer recycles to WAITING
  ▼
WageService.compute_run                                    ← reads the SAME events
  └──> frozen wage_line + wage_line_detail
```

Two properties worth internalising:

1. **Nothing is minted before release.** Upload and commit are safe, reversible operations.
2. **Production events are the single source of truth for both traceability and payroll.** Nothing is counted twice, and the two can never disagree.

29. The key algorithms

29.1 Stage inference

```
def next_chain_stage(completed_codes):
    done = {c.strip().upper() for c in completed_codes}
    chain = ProductionStage.leather_chain()
    furthest = max((i for i, s in enumerate(chain) if s.value in done),
                   default=-1)
    nxt = furthest + 1
    return chain[nxt] if 0 <= nxt < len(chain) else None
```

Pure. No database. Called by both the write path and both read paths.

"**Furthest completed, plus one**", not "first not completed" — a reworked or out-of-order piece advances from how far it actually got.

29.2 The four gates

GATE 1	ROLE	role in _STAGE_BYPASS_ROLES?	→ pass
		role in STAGE_ROLE_ACCESS[stage]?	→ pass
		operation in operation_access[role]?	→ pass (runtime override)
		else → 403, naming the roles that can	
GATE 2	SKILL	designation in MULTI_STAGE_DESIGNATIONS?	→ pass (HELPER, SUPERVISOR)
		designation unknown?	→ pass (FAIL-OPEN)
		designation in STAGE_DESIGNATIONS[stage]?	→ pass
		else → WARNING, still logged	
GATE 3	SEQUENCE	stage.predecessor() is None?	→ pass (cut entries, LINE_STITCHING)
		piece has an event at predecessor?	→ pass
		rework?	→ pass
		else → sequence_blocked	
GATE 4	MERGE	stage is not LINE_STITCHING?	→ pass
		drawer.state == SENDED?	→ pass
		rework?	→ pass
		else → merge_blocked	

Gate 2 fails open on purpose. Seeded data carries uncatalogued job titles, and refusing to record work because HR has not backfilled a vocabulary is worse than a warning.

29.3 Completeness

needs_lining = EFFECTIVE requirement (style → SKU → cut history) NOT the stored piece.needs_lining flag
complete = leather_in AND (lining_in OR NOT needs_lining)
complete → drawer automatically reaches RECEIVED RECEIVED + a human decision → SENDED SENDED → the merge gate opens for that piece

29.4 Part inference

Reads the piece's cut history and what the drawer is already holding. Returns **LEATHER or LINING and nothing else** — never ACCESSORY, because a mis-inferred kit spends stock. `part_inferred` on the response stays honest about whether the server chose.

29.5 Wage computation

1. GUARD overlap with an existing run over this window? → 409 naming it
2. SCOPE piece run → resolve style_code / order_number (REQUIRED)
monthly → no scope; any given one is a LABEL
3. POPULATE piece → ProductionEvent rows in the window, for the scope
monthly → salaried employees, priced by the calendar (proration)
4. PRICE per event: the rate in force ON THAT DAY for (style, operation)
unrated → 0, and recorded in unrated_operations
5. FOLD wage_line_detail per (employee, style, operation) cell
wage_line one per employee
6. FREEZE if freeze=true → CLOSED

Recompute repeats 3–5 with the **same window and scope**, keeping the run id and incrementing `recompute_count`.

29.6 The stock decrement

```
per batch, once, in the same transaction as the events:
  requested = dcm_per_piece × piece_count
  available = on_hand - Σ active reservations
  if requested > available:
    RECORD THE CUT ANYWAY, and return stock_warning
    {lot_id, requested, available_before, short_by, on_hand_after, note}
```

The garment is physically cut. Refusing to record it would lose the traceability the whole system exists for. Silently driving `on_hand` negative would corrupt the ledger. Recording it **and surfacing the shortfall** is the only honest option.

30. Configuration and migration notes

30.1 Settings that change behaviour

Setting	Effect
<code>max_upload_mb</code>	Import cap; streamed, aborts mid-upload
<code>debug</code>	Enables <code>create_all</code> at startup — development only
Shift policy	Not config — a database row (<code>ShiftConfig</code>). No longer editable over the API : <code>GET / PATCH /attendance/config</code> were removed on 2026-09-19. Change it by migration or seed.
Page size	<code>DEFAULT_LIMIT = 50</code> , <code>MAX_LIMIT = 200</code> in <code>core/pagination.py</code> . Constants, not settings — raising the cap is a code change, deliberately, because it is the thing that keeps one list read from holding a pooled connection open over the whole table.
~~Drawer pool size~~	Gone . There is no drawer pool and no allocation. The store is a state on the garment, so it has no capacity to size.

Why the shift-policy write went. The read went first — nothing on the floor sets policy per session. Keeping the write without the read would have left an edit form that cannot load its own current values, which is a screen that overwrites policy with whatever the frontend happened to hold. If policy needs changing from the UI, both come back together. The policy itself is unaffected: `AttendanceService` still reads `ShiftConfig` on every punch to set `is_late` / `is_short` / `is_overtime` , and the wage run still prices against it.

30.2 The native-enum trap

`app_user.role` is a native Postgres enum. Adding a member to `UserRole` in Python is **not enough** — Postgres needs the label added to the type:

```
if op.get_bind().dialect.name == "postgresql":
    op.execute("ALTER TYPE user_role ADD VALUE IF NOT EXISTS 'LINING_MANAGER'")
```

And it must be the member NAME, uppercase — not the value.

`Enum(UserRole, ...)` persists the enum **member name**, because this project never passes `values_callable`. For `SECURITY = "security"` the driver sends `'SECURITY'`. Adding the lowercase `'security'` creates a label the ORM will never emit, and the role stays unusable — the INSERT still dies with `invalid input value for enum user_role: "SECURITY"` **even though** `'security'` is on the type.

This bit `lining_manager`, `security` and `merchandiser`. Write the name exactly as it appears left of the `=` in `core/enums.py`. The schema's other native enums (`attendance_source`, `wage_type`, `run_status`) are all uppercase names — match them.

30.3 Model imports

Every model module must be imported in `main.py` so `Base.metadata` sees every table. A missed import makes Alembic autogenerate try to **DROP** the table.

`barcode.models` holds the barcode, material, drawer, supplier, style-spec and issue-ledger tables. `dashboard` and `analytics` own none — verify that before adding a model-import line for them.

30.4 Router locking

Manager-only routers are wrapped with `block_employees`. **Auth, users, attendance and `/barcode/resolve` stay open** at the router level — the attendance write routes do their own operator gate, and resolve must stay reachable from the attendance screen.

30.5 Route ordering

FastAPI matches in **registration order**. Three files depend on it:

File	The trap
<code>clients/route_r.py</code>	<code>GET /clients/styles</code> must precede <code>GET /clients/{client_id}</code> — "styles" is not a UUID, so the request would 422 instead of reaching the handler
<code>drawers/route_r.py</code>	<code>/pool</code> , <code>/by-code/{code}</code> and <code>/send</code> must precede <code>/ {drawer_id}</code>
<code>wages/router.py</code>	Every static segment must precede <code>/runs/{run_id}</code>

Style codes are **query** parameters, not path segments, for a related reason: a code like `JP-CLERMONT_VEST` is fine in a path, but the day someone imports a style whose name slugs to something containing a slash, a path parameter breaks and a query parameter does not.

30.6 Known traps — do not reintroduce

Trap	Symptom
Importing <code>api</code> from <code>sqlalchemy.event</code>	Wrong object; routers never register. Use <code>app.include_router</code>
Defining <code>lifespan</code> twice	The second silently overrides the first

Trap	Symptom
Hoisting a lazy cross-module import	Import cycle. <code>production.service → materials.service , → drawers.service</code> and <code>drawers.service → production.models</code> are all inside the method that uses them
Adding an enum member without the PG migration	The role is unusable
Adding the enum value instead of the name	The role is <i>still</i> unusable, confusingly
Encoding stage order against <code>Operation.sequence</code>	A stray UPDATE reorders the factory
Duplicating <code>next_chain_stage</code>	Read and write paths drift
Reading <code>piece.needs_lining</code> directly	It is written once at release and wrong for most of a live order. Use the effective resolver

31. A code-review checklist

Layering

- [] Router contains no business logic — dependency, **barcode→id resolution**, delegate.
- [] Commits live in the service; the whole scan is one transaction.
- [] All DB access is in the repository.
- [] Cross-module calls go **service → service**, and the import is **lazy**.

The production contract

- [] **No endpoint accepts a stage from the client.** Stage is derived.
- [] Screen context is derived from the role; only DM/MD/HR may override.
- [] Both doors converge on ids before the service sees anything.
- [] Gate 1 is whole-request; gates 2–4 are per-piece.
- [] Every per-piece rejection lands in `blocked[]` with `{piece, stage, gate, reason}`.
- [] `next_chain_stage` is called, never reimplemented.

Correctness

- [] Blocking work runs in `run_in_threadpool`.
- [] Money and quantities are `Decimal`.
- [] `available` is derived, never stored.
- [] Stock decrements **once per batch**, in the same transaction as the events.
- [] The lot link is on the **event**, never on the piece.
- [] Idempotent writes are idempotent — check-in re-tap, accessory re-scan, close-run.

State and safety

- [] Hard transitions write an `audit_log` row: release, receive, send, barcode reissue/deactivate, material receipt, kit issue, spec confirm, run reopen.
- [] Nothing is hard-deleted where a soft-deactivate or retire would do.
- [] A retired barcode returns **410**, not 404.
- [] A removed endpoint returns **410 naming the replacement**, not 404.

- [] **Partial accept:** batch operations report per-item outcomes and commit the good ones.
 - [] **When unsure, ask** — ambiguous lots, undeclared lining, unconfirmed specs all stop and surface the choice.
- Contract**
- [] New status columns are `str`-Enum in VARCHAR — **not** a native PG enum.
 - [] A new `UserRole` member ships with an `ALTER TYPE ... ADD VALUE 'NAME'` migration.
 - [] New models are imported in `main.py`.
 - [] New endpoints carry a role gate, or are deliberately and documentedly open.
 - [] Tenancy: any client-reachable read threads `client_scope`, and a cross-tenant id yields **404**.
 - [] Cost and pay data is gated to HR/DM/MD — never bare `get_current_user`.
-

APPENDICES

Appendix A — Glossary

Term	Meaning
Piece	ONE physical garment. The tracked unit. Identity is <code>(sku_id, seq)</code>
SKU	A colour + size combination of a style, with a quantity ordered
Breakdown sheet	The workbook that turns a client order into styles and SKUs
Release	The hard, audited transition that mints pieces, barcodes and drawer merges
Mint	To create a barcode. Irreversible
Compact code	The short <code>PC-004821</code> that is printed and scanned
Alias	The long legacy code kept scannable after the compact switch
dcm	Square decimetres — the unit leather is measured and consumed in
Lot	A batch of material with its own barcode and its own three stock numbers
Drawer	A physical storage slot. Static code, recycling state
Merge	Assigning a piece to a drawer at release
Merge gate	The completeness rule blocking <code>LINE_STITCHING</code> until the drawer is <code>SENDED</code>
Completeness	Leather present, and lining present if the garment needs one
Kit	A garment's accessory set, issued from the style's recipe
Recipe	<code>style_material_spec</code> — what one garment of this style needs
Rework	Logging a piece at a stage it already passed. Permitted, flagged
Screen context	<code>LEATHER_CUT</code> / <code>LINING_CUT</code> / <code>PIPELINE</code> — derived from the role
Designation	An employee's skill. Uppercase, controlled vocabulary
Operator	A login permitted to write attendance: Security, HR, MD, DM
Proxy	An attendance entry made by an operator for a worker
Piece run	A payroll for <code>PIECE_RATE</code> workers. Requires a style or order scope

Term	Meaning
Monthly run	A payroll for salaried staff, priced by the calendar
Frozen run	A CLOSED wage run — the document the cash was counted against
Sea cut-off	The last day to make sea freight. Missing it means air
Bottleneck	The deepest queue — the stage with the most work waiting

Appendix B — Complete enum reference

UserRole `managing_director` · `direct_manager` · `cutting_manager` · `lining_manager` · `stitching_manager` · `store_manager` · `supervisor` · `hr` · `security` · `merchandiser` · `client` · `viewer` · `~~ employee ~~ (legacy)`

ATTENDANCE_OPERATOR_ROLES `security` · `hr` · `managing_director` · `direct_manager`

ProductionStage `LEATHER_CUTTING` · `LINING_CUTTING` · `FUSING` · `PASTING` · `LINE_STITCHING` · `SHELL_STITCHING` · `FINAL_FINISH` · `FINAL_INSPECTION` · `PACKAGE_EXPORT`

ScreenContext `LEATHER_CUT` · `LINING_CUT` · `PIPELINE`

Designation `CUTTER` · `LINING_CUTTER` · `FUSER` · `PASTER` · `LINE_TAILOR` · `SHELL_TAILOR` · `FINISHER` · `INSPECTOR` · `PACKER` · `TAILOR` · `HELPER` · `SUPERVISOR` · `TRIMMER` · `CHEMICAL_TECHNICIAN` · `SECURITY` · `MERCHANDISER` · `STITCHING_INSTRUCTOR` · `QC_INSPECTOR` *Multi-stage (no skill gate):* `HELPER` · `SUPERVISOR`

STAGE_ROLE_ACCESS (Gate 1) and **STAGE_DESIGNATIONS** (Gate 2) are tabulated in full in §12.3.

MULTI_STAGE_DESIGNATIONS `HELPER` · `SUPERVISOR` — exempt from Gate 2 at every stage.

_STAGE_BYPASS_ROLES `managing_director` · `direct_manager` · `hr` — the three logins that log any stage.

BarcodeType `PIECE` · `LEATHER_LOT` · `LINING_LOT` · `ACCESSORY_LOT` · `LEATHER_SHEET` · `EMPLOYEE` · `DRAWER`
LEATHER_SHEET is the per-hide barcode minted by Cutting V2 (§13). DRAWER is retained so printed drawer stickers still resolve rather than 404 — nothing mints a new one.

BarcodeStatus `active` · `retired`

The store — use these, not the drawer pair

StoreState `waiting` · `merged` · `holding_leather` · `holding_lining` · `holding_both` · `received` · `sended` *Lives on `piece.store_state`. This is the live enum.*

StorePart `LEATHER` · `LINING` · `ACCESSORY` (*ACCESSORY is never inferred — safety rule, §14*)

STORE_HOLDING_STATES `holding_leather` · `holding_lining` · `holding_both` · `received` · `sended` — the states in which the store is holding something.

DrawerState and **DrawerPart** still exist in `enums_barcode.py` with identical members, and they are NOT the ones to code against. They belong to the withdrawn `drawers/` module and survive only so its historical rows still deserialise for audit. New code reads `piece.store_state` and `StoreState`. If you find yourself importing `DrawerState`, you are in the wrong module.

Cutting V2

CuttingRowStatus `DRAFT` · `APPROVED` · `LOGGED` · `CANCELLED` **CUTTING_ROW_HOLDS_SHEETS** `DRAFT` · `APPROVED` — the two states in which a row still owns its allocated hides.

SheetStatus `IN_STOCK` · `ALLOCATED` · `ISSUED` · `CONSUMED` · `RETURNED` · `SCRAPPED` **SHEET_ALLOCATABLE** / **SHEET_IN_STORE** both `IN_STOCK` · `RETURNED` — a returned hide goes back on the shelf and can be allocated again.

Inspections

`InspectionVerdict` PASS · REJECT `InspectionStatus` PENDING · APPROVED · DECLINED · RESOLVED `ReworkAction` FIX · REDO `DefectType` PRODUCT_DAMAGE · WORKMANSHIP `INSPECTION_RAISER_ROLES` every floor manager + store_manager + supervisor + hr + DM/MD · `INSPECTION_APPROVER_ROLES` direct_manager · managing_director only.

Job work

`JobWorkStatus` OUT · PARTIAL · RETURNED · CANCELLED `JobWorkPieceStatus` OUT · BACK · SHORT · REJECTED `JOBWORK_PIECE_AWAY` OUT — the one status in which a piece is off-site and cannot be scanned in-house.

`MaterialCategory` LEATHER · LINING · ACCESSORY

`MaterialSubtype` RIBS · KNIT · PLAIN_LINING · BUTTON · ZIP · THREAD · OTHER

`KitStatus` NOT_REQUIRED · PENDING · PARTIAL · ISSUED

`MaterialIssueSource` STORE_KIT · CUT (*reserved*) · MANUAL

`ReceiptStatus` approved · rejected

`SupplierOrderStatus` ordered · arrived

`ProductionReleaseStatus` DRAFT · RELEASED · CANCELLED

`WageType` monthly · piece_rate

`WageRunKind` piece · monthly · ~~ combined ~~ (*legacy*)

`RunStatus` open · closed

`AttendanceSource` self · proxy

`ShipMode` sea · air

Appendix C — Audit log actions

Twenty-nine actions are written by Phase-1 code. All of them are below, grouped by the module that writes them. Some are `BarcodeAuditAction` members; some are plain strings written at the call site — **the column that matters is what lands in `audit_log.action`, which is what a query filters on.**

Intake — `imports/`

Action	Written when
<code>BREAKDOWN_STYLE_RELEASED</code>	The mint. A style is released and its pieces and barcodes come into existence
<code>BREAKDOWN_STYLE_UPDATED</code>	A style row is edited while still DRAFT
<code>BREAKDOWN_STYLE_CANCELLED</code>	A breakdown style is cancelled before release
<code>BREAKDOWN_SKU_UPDATED</code>	A SKU's colour / size / quantity is edited while DRAFT
<code>BREAKDOWN_SKU_DELETED</code>	A SKU is removed from an unreleased breakdown

The spine — `barcode/`

Action	Written when
<code>EMPLOYEE_BARCODE_REISSUE</code>	A lost or damaged card is replaced. The old code is retired; history is untouched
<code>EMPLOYEE_BARCODE_DEACTIVATE</code>	A worker leaves. The code returns 410 Gone; the person, their events and their wage lines stay

Materials — materials/

Action	Written when
MATERIAL_RECEIVED	A delivery is booked in — approved and rejected quantities recorded separately
MATERIAL_RECEIVED_SUBSTITUTE	The same, where what arrived is not what was ordered. Written as a raw string and not a BarcodeAuditAction member — filter on the literal
MATERIAL_STOCK_ADJUSTED	A manual correction to <code>on_hand</code>
MATERIAL_LOT_RETIRED	A lot is withdrawn from stock
MATERIAL_ISSUED_MANUAL	Material issued outside the kit flow
SUPPLIER_ORDER_SPEC_EDIT	A supplier order's spec is amended
STYLE_MATERIAL_SPEC_CONFIRMED	A style's recipe is frozen
STYLE_MATERIAL_SPEC_AMENDED	A confirmed recipe is changed afterwards

Cutting — cutting/

Action	Written when
CUTTING_ROW_APPROVED	A cut sheet is frozen — these hides, this total, this cutter
CUTTING_ROW_REOPENED	An approved cut sheet is un-frozen

The store — store/

Action	Written when
DRAWER_RECEIVED	A garment reaches completeness in the store (<i>name kept from the drawer era — it is written by <code>store/service.py</code></i>)
DRAWER_SENDED	A batch is released to line-stitching

Production and inspections — production/

Action	Written when
PIECE_REJECTED	A garment fails inspection, recorded against the responsible stage
PIECE_REWORK_APPROVED	The DM approves the re-walk
PIECE_REWORK_DECLINED	The DM refuses it
PRODUCTION_EVENT_REASSIGNED	Work was filed against the wrong worker
PRODUCTION_EVENT_DELETED	A production event is removed

Job work — jobwork/

Action	Written when
JOB_WORK_DISPATCHED	Garments leave for an outside factory. While <code>OUT</code> they cannot be scanned in-house
JOB_WORK_RETURNED	They come back; the stage logs against the vendor , advancing the garment without generating a wage

Attendance — attendance/

Action	Written when
ATTENDANCE_CORRECT ED	A punch is edited, or re-allocated — the <code>after</code> payload carries <code>reallocated_from</code> and <code>production_events_moved</code>
ATTENDANCE_DELETED	A punch is removed. <code>reason</code> is mandatory

Two that are defined but never written

`BarcodeAuditAction` also declares `MATERIAL_KIT_ISSUED` and `CUTTING_SHEET_RETURNED`. Neither reaches `audit_log` today: `MATERIAL_KIT_ISSUED` is written only by `drawers/service.py`, which is unrouted, and `CUTTING_SHEET_RETURNED` has no call site at all. **Do not build a report that expects either.** They are left in the enum because the kit-issue path returns with the store, not because they fire now.

Phase 2 writes its own actions — `BOM_*`, `PO_*`, `SUPPLIER_*`, `INVENTORY_CHECK_RUN`, `PRODUCTION_TRACKING_UPDATE`, `VIRUS_DETECTED`, `DOCUMENT_MANUAL_OVERRIDE` — into the same `audit_log` table. A query that does not filter by action will see both phases. | `PRODUCTION_EVENT_DELETED` | A record that should not exist is removed, and its stock returned || `EMPLOYEE_BARCODE_REISSUE` | A card is replaced || `EMPLOYEE_BARCODE_DEACTIVATE` | A worker leaves || `MATERIAL_RECEIVED` | A delivery is received || `MATERIAL_KIT_ISSUED` | An accessory kit is issued — **it spends stock** || `MATERIAL_ISSUED_MANUAL` | An off-spec correction || `STYLE_MATERIAL_SPEC_CONFIRMED` | A recipe is signed off || `STYLE_MATERIAL_SPEC_AMENDED` | A recipe is changed |

Plus release, style cancel, lot adjust, lot retire, and every wage-run reopen/recompute/delete.