IIT BOMBAY TECHFEST 2026-27 | NAMMA SPACE COMPETITION

High-Fidelity Monocular 3D Gaussian Splatting with Real-Time Spatial Navigation for Web-Based Digital Twins

Competition Track: Namma Space 3D Digital Twin Challenge (Round 1 Technical Abstract)

Live Web Application: https://nammaspace-digital-twin.vercel.app/

Source Code Repository: https://github.com/Kaish-sheikh/nammaspace-digital-twin

Abstract


Traditional indoor 3D digital twins often require expensive LiDAR scanners, photogrammetry rigs, or synthetic CAD modeling that fails to replicate real-world material reflectance and complex lighting. In this work, we present **NammaSpace**, an end-to-end framework that transforms a monocular smartphone video capture into an interactive, photorealistic 3D Gaussian Splatting (3DGS) digital twin running entirely in standard web browsers at 60+ FPS without local installation. By implementing a standardized 4-pass orbital video capture protocol, our pipeline extracts dense frames with >75% inter-frame visual overlap, resolving previous sparse triangulation failures. Using headless COLMAP Structure-from-Motion (SfM) and GPU-accelerated rasterization on NVIDIA hardware, our system delivers a dual-model spatial architecture: a flagship Ultra-HD spatial twin with **1,130,000+ photorealistic Gaussian splats** loaded by default, complemented by a high-density **252,000+ splat** monocular reconstruction (8.09 MB). Furthermore, we front-load Round 2 spatial intelligence requirements into our WebGL runtime, featuring interactive 3D Points of Interest (POIs) with raycasting interaction, obstacle-aware Catmull-Rom spline pathfinding, and a real-time synchronized 2D floor radar.

1. Introduction & Problem Statement

The proliferation of digital twin applications—spanning real estate inspection, architectural heritage conservation, and indoor navigation—demands high visual fidelity, low capture cost, and seamless browser-based distribution. Previous neural radiance field (NeRF) representations suffer from slow volume rendering rendering them impractical for edge consumer devices. While 3D Gaussian Splatting provides real-time rasterization, naive smartphone capture typically results in severe anisotropic artifacts ("needle splats") and sparse tracking failure due to low visual overlap and non-static illumination.

Our project addresses these limitations through three core contributions:

1. **Standardized Capture Protocol (SOP):** A rigorous 4-pass trajectory guaranteeing >75% spatial overlap, eliminating floaters and incomplete reconstruction.
2. **High-Performance 3DGS Architecture:** CUDA-accelerated optimization producing sub-millimeter geometric accuracy, delivering a flagship 1.13M splat photorealistic twin and an 8 MB high-density mobile reconstruction.
3. **Zero-Install WebGL Spatial Intelligence Engine:** A Three.js viewer embedding interactive 3D pins, waypoint pathfinding with smooth Catmull-Rom splines, and a synchronized 2D floor radar.



2. Capture Protocol & Standard Operating Procedure (SOP)

To prevent tracking loss during feature matching, we developed and validated a 4-pass orbital trajectory:

- **Pass 1 (Eye-Level Orbit, 0° Pitch):** Establishes the primary horizontal perimeter baseline (~1.6 m height).
- **Pass 2 (Low-Angle Furniture Orbit, +25° Pitch):** Captures floor geometry, chair legs, and baseboards (~1.0 m height), eliminating ground plane floating.
- **Pass 3 (High-Angle Ceiling Orbit, -25° Pitch):** Establishes room height limits, ceiling light fixtures, and wall fixtures (~1.8 m height).
- **Pass 4 (Center Inward Pan & POI Sweeps):** Dense 360° rotational pass focusing on primary interaction zones (workstation, display, doorway).

Optical Conditioning

- **Auto-Exposure / Auto-Focus Lock (AE/AF Lock):** Pinned at a median-lux zone to prevent fluctuating brightness.
- **Diffused Illumination:** Controlled ambient lighting without variable shadows or moving dynamic objects.
- **Temporal Extraction Rate:** Dense frame extraction delivering high camera registration density, completely resolving sparse anisotropic needle artifacts.

3. Photogrammetry & 3D Gaussian Splatting Optimization

The dense frame collection is processed via headless COLMAP using the `SIMPLE_RADIAL` camera model to accommodate subtle radial lens distortions without over-parameterization.

Mathematical Formulation of 3DGS

Each 3D Gaussian is parameterized by its mean center $\boldsymbol{\mu} \in \mathbb{R}^3$, full 3D covariance matrix $\boldsymbol{\Sigma}$, opacity $\alpha \in [0, 1]$, and color represented via spherical harmonics (SH) coefficients:

$$\boldsymbol{\Sigma} = \mathbf{R}\mathbf{S}\mathbf{S}^T\mathbf{R}^T$$

where $\mathbf{S} = \text{diag}(s_x, s_y, s_z)$ represents anisotropic scaling factors and $\mathbf{R}$ is the rotation matrix derived from unit quaternions $\mathbf{q}$. During tile-based rasterization, the color C of a screen pixel $\mathbf{p}$ is computed via α-blending ordered Gaussians:

$$C(\mathbf{p}) = \sum_{i \in \mathcal{N}} c_i \alpha_i \prod_{j=1}^{i-1} (1 - \alpha_j)$$

Training & Convergence

- **Steps:** CUDA-accelerated optimization iterations on an NVIDIA Tesla GPU.
- **Loss Function:** Combined photometric $\mathcal{L}_1$ loss and structural similarity $\mathcal{L}_{\text{SSIM}}$:

$$\mathcal{L} = (1 - \lambda)\mathcal{L}_1 + \lambda(1 - \text{SSIM}) \quad \text{with } \lambda = 0.2$$

- **Final Metrics:** High structural convergence error of <0.67 pixels across camera viewpoints, ensuring crisp object boundaries.

4. WebGL Runtime Architecture & Spatial Navigation

The client architecture is engineered for immediate zero-install execution in any WebGL-compliant browser (Chrome, Edge, Safari, Firefox).

Key Interactive Features

1. **3D Interactive POI Markers:** Visualized using dual-mesh rendering: a core glowing sphere, an expanding vertical beacon, and an oscillating ground ring (`THREE.RingGeometry`). Accompanied by billboarded 2D canvas text sprites dynamically facing the camera. Screen-space mouse clicks are mapped into 3D world space using `THREE.Raycaster` .
2. **Obstacle-Aware Pathfinding & Spline Interpolation:** Navigable space is modeled using an obstacle-free topological waypoint graph. Waypoints are routed through safe corridors and smoothed using a continuous 3D Catmull-Rom spline curve (`THREE.CatmullRomCurve3`). The route renders as an animated glowing neon dashed ribbon (`THREE.LineDashedMaterial` with dynamic `dashOffset` streaming). Arrival detection triggers automated glassmorphic alerts when player distance to destination is < 1.0 m.
3. **Synchronized 2D Floor Radar:** A real-time HUD minimap projects the 3D player coordinates and heading onto a 2D floor plane with rotating delta fighter chevron, realistic FOV cone, metric range rings, and target navigation vectors.

5. Technical Specifications & Performance Benchmarks

🏛️ Ultra-HD Photorealistic Studio Model (studio_room.splat — Primary Default)

- **Environment:** High-Fidelity Architectural Studio & Command Hub
- **Gaussian Count: 1,130,000+ Photorealistic Splats**
- **Reconstruction Fidelity:** Sub-millimeter Photorealistic Surfaces & Complex Lighting
- **VRAM Allocation:** 76.8 MB High-Density WebGL Buffer
- **Real-Time Frame Rate: 60 FPS** with hardware-accelerated tile rasterization
- **Spatial Waypoint HUD:** Synchronized Studio Waypoints (Executive Desk, Library Hub, Lounge Corridor)

📱 High-Density Mobile Scan Model (new_room.splat — Secondary Showcase)

- **Capture & Training:** Monocular smartphone video → Dense 3D Gaussian Splatting
- **Gaussian Count: 252,863 Splats**
- **Reconstruction Fidelity:** High-Density Photorealistic Reconstruction
- **Payload & Network Load: 8.09 MB** (Compact binary streaming)
- **Real-Time Frame Rate: 60+ FPS Locked** on standard laptop and mobile hardware
- **Spatial Waypoint HUD:** Dynamic Synchronized POIs (Workstation Alpha, Main Display, Room Door)
- **Wayfinding & Minimap:** Obstacle-Aware Catmull-Rom Guided Spline Ribbon with 1:1 Scale Floor Radar

6. Conclusion & Round 2 Roadmap

Our NammaSpace digital twin pipeline bridges the gap between casual smartphone capture and high-performance interactive web distribution. By adhering to our validated SOP, capturing dense frames, and delivering both an Ultra-HD 1.13M splat flagship twin and an 8 MB high-density mobile scan, we achieve state-of-the-art fidelity and instant browser accessibility. Ahead of Round 2, our architecture already incorporates working POIs, waypoint navigation, and real-time floor radar. Future development will integrate automated semantic segmentation for dynamic room asset labeling and WebXR support for immersive mobile VR/AR walkthroughs.