



University of Dhaka

DU_Kronos

Yeamin Kaiser, Sakib Hassan, Bholanath Das Niloy

Team Reference Document for ICPC WORLD FINALS, EGYPT

Updated: April 2024

Contents			1
1 DP	1	5 Math	13
1.1 CHT	1	5.1 FWHT	13
1.2 DC_Optimization	2	5.2 FloorSum	14
1.3 SOS_DP	2	5.3 NOD	14
1.4 dynamic cht	2	5.4 Pollard Rho	14
2 Data Structure	2	5.5 catalan	14
2.1 2D_segtree	2	5.6 crt	14
2.2 Segtree_beats_desc	3	5.7 derangement	14
2.3 gp_hash_table	3	5.8 diophantine	15
2.4 iterative_segtree	3	5.9 discrete_log	15
2.5 mos_algo	3	5.10 factorial_mod_p	15
2.6 ordered_set	3	5.11 fft	15
2.7 persistant_segtree	3	5.12 find_roots	15
2.8 segment_tree	4	5.13 gauss_elimination	15
2.9 sparse_table	4	5.14 gen_all_k_combs	16
3 Geometry	4	5.15 integrate_adaptive	16
3.1 2D Primitive	4	5.16 lagrange_interpolation	16
3.1.1 Angle	4	5.17 matrix_expo	17
3.1.2 Line Distance	4	5.18 next_lexicographical_k_comb	17
3.1.3 Line Intersection	4	5.19 ntt	17
3.1.4 Linear Transformation	5	5.20 seg_sieve	17
3.1.5 On Segment	5	5.21 stirling	17
3.1.6 Point Sort	5	5.22 stirling_number_of_the_second_kind	17
3.1.7 Point	5	5.23 sum_of_totient	17
3.1.8 Segment Distance	5	5.24 totient	18
3.1.9 Segment Intersection	5	5.25 xor_basis	18
3.1.10 Side Of	5	6 Misc	18
3.2 3D	5	6.1 check	18
3.2.1 3D Convex Hull	5	6.2 debug	18
3.2.2 Point3D	6	6.3 flags	18
3.2.3 Polyhedron Volume	6	6.4 interval_container	18
3.2.4 Spherical Distance	6	6.5 interval_cover	19
3.3 Circle	6	6.6 pragma	19
3.3.1 Circle Intersection	6	6.7 random	19
3.3.2 Circle Polygon Intersection	6	6.8 vimrc	19
3.3.3 Circle Tangents	6	7 Notes	19
3.3.4 CircumCircle	6	7.1 Counting	19
3.4 Polygon	7	7.2 Fibonacci	19
3.4.1 Hull Diameter	7	7.3 Notes	19
3.4.2 Line Hull Intersection	7	7.4 Geometry	19
3.4.3 Polygon Center	7	7.4.1 Triangles	19
3.4.4 Polygon Cut	7	7.4.2 Quadrilaterals	19
3.5 Closest Pair	7	7.4.3 Spherical coordinates	19
3.6 Convex Hull	7	7.5 Sums	20
3.7 Minimum Enclosing Circle	7	7.6 Series	20
3.8 Point In Polygon	8	7.7 Pythagorean Triples	20
3.9 near_pair	8	7.8 Number Theory	20
3.10 sweep	8	7.8.1 Primes	20
4 Graph	9	7.8.2 Estimates	20
4.1 2Sat	9	7.8.3 Perfect numbers	20
4.2 Centroid_decomp	9	7.8.4 Carmichael numbers	20
4.3 articulation_point	10	7.8.5 Mobius function	20
4.4 bcc	10	7.8.6 Legendre symbol	20
4.5 bridge_tree	10	7.8.7 Jacobi symbol	20
4.6 dinic	10	7.8.8 Primitive roots	20
4.7 dsu_on_tree	11	7.8.9 Discrete logarithm problem	20
4.8 euler_path	11	7.8.10 Pythagorean triples	20
4.9 hld	11	7.8.11 Postage stamps/McNuggets problem	20
4.10 hopcroft_karp	11	7.8.12 Fermat's two-squares theorem	20
4.11 hungarian	12	7.9 Permutations	20
4.12 kuhn	12	7.9.1 Factorial	20
4.13 lca	12	7.9.2 Cycles	20
4.14 manhattan_MST	12	7.9.3 Derangements	20
4.15 mcmf	13	7.9.4 Burnside's lemma	20
4.16 tree_hash_all_root	13	7.10 Partitions and subsets	20
		7.10.1 Partition function	20
		7.11 General purpose numbers	20
		7.11.1 Stirling numbers of the first kind	20
		7.11.2 Eulerian numbers	20
		7.11.3 Stirling numbers of the second kind	20
		7.11.4 Bell numbers	20
		7.11.5 Bernoulli numbers	20
		7.11.6 Catalan numbers	21
		7.12 Inequalities	21
		7.12.1 Titu's Lemma	21
		7.13 Games	21
		7.13.1 Grundy numbers	21
		7.13.2 Sums of games	21
		7.13.3 Misère Nim	21
		7.14 NumberTheory	21
		7.15 troubleshoot	21
		8 String	21
		8.1 aho_corasick	21
		8.2 fft_match	22
		8.3 hash	22
		8.4 hash_segtree	22
		8.5 kmp	23
		8.6 manacher	23
		8.7 palindromic_tree	23
		8.8 persistant_trie	23
		8.9 suffix_array	23
		8.10 suffix_automata	24
		8.11 trie	24
		8.12 z_algo	24
		1 DP	1
		1.1 CHT	1
		/*	19
		Lines should be added non-increasing order of m	19
		for minimizing	19
		Non-decreasing order of m for maximizing	19
		* Intersection point of two lines (m1,c1) , (m2,c2)	19
		is	19
		x = (c2-c1)/(m1-m2)	19
		*/	19
		ll M[MAX] , C[MAX];	19
		struct CHT {	19
		int len , cur;	19
		void init() {	19
		len = 0 , cur = 0;	19
		}	19
		// returns true if line[len-1] is unnecessary when	20
		we add line(nm,nc)	20
		inline bool isBad(ll nm,ll nc) {	20
		return ((C[len-1]-C[len-2])/(double)(M[len-2]-M[en-1]) >= (nc-C[len-2])/(double)(M[len-2]-nm)	20
		=);	20
		//return ((C[len-1]-C[len-2])*(M[len-2]-nm) >=	20
		(M[len-2]-M[len-1])*(nc-C[len-2]));	20
		}	20
		inline void addLine(ll nm,ll nc) {	20
		if(len == 0) M[len] = nm , C[len] = nc , ++len;	20
		else if(M[len-1] == nm) {	20
		if(C[len-1] <= nc) return; // <= to minimize, >=	20
		to maximize	20
		else C[len-1] = nc;	20
		}	20
		else {	20
		while(len >= 2 && isBad(nm,nc)) --len;	20
		M[len] = nm , C[len] = nc , ++len;	20
		}	20
		inline ll getY(int id , ll x) {	20
		return (M[id]*x + C[id]);	20
		}	20
		inline ll sortedQuery(ll x) {	20

```

if(cur >= len) cur = len-1;
while( cur < len-1 && getY(cur+1,x) >= getY(cur,x)
    ) cur++; // <= to minimize, >= to maximize
return getY(cur,x);
}
inline ll TS( ll x ) {
    int low = 0, high = len-1, mid;
    while( high - low > 1 ) {
        mid = low + high >> 1;
        if(getY(mid,x) < getY(mid+1,x)) low = mid + 1;
        // > to minimize, < to maximize
        else high = mid;
    }
    return max(getY(low,x),getY(high,x)); // adjust
    // min/max
};
}
}
CHT cht;
cht.init();

```

1.2 DC_Optimization

```

void compute(int L, int R, int optL, int optR){
    if(L > R) return;
    int M = L + R >> 1;
    pair<ll, int> best(1LL << 60, -1);
    for(int k = optL; k <= min(M, optR); k++){
        best = min(best, {dp[prv][k] + C[k+1][M], k});
    }
    dp[now][M] = best.ff;
    compute(L, M - 1, optL, best.ss);
    compute(M + 1, R, best.ss, optR);
}

```

1.3 SOS DP

```

/*
S(mask,i) denotes those submasks of mask which
    differ
from mask only in the least significant i+1 bits (
    0, 1, 2, ..., i--> 0 based indexing)
Example : S(1011010,3) =
    {1011010,1010010,1011000,1010000}
if(bit i is on)
    S(mask, i) = S(mask, i - 1) U S(mask ^ (1<<i),
        i - 1)
else
    S(mask, i) = S(mask, i - 1)
Let Sum(mask,i) denote the sum of the all A[x]
    where x element of S(mask,i)
So, Sum(mask,N-1) will contain SOS DP result for a
    particular mask
Recurrence :
if(i'th bit is on)
    Sum(mask, i) = Sum(mask, i-1) + Sum(mask ^
        (1<<i), i-1)
else
    Sum(mask, i) = Sum(mask, i-1)
*/
for(int mask = 0; mask < (1<<N); ++mask){
    dp[mask][-1] = A[mask];
    for(int i = 0; i < N; ++i){
        if(mask & (1<<i)) dp[mask][i] =
            dp[mask][i-1] + dp[mask ^ (1<<i)][i-1];
        else dp[mask][i] = dp[mask][i-1];
    }
    F[mask] = dp[mask][N-1];
}
for(int i = 0; i < (1<<N); ++i) F[i] = A[i];
for(int i = 0; i < N; ++i)
    for(int mask = 0; mask < (1<<N); ++mask){
        if(mask & (1<<i))
            F[mask] += F[mask^(1<<i)];
    }
}

```

```

}
/*
* c = x&-x, r = x+c; (((r^x) >> 2)/c) | r is the next
* number after x with the same number of bits set.
*/
1.4 dynamic cht
//add lines with -m and -b and return -ans to
//make this code work for minimums.(not -x)
const ll inf = -1LL << 62;
struct line {
    ll m, b;
    mutable function<const line*() > succ;
    bool operator < (const line& rhs) const {
        if (rhs.b != inf) return m < rhs.m;
        const line* s = succ();
        if (!s) return 0;
        ll x = rhs.m;
        return b - s->b < (s->m - m) * x;
    }
};
struct CHT : public multiset<line> {
    bool bad(iterator y) {
        auto z = next(y);
        if (y == begin()) {
            if (z == end()) return 0;
            return y -> m == z -> m && y -> b <= z -> b;
        }
        auto x = prev(y);
        if (z == end()) return y -> m == x -> m && y -> b
            <= x -> b;
        return 1.0 * (x -> b - y -> b) * (z -> m - y -> m)
            <= 1.0 * (y -> b - z -> b) * (y -> m - x -> m);
    }
    void add(ll m, ll b) {
        auto y = insert({ m, b });
        y->succ = [ = ] { return next(y) == end() ? 0 :
            &*next(y); };
        if (bad(y)) {
            erase(y);
            return;
        }
        while (next(y) != end() && bad(next(y)))
            erase(next(y));
        while (y != begin() && bad(prev(y)))
            erase(prev(y));
    }
    ll query(ll x) {
        auto l = *lower_bound((line) {
            x, inf
        });
        return l.m * x + l.b;
    }
};
CHT* cht;
ll a[N], b[N];
int32_t main() {
    ios_base::sync_with_stdio(0);
    cin.tie(0);
    int n;
    cin >> n;
    for(int i = 0; i < n; i++) cin >> a[i];
    for(int i = 0; i < n; i++) cin >> b[i];
    cht = new CHT();
    cht -> add(-b[0], 0);
    ll ans = 0;
    for(int i = 1; i < n; i++) {
        ans = -cht -> query(a[i]);
        cht -> add(-b[i], -ans);
    }
    cout << ans << nl;
    return 0;
}

```

```

}
2 Data_Structure
2.1 2D_segtree
struct Point {
    int x, y, mx;
    Point() {}
    Point(int x, int y, int mx) : x(x), y(y), mx(mx) {}
    bool operator < (const Point& other) const {
        return mx < other.mx;
    }
};
struct Segtree2d {
    // I didn't calculate the exact size needed in
    // terms of 2D container size.
    // If anyone, please edit the answer.
    // It's just a safe size to store nodes for MAX *
    // MAX 2D grids which won't cause stack overflow
    // :)
    Point T[500000]; // TODO: calculate the accurate
    // space needed
    int n, m;
    // initialize and construct segment tree
    void init(int n, int m) {
        this -> n = n;
        this -> m = m;
        build(1, 1, 1, n, m);
    }
    // build a 2D segment tree from data [ (a1, b1),
    // (a2, b2) ]
    // Time: O(n logn)
    Point build(int node, int a1, int b1, int a2, int
        b2) {
        // out of range
        if (a1 > a2 or b1 > b2)
            return def();
        // if it is only a single index, assign value
        // to node
        if (a1 == a2 and b1 == b2)
            return T[node] = Point(a1, b1, P[a1][b1]);
        // split the tree into four segments
        T[node] = def();
        T[node] = maxNode(T[node], build(4 * node - 2,
            a1, b1, (a1 + a2) / 2, (b1 + b2) / 2 ));
        T[node] = maxNode(T[node], build(4 * node - 1,
            (a1 + a2) / 2 + 1, b1, a2, (b1 + b2) / 2
            ));
        T[node] = maxNode(T[node], build(4 * node + 0,
            a1, (b1 + b2) / 2 + 1, (a1 + a2) / 2, b2)
            );
        T[node] = maxNode(T[node], build(4 * node + 1,
            (a1 + a2) / 2 + 1, (b1 + b2) / 2 + 1, a2,
            b2 ));
        return T[node];
    }
    // helper function for query(int, int, int, int);
    Point query(int node, int a1, int b1, int a2, int
        b2, int x1, int y1, int x2, int y2) {
        // if we out of range, return dummy
        if (x1 > a2 or y1 > b2 or x2 < a1 or y2 < b1
            or a1 > a2 or b1 > b2)
            return def();
        // if it is within range, return the node
        if (x1 <= a1 and y1 <= b1 and a2 <= x2 and b2
            <= y2)
            return T[node];
        // split into four segments
    }
}

```

```

Point mx = def();
mx = maxNode(mx, query(4 * node - 2, a1, b1,
    (a1 + a2) / 2, (b1 + b2) / 2, x1, y1, x2,
    y2));
mx = maxNode(mx, query(4 * node - 1, (a1 + a2)
    / 2 + 1, b1, a2, (b1 + b2) / 2, x1, y1,
    x2, y2));
mx = maxNode(mx, query(4 * node + 0, a1, (b1 +
    b2) / 2 + 1, (a1 + a2) / 2, b2, x1, y1,
    x2, y2));
mx = maxNode(mx, query(4 * node + 1, (a1 + a2)
    / 2 + 1, (b1 + b2) / 2 + 1, a2, b2, x1,
    y1, x2, y2));
// return the maximum value
return mx;
}
// query from range [ (x1, y1), (x2, y2) ]
// Time: O(logn)
Point query(int x1, int y1, int x2, int y2) {
    return query(1, 1, 1, n, m, x1, y1, x2, y2);
}
// helper function for update(int, int, int);
Point update(int node, int a1, int b1, int a2, int
    b2, int x, int y, int value) {
    if (a1 > a2 or b1 > b2)
        return def();
    if (x > a2 or y > b2 or x < a1 or y < b1)
        return T[node];
    if (x == a1 and y == b1 and x == a2 and y ==
        b2)
        return T[node] = Point(x, y, value);
    Point mx = def();
    mx = maxNode(mx, update(4 * node - 2, a1, b1,
        (a1 + a2) / 2, (b1 + b2) / 2, x, y, value)
        );
    mx = maxNode(mx, update(4 * node - 1, (a1 +
        a2) / 2 + 1, b1, a2, (b1 + b2) / 2, x, y,
        value));
    mx = maxNode(mx, update(4 * node + 0, a1, (b1
        + b2) / 2 + 1, (a1 + a2) / 2, b2, x, y,
        value));
    mx = maxNode(mx, update(4 * node + 1, (a1 +
        a2) / 2 + 1, (b1 + b2) / 2 + 1, a2, b2, x,
        y, value));
    return T[node] = mx;
}
// update the value of (x, y) index to 'value'
// Time: O(logn)
Point update(int x, int y, int value) {
    return update(1, 1, 1, n, m, x, y, value);
}
// utility functions; these functions are virtual
// because they will be overridden in child class
virtual Point maxNode(Point a, Point b) {
    return max(a, b);
}
// dummy node
virtual Point def() {
    return Point(0, 0, -INF);
}
};
/* 2D Segment Tree for range minimum query; a override
of Segtree2d class */
struct Segtree2dMin : Segtree2d {
    // overload maxNode() function to return minimum
    value
    Point maxNode(Point a, Point b) {
        return min(a, b);
    }
}

```

```

Point def() {
    return Point(0, 0, INF);
}
};

```

2.2 Segtree_beats_desc

/ Description: For update Ai Ai mod x and similar, keep range min, max in node and lazily update whenever min = max. For update Ai min(Ai, x) and similar, keep range max, second max in node and lazily update whenever x > second max. Time: O(log^2 N), (log N) */*

2.3 gp_hash_table

```

using namespace __gnu_pbds;
const int RANDOM = chrono::high_resolution_clock::now()
    .time_since_epoch().count();
using namespace __gnu_pbds;
struct chash {
    const int RANDOM = (long
        long)(make_unique<char>().get()) ^
        chrono::high_resolution_clock::now().time_since_
        epoch().count();
    static unsigned long long hash_f(unsigned long long
        x) {
        x += 0x9e3779b97f4a7c15;
        x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
        return x ^ (x >> 31);
    }
    static unsigned hash_combine(unsigned a, unsigned b)
        { return a * 31 + b; }
    ll operator()(ll x) const { return hash_f(x)^RANDOM; }
};
gp_hash_table<key, long long, chash> table;

```

2.4 iterative_segtree

```

const int N = 500010;
int n, a[N], tree[N << 1];
void init() {
    for (int i = 0; i < n; ++i) tree[n + i] = a[i];
    for (int i = n - 1; i >= 0; --i) {
        tree[i] = min(tree[i << 1], tree[i << 1 | 1]);
    }
}
void update(int p, int v) {
    for (tree[p += n] = v; p > 1; p >>= 1) {
        tree[p >> 1] = min(tree[p], tree[p ^ 1]);
    }
}
int query(int l, int r) {
    int ret = INT_MAX;
    for (l += n, r += n; l < r; l >>= 1, r >>= 1) {
        if (l & 1) ret = min(ret, tree[l++]);
        if (r & 1) ret = min(ret, tree[--r]);
    }
    return ret;
}

```

2.5 mos_algo

```

struct data {
    int l, r, id, bn;
    data() {}
    data(int _l, int _r, int _id) {

```

```

        l = _l, r = _r, id = _id;
        bn = l / block_sz;
    }
    bool operator < (const data& other) const {
        if (bn != other.bn) return (bn < other.bn);
        return ((bn & 1) ? (r < other.r) : (r > other.r));
    }
}
int curL = 0, curR = -1;
for (int i = 0; i < Q.sz; i++) {
    while (curL > Q[i].L) {
        curL--; add(curL);
    }
    while (curR < Q[i].R) {
        curR++; add(curR);
    }
    while (curL < Q[i].L) {
        remove(curL); curL++;
    }
    while (curR > Q[i].R) {
        remove(curR); curR--;
    }
}

```

2.6 ordered_set

```

using namespace std;
using namespace __gnu_pbds;
typedef tree<
    int, null_type,
    less<int>, // "less_equal<int>" for multiset
    rb_tree_tag,
    tree_order_statistics_node_update > ordered_set;
ordered_set OS;

```

2.7 persistant_segtree

```

/* Persistent Segment Tree using static Array
Point Update, Range Sum
Initialize ncnt to 0 in every test case */
const int MAX = 100010;
int ncnt = 0;
struct node {
    int sum;
    int left, right;
    node() {}
    node(int val) {
        sum = val;
        left = right = -1;
    }
} tree[?];
int ara[MAX];
int version[MAX];
void build(int n, int st, int ed) {
    if (st == ed) {
        tree[ncnt] = node(ara[st]);
        return;
    }
    int mid = (st + ed) / 2;
    tree[ncnt].left = ++ncnt;
    tree[ncnt].right = ++ncnt;
    build(tree[ncnt].left, st, mid);
    build(tree[ncnt].right, mid + 1, ed);
    tree[ncnt].sum = tree[tree[ncnt].left].sum +
        tree[tree[ncnt].right].sum;
}
void update(int prev, int cur, int st, int ed, int id, int
    val)
{

```

```

if (id > ed or id < st) return;
if (st == ed) {
    tree[cur] = node(val);
    return;
}
int mid = (st+ed) / 2;
if (id <= mid) {
    tree[cur].right = tree[prev].right;
    tree[cur].left = ++ncnt;
    update(tree[prev].left, tree[cur].left, st, mid,
        id, val);
}
else {
    tree[cur].left = tree[prev].left;
    tree[cur].right = ++ncnt;
    update(tree[prev].right, tree[cur].right, mid+1,
        ed, id, val);
}
tree[cur].sum = tree[tree[cur].left].sum +
    tree[tree[cur].right].sum;
}
int query(int n, int st, int ed, int i, int j) {
    if (st >= i && ed <= j) return tree[n].sum;
    int mid = (st+ed)/2;
    if (mid < i) return query(tree[n].right, mid+1, ed, i, j);
    else if (mid >= j) return
        query(tree[n].left, st, mid, i, j);
    else return query(tree[n].left, st, mid, i, j) +
        query(tree[n].right, mid+1, ed, i, j);
}
int main() {
    int n, q, l, r, k;
    sii(n, q);
    version[0] = ++ncnt;
    build(version[0], l, n);
    version[1] = ++ncnt;
    update(version[0], version[1], l, n, id, val);
    query(version[0], l, n, id, id);
    query(version[1], l, n, id, id);
    return 0;
}

```

2.8 segment_tree

```

int ara[MAX];
struct node {
    int sum;
} tree[4 * MAX];
int lazy[4 * MAX];
node Merge(node a, node b) {
    node ret;
    ret.sum = a.sum + b.sum;
    return ret;
}
void lazyUpdate(int n, int st, int ed) {
    if (lazy[n] != 0) {
        tree[n].sum += ((ed - st + 1) * lazy[n]);
        if (st != ed) {
            lazy[2 * n] += lazy[n];
            lazy[2 * n + 1] += lazy[n];
        }
        lazy[n] = 0;
    }
}
void build(int n, int st, int ed) {
    lazy[n] = 0;
    if (st == ed) {
        tree[n].sum = ara[st];
        return;
    }
    int mid = (st + ed) / 2;

```

```

build(2 * n, st, mid);
build(2 * n + 1, mid + 1, ed);
tree[n] = Merge(tree[2 * n], tree[2 * n + 1]);
}
void update(int n, int st, int ed, int i, int j, int
    v) {
    lazyUpdate(n, st, ed);
    if (st > j or ed < i) return;
    if (st >= i and ed <= j) {
        lazy[n] += v;
        lazyUpdate(n, st, ed);
        return;
    }
    int mid = (st + ed) / 2;
    update(2 * n, st, mid, i, j, v);
    update(2 * n + 1, mid + 1, ed, i, j, v);
    tree[n] = Merge(tree[2 * n], tree[2 * n + 1]);
}
node query(int n, int st, int ed, int i, int j) {
    lazyUpdate(n, st, ed);
    if (st >= i and ed <= j) return tree[n];
    int mid = (st + ed) / 2;
    if (mid < i) return query(2 * n + 1, mid + 1, ed, i,
        j);
    else if (mid >= j) return query(2 * n, st, mid, i, j);
    else return Merge(query(2 * n, st, mid, i, j),
        query(2 * n + 1, mid + 1, ed, i, j));
}

```

2.9 sparse_table

```

int st[K + 1][MAXN];
void build() {
    std::copy(array.begin(), array.end(), st[0]);
    for (int i = 1; i <= K; i++)
        for (int j = 0; j + (1 << i) <= N; j++)
            st[i][j] = f(st[i - 1][j], st[i - 1][j + (1 <<
                i - 1)]);
}

```

3 Geometry

3.1 2D Primitive

3.1.1 Angle

A class for ordering angles (as represented by int points and a number of rotations around the origin). Useful for rotational sweeping. Sometimes also represents points or vectors.

```

/* Usage:
 * vector<Angle> v = {w[0], w[0].t360() ...}; //
 * sorted
 * int j = 0; rep(i, 0, n) { while (v[j] < v[i].t180())
 * ++j; }
 * // sweeps j such that (j-i) represents the number
 * of positively oriented triangles with vertices at
 * 0 and i
 */
struct Angle {
    int x, y;
    int t;
    Angle(int x, int y, int t=0) : x(x), y(y), t(t) {}
    Angle operator-(Angle b) const { return {x-b.x,
        y-b.y, t}; }
    int half() const {
        assert(x || y);
        return y < 0 || (y == 0 && x < 0);
    }
    Angle t90() const { return {-y, x, t + (half() && x
        <= 0)}; }
    Angle t180() const { return {-x, -y, t + half()}; }
    Angle t360() const { return {x, y, t + 1}; }
};

```


```

bool operator<(Angle a, Angle b) {
    // add a.dist2() and b.dist2() to also compare
    // distances
    return make_tuple(a.t, a.half(), a.y * (ll)b.x) <
        make_tuple(b.t, b.half(), a.x * (ll)b.y);
}
// Given two points, this calculates the smallest
// angle between
// them, i.e., the angle that covers the defined line
// segment.
pair<Angle, Angle> segmentAngles(Angle a, Angle b) {
    if (b < a) swap(a, b);
    return (b < a.t180()) ? make_pair(a, b) :
        make_pair(b, a.t360());
}
Angle operator+(Angle a, Angle b) { // point a +
    // vector b
    Angle r(a.x + b.x, a.y + b.y, a.t);
    if (a.t180() < r) r.t--;
    return r.t180() < a ? r.t360() : r;
}
Angle angleDiff(Angle a, Angle b) { // angle b - angle
    // a
    int tu = b.t - a.t; a.t = b.t;
    return {a.x*b.x + a.y*b.y, a.x*b.y - a.y*b.x, tu -
        (b < a)};
}

```

3.1.2 Line Distance

Returns the signed distance between point p and the line containing points a and b. Positive value on left side and negative on right as seen from a towards b. $a=b$ gives nan. P is supposed to be Point<T> or Point3D<T> where T is e.g. double or long long. It uses products in intermediate steps so watch out for overflow if using int or long long. Using Point3D will always give a non-negative distance. For Point3D, call .dist on the result of the cross product.



```
#include "Point.h"
```

```

template<class P>
double lineDist(const P& a, const P& b, const P& p) {
    return (double)(b-a).cross(p-a)/(b-a).dist();
}

```

3.1.3 Line Intersection

If a unique intersection point of the lines going through s1, e1 and s2, e2 exists {1, point} is returned. If no intersection point exists {0, (0,0)} is returned and if infinitely many exists {-1, (0,0)} is returned. The wrong position will be returned if P is Point<ll> and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or ll.



```

/* Usage:
 * auto res = lineInter(s1, e1, s2, e2);
 * if (res.first == 1)
 *     cout << "intersection point at " << res.second
 *     << endl;
 */
#pragma once
#include "Point.h"
template<class P>
pair<int, P> lineInter(P s1, P e1, P s2, P e2) {
    auto d = (e1 - s1).cross(e2 - s2);
    if (d == 0) // if parallel
        return {- (s1.cross(e1, s2) == 0), P(0, 0)};
}

```



```

    auto p = s2.cross(e1, e2), q = s2.cross(e2, s1);
    return {1, (s1 * p + e1 * q) / d};
}

```

3.1.4 Linear Transformation

Apply the linear transformation (translation, rotation and scaling) which takes line p_0p_1 to line q_0q_1 to point r .

```
#include "Point.h"
```

```

typedef Point<double> P;
P linearTransformation(const P& p0, const P& p1, const
    P& q0, const P& q1, const P& r) {
    P dp = p1-p0, dq = q1-q0, num(dp.cross(dq),
        dp.dot(dq));
    return q0 + P((r-p0).cross(num),
        (r-p0).dot(num))/dp.dist2();
}

```

3.1.5 On Segment

```

/* Description: Returns true iff p lies on the line
    segment from s to e.
    * Use \texttt{segDist(s,e,p)<=epsilon} instead when
    using Point<double>.
    */
#include "Point.h"
template<class P> bool onSegment(P s, P e, P p) {
    return p.cross(s, e) == 0 && (s - p).dot(e - p) <= 0;
}

```

3.1.6 Point Sort

```

// sort the points in counterclockwise order that
    starts from the half line x0,y=0.
using namespace std;
typedef long long ll;
typedef pair<ll, ll> point;
#define x first
#define y second
int main() {
    int n; cin >> n;
    vector<point> p(n);
    for (auto &it : p) scanf("%lld %lld", &it.x, &it.y);
    sort(p.begin(), p.end(), [] (point a, point b) {
        return atan2l(a.y, a.x) < atan2l(b.y, b.x);
    });
    for (auto it : p) printf("%lld %lld\n", it.x, it.y);
    return 0;
}

```

3.1.7 Point

```

// Class to handle points in the plane. T can be e.g.
    double or long long. (Avoid int.)
template <class T> int sgn(T x) { return (x > 0) - (x
    < 0); }
template<class T>
struct Point {
    typedef Point P;
    T x, y;
    explicit Point(T x=0, T y=0) : x(x), y(y) {}
    bool operator<(P p) const { return tie(x,y) <
        tie(p.x,p.y); }
    bool operator==(P p) const { return
        tie(x,y)==tie(p.x,p.y); }
    P operator+(P p) const { return P(x+p.x, y+p.y); }
    P operator-(P p) const { return P(x-p.x, y-p.y); }
    P operator*(T d) const { return P(x*d, y*d); }
    P operator/(T d) const { return P(x/d, y/d); }
    T dot(P p) const { return x*p.x + y*p.y; }
    T cross(P p) const { return x*p.y - y*p.x; }
}

```

```

T cross(P a, P b) const { return
    (a-*this).cross(b-*this); }
T dist2() const { return x*x + y*y; }
double dist() const { return sqrt((double)dist2()); }
// angle to x-axis in interval [-pi, pi]
double angle() const { return atan2(y, x); }
P unit() const { return *this/dist(); } // makes
    dist()==1
P perp() const { return P(-y, x); } // rotates +90
    degrees
P normal() const { return perp().unit(); }
// returns point rotated 'a' radians ccw around the
    origin
P rotate(double a) const {
    return P(x*cos(a)-y*sin(a),x*sin(a)+y*cos(a)); }
friend ostream& operator<<(ostream& os, P p) {
    return os << "(" << p.x << "," << p.y << ")"; }
};

```

3.1.8 Segment Distance

Returns the shortest distance between point p and the line segment from point s to e .

```

/* Usage:
    * Point<double> a, b(2,2), p(1,1);
    * bool onSegment = segDist(a,b,p) < 1e-10;
    * Status: tested
    */
#pragma once
#include "Point.h"
typedef Point<double> P;
double segDist(P& s, P& e, P& p) {
    if (s==e) return (p-s).dist();
    auto d = (e-s).dist2(), t =
        min(d,max(0,(p-s).dot(e-s)));
    return ((p-s)*d-(e-s)*t).dist()/d;
}

```

3.1.9 Segment Intersection

If a unique intersection point between the line segments going from s_1 to e_1 and from s_2 to e_2 exists then it is returned. If no intersection point exists an empty vector is returned. If infinitely many exist a vector with 2 elements is returned, containing the endpoints of the common line segment. The wrong position will be returned if P is $\text{Point}<\text{ll}>$ and the intersection point does not have integer coordinates. Products of three coordinates are used in intermediate steps so watch out for overflow if using int or long long .

```

/* Usage:
    * vector<P> inter = segInter(s1,e1,s2,e2);
    * if (sz(inter)==1)
    *     cout << "segments intersect at " << inter[0] <<
        endl;
    * Status: stress-tested, tested on kattis:intersection
    */
#include "Point.h"
#include "OnSegment.h"
template<class P> vector<P> segInter(P a, P b, P c, P
    d) {
    auto oa = c.cross(d, a), ob = c.cross(d, b),
        oc = a.cross(b, c), od = a.cross(b, d);
    // Checks if intersection is single non-endpoint
        point.
    if (sgn(oa) * sgn(ob) < 0 && sgn(oc) * sgn(od) < 0)
        return {(a * ob - b * oa) / (ob - oa)};
    set<P> s;
    if (onSegment(c, d, a)) s.insert(a);
    if (onSegment(c, d, b)) s.insert(b);
}

```

```

if (onSegment(a, b, c)) s.insert(c);
if (onSegment(a, b, d)) s.insert(d);
return {all(s)};
}

```

3.1.10 Side Of

Returns where p is as seen from s towards e . $1/0/-1 \Leftrightarrow$ left/on line/right. If the optional argument eps is given 0 is returned if p is within distance eps from the line. P is supposed to be $\text{Point}<\text{T}>$ where T is e.g. double or long long . It uses products in intermediate steps so watch out for overflow if using int or long long .

```

/* Usage:
    * bool left = sideOf(p1,p2,q)==1;
    * Status: tested
    */
#include "Point.h"
template<class P>
int sideOf(P s, P e, P p) { return sgn(s.cross(e, p)); }
template<class P>
int sideOf(const P& s, const P& e, const P& p, double
    eps) {
    auto a = (e-s).cross(p-s);
    double l = (e-s).dist()*eps;
    return (a > l) - (a < -l);
}

```

3.2 3D

3.2.1 3D Convex Hull

```

#define ll long long
#define sz(x) ((int) (x).size())
#define all(x) (x).begin(), (x).end()
#define vi vector<int>
#define pii pair<int, int>
#define rep(i, a, b) for(int i = (a); i < (b); i++)
using namespace std;
template<typename T>
using minpq = priority_queue<T, vector<T>, greater<T>>;
typedef long double ftype;
struct pt3 {
    ftype x, y, z;
    pt3(ftype x = 0, ftype y = 0, ftype z = 0) : x(x),
        y(y), z(z) {}
    pt3 operator-(const pt3 &o) const {
        return pt3(x - o.x, y - o.y, z - o.z);
    }
    pt3 cross(const pt3 &o) const {
        return pt3(y * o.z - z * o.y, z * o.x - x * o.z, x
            * o.y - y * o.x);
    }
    ftype dot(const pt3 &o) const {
        return x * o.x + y * o.y + z * o.z;
    }
};
// A face is represented by the indices of its three
    points a, b, c.
// It also stores an outward-facing normal vector q
struct face {
    int a, b, c;
    pt3 q;
};
// modify this depending on the coordinate sizes in
    your use case
const ftype EPS = 1e-9;
vector<face> hull3(const vector<pt3> &p) {
    int n = sz(p);
    assert(n >= 3);
    vector<face> f;
}

```

```
// Consider an edge (a->b) dead if it is not a CCW
  ~ edge of some current face
// If an edge is alive but not its reverse, this is
  ~ an exposed edge.
// We should add new faces on the exposed edges.
vector<vector<bool>> dead(n, vector<bool>(n, true));
auto add_face = [&](int a, int b, int c) {
    f.push_back({a, b, c, (p[b] - p[a]).cross(p[c] -
    ~ p[a])});
    dead[a][b] = dead[b][c] = dead[c][a] = false;
};
// Initialize the convex hull of the first 3 points
  ~ as a
// triangular disk with two faces of opposite
  ~ orientation
add_face(0, 1, 2);
add_face(0, 2, 1);
rep(i, 3, n) {
    // f2 will be the list of faces invisible to the
    ~ added point p[i]
    vector<face> f2;
    for(face &F : f) {
        if((p[i] - p[F.a]).dot(F.q) > EPS) {
            // this face is visible to the new point, so
            ~ mark its edges as dead
            dead[F.a][F.b] = dead[F.b][F.c] =
            ~ dead[F.c][F.a] = true;
        } else {
            f2.push_back(F);
        }
    }
    // Add a new face for each exposed edge.
    // Only check edges of alive faces for being
    ~ exposed.
    f.clear();
    for(face &F : f2) {
        int arr[3] = {F.a, F.b, F.c};
        rep(j, 0, 3) {
            int a = arr[j], b = arr[(j + 1) % 3];
            if(dead[b][a]) {
                add_face(b, a, i);
            }
        }
        f.insert(f.end(), all(f2));
    }
}
return f;
```

3.2.2 Point3D

Class to handle points in 3D space. T can be e.g. double or long long.

```
template<class T> struct Point3D {
    typedef Point3D P;
    typedef const P& R;
    T x, y, z;
    explicit Point3D(T x=0, T y=0, T z=0) : x(x), y(y),
    ~ z(z) {}
    bool operator<(R p) const {
        return tie(x, y, z) < tie(p.x, p.y, p.z); }
    bool operator==(R p) const {
        return tie(x, y, z) == tie(p.x, p.y, p.z); }
    P operator+(R p) const { return P(x+p.x, y+p.y,
    ~ z+p.z); }
    P operator-(R p) const { return P(x-p.x, y-p.y,
    ~ z-p.z); }
    P operator*(T d) const { return P(x*d, y*d, z*d); }
    P operator/(T d) const { return P(x/d, y/d, z/d); }
    T dot(R p) const { return x*p.x + y*p.y + z*p.z; }
    P cross(R p) const {
        return P(y*p.z - z*p.y, z*p.x - x*p.z, x*p.y -
        ~ y*p.x);
    }
```

```
}
    dist2() const { return x*x + y*y + z*z; }
    double dist() const { return sqrt((double)dist2()); }
    //Azimuthal angle (longitude) to x-axis in interval
    ~ [-pi, pi]
    double phi() const { return atan2(y, x); }
    //Zenith angle (latitude) to the z-axis in interval
    ~ [0, pi]
    double theta() const { return
    ~ atan2(sqrt(x*x+y*y), z); }
    P unit() const { return *this/(T)dist(); } //makes
    ~ dist()==1
    //returns unit vector normal to *this and p
    P normal(P p) const { return cross(p).unit(); }
    //returns point rotated 'angle' radians ccw around
    ~ axis
    P rotate(double angle, P axis) const {
        double s = sin(angle), c = cos(angle); P u =
        ~ axis.unit();
        return u*dot(u)*(1-c) + (*this)*c - cross(u)*s;
    }
};
```

3.2.3 Polyhedron Volume

Description: Magic formula for the volume of a polyhedron. Faces should point outwards.

```
template<class V, class L>
double signedPolyVolume(const V& p, const L& trilst) {
    double v = 0;
    for (auto i : trilst) v +=
    ~ p[i.a].cross(p[i.b]).dot(p[i.c]);
    return v / 6;
}
```

3.2.4 Spherical Distance

Returns the shortest distance on the sphere with radius radius between the points with azimuthal angles (longitude) f_1 (ϕ_1) and f_2 (ϕ_2) from x axis and zenith angles (latitude) t_1 (θ_1) and t_2 (θ_2) from z axis (0 = north pole). All angles measured in radians. The algorithm starts by converting the spherical coordinates to cartesian coordinates so if that is what you have you can use only the two last rows. $dx*$ radius is then the difference between the two points in the x direction and $d*$ radius is the total distance between the points.

```
double sphericalDistance(double f1, double t1,
    double f2, double t2, double radius) {
    double dx = sin(t2)*cos(f2) - sin(t1)*cos(f1);
    double dy = sin(t2)*sin(f2) - sin(t1)*sin(f1);
    double dz = cos(t2) - cos(t1);
    double d = sqrt(dx*dx + dy*dy + dz*dz);
    return radius*2*asin(d/2);
}
```

3.3 Circle

3.3.1 Circle Intersection

Computes the pair of points at which two circles intersect. Returns false in case of no intersection.

```
#include "Point.h"
typedef Point<double> P;
bool circleInter(P a, P b, double r1, double r2, pair<P,
    ~ P>& out) {
    if (a == b) { assert(r1 != r2); return false; }
    P vec = b - a;
    double d2 = vec.dist2(), sum = r1+r2, dif = r1-r2,
    p = (d2 + r1*r1 - r2*r2)/(d2*2), h2 = r1*r1 -
    ~ p*p*d2;
    if (sum*sum < d2 || dif*dif > d2) return false;
    P mid = a + vec*p, per = vec.perp() * sqrt(fmax(0,
    ~ h2) / d2);
```

```
*out = {mid + per, mid - per};
return true;
}
```

3.3.2 Circle Polygon Intersection

Returns the area of the intersection of a circle with a ccw polygon. Time: $O(n)$

```
#include "Point.h"
typedef Point<double> P;
#define arg(p, q) atan2(p.cross(q), p.dot(q))
double circlePoly(P c, double r, vector<P> ps) {
    auto tri = [&](P p, P q) {
        auto r2 = r * r / 2;
        P d = q - p;
        auto a = d.dot(p)/d.dist2(), b =
        ~ (p.dist2()-r*r)/d.dist2();
        auto det = a * a - b;
        if (det <= 0) return arg(p, q) * r2;
        auto s = max(0., -a-sqrt(det)), t = min(1.,
        ~ -a+sqrt(det));
        if (t < 0 || 1 <= s) return arg(p, q) * r2;
        P u = p + d * s, v = p + d * t;
        return arg(p, u) * r2 + u.cross(v)/2 + arg(v, q) *
        ~ r2;
    };
    auto sum = 0.0;
    rep(i, 0, sz(ps))
        sum += tri(ps[i] - c, ps[(i + 1) % sz(ps)] - c);
    return sum;
}
```


3.3.3 Circle Tangents

Finds the external tangents of two circles, or internal if r2 is negated. Can return 0, 1, or 2 tangents – 0 if one circle contains the other (or overlaps it, in the internal case, or if the circles are the same); 1 if the circles are tangent to each other (in which case .first = .second and the tangent line is perpendicular to the line between the centers). .first and .second give the tangency points at circle 1 and 2 respectively. To find the tangents of a circle with a point set r2 to 0.

```
#include "Point.h"
template<class P>
vector<pair<P, P>> tangents(P c1, double r1, P c2,
    ~ double r2) {
    P d = c2 - c1;
    double dr = r1 - r2, d2 = d.dist2(), h2 = d2 - dr *
    ~ dr;
    if (d2 == 0 || h2 < 0) return {};
    vector<pair<P, P>> out;
    for (double sign : {-1, 1}) {
        P v = (d * dr + d.perp() * sqrt(h2) * sign) / d2;
        out.push_back({c1 + v * r1, c2 + v * r2});
    }
    if (h2 == 0) out.pop_back();
    return out;
}
```

3.3.4 CircumCircle

The circumcircle of a triangle is the circle intersecting all three vertices. ccRadius returns the radius of the circle going through points A, B and C and ccCenter returns the center of the same circle.



```
#include "Point.h"
typedef Point<double> P;
double ccRadius(const P& A, const P& B, const P& C) {
    return (B-A).dist()*(C-B).dist()*(A-C).dist()/
    ~ abs((B-A).cross(C-A))/2;
```

```

}
P ccCenter(const P& A, const P& B, const P& C) {
    P b = C-A, c = B-A;
    return A +
        (b*c.dist2()-c*b.dist2()).perp()/b.cross(c)/2;
}

```

3.4 Polygon

3.4.1 Hull Diameter

Returns the two points with max distance on a convex hull (ccw, no duplicate/collinear points).

```

#include "Point.h"
typedef Point<ll> P;
array<P, 2> hullDiameter(vector<P> S) {
    int n = sz(S), j = n < 2 ? 0 : 1;
    pair<ll, array<P, 2>> res({0, {S[0], S[0]}});
    rep(i, 0, j)
        for (; j = (j + 1) % n) {
            res = max(res, {(S[i] - S[j]).dist2(), {S[i],
                S[j]}});
            if ((S[(j + 1) % n] - S[j]).cross(S[i + 1] -
                S[i]) >= 0)
                break;
        }
    return res.second;
}

```

3.4.2 Line Hull Intersection

Line-convex polygon intersection. The polygon must be ccw and have no collinear points. lineHull(line, poly) returns a pair describing the intersection of a line with the polygon:

(-1, -1) if no collision,

(i, -1) if touching the corner i,

(i, i) if along side (i, i + 1),

(i, j) if crossing sides (i, i + 1) and (j, j + 1). In the last case, if a corner i is crossed, this is treated as happening on side (i, i + 1). The points are returned in the same order as the line hits the polygon. extrVertex returns the point of a hull with the max projection onto a line.

Time: $O(\log n)$

```

#include "Point.h"
#define cmp(i, j)
    ~ sgn(dir.perp().cross(poly[(i)%n]-poly[(j)%n]))
#define extr(i) cmp(i + 1, i) >= 0 && cmp(i, i - 1 +
    ~ n) < 0
template <class P> int extrVertex(vector<P>& poly, P
    ~ dir) {
    int n = sz(poly), lo = 0, hi = n;
    if (extr(0)) return 0;
    while (lo + 1 < hi) {
        int m = (lo + hi) / 2;
        if (extr(m)) return m;
        int ls = cmp(lo + 1, lo), ms = cmp(m + 1, m);
        (ls < ms || (ls == ms && ls == cmp(lo, m)) ? hi :
            ~ lo) = m;
    }
    return lo;
}
#define cmpL(i) sgn(a.cross(poly[i], b))
template <class P>
array<int, 2> lineHull(P a, P b, vector<P>& poly) {
    int endA = extrVertex(poly, (a - b).perp());
    int endB = extrVertex(poly, (b - a).perp());
    if (cmpL(endA) < 0 || cmpL(endB) > 0)
        return {-1, -1};
    array<int, 2> res;
    rep(i, 0, 2) {

```

```

    int lo = endB, hi = endA, n = sz(poly);
    while ((lo + 1) % n != hi) {
        int m = ((lo + hi + (lo < hi ? 0 : n)) / 2) % n;
        (cmpL(m) == cmpL(endB) ? lo : hi) = m;
    }
    res[i] = (lo + !cmpL(hi)) % n;
    swap(endA, endB);
}
if (res[0] == res[1]) return {res[0], -1};
if (!cmpL(res[0]) && !cmpL(res[1]))
    switch ((res[0] - res[1] + sz(poly) + 1) %
        ~ sz(poly)) {
        case 0: return {res[0], res[0]};
        case 2: return {res[1], res[1]};
    }
return res;
}

```

3.4.3 Polygon Center

Returns the center of mass for a polygon.

Time: $O(n)$


```

#include "Point.h"
typedef Point<double> P;
P polygonCenter(const vector<P>& v) {
    P res(0, 0); double A = 0;
    for (int i = 0, j = sz(v) - 1; i < sz(v); j = i++) {
        res = res + (v[i] + v[j]) * v[j].cross(v[i]);
        A += v[j].cross(v[i]);
    }
    return res / A / 3;
}

```

3.4.4 Polygon Cut

Returns a vector with the vertices of a polygon with everything to the left of the line going from s to e cut away.



```

/* Usage:
 * vector<P> p = ...;
 * p = polygonCut(p, P(0,0), P(1,0));
 * Status: tested but not extensively
 */
#include "Point.h"
#include "lineIntersection.h"
typedef Point<double> P;
vector<P> polygonCut(const vector<P>& poly, P s, P e) {
    vector<P> res;
    rep(i, 0, sz(poly)) {
        P cur = poly[i], prev = i ? poly[i-1] :
            ~ poly.back();
        bool side = s.cross(e, cur) < 0;
        if (side != (s.cross(e, prev) < 0))
            res.push_back(lineInter(s, e, cur, prev).second);
        if (side)
            res.push_back(cur);
    }
    return res;
}

```

3.5 Closest Pair

Finds the closest pair of points.

Time: $O(n \log n)$

```

#include "Point.h"
typedef Point<ll> P;
pair<P, P> closest(vector<P> v) {
    assert(sz(v) > 1);
    set<P> S;
    sort(all(v), [](P a, P b) { return a.y < b.y; });
    pair<ll, pair<P, P>> ret{LLONG_MAX, {P(), P()}};
    int j = 0;
    for (P p : v) {

```

```

        P d{1 + (ll)sqrt(ret.first), 0};
        while (v[j].y <= p.y - d.x) S.erase(v[j++]);
        auto lo = S.lower_bound(p - d), hi =
            ~ S.upper_bound(p + d);
        for (; lo != hi; ++lo)
            ret = min(ret, {(p - *lo).dist2(), {*lo, p}});
        S.insert(p);
    }
    return ret.second;
}

```

3.6 Convex Hull

```

typedef long long ll;
typedef pair<ll, ll> point;
#define x first
#define y second
inline ll area (point a, point b, point c) {
    return (b.x - a.x) * (c.y - a.y) - (b.y - a.y) *
        ~ (c.x - a.x);
}
vector<point> convexHull (vector<point> p) {
    int n = p.size(), m = 0;
    if (n < 3) return p;
    vector<point> hull(n + n);
    sort(p.begin(), p.end());
    for (int i = 0; i < n; ++i) {
        while (m > 1 and area(hull[m - 2], hull[m - 1],
            ~ p[i]) <= 0) --m;
        hull[m++] = p[i];
    }
    for (int i = n - 2, j = m + 1; i >= 0; --i) {
        while (m >= j and area(hull[m - 2], hull[m - 1],
            ~ p[i]) <= 0) --m;
        hull[m++] = p[i];
    }
    hull.resize(m - 1); return hull;
}

```

3.7 Minimum Enclosing Circle

// Expected runtime: $O(n)$
 // Solves Gym 102299J

```

using namespace std;
typedef long double ld;
typedef pair<ld, ld> point;
#define x first
#define y second
point operator + (const point &a, const point &b) {
    return point(a.x + b.x, a.y + b.y);
}
point operator - (const point &a, const point &b) {
    return point(a.x - b.x, a.y - b.y);
}
point operator * (const point &a, const ld &b) {
    return point(a.x * b, a.y * b);
}
point operator / (const point &a, const ld &b) {
    return point(a.x / b, a.y / b);
}
const ld EPS = 1e-8;
const ld INF = 1e20;
const ld PI = acos(-1);
inline ld dist (point a, point b) {
    return hypotl(a.x - b.x, a.y - b.y);
}
inline ld sqDist (point a, point b) {
    return (a.x - b.x) * (a.x - b.x) + (a.y - b.y) *
        ~ (a.y - b.y);
}

```



```

}
inline ld dot (point a, point b) {
    return a.x * b.x + a.y * b.y;
}
inline ld cross (point a, point b) {
    return a.x * b.y - a.y * b.x;
}
inline ld cross (point a, point b, point c) {
    return cross(b - a, c - a);
}
inline point perp (point a) {
    return point(-a.y, a.x);
}
// circle through 3 points
pair<point, ld> getCircle (point a, point b, point c)
{
    pair<point, ld> ret;
    ld den = (ld) 2 * cross(a, b, c);
    ret.x.x = ((c.y - a.y) * (dot(b, b) - dot(a, a)) -
        (b.y - a.y) * (dot(c, c) - dot(a, a))) / den;
    ret.x.y = ((b.x - a.x) * (dot(c, c) - dot(a, a)) -
        (c.x - a.x) * (dot(b, b) - dot(a, a))) / den;
    ret.y = dist(ret.x, a);
    return ret;
}
pair<point, ld> minCircleAux (vector<point> &s,
    point a, point b, int n) {
    ld lo = -INF, hi = INF;
    for (int i = 0; i < n; ++i) {
        auto si = cross(b - a, s[i] - a);
        if (fabs(si) < EPS) continue;
        point m = getCircle(a, b, s[i]).x;
        auto cr = cross(b - a, m - a);
        si < 0 ? hi = min(hi, cr) : lo = max(lo, cr);
    }
    ld v = 0 < lo ? lo : hi < 0 ? hi : 0;
    point c = (a + b) * 0.5 + perp(b - a) * v /
        sqrtDist(a, b);
    return {c, sqDist(a, c)};
}
pair<point, ld> minCircle (vector<point> &s, point
    a, int n) {
    random_shuffle(s.begin(), s.begin() + n);
    point b = s[0], c = (a + b) * 0.5;
    ld r = sqDist(a, c);
    for (int i = 1; i < n; ++i) {
        if (sqDist(s[i], c) > r * (1 + EPS)) {
            tie(c, r) = n == s.size() ? minCircle(s, s[i],
                i) : minCircleAux(s, a, s[i], i);
        }
    }
    return {c, r};
}
pair<point, ld> minCircle (vector<point> s) {
    assert(!s.empty());
    if (s.size() == 1) return {s[0], 0};
    return minCircle(s, s[0], s.size());
}
int n; vector<point> p;
int main() {
    cin >> n;
    while (n--) {
        double x, y;
        scanf("%lf %lf", &x, &y);
        p.emplace_back(x, y);
    }
    pair<point, ld> circ = minCircle(p);
    printf("%.12f %.12f %.12f\n", (double) circ.x.x,
        (double) circ.x.y, (double) (0.5 * circ.y));
    return 0;
}

```

3.8 Point In Polygon

```

// Test if a point is inside a convex polygon in O(lg
    n) time
// Solves SPOJ INOROUT
typedef long long ll;
typedef pair<ll, ll> point;
#define x first
#define y second
struct segment {
    point P1, P2;
    segment () {}
    segment (point P1, point P2) : P1(P1), P2(P2) {}
};
inline ll ccw (point A, point B, point C) {
    return (B.x - A.x) * (C.y - A.y) - (C.x - A.x) *
        (B.y - A.y);
}
inline bool pointOnSegment (segment S, point P) {
    ll x = P.x, y = P.y, x1 = S.P1.x, y1 = S.P1.y, x2 =
        S.P2.x, y2 = S.P2.y;
    ll a = x - x1, b = y - y1, c = x2 - x1, d = y2 - y1,
        dot = a * c + b * d, len = c * c + d * d;
    if (x1 == x2 and y1 == y2) return x1 == x and y1 ==
        y;
    if (dot < 0 or dot > len) return 0;
    return x1 * len + dot * c == x * len and y1 * len +
        dot * d == y * len;
}
const int M = 17;
const int N = 10010;
struct polygon {
    int n; // n > 1
    point p[N]; // clockwise order
    polygon () {}
    polygon (int _n, point *T) {
        n = _n;
        for (int i = 0; i < n; ++i) p[i] = T[i];
    }
    bool contains (point P, bool strictlyInside) {
        int lo = 1, hi = n - 1;
        while (lo < hi) {
            int mid = lo + hi >> 1;
            if (ccw(p[0], P, p[mid]) > 0) lo = mid + 1;
            else hi = mid;
        }
        if (ccw(p[0], P, p[lo]) > 0) lo = 1;
        if (!strictlyInside and
            pointOnSegment(segment(p[0], p[n - 1]), P))
            return 1;
        if (!strictlyInside and
            pointOnSegment(segment(p[lo], p[lo - 1]), P))
            return 1;
        if (lo == 1 or ccw(p[0], P, p[n - 1]) == 0) return
            0;
        return ccw(p[lo], P, p[lo - 1]) < 0;
    }
};

```

3.9 near_pair

```

struct pt {
    int x, y, id;
};
struct cmp_x {
    bool operator()(const pt &a, const pt &b) const {
        return a.x < b.x || (a.x == b.x && a.y < b.y);
    }
};

```

```

struct cmp_y {
    bool operator()(const pt &a, const pt &b) const {
        return a.y < b.y;
    }
};
int n;
vector<pt> a;
double mindist;
pair<int, int> best_pair;
void upd_ans(const pt &a, const pt &b) {
    double dist = sqrt((a.x - b.x)*(a.x - b.x) + (a.y -
        b.y)*(a.y - b.y));
    if (dist < mindist) {
        mindist = dist;
        best_pair = {a.id, b.id};
    }
}
vector<pt> t;
void rec(int l, int r) {
    if (r - l <= 3) {
        for (int i = l; i < r; ++i) {
            for (int j = i + 1; j < r; ++j) {
                upd_ans(a[i], a[j]);
            }
        }
        sort(a.begin() + l, a.begin() + r, cmp_y());
        return;
    }
    int m = (l + r) >> 1;
    int midx = a[m].x;
    rec(l, m);
    rec(m, r);
    merge(a.begin() + l, a.begin() + m, a.begin() + m,
        a.begin() + r, t.begin(), cmp_y());
    copy(t.begin(), t.begin() + r - l, a.begin() + l);
    int tsz = 0;
    for (int i = l; i < r; ++i) {
        if (abs(a[i].x - midx) < mindist) {
            for (int j = tsz - 1; j >= 0 && a[i].y - t[j].y
                < mindist; --j) {
                upd_ans(a[i], t[j]);
                t[tsz++] = a[i];
            }
        }
    }
}
void solve(int n)
{
    t.resize(n);
    sort(a.begin(), a.end(), cmp_x());
    mindist = 1E20;
    rec(0, n);
}

```

3.10 sweep

```

const double EPS = 1E-9;
struct pt {
    double x, y;
};
struct seg {
    pt p, q;
    int id;
    double get_y(double x) const {
        if (abs(p.x - q.x) < EPS)
            return p.y;
        return p.y + (q.y - p.y) * (x - p.x) / (q.x - p.x);
    }
};
bool intersectld(double l1, double r1, double l2,
    double r2) {

```

```

    if (l1 > r1)
        swap(l1, r1);
    if (l2 > r2)
        swap(l2, r2);
    return max(l1, l2) <= min(r1, r2) + EPS;
}

int vec(const pt& a, const pt& b, const pt& c) {
    double s = (b.x - a.x) * (c.y - a.y) - (b.y - a.y) *
        (c.x - a.x);
    return abs(s) < EPS ? 0 : s > 0 ? +1 : -1;
}

bool intersect(const seg& a, const seg& b)
{
    return intersectld(a.p.x, a.q.x, b.p.x, b.q.x) &&
        intersectld(a.p.y, a.q.y, b.p.y, b.q.y) &&
        vec(a.p, a.q, b.p) * vec(a.p, a.q, b.q) <= 0 &&
        vec(b.p, b.q, a.p) * vec(b.p, b.q, a.q) <= 0;
}

bool operator<(const seg& a, const seg& b)
{
    double x = max(min(a.p.x, a.q.x), min(b.p.x, b.q.x));
    return a.get_y(x) < b.get_y(x) - EPS;
}

struct event {
    double x;
    int tp, id;
    event() {}
    event(double x, int tp, int id) : x(x), tp(tp),
        id(id) {}
    bool operator<(const event& e) const {
        if (abs(x - e.x) > EPS)
            return x < e.x;
        return tp > e.tp;
    }
};

set<seg> s;
vector<set<seg>::iterator> where;
set<seg>::iterator prev(set<seg>::iterator it) {
    return it == s.begin() ? s.end() : --it;
}

set<seg>::iterator next(set<seg>::iterator it) {
    return ++it;
}

pair<int, int> solve(const vector<seg>& a) {
    int n = (int)a.size();
    vector<event> e;
    for (int i = 0; i < n; ++i) {
        e.push_back(event(min(a[i].p.x, a[i].q.x), +1, i));
        e.push_back(event(max(a[i].p.x, a[i].q.x), -1, i));
    }
    sort(e.begin(), e.end());
    s.clear();
    where.resize(a.size());
    for (size_t i = 0; i < e.size(); ++i) {
        int id = e[i].id;
        if (e[i].tp == +1) {
            set<seg>::iterator nxt = s.lower_bound(a[id]),
                prv = prev(nxt);
            if (nxt != s.end() && intersect(*nxt, a[id]))
                return make_pair(nxt->id, id);
            if (prv != s.end() && intersect(*prv, a[id]))
                return make_pair(prv->id, id);
            where[id] = s.insert(nxt, a[id]);
        } else {
            set<seg>::iterator nxt = next(where[id]), prv =
                prev(where[id]);
            if (nxt != s.end() && prv != s.end() &&
                intersect(*nxt, *prv))
                return make_pair(prv->id, nxt->id);
            s.erase(where[id]);
        }
    }
}

```

```

    }
    return make_pair(-1, -1);
}

4 Graph
4.1 2Sat

namespace sat {
    const int MAX = 200010;
    bool vis[MAX];
    vector<int> ed[MAX], rev[MAX];
    int n, m, ptr, dfs_t[MAX], ord[MAX], par[MAX];

    inline int inv(int x) {
        return ((x) <= n ? (x + n) : (x - n));
    }

    void init(int vars) {
        n = vars, m = vars << 1;
        for (int i = 1; i <= m; i++) {
            ed[i].clear();
            rev[i].clear();
        }
    }

    inline void add(int a, int b) {
        ed[a].push_back(b);
        rev[b].push_back(a);
    }

    inline void OR(int a, int b) {
        add(inv(a), b);
        add(inv(b), a);
    }

    inline void AND(int a, int b) {
        add(a, b);
        add(b, a);
    }

    void XOR(int a, int b) {
        add(inv(b), a);
        add(a, inv(b));
        add(inv(a), b);
        add(b, inv(a));
    }

    inline void XNOR(int a, int b) {
        add(a, b);
        add(b, a);
        add(inv(a), inv(b));
        add(inv(b), inv(a));
    }

    inline void force_true(int x) {
        add(inv(x), x);
    }

    inline void topsort(int s) {
        vis[s] = true;
        for (int x : rev[s]) if (!vis[x]) topsort(x);
        dfs_t[s] = ++ptr;
    }

    inline void dfs(int s, int p) {
        par[s] = p;
        vis[s] = true;
        for (int x : ed[s]) if (!vis[x]) dfs(x, p);
    }

    void build() {
        CLR(vis);
        ptr = 0;
        for (int i = m; i >= 1; i--) {
            if (!vis[i]) topsort(i);
            ord[dfs_t[i]] = i;
        }
        CLR(vis);
        for (int i = m; i >= 1; i--) {
            int x = ord[i];
            if (!vis[x]) dfs(x, x);
        }
    }
}

```

```

    }
    bool satisfy(vector<int>& res) {
        build();
        CLR(vis);
        for (int i = 1; i <= m; i++) {
            int x = ord[i];
            if (par[x] == par[inv(x)]) return false;
            if (!vis[par[x]]) {
                vis[par[x]] = true;
                vis[par[inv(x)]] = false;
            }
        }
        res.clear();
        for (int i = 1; i <= n; i++) {
            if (vis[par[i]]) res.push_back(i);
        }
        return true;
    }
}

4.2 Centroid_decomp

vector<int> ed[MAX];
bool isCentroid[MAX];
int sub[MAX], cpar[MAX], clevel[MAX];
int dis[20][MAX];
void calcSubTree(int s, int p) {
    sub[s] = 1;
    for (int x : ed[s]) {
        if (x == p or isCentroid[x]) continue;
        calcSubTree(x, s);
        sub[s] += sub[x];
    }
}

int nn;
int getCentroid(int s, int p) {
    for (int x : ed[s]) {
        if (!isCentroid[x] && x != p && sub[x] > (nn/2)) return
            getCentroid(x, s);
    }
    return s;
}

void setDis(int s, int from, int p, int lev) {
    dis[from][s] = lev;
    for (int x : ed[s]) {
        if (x == p or isCentroid[x]) continue;
        setDis(x, from, s, lev+1);
    }
}

void decompose(int s, int p, int lev) {
    calcSubTree(s, p);
    nn = sub[s];
    int c = getCentroid(s, p);
    setDis(c, lev, p, 0);
    isCentroid[c] = true;
    cpar[c] = p;
    clevel[c] = lev;
    for (int x : ed[c]) {
        if (!isCentroid[x]) decompose(x, c, lev+1);
    }
}

int ans[MAX];
inline void update(int v) {
    int u = v;
    while (u != -1) {
        ans[u] = min(ans[u], dis[clevel[u]][v]);
        u = cpar[u];
    }
}

```

```

inline int query(int v) {
    int ret = INF;
    int u = v;
    while(u != -1) {
        ret = min(ret, dis[clevel[u]][v]+ans[u]);
        u = cpar[u];
    }
    return ret;
}

int main() {
    decompose(1, -1, 0);
    for(int i=1; i<=n; i++) ans[i] = INF;
    update(v);
    query(v);
    return 0;
}

```

4.3 articulation_point

```

using namespace std;
const int N = 1e5 + 10;
vector<int> g[N];
int vis[N], low[N], cut[N], now = 0, n, m;
void dfs(int u, int p) {
    low[u] = vis[u] = ++now; int ch = 0;
    for(int v : g[u]) {
        if(v ^ p) {
            if(vis[v]) low[u] = min(low[u], vis[v]);
            else {
                ch++; dfs(v, u);
                low[u] = min(low[u], low[v]);
                if(p + 1 && low[v] >= vis[u]) cut[u] = 1;
                if(low[v] > vis[u]) {
                    printf("Bridge %d -- %d\n", u, v);
                }
            }
        }
        if(p == -1 && ch > 1) cut[u] = 1;
    }
}

void ArticulationPointAndBridge() {
    now = 0;
    for(int i = 0; i < n; i++) {
        if(!vis[i]) dfs(i, -1);
    }
}

```

4.4 bcc

```

// clear ed[] every test case
// tot -> total number of components
// bcc[i] contains the nodes of the i'th component
// any self loop or multiple edge?
const int MAX = ?;
vector<int> ed[MAX];
bool cut[MAX];
int tot, Time, low[MAX], st[MAX];
vector<int> bcc[MAX];
stack<int> S;
void popBCC(int s, int x) {
    cut[s] = 1;
    bcc[++tot].pb(s);
    while(bcc[tot].back() ^ x) {
        bcc[tot].pb(S.top());
        S.pop();
    }
}

void dfs(int s, int p = -1) {
    S.push(s);
    int ch = 0;
    st[s] = low[s] = ++Time;
    for(int x : ed[s]) {
        if(!st[x]) {
            ch++;

```

```

        dfs(x, s);
        low[s] = min(low[s], low[x]);
        if(p != -1 and low[x] >= st[s]) popBCC(s, x);
        else if(p == -1) if(ch > 1) popBCC(s, x);
    }
    else if(p != x) low[s] = min(low[s], st[x]);
}
if(p == -1 && ch > 1) cut[s] = 1;
}

void processBCC(int n) {
    for(int i=1; i<=n; i++) bcc[i].clear();
    CLR(st); CLR(cut);
    Time = tot = 0;
    for(int i=1; i<=n; i++) {
        if(!st[i]) {
            dfs(i, -1);
            if(!S.empty()) ++tot;
            while(!S.empty()) {
                bcc[tot].push_back(S.top());
                S.pop();
            }
        }
    }
}

```

4.5 bridge_tree

```

const int MAXN = ?;
const int MAXE = ?;
struct edges {
    int u, v;
} ara[MAXN];
vector<int> ed[MAXN];
vector<int> isBridge[MAXN];
vector<int> brTree[MAXN];
bool vis[MAXN];
int st[MAXN], low[MAXN], Time = 0;
int cnum;
int comp[MAXN];
void findBridge(int s, int par) {
    int i, x, child = 0, j;
    vis[s] = 1;
    Time++;
    st[s] = low[s] = Time;
    for(i=0; i<ed[s].size(); i++) {
        x = ed[s][i];
        if(!vis[x]) {
            child++;
            findBridge(x, s);
            low[s] = min(low[s], low[x]);
            if(low[x] > st[s]) {
                isBridge[s][i] = 1;
                j = lower_bound(ed[x].begin(), ed[x].end(), s) - ed[x].begin();
                isBridge[x][j] = 1;
            }
        }
        else if(par != x)
            low[s] = min(low[s], st[x]);
    }
}

void dfs(int s) {
    int i, x;
    vis[s] = 1;
    comp[s] = cnum;
    for(i=0; i<ed[s].size(); i++) {
        if(!isBridge[s][i]) {
            x = ed[s][i];
            if(!vis[x]) dfs(x);
        }
    }
}

```

```

void processBridge(int n, int m) {
    CLR(vis);
    Time = 0;
    for(int i=1; i<=n; i++) if(!vis[i]) findBridge(i, -1);
    cnum = 0;
    CLR(vis);
    for(int i=1; i<=n; i++) {
        if(!vis[i]) {
            cnum++;
            dfs(i);
        }
    }
    n = cnum;
    for(int i=1; i<=m; i++) {
        if(comp[ara[i].u] != comp[ara[i].v]) {
            brTree[comp[ara[i].u]].pb(comp[ara[i].v]);
            brTree[comp[ara[i].v]].pb(comp[ara[i].u]);
        }
    }
}

int main() {
    int n, m, u, v;
    scanf("%d %d", &n, &m);
    for(int i=1; i<=m; i++) {
        sii(u, v);
        ed[u].pb(v);
        ed[v].pb(u);
        isBridge[u].pb(0);
        isBridge[v].pb(0);
        ara[i].u = u;
        ara[i].v = v;
    }
    for(int i=1; i<=n; i++) sort(all(ed[i]));
    processBridge(n, m);
    return 0;
}

```

4.6 dinic

```

namespace dinic {
    using T = int;
    const T INF = 0x3f3f3f3f;
    const int MAXN = 5010;
    int n, src, snk, work[MAXN];
    T dist[MAXN];
    struct Edge {
        int to, rev_pos;
        T c, f;
    };
    vector<Edge> ed[MAXN];
    void init(int n, int src, int snk) {
        n = n, src = src, snk = snk;
        for(int i=1; i<=n; i++) ed[i].clear();
    }
    inline void addEdge(int u, int v, T c, T rc = 0) {
        Edge a = {v, (int)ed[v].size(), c, 0};
        Edge b = {u, (int)ed[u].size(), rc, 0};
        ed[u].push_back(a);
        ed[v].push_back(b);
    }
    bool dinic bfs() {
        SET(dist);
        dist[src] = 0;
        queue<int> q;
        q.push(src);
        while(!q.empty()) {
            int u = q.front(); q.pop();
            for(Edge &e : ed[u]) {
                if(dist[e.to] == -1 and e.f < e.c) {
                    dist[e.to] = dist[u] + 1;

```

```

        q.push(e.to);
    }
}
return (dist[snk]>=0);
}
T dinic_dfs(int u, T fl){
    if (u == snk) return fl;
    for (; work[u] < (int)ed[u].size(); work[u]++) {
        Edge &e = ed[u][work[u]];
        if (e.c <= e.f) continue;
        int v = e.to;
        if (dist[v] == dist[u] + 1){
            T df = dinic_dfs(v, min(fl, e.c - e.f));
            if (df > 0){
                e.f += df;
                ed[v][e.rev_pos].f -= df;
                return df;
            }
        }
    }
    return 0;
}
T solve() {
    T ret = 0;
    while (dinic_bfs()) {
        CLR(work);
        while (T delta = dinic_dfs(src, INF)) ret += delta;
    }
    return ret;
}
}
int main() {
    int n, m, u, v, c;
    cin >> n >> m;
    dinic::init(n, 1, n);
    while(m--){
        cin >> u >> v >> c;
        dinic::addEdge(u, v, c, c);
    }
    cout << dinic::solve() << '\n';
    return 0;
}

```

4.7 dsu on tree

```

void calcSubSize(int s,int p) {
    sub[s] = 1;
    for(int x : G[s]) {
        if(x==p) continue;
        calcSubSize(x,s);
        sub[s] += sub[x];
    }
}
void add(int s,int p,int v,int bigchild = -1) {
    freq[color[s]] += v;
    for(int x : G[s]) {
        if(x==p || x==bigchild) continue;
        add(x,s,v);
    }
}
void dfs(int s,int p,bool keep) {
    int bigChild = -1;
    for(int x : G[s]) {
        if(x==p) continue;
        if(bigChild==-1 || sub[bigChild] < sub[x])
            bigChild = x;
    }
    for(int x : G[s]) {
        if(x==p || x==bigChild) continue;
        dfs(x,s,0);
    }
    if(bigChild!=-1) dfs(bigChild,s,1);
}

```

```

add(s,p,1,bigChild);
if(keep==0)
    add(s,p,-1);
}

```

4.8 euler_path

```

vector<int> ed[MAX+5], sltn;
int inDeg[MAX+5], outDeg[MAX+5];
bool vis[MAX+5];
void dfs(int nd) {
    vis[nd] = true;
    while(ed[nd].size()) {
        int v = ed[nd].back();
        ed[nd].pop_back();
        dfs(v);
    }
    sltn.pb(nd);
}
int findEuler(int n) {
    int src, snk, ret = 1;
    bool found_src = false, found_snk = false;
    CLR(inDeg); CLR(outDeg);
    for(int u = 1; u <= n; u++) {
        for(int i = 0; i < ed[u].size(); i++) {
            int v = ed[u][i];
            outDeg[u]++;
            inDeg[v]++;
        }
    }
    int diff;
    for(int i = 1; i <= n; i++) {
        diff = outDeg[i] - inDeg[i];
        if(diff == 1) {
            if(found_src) return 0;
            found_src = true;
            src = i;
        }
        else if (diff == -1) {
            if(found_snk) return 0;
            found_snk = true;
            snk = i;
        }
        else if(diff != 0) return 0;
    }
    if(!found_src) {
        ret = 2;
        for(int i = 1; i <= n; i++) {
            if( outDeg[i] ) {
                found_src = true;
                src = i;
                break;
            }
        }
    }
    if(!found_src) return ret;
    CLR(vis);
    sltn.clear();
    dfs(src);
    for(int i = 1; i <= n; i++) {
        if(outDeg[i] && !vis[i]) return 0;
    }
    for(int i = (int)sltn.size()-1; i >= 0; i--)
        printf("%d ", sltn[i]);
    puts("");
    return ret;
}

```

4.9 hld

```

const int N = 3e4 + 5;
vector<int> G[N];
int sz[N], H[N], P[N];

```

```

void dfs(int cur, int h)
{
    sz[cur] = 1;
    H[cur] = h;
    for(int& to : G[cur]) {
        G[to].erase(find(G[to].begin(), G[to].end(),
            cur));
        P[to] = cur;
        dfs(to, h + 1);
        sz[cur] += sz[to];
        if(sz[to] > sz[G[cur][0]]) swap(G[cur][0], to);
    }
}
int base[N], pos[N], head[N];
int ptr = 0;
void hld(int cur)
{
    pos[cur] = ++ptr;
    base[ptr] = cur;
    for(int to : G[cur]) {
        head[to] = (to == G[cur][0] ? head[cur] : to);
        hld(to);
    }
}
segtree ST;
int query(int u, int v)
{
    int ret = 0;
    while(head[u] != head[v]) {
        if(H[head[u]] > H[head[v]]) swap(u, v);
        ret += ST.query(pos[head[v]], pos[v]);
        v = P[head[v]];
    }
    if(H[u] > H[v]) swap(u, v);
    ret += ST.query(pos[u], pos[v]);
    return ret;
}
void update(int u, int val) {
    ST.update(pos[u], val);
}
void build(int n, int root)
{
    ptr = 0;
    dfs(root, 0);
    head[root] = root;
    hld(root);
    ST = segtree(n);
}
/*
 * clear graph
 * call build
 * Prob : sum of values from u to v
 */

```

4.10 hopcroft_karp

```

struct HopcroftKarp {
    const int N, M;
    std::vector<std::vector<int>> adj_left;
    std::vector<int> matchL, matchR;
    HopcroftKarp(int N, int M, const
        std::vector<std::pair<int, int>>& edge)
        : N(N), M(M), matchL(N, -1), matchR(M, -1),
          adj_left(N) {
        for (auto [l, r] : edge)
            adj_left[l].push_back(r);
    }
    int maxmatching() {
        int sz = 0;
        for (bool updated = true; updated;) {

```



```

updated = false;
static std::vector<int> root(N), prev(N), qq(N);
static int qi, qj;
// std::queue<int> q;
qi = qj = 0;
std::fill(root.begin(), root.end(), -1);
std::fill(prev.begin(), prev.end(), -1);
for (int i = 0; i < N; i++)
    if (matchL[i] == -1)
        qq[qj++] = i, root[i] = i, prev[i] = i;
// q.push(i), root[i] = i;
while (qi < qj) {
    int u = qq[qi++];
    // int u = q.front(); q.pop();
    if (matchL[root[u]] != -1) continue;
    for (int v : adj_left[u]) {
        if (matchR[v] == -1) {
            while (v != -1)
                matchR[v] = u, std::swap(matchL[u], v),
                u = prev[u];
            updated = true, sz++;
            break;
        }
        if (prev[matchR[v]] == -1)
            v = matchR[v], prev[v] = u, root[v] =
            root[u], qq[qj++] = v;
        // v = matchR[v], prev[v] = u, root[v] =
        root[u], q.push(v);
    }
}
return sz;
};

```

4.11 hungarian

```

// Given NN matrix A[i][j]. Calculate a permutation
// p[i] that minimize A[i][p[i]].
template <typename T>
pair <T, vector <int>> Hungarian (int n, int m, T
    c[N][N]) {
    vector <T> v(m), dist(m);
    vector <int> L(n, -1), R(m, -1);
    vector <int> index(m), prev(m);
    auto residue = [&] (int i, int j) {return c[i][j] -
        v[j];};
    iota(index.begin(), index.end(), 0);
    for (int f = 0; f < n; ++f) {
        for (int j = 0; j < m; ++j) {
            dist[j] = residue(f, j), prev[j] = f;
        }
        int w, int i, j, l, s = 0, t = 0;
        while (true) {
            if (s == t) {
                l = s, w = dist[index[t++]];
                for (int k = t; k < m; ++k) {
                    j = index[k]; T h = dist[j];
                    if (h <= w) {
                        if (h < w) t = s, w = h;
                        index[k] = index[t], index[t++] = j;
                    }
                }
                for (int k = s; k < t; ++k) {
                    j = index[k];
                    if (R[j] < 0) goto augment;
                }
            }
            int q = index[s++], i = R[q];
            for (int k = t; k < m; ++k) {
                j = index[k];
                T h = residue(i, j) - residue(i, q) + w;

```

```

            if (h < dist[j]) {
                dist[j] = h, prev[j] = i;
                if (h == w) {
                    if (R[j] < 0) goto augment;
                    index[k] = index[t], index[t++] = j;
                }
            }
        }
        augment:
        for (int k = 0; k < l; ++k) v[index[k]] +=
            dist[index[k]] - w;
        do {
            R[j] = i = prev[j], swap(j, L[i]);
        } while (i ^ f);
        ret = 0;
        for (int i = 0; i < n; ++i) ret += c[i][L[i]];
        return {ret, L};
    }
}

```

4.12 kuhn

```

namespace bpm{
    const int L = 105;
    const int R = 105;
    vector <int> G[L];
    int matchR[R], matchL[L], vis[L], it;
    void init(int n) {
        SET(matchL), SET(matchR), CLR(vis);
        it = 1;
        for (int i = 1; i <= n; i++) G[i].clear();
    }
    inline void addEdge(int u, int v) { G[u].pb(v); }
    bool dfs(int s) {
        vis[s] = it;
        for (auto x : G[s]) {
            if (matchR[x] == -1 or (vis[matchR[x]] != it and
                dfs(matchR[x]))) {
                matchL[s] = x; matchR[x] = s;
                return true;
            }
        }
        return false;
    }
    int solve() {
        int cnt = 0;
        for (int i = 1; i <= n; i++) {
            if (dfs(i)) cnt++, it++;
        }
        return cnt;
    }
}

```

4.13 lca

```

// Don't forget to clear ed after test case ends(vt,
// cost are cleared inside)
using namespace std;
const int MAX = 100010;
int LG;
int dep[MAX], par[MAX][21];
vector <int> ed[MAX];
void dfs(int s, int p, int d) {
    dep[s] = d, par[s][0] = p;
    for (int x : ed[s]) {
        if (x == p) continue;
        dfs(x, s, d+1);
    }
}
void preprocess(int root, int n) {
    LG = lg(n);
    memset(par, -1, sizeof(par));
}

```

```

dfs(root, -1, 0);
for (int j = 1; j <= LG; j++) {
    for (int i = 1; i <= n; i++) {
        if (par[i][j-1] != -1) par[i][j] =
            par[par[i][j-1]][j-1];
    }
}
int getLCA(int u, int v) {
    if (dep[u] < dep[v]) swap(u, v);
    for (int i = LG; i >= 0; i--) {
        if (dep[u] - (1<<i) >= dep[v]) u = par[u][i];
    }
    if (u == v) return u;
    for (int i = LG; i >= 0; i--) {
        if (par[u][i] != -1 and par[u][i] - par[v][i]) {
            u = par[u][i], v = par[v][i];
        }
    }
    return par[u][0];
}

```

4.14 manhattan_MST

```

using namespace std;
using ll = long long;
struct UnionFind {
    vector <int> UF;
    int cnt;
    UnionFind(int N) : UF(N, -1), cnt(N) {}
    int find(int v) { return UF[v] < 0 ? v : UF[v] =
        find(UF[v]); }
    bool join(int v, int w) {
        if ((v = find(v)) == (w = find(w))) return
            false;
        if (UF[v] > UF[w]) swap(v, w);
        UF[v] += UF[w];
        UF[w] = v;
        cnt--;
        return true;
    }
    bool connected(int v, int w) {
        return find(v) == find(w);
    }
    int getSize(int v) { return -UF[find(v)]; }
};
template <class T>
struct KruskalMST {
    using Edge = tuple<int, int, T>;
    T mstWeight;
    vector <Edge> mstEdges;
    UnionFind uf;
    KruskalMST(int V, vector <Edge> edges) :
        mstWeight(), uf(V) {
        sort(edges.begin(), edges.end(), [&] (const
            Edge &a, const Edge &b) {
                return get<2>(a) < get<2>(b);
            });
        for (auto &e : edges) {
            if (int(mstEdges.size()) >= V - 1) break;
            if (uf.join(get<0>(e), get<1>(e))) {
                mstEdges.push_back(e);
                mstWeight += get<2>(e);
            }
        }
    }
};
template <class T>
struct ManhattanMST : public KruskalMST<T> {

```

```

using Edge = typename KruskalMST<T>::Edge;
static vector<Edge>
generateCandidates(vector<pair<T, T>>, P) {
    vector<int> id(P.size());
    iota(id.begin(), id.end(), 0);
    vector<Edge> ret;
    ret.reserve(P.size() * 4);
    for (int h = 0; h < 4; h++) {
        sort(id.begin(), id.end(), [&](int i, int
            j) {
                return P[i].first - P[j].first <
                    P[j].second - P[i].second;
            });
        map<T, int> M;
        for (int i : id) {
            auto it = M.lower_bound(-P[i].second);
            for (; it != M.end(); it =
                M.erase(it)) {
                    int j = it->second;
                    T dx = P[i].first - P[j].first, dy
                        = P[i].second - P[j].second;
                    if (dy > dx) break;
                    ret.emplace_back(i, j, dx + dy);
                }
            M[-P[i].second] = i;
        }
        for (auto &p : P) {
            if (h % 2)
                p.first = -p.first;
            else
                swap(p.first, p.second);
        }
    }
    return ret;
}
ManhattanMST(const vector<pair<T, T>> &P)
: KruskalMST<T>(P.size(),
    generateCandidates(P)) {}
};
int main() {
    int N;
    cin >> N;
    vector<pair<ll, ll>> P(N);
    for (auto &p : P) cin >> p.first >> p.second;
    ManhattanMST mst(P);
    cout << mst.mstWeight << '\n';
    for (auto &&[v, w, weight] : mst.mstEdges) cout <<
        v << " ", w << " " << w << '\n'; return 0;
}

```

4.15 mcmf

```

namespace mcmf {
using T = int;
const T INF = ?; // 0x3f3f3f3f or
    0x3f3f3f3f3f3f3f3f
const int MAX = ?; // maximum number of nodes
int n, src, snk;
T dis[MAX], mCap[MAX];
int par[MAX], pos[MAX];
bool vis[MAX];
struct Edge {
    int to, rev_pos;
    T cap, cost, flow;
};
vector<Edge> ed[MAX];
void init(int n, int src, int snk) {
    n = n, src = src, snk = snk;
    for (int i = 1; i <= n; i++) ed[i].clear();
}
void addEdge(int u, int v, T cap, T cost) {

```

```

Edge a = {v, (int)ed[v].size(), cap, cost, 0};
Edge b = {u, (int)ed[u].size(), 0, -cost, 0};
ed[u].pb(a);
ed[v].pb(b);
}
inline bool SPFA() {
    CLR(vis);
    for (int i = 1; i <= n; i++) mCap[i] = dis[i] = INF;
    queue<int> q;
    dis[src] = 0;
    vis[src] = true;
    q.push(src);
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        vis[u] = false;
        for (int i = 0; i < (int)ed[u].size(); i++) {
            Edge &e = ed[u][i];
            int v = e.to;
            if (e.cap > e.flow && dis[v] > dis[u] + e.cost) {
                dis[v] = dis[u] + e.cost;
                par[v] = u;
                pos[v] = i;
                mCap[v] = min(mCap[u], e.cap - e.flow);
                if (!vis[v]) {
                    vis[v] = true;
                    q.push(v);
                }
            }
        }
    }
    return (dis[snk] != INF);
}
inline pair<T, T> solve() {
    T F = 0, C = 0, f;
    int u, v;
    while (SPFA()) {
        u = snk;
        f = mCap[u];
        F += f;
        while (u != src) {
            v = par[u];
            ed[v][pos[u]].flow += f; // edge of v->u
            // increases
            ed[u][ed[v][pos[u]].rev_pos].flow -= f;
            u = v;
        }
        C += dis[snk] * f;
    }
    return make_pair(F, C);
}
}

```

4.16 tree hash all root

```

/*Description : Find hashes of a tree when rooted at
    each possible
    node(unrooted tree isomorphism test).Time : O(n)*
const int sz = 2e5 + 5, mod = 1e9 + 7;
ll hval[sz], h[sz], dp[sz], rans[sz];
void dfs(vector<vector<int>> &g, int u = 0, int p =
    -1, int val = 0, int up = 0) {
    vector<int> cv, cht; // current child values &
        heights
    if (u > 0) {
        cv.push_back(val);
        cht.push_back(up);
    }
    for (int v : g[u])
        if (v - p) {
            cv.push_back(dp[v]);
            cht.push_back(1 + h[v]);
        }
}

```

```

sort(cht.begin(), cht.end(), greater<int>());
if (cv.size() > 1) {
    ll ret[] = {1, 1}; // for biggest &
        2nd-biggest heights
    for (int i = 0; i < 2; i++)
        for (int value : cv)
            ret[i] = ret[i] * (hval[cht[i]] +
                value) % mod;
    rans[u] = ret[0]; // biggest is hash for this
    // root
    for (int v : g[u])
        if (v - p) {
            int id = 1;
            if (cht[0] - 1 - h[v]) id = 0; // v
                is not on the biggest height path
            val = ret[id] * invmod((hval[cht[id]]
                + dp[v]) % mod) % mod;
            // division of v subtree hash value */
            dfs(g, v, u, val, cht[id] + 1);
        }
    } else if (cv.size() > 0) { // Leaf node u OR vertex
        // 1 has only one child
        if (!up)
            val = 1;
        else
            val = (val + hval[up]) % mod;
        rans[u] = val;
        for (int v : g[u])
            if (v - p) dfs(g, v, u, val, up + 1);
    }
}
ll get(vector<vector<int>> &g, int u = 0, int p = -1) {
    h[u] = 0;
    vector<ll> childs;
    for (int v : g[u])
        if (v - p) {
            childs.push_back(get(g, v, u));
            h[u] = max(h[u], 1 + h[v]);
        }
    ll ret = 1;
    for (int value : childs) ret = ret * (hval[h[u]] +
        value) % mod;
    return dp[u] = ret;
}
int main() { // can remove the g as param, can change
    to 1-index, multi-test works, no further change
    get(g);
    dfs(g);
    tree[k] = rans[0] = dp[0];
    // rans[i] = tree hash with i as root
}

```

5 Math

5.1 FWHT

```

const int N = 1 << 20;
// apply modulo if necessary
void fwht_xor(int *a, int n, int dir = 0) {
    for (int h = 1; h < n; h <= 1) {
        for (int i = 0; i < n; i += h <= 1) {
            for (int j = i; j < i + h; j++) {
                int x = a[j], y = a[j + h];
                a[j] = x + y, a[j + h] = x - y;
                if (dir) a[j] >= 1, a[j + h] >= 1;
            }
        }
    }
}
void fwht_or(int *a, int n, int dir = 0) {
    for (int h = 1; h < n; h <= 1) {
        for (int i = 0; i < n; i += h <= 1) {

```

```

    for (int j = i; j < i + h; ++j) {
        int x = a[j], y = a[j + h];
        a[j] = x, a[j + h] = dir ? y - x : x + y;
    }
}

void fwht and(int *a, int n, int dir = 0) {
    for (int h = 1; h < n; h <= 1) {
        for (int i = 0; i < n; i += h <= 1) {
            for (int j = i; j < i + h; ++j) {
                int x = a[j], y = a[j + h];
                a[j] = dir ? x - y : x + y, a[j + h] = y;
            }
        }
    }
}

```

5.2 FloorSum

```

// 0(log a) sum^n floor(ax + b / c) = f
long long FloorSumAP(long long a, long long b, long long c, long long n) {
    if (!a) return (b / c) * (n + 1);
    if (a >= c or b >= c) return ((n * (n + 1)) / 2) * (a / c) + (n + 1) * (b / c) + FloorSumAP(a % c, b % c, c, n);
    long long m = (a * n + b) / c;
    return m * n - FloorSumAP(c, c - b - 1, a, m - 1);
}

// 0(log a) sum^n x * floor(ax + b / c) = g, sum^n floor(ax + b / c)^2 = h
struct dat {
    long long f, g, h;
    dat(long long f = 0, long long g = 0, long long h = 0) : f(f), g(g), h(h) {};
};

long long mul(long long a, long long b) {
    return (a * b) % MOD;
}

dat query(long long a, long long b, long long c, long long n) {
    if (!a) return {mul(n + 1, b / c), mul(mul(mul(b / c, n), n + 1), inv2), mul(mul(n + 1, b / c), b / c)};
    long long f, g, h;
    dat nxt;
    if (a >= c or b >= c) {
        nxt = query(a % c, b % c, c, n);
        f = (nxt.f + mul(mul(mul(n, n + 1), inv2), a / c) + mul(n + 1, b / c)) % MOD;
        g = (nxt.g + mul(a / c, mul(mul(n, n + 1), mul(2 * n + 1, inv6))) + mul(mul(b / c, mul(n, n + 1)), inv2)) % MOD;
        h = (nxt.h + 2 * mul(b / c, nxt.f) + 2 * mul(a / c, nxt.g) + mul(mul(a / c, a / c), mul(mul(n, n + 1), mul(2 * n + 1, inv6))) + mul(mul(b / c, b / c), n + 1) + mul(mul(a / c, b / c), mul(n, n + 1))) % MOD;
        return {f, g, h};
    }
    long long m = (a * n + b) / c;
    nxt = query(c, c - b - 1, a, m - 1);
    f = (mul(m, n) - nxt.f) % MOD;
    g = mul(mul(m, mul(n, n + 1)) - nxt.h - nxt.f, inv2);
    h = (mul(n, mul(m, m + 1)) - 2 * nxt.g - 2 * nxt.f - f) % MOD;
    return {f, g, h};
}

```

5.3 NOD

```

N = input();
primes = array containing primes till 10^6
ans = 1
for all p in primes :
    if p * p > N:
        break
    count = 1
    while N divisible by p:
        N = N / p
        count = count + 1
    ans = ans * count
if N is prime:
    ans = ans * 2
else if N is square of a prime:
    ans = ans * 3
else if N != 1:
    ans = ans * 4

```

5.4 Pollard Rho

```

#include <bits/stdc++.h>
using namespace std;
typedef long long ll;
typedef unsigned long long ull;
namespace Rho {
    ull mul(ull a, ull b, ull mod) {
        ll ret = a * b - mod * (ull) (1.L / mod * a * b);
        return ret + mod * (ret < 0) - mod * (ret >= (ll) mod);
    }
    ull bigMod(ull a, ull e, ull mod) {
        ull ret = 1;
        while (e) {
            if (e & 1) ret = mul(ret, a, mod);
            a = mul(a, a, mod); e >= 1;
        }
        return ret;
    }
    bool isPrime(ull n) {
        if (n < 2 or n % 6 % 4 != 1) return (n | 1) == 3;
        ull a[] = {2, 325, 9375, 28178, 450775, 9780504, 1795265022};
        ull s = builtin_ctzll(n - 1), d = n >> s;
        for (ull x : a) {
            ull p = bigMod(x % n, d, n), i = s;
            while (p != 1 and p != n - 1 and x % n and i--)
                p = mul(p, p, n);
            if (p != n - 1 and i != s) return 0;
        }
        return 1;
    }
    ull pollard(ull n) {
        auto f = [&](ull x) {return mul(x, x, n) + 1;};
        ull x = 0, y = 0, t = 0, prod = 2, i = 1, q;
        while (t++ % 40 or __gcd(prod, n) == 1) {
            if (x == y) x = ++i, y = f(x);
            if ((q = mul(prod, max(x, y) - min(x, y), n)))
                prod = q;
            x = f(x), y = f(f(y));
        }
        return __gcd(prod, n);
    }
}
vector<ull> factor(ull n) {
    if (n == 1) return {};
    if (isPrime(n)) return {n};
    ull x = pollard(n);
    auto l = factor(x), r = factor(n / x);
    l.insert(l.end(), r.begin(), r.end());
    return l;
}

```

```

int t; ll n;
int main() {
    cin >> t;
    while (t--) {
        scanf("%lld", &n);
        vector<ull> facs = Rho::factor(n);
        sort(facs.begin(), facs.end());
        printf("%d", (int) facs.size());
        for (auto it : facs) printf(" %llu", it);
        puts("");
    }
    return 0;
}

```

5.5 catalan

```

//Recursive
const int MOD = ....
const int MAX = ....
int catalan[MAX];
void init() {
    catalan[0] = catalan[1] = 1;
    for (int i = 2; i <= n; i++) {
        catalan[i] = 0;
        for (int j = 0; j < i; j++) {
            catalan[i] += (catalan[j] * catalan[i - j - 1]) % MOD;
            if (catalan[i] >= MOD) {
                catalan[i] -= MOD;
            }
        }
    }
}

//Analytical formula:
ans = ncr(2*n, n) - ncr(2*n, n - 1) = ncr(2*n, n) / (n + 1)

```

5.6 crt

```

//r[i][j] = inverse of p[i] modulo p[j]
//ans = x[0] + x[1] * p[0] + x[2] * (p[0] * p[1]) + ... + x[k-1] * (p[0] * ... * p[k-2])
//ans %= ((p[0] * p[1] * p[2] * ... * p[k-1]))
for (int i = 0; i < k; ++i) {
    x[i] = a[i];
    for (int j = 0; j < i; ++j) {
        x[i] = r[j][i] * (x[i] - x[j]);
        x[i] = x[i] % p[i];
        if (x[i] < 0)
            x[i] += p[i];
    }
}
ll mul = p[0], res = x[0], tot = 1;
F(i, 0, k) tot *= p[i];
F(i, 1, k) {
    res += x[i] * mul;
    res %= tot;
    mul *= p[i];
}
res %= mul;
return res;

```

5.7 derangement

```

int derangement(int n) {
    if (!n) return n;
    if (n <= 2) return n - 1;
    return (n - 1) * (derangement(n - 1) + derangement(n - 2));
}

```

5.8 diophantine

```
void print_solution(int a, int b, int c)
{
    int x, y;
    if (a == 0 && b == 0) {
        if (c == 0) {
            cout << "Infinite Solutions Exist" << endl;
        }
        else {
            cout << "No Solution exists" << endl;
        }
    }
    int gcd = gcd_extend(a, b, x, y);
    if (c % gcd != 0) {
        cout << "No Solution exists" << endl;
    }
    else {
        cout << "x = " << x * (c / gcd) << ", y = " <<
            y * (c / gcd) << endl;
    }
}
```

5.9 discrete_log

// Returns minimum x for which $a^x \% m = b \% m$, a and m are coprime.

```
int solve(int a, int b, int m) {
    a %= m, b %= m;
    int n = sqrt(m) + 1;
    int an = 1;
    for (int i = 0; i < n; ++i)
        an = (an * 1ll * a) % m;
    unordered_map<int, int> vals;
    for (int q = 0, cur = b; q <= n; ++q) {
        vals[cur] = q;
        cur = (cur * 1ll * a) % m;
    }
    for (int p = 1, cur = 1; p <= n; ++p) {
        cur = (cur * 1ll * an) % m;
        if (vals.count(cur)) {
            int ans = n * p - vals[cur];
            return ans;
        }
    }
    return -1;
}
```

5.10 factorial_mod_p

// $O(\log p(n))$ gives me $n! \% p$ for large n, p

```
int factmod(int n, int p) {
    vector<int> f(p);
    f[0] = 1;
    for (int i = 1; i < p; i++)
        f[i] = f[i-1] * i % p;
    int res = 1;
    while (n > 1) {
        if ((n/p) % 2)
            res = p - res;
        res = res * f[n%p] % p;
        n /= p;
    }
    return res;
}
```

5.11 fft

```
typedef complex<double> base;
#define PI acos(-1)
void fft(vector<base> &a, bool invert) {
    int n = (int)a.size();
    for (int i = 1, j = 0; i < n; ++i) {
        int bit = n >> 1;
```

```
for (; j >= bit; bit >>= 1) j -= bit;
j += bit;
if (i < j) swap(a[i], a[j]);
}
for (int len = 2; len <= n; len <= 1) {
    double ang = 2 * PI / len * (invert ? -1 : 1);
    base wlen(cos(ang), sin(ang));
    for (int i = 0; i < n; i += len) {
        base w(1);
        for (int j = 0; j < len / 2; ++j) {
            base u = a[i + j], v = a[i + j + len / 2] * w;
            a[i + j] = u + v;
            a[i + j + len / 2] = u - v;
            w *= wlen;
        }
    }
}
if (invert) for (int i = 0; i < n; ++i) a[i] /= n;
}
void multiply(const vector<int> &a, const vector<int>
    &b, vector<int> &res) {
    vector<base> fa(a.begin(), a.end()), fb(b.begin(),
        b.end());
    size_t n = 1;
    while (n < max(a.size(), b.size())) n <= 1;
    fa.resize(n), fb.resize(n);
    fft(fa, false), fft(fb, false);
    for (size_t i = 0; i < n; ++i) fa[i] *= fb[i];
    fft(fa, true); res.resize(n);
    for (size_t i = 0; i < n; ++i) res[i] =
        (int)(fa[i].real() + 0.5);
}
```

5.12 find_roots

/*Description: Finds the real roots to a polynomial.
Usage: polyRoots({{2,-3,1}},-1e9,1e9) // solve x^2-3x+2

Time: $O(n^2 \log(1/n))$ */
struct Poly {
 vector<double> a;
 double operator()(double x) const {
 double val = 0;
 for (int i = a.size(); i--;) (val *= x) +=
 a[i];
 return val;
 }
 void diff() {
 for (int i = 1; i < a.size(); ++i) a[i - 1] =
 i * a[i];
 a.pop_back();
 }
 void divroot(double x0) {
 double b = a.back(), c;
 a.back() = 0;
 for (int i = a.size() - 1; i--;) c = a[i],
 a[i] = a[i + 1] * x0 + b, b = c;
 a.pop_back();
 }
};
vector<double> polyRoots(Poly p, double xmin = -1e9,
 double xmax = 1e9) {
 if (p.a.size() == 2) {
 return {-p.a[0] / p.a[1]};
 }
 vector<double> ret;
 Poly der = p;
 der.diff();
 auto dr = polyRoots(der, xmin, xmax);
 dr.push_back(xmin - 1);
 dr.push_back(xmax + 1);

```
sort(dr.begin(), dr.end());
for (int i = 0; i < dr.size() - 1; ++i) {
    double l = dr[i], h = dr[i + 1];
    bool sign = p(l) > 0;
    if (sign ^ (p(h) > 0)) {
        for (int it = 0; it < 60; ++it) { //
            while (h - l > 1e-8)
                double m = (l + h) / 2, f = p(m);
                if ((f <= 0) ^ sign)
                    l = m;
                else
                    h = m;
            }
        ret.push_back((l + h) / 2);
    }
}
return ret;
}
```

5.13 gauss_elimination

```
const double EPS = 1e-9;
const int INF = 2; // it doesn't actually have to be
    infinity or a big number
int gauss(vector<vector<double>> &a, vector<double>
    &ans) {
    int n = (int)a.size();
    int m = (int)a[0].size() - 1;
    vector<int> where(m, -1);
    for (int col = 0, row = 0; col < m && row < n; ++col) {
        int sel = row;
        for (int i = row; i < n; ++i)
            if (abs(a[i][col]) > abs(a[sel][col]))
                sel = i;
        if (abs(a[sel][col]) < EPS)
            continue;
        for (int i = col; i <= m; ++i)
            swap(a[sel][i], a[row][i]);
        where[col] = row;
        for (int i = 0; i < n; ++i)
            if (i != row) {
                double c = a[i][col] / a[row][col];
                for (int j = col; j <= m; ++j)
                    a[i][j] -= a[row][j] * c;
            }
        ++row;
    }
    ans.assign(m, 0);
    for (int i = 0; i < m; ++i)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    for (int i = 0; i < n; ++i) {
        double sum = 0;
        for (int j = 0; j < m; ++j)
            sum += ans[j] * a[i][j];
        if (abs(sum - a[i][m]) > EPS)
            return 0;
    }
    for (int i = 0; i < m; ++i)
        if (where[i] == -1)
            return INF;
    return 1;
}
```

//modular

```
int gauss(vector<bitset<N>> &a, int n, int m,
    bitset<N> &ans) {
    vector<int> where(m, -1);
    for (int col = 0, row = 0; col < m && row < n; ++col) {
        for (int i = row; i < n; ++i)
            if (a[i][col]) {
                swap(a[i], a[row]);
                break;
            }
    }
```



```

    }
    if (!a[row][col])
        continue;
    where[col] = row;
    for (int i=0; i<n; ++i)
        if (i != row && a[i][col])
            a[i] ^= a[row];
    ++row;
}
// The rest of implementation is the same as
// above
}
//rank
const double EPS = 1E-9;
int compute_rank(vector<vector<double>> A) {
    int n = A.size();
    int m = A[0].size();
    int rank = 0;
    vector<bool> row_selected(n, false);
    for (int i = 0; i < m; ++i) {
        int j;
        for (j = 0; j < n; ++j) {
            if (!row_selected[j] && abs(A[j][i]) > EPS)
                break;
        }
        if (j != n) {
            ++rank;
            row_selected[j] = true;
            for (int p = i + 1; p < m; ++p)
                A[j][p] /= A[j][i];
            for (int k = 0; k < n; ++k) {
                if (k != j && abs(A[k][i]) > EPS) {
                    for (int p = i + 1; p < m; ++p)
                        A[k][p] -= A[j][p] * A[k][i];
                }
            }
        }
    }
    return rank;
}

```

5.14 gen_all_k_combs

```

vector<int> ans;
void gen(int n, int k, int idx, bool rev) {
    if (k > n || k < 0)
        return;
    if (!n) {
        for (int i = 0; i < idx; ++i) {
            if (ans[i])
                cout << i + 1;
        }
        cout << "\n";
        return;
    }
    ans[idx] = rev;
    gen(n - 1, k - rev, idx + 1, false);
    ans[idx] = !rev;
    gen(n - 1, k - !rev, idx + 1, true);
}
void all_combinations(int n, int k) {
    ans.resize(n);
    gen(n, k, 0, false);
}

```

5.15 integrate_adaptive

```

/*Description: Fast integration using an adaptive
- Simpsons rule.
Usage: double sphereVolume = quad(-1, 1, [](double x) {
return quad(-1, 1, [&](double y) {
return quad(-1, 1, [&](double z) {

```

```

return x*x + y*y + z*z < 1; }));});});*/
typedef double d;
#define S(a, b) (f(a) + 4 * f((a + b) / 2) + f(b)) *
    (b - a) / 6
template <class F>
d rec(F& f, d a, d b, d eps, d S) {
    d c = (a + b) / 2;
    d S1 = S(a, c), S2 = S(c, b), T = S1 + S2;
    if (abs(T - S) <= 15 * eps || b - a < 1e-10)
        return T + (T - S) / 15;
    return rec(f, a, c, eps / 2, S1) + rec(f, c, b,
        eps / 2, S2);
}
template <class F>
d quad(d a, d b, F f, d eps = 1e-8) {
    return rec(f, a, b, eps, S(a, b));
}

```

5.16 lagrange_interpolation

/*Description: A polynomial of degree d can be uniquely identified given its values on $d + 1$ unique points. $O(n)$ to pre-calculate given the first n points ($x=0$ to $n-1$) of the polynomial. Then answer each query to interpolate the x th term in $O(n)$. All values are done modulo mod , which needs to be a prime as we need its inverse modulo. Also includes an additional helper function called `find_degree`(terms, mod). Given at least the first $d+2$ points of a polynomial of degree d , it finds d in roughly $O(n \log d)$. Note, n should not exceed mod due to the way modular inverse is used. In such cases, we can use interpolation without modulo in big integers and take the remainder later
Time: $O(n)$ */

```

using namespace std;
struct Lagrange {
    vector<int> terms, dp;
    int mod, n;
    Lagrange() {}
    Lagrange(const vector<int>& terms, int mod) :
        terms(terms), mod(mod) {
        n = terms.size();
        assert(n <= mod);
        int i, v, f;
        for (f = 1, i = 1; i < n; i++) f = (long
            long)f * i % mod;
        v = expo(f, mod - 2);
        vector<int> inv(n, v);
        for (i = n - 1; i > 0; i--) {
            inv[i - 1] = (long long)inv[i] * i % mod;
        }
        dp.resize(n, 1);
        for (i = 0; i < n; i++) {
            dp[i] = (long long)inv[i] * inv[n - i - 1]
                % mod;
            dp[i] = (long long)dp[i] * terms[i] % mod;
        }
    }
    int expo(int a, int b) {
        int res = 1;
        while (b) {
            if (b & 1) res = (long long)res * a % mod;
            a = (long long)a * a % mod;
            b >>= 1;
        }
        return res;
    }
}

```

```

}
int interpolate(long long x) {
    if (x < n) return terms[x] % mod;
    x %= mod;
    int i, w;
    vector<int> X(n, 1), Y(n, 1);
    for (i = 1; i < n; i++) {
        X[i] = (long long)X[i - 1] * (x - i + 1) %
            mod;
        if (X[i] < 0) X[i] += mod;
    }
    for (i = n - 2; i >= 0; i--) {
        Y[i] = (long long)Y[i + 1] * (x - i - 1) %
            mod;
        if (Y[i] < 0) Y[i] += mod;
    }
    long long res = 0;
    for (i = 0; i < n; i++) {
        w = ((long long)X[i] * Y[i] % mod) * dp[i]
            % mod;
        if ((n - i + 1) & 1) w = mod - w;
        res += w;
    }
    return res % mod;
}
vector<int> get_terms(const vector<int>& terms, int
    mod, int l, int r) {
    auto lagrange = Lagrange(terms, mod);
    vector<int> res;
    for (int i = l; i <= r; i++) {
        res.push_back(lagrange.interpolate(i));
    }
    return res;
}
int find_degree(const vector<int>& terms, int mod) {
    long long v = mod;
    int k = 1, n = terms.size();
    while (v < INT_MAX) {
        v *= mod;
        k++;
    }
    int l = 1 << 30, r = l + k - 1;
    auto expected = get_terms(terms, mod, l, r);
    int low = 1, high = n - 1;
    while ((low + 1) < high) {
        int mid = (low + high) >> 1;
        vector<int> v(terms.begin(), terms.begin() +
            mid);
        if (get_terms(v, mod, l, r) == expected)
            high = mid;
        else
            low = mid;
    }
    for (int d = low; d <= high; d++) {
        vector<int> v(terms.begin(), terms.begin() +
            d);
        if (get_terms(v, mod, l, r) == expected)
            return d - 1;
    }
    return -1;
}
int main() {
    const int mod = 1000000007;
    vector<int> terms = vector<int>{0, 1, 5, 14, 30};
    auto lagrange = Lagrange(terms, mod);
    assert(lagrange.interpolate(5) == 55);
    assert(lagrange.interpolate(6) == 91);
    assert(lagrange.interpolate(1 << 30) == 300663155);
    assert(lagrange.interpolate(1LL << 60) ==
        717860166);
    assert(find_degree(terms, mod) == 3);
}

```

```

terms.pop_back();
assert(find_degree(terms, mod) == -1);
return 0;
}

5.17 matrix_expo
ll mod=(1e9)+7;
struct Matrix{
    int row, col;
    vector<vector<ll>> mat;
    Matrix(int x, int y){
        row=x;
        col=y;
        mat.assign(row,vector<ll>(col,0));
    }
    Matrix operator *(Matrix &other){
        assert(col==other.row);
        Matrix product(row,other.col);
        for(int i=0;i<row;i++){
            for(int j=0;j<col;j++){
                for(int k=0;k<other.col;k++){
                    product.mat[i][k]=(product.mat[i][j]
                    *mat[j][k])%mod;
                }
            }
        }
        return product;
    };
};

Matrix expo(Matrix &m, ll n){
    assert(m.row==m.col);
    Matrix ret(m.row,m.col);
    for(int i=0;i<m.row;i++) ret.mat[i][i]=1;
    while(n){
        if(n&1) ret=ret*m;
        n/=2;
        m=m*m;
    }
    return ret;
}

```

5.18 next_lexicographical_k_comb

```

bool next_combination(vector<int>& a, int n) {
    int k = (int)a.size();
    for (int i = k - 1; i >= 0; i--) {
        if (a[i] < n - k + i + 1) {
            a[i]++;
            for (int j = i + 1; j < k; j++)
                a[j] = a[j - 1] + 1;
            return true;
        }
    }
    return false;
}

```

5.19 ntt

```

const int mod = 998244353;
const int root = 15311432;
const int k = 1 << 23;
int root_1;
vector<int> rev;
void pre(int sz){
    root_1 = bigmod(root, mod - 2, mod);
    if (rev.size() == sz) return;
    rev.resize(sz);
    rev[0] = 0;
    int lg_n = __builtin_ctz(sz);
    for (int i = 1; i < sz; ++i)
        rev[i] = (rev[i >> 1] >> 1) | ((i & 1) << (lg_n - 1));
}

```

```

void fft(vector<int> &a, bool inv){
    int n = a.size();
    for (int i = 1; i < n - 1; ++i) if (i < rev[i])
        swap(a[i], a[rev[i]]);
    for (int len = 2; len <= n; len <= 1) {
        int wlen = inv ? root_1 : root;
        for (int i = len; i < k; i <= 1) wlen = 1ll *
            wlen * wlen % mod;
        for (int st = 0; st < n; st += len){
            int w = 1;
            for (int j = 0; j < len / 2; j++){
                int ev = a[st + j];
                int od = 1ll * a[st + j + len / 2] * w
                    % mod;
                a[st + j] = ev + od < mod ? ev + od :
                    ev + od - mod;
                a[st + j + len / 2] = ev - od >= 0 ?
                    ev - od : ev - od + mod;
                w = 1ll * w * wlen % mod;
            }
        }
    }
    if (inv){
        int n_1 = bigmod(n, mod - 2, mod);
        for (int &x : a) x = 1ll * x * n_1 % mod;
    }
}

vector<int> mul(vector<int> &a, vector<int> &b){
    int n = a.size(), m = b.size(), sz = 1;
    while (sz < n + m - 1) sz <= 1;
    vector<int> x(sz), y(sz), z(sz);
    for (int i = 0; i < sz; ++i){
        x[i] = i < n ? a[i] : 0;
        y[i] = i < m ? b[i] : 0;
    }
    pre(sz);fft(x, 0);fft(y, 0);
    for (int i = 0; i < sz; ++i) z[i] = 1ll * x[i] *
        y[i] % mod;
    fft(z, 1);z.resize(n + m - 1);
    return z;
}

```

5.20 seg_sieve

```

/*
Segmented Sieve
This code was for 1 <= a <= b <= 2^31-1
Change variable types appropriately.
*/
bool notPrime[?];
void segmented_sieve(int a, int b)
{
    int p, f;
    mem(notPrime, 0);
    for (int i = 0; i < tot_prime; i++)
    {
        p = prime[i];
        if (a % p == 0)
            f = a;
        else
            f = (a - (a % p) + p);
        f = max(p * p, f);
        for (unsigned j = f; j <= b; j += p)
            notPrime[j - a] = true;
    }
    if (a == 1)
        notPrime[0] = 1;
}

```

5.21 stirling

that no box is empty□.

```

int stirling2(int n, int k)

```

```

{
    if(n < k)
        return 0;
    if(k == 1)
        return 1;
    if(dp[n][k] == dp[n][k])
        return dp[n][k];
    return dp[n][k] = stirling2(n-1,k-1) +
        stirling2(n-1,k)*k;
}

is empty
int stirling1(int n, int k)
{
    dp[n][k] = stirling1(n-1,k-1) + stirling(n-1,k)*n-1;
}

```

5.22 stirling_number_of_the_second_kind

```

// 1 / k! * sum (-1)^i nCr(k, i) * (k - i) ^ n
ll f(int n, int k) {
    ll res = 0;
    for (int i = 0; i < k; ++i) {
        if (i & 1) res = (res - nCr(k, i) * bp(k - i,
            n, mod) % mod + mod) % mod;
        else res = (res + nCr(k, i) * bp(k - i, n,
            mod) % mod) % mod;
    }
    if (res < 0) res += mod;
    return res * ifac[k] % mod;
}

```

5.23 sum_of_totient

```

using namespace __gnu_pbds;
const int N = 3e5 + 9, mod = 998244353;
template <const int32_t MOD>
struct modint {
    int32_t value;
    modint() = default;
    modint(int32_t value) : value(value) {}
    inline modint<MOD> operator+(modint<MOD> other)
        const {
        int32_t c = this->value + other.value;
        return modint<MOD>(c >= MOD ? c - MOD : c);
    }
    inline modint<MOD> operator-(modint<MOD> other)
        const {
        int32_t c = this->value - other.value;
        return modint<MOD>(c < 0 ? c + MOD : c);
    }
    inline modint<MOD> operator*(modint<MOD> other)
        const {
        int32_t c = (int64_t)this->value * other.value
            % MOD;
        return modint<MOD>(c < 0 ? c + MOD : c);
    }
    inline modint<MOD> &operator+=(modint<MOD> other) {
        this->value += other.value;
        if (this->value >= MOD)
            this->value -= MOD;
        return *this;
    }
    inline modint<MOD> &operator-=(modint<MOD> other) {
        this->value -= other.value;
        if (this->value < 0)
            this->value += MOD;
        return *this;
    }
    inline modint<MOD> &operator*=(modint<MOD> other) {
        this->value = (int64_t)this->value *
            other.value %

```

```

MOD;
if (this->value < 0) this->value += MOD;
return *this;
}
inline modint<MOD> operator-() const { return
modint<MOD>(this->value ? MOD - this->value :
0); }
modint<MOD> pow(uint64_t k) const {
modint<MOD> x =
*this,
y = 1;
for (; k; k >= 1) {
if (k & 1) y *= x;
x *= x;
}
return y;
}
modint<MOD> inv() const { return pow(MOD - 2); }
// MOD must be a prime
inline modint<MOD> operator/(modint<MOD> other)
const { return *this * other.inv(); }
inline modint<MOD> operator/=(modint<MOD> other) {
return *this *= other.inv(); }
inline bool operator==(modint<MOD> other) const {
return value == other.value; }
inline bool operator!=(modint<MOD> other) const {
return value != other.value; }
inline bool operator<(modint<MOD> other) const {
return value < other.value; }
inline bool operator>(modint<MOD> other) const {
return value > other.value; }
};
template <int32_t MOD>
modint<MOD> operator*(int64_t value, modint<MOD> n) {
return modint<MOD>(value) * n; }
template <int32_t MOD>
modint<MOD> operator*(int32_t value, modint<MOD> n) {
return modint<MOD>(value % MOD) * n; }
template <int32_t MOD>
istream &operator>>(istream &in, modint<MOD> &n) {
return in >> n.value; }
template <int32_t MOD>
ostream &operator<<(ostream &out, modint<MOD> n) {
return out << n.value; }
using mint = modint<mod>;
namespace Dirichlet {
// solution for f(x) = phi(x)
const int T = 1e7 + 9;
long long phi[T];
gp_hash_table<long long, mint> mp;
mint dp[T], inv;
int sz, spf[T], prime[T];
void init() {
memset(spf, 0, sizeof spf);
phi[1] = 1;
sz = 0;
for (int i = 2; i < T; i++) {
if (spf[i] == 0) phi[i] = i - 1, spf[i] = i,
prime[sz++] = i;
for (int j = 0; j < sz && i * prime[j] < T &&
spf[i * prime[j]] == 0) {
spf[i * prime[j]] = prime[j];
if (i % prime[j] == 0)
phi[i * prime[j]] = phi[i] * prime[j];
else
phi[i * prime[j]] = phi[i] * (prime[j]
- 1);
}
}
dp[0] = 0;

```

```

for (int i = 1; i < T; i++) dp[i] = dp[i - 1] +
phi[i] % mod;
inv = 1; // g(1)
}
mint p_c(long long n) {
if (n % 2 == 0) return n / 2 % mod * ((n + 1) %
mod) % mod;
return (n + 1) / 2 % mod * (n % mod) % mod;
}
mint p_g(long long n) {
return n % mod;
}
mint solve(long long x) {
if (x < T) return dp[x];
if (mp.find(x) != mp.end()) return mp[x];
mint ans = 0;
for (long long i = 2, last; i <= x; i = last + 1) {
last = x / (x / i);
ans += solve(x / i) * (p_g(last) - p_g(i - 1));
}
ans = p_c(x) - ans;
ans /= inv;
return mp[x] = ans;
}; // namespace Dirichlet

```

5.24 totient

```

int phi(int n) {
int result = n;
for (int i = 2; i * i <= n; i++) {
if (n % i == 0) {
while (n % i == 0)
n /= i;
result -= result / i;
}
}
if (n > 1)
result -= result / n;
return result;
}
void phi_1_to_n(int n) {
vector<int> phi(n + 1);
phi[0] = 0;
phi[1] = 1;
for (int i = 2; i <= n; i++)
phi[i] = i;
for (int i = 2; i <= n; i++) {
if (phi[i] == i) {
for (int j = i; j <= n; j += i)
phi[j] -= phi[j] / i;
}
}
}

```

5.25 xor basis

```

int basis[d]; // basis[i] keeps the mask of the vector
whose f value is i
int sz;
void insertVector(int mask) {
for (int i = 0; i < d; i++) {
if ((mask & 1 << i) == 0) continue;
if (!basis[i]) { // If there is no basis vector with
the i'th bit set, then insert this vector into
the basis
basis[i] = mask;
++sz;
return;
}
mask ^= basis[i]; // Otherwise subtract the basis
vector from this vector
}
}

```

6 Misc

6.1 check

```

g++ a.cpp -o a.out && g++ ac.cpp -o ac.out && g++
gen.cpp -o gen && for ((i=0;i<1000;i++)) \
do
echo $i
./gen > in
./a.out < inp > out
./ac.out < inp > out1
diff out1 out2
if [ $? -ne 0 ]
then
echo "-----Input-----"
cat in
echo "-----Output-----"
cat out
echo "-----Accepted-----"
cat out1
break
fi
done

```

6.2 debug

```

struct debug {
#define contPrint { *this << "["; \
int f = 0; for(auto it : x) { *this << (f?", \
": ""); *this << it; f = 1; } \
*this << "]" ; return *this; }
~debug(){cerr << endl;}
template<class c> debug& operator<<(c x) {cerr <<
x; return *this;}
template<class c, class d>
debug& operator<<(pair<c, d> x) { *this << "(" <<
x.first << ", " << x.second << ")";
return *this;}
template<class c> debug& operator<<(vector<c> x)
{ contPrint;
return *this;}
#undef contPrint
};
#define dbg(x) "[" << #x << ": " << x << "]"
#define Wa() cerr << "[LINE: " << __LINE__ << "] -> ";
debug() <<

```

6.3 flags

```

g++ -std=c++17 -Wall -Wextra -pedantic -Wshadow
-Wformat=2 -Wfloat-equal -Wconversion -Wlogical-op
-Wshift-overflow=2 -Wduplicated-cond -Wcast-qual
-Wcast-align -D GLIBCXX_DEBUG
-D GLIBCXX_DEBUG_PEDANTIC -D FORTIFY_SOURCE=2
-fsanitize=address -fsanitize=undefined
-fno-sanitize-recover -fstack-protector -o $1
-Wno-unused-result $1.cpp

```

6.4 interval_container

```

/* Description: Add and remove intervals from a set of
disjoint intervals. Will merge the added interval
with any overlapping intervals in
the set when adding. Intervals are [inclusive,
exclusive).
Time: O(log N)
*/
set<pii>::iterator addInterval(set<pii>& is, int L,
int R) {
if (L == R) return is.end();
auto it = is.lower_bound({L, R}), before = it;
while (it != is.end() && it->first <= R) {
R = max(R, it->second);
before = it = is.erase(it);
}

```

```

    }
    if (it != is.begin() && (--it)->second >= L) {
        L = min(L, it->first);
        R = max(R, it->second); is.erase(it);
    }
    return is.insert(before, {L, R});
}
void removeInterval(set<pii>& is, int L, int R) {
    if (L == R) return;
    auto it = addInterval(is, L, R);
    auto r2 = it->second;
    if (it->first == L)
        is.erase(it);
    else
        (int&)it->second = L;
    if (R != r2) is.emplace(R, r2);
}

```

6.5 interval_cover

```

template <class T>
vi cover(pair<T, T> G, vector<pair<T, T>> I) {
    vi S(sz(I)), R;
    iota(all(S), 0);
    sort(all(S), [&](int a, int b) { return I[a] <
        I[b]; });
    T cur = G.first;
    int at = 0;
    while (cur < G.second) { // (A)
        pair<T, int> mx = make_pair(cur, -1);
        while (at < sz(I) && I[S[at]].first <= cur) {
            mx = max(mx, make_pair(I[S[at]].second,
                S[at]));
            at++;
        }
        if (mx.second == -1) return {};
        cur = mx.first;
        R.push_back(mx.second);
    }
    return R;
}

```

6.6 pragma

```

// Pragas
#pragma comment(linker, "/stack:200000000")
#pragma GCC optimize("O3,unroll-loops")
#pragma GCC target("avx,avx2,fma")

```

6.7 random

```

// shuffle(v.begin(), v.end(),
    default_random_engine(rnd(1, 1000)));
mt19937 rng(chrono::steady_clock::now().time_since_epoch()
    chrono::duration<int, chrono::seconds>().count());
ll rnd(ll l, ll r) {
    return uniform_int_distribution<ll>(l, r)(rng);
}

```

6.8 vimrc

```

imap jk <Esc>
set nu
set mouse=a
set autoindent
set tabstop=4
set shiftwidth=4
set smartindent
set relativenumber
set laststatus=2
set hlsearch
let mapleader = " "
nnoremap <leader>s :w<Enter>
nnoremap <leader>y ggVG"y<CR>
syntax on
vnoremap <leader>/ :s!^!//!<CR> :noh <CR>

```

```

vnoremap <leader>u :s!^!//!<CR>
nnoremap <leader>/ :s!^!//!<CR> :noh <CR>
nnoremap <leader>u :s!^!//!<CR>

```

7 Notes

7.1 Counting

1. Lucas Theorem

For non-negative integers m and n and a prime p , the following congruence relation holds :

$$\binom{m}{n} \equiv \prod_{i=0}^k \binom{m_i}{n_i} \pmod{p}, \quad (1)$$

where :

$$m = m_k p^k + m_{k-1} p^{k-1} + \dots + m_1 p + m_0,$$

and :

$$n = n_k p^k + n_{k-1} p^{k-1} + \dots + n_1 p + n_0$$

are the base p expansions of m and n respectively. This uses the convention that $\binom{m}{n} = 0$ if $m \leq n$.

2. Stirling Numbers of the first kind

$S(n, k)$ counts the number of permutations of n elements with k disjoint cycles.

$$S(n, k) = (n-1) \cdot S(n-1, k) + S(n-1, k-1) \quad (2)$$

where, $S(0, 0) = 1, S(n, 0) = S(0, n) = 0$

$$\sum_{k=0}^n S(n, k) = n! \quad (3)$$

3. Stirling Numbers of the second kind

$S(n, k) \cdot k!$ = number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

An r -associated Stirling number of the second kind is the number of ways to partition a set of n objects into k subsets, with each subset containing at least r elements. It is denoted by $S_r(n, k)$ and obeys the recurrence relation.

$$S_r(n+1, k) = k S_r(n, k) + \binom{n}{r-1} S_r(n-r+1, k-1) \quad (4)$$

4. Bell Numbers

Counts the number of partitions of a set.

$$B_{n+1} = \sum_{k=0}^n \binom{n}{k} \cdot B_k \quad (5)$$

$B_n = \sum_{k=0}^n S(n, k)$, where $S(n, k)$ is stirling number of second kind.

5. Some identities

Vandermonde's Identify: $\sum_{k=0}^r \binom{m}{k} \binom{n}{r-k} = \binom{m+n}{r}$

Hockey-Stick Identify: $n, r \in \mathbb{N}, n > r, \sum_{i=r}^n \binom{i}{r} = \binom{n+1}{r+1}$

Involutions: permutations such that $p^2 = \text{identity permutation}$. $a_0 = a_1 = 1$ and $a_n = a_{n-1} + (n-1)a_{n-2}$ for $n > 1$.

7.2 Fibonacci

Let A, B and n be integer numbers.

$$k = A - B$$

$$F_A F_B = F_{k+1} F_A^2 + F_k F_A F_{A-1} \quad (6)$$

$$\sum_{i=0}^n F_i^2 = F_{n+1} F_n \quad (7)$$

$$\sum_{i=0}^n F_i F_{i+1} = F_{n+1}^2 - (-1)^n \quad (8)$$

$$\sum_{i=0}^n F_i F_{i-1} = \sum_{i=0}^{n-1} F_i F_{i+1} \quad (9)$$

$$GCD(F_m, F_n) = F_{GCD(m, n)} \quad (10)$$

$$\sum_{0 \leq k \leq n} \binom{n-k}{k} = Fib_{n+1} \quad (11)$$

$$\gcd(F_n, F_{n+1}) = \gcd(F_n, F_{n+2}) = \gcd(F_{n+1}, F_{n+2}) = 1 \quad (12)$$

7.3 Notes

7.4 Geometry

7.4.1 Triangles

Circumradius: $R = \frac{abc}{4A}$, Inradius: $r = \frac{A}{s}$

Length of median (divides triangle into two equal-area triangles): $m_a = \frac{1}{2} \sqrt{2b^2 + 2c^2 - a^2}$

Length of bisector (divides angles in two): $s_a = \sqrt{bc \left[1 - \left(\frac{a}{b+c} \right)^2 \right]}$

Law of tangents: $\frac{a+b}{a-b} = \frac{\tan \frac{\alpha+\beta}{2}}{\tan \frac{\alpha-\beta}{2}}$

7.4.2 Quadrilaterals

With side lengths a, b, c, d , diagonals e, f , diagonals angle θ , area A and magic flux $F = b^2 + d^2 - a^2 - c^2$:

$$4A = 2ef \cdot \sin \theta = F \tan \theta = \sqrt{4e^2 f^2 - F^2}$$

For cyclic quadrilaterals the sum of opposite angles is 180° , $ef = ac + bd$, and $A = \sqrt{(p-a)(p-b)(p-c)(p-d)}$.

7.4.3 Spherical coordinates

$$x = r \sin \theta \cos \phi \quad r = \sqrt{x^2 + y^2 + z^2}$$

$$y = r \sin \theta \sin \phi \quad \theta = \arccos(z / \sqrt{x^2 + y^2 + z^2})$$

$$z = r \cos \theta \quad \phi = \operatorname{atan2}(y, x)$$

7.5 Sums

$$1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(2n+1)(n+1)}{6}$$

$$1^3 + 2^3 + 3^3 + \dots + n^3 = \frac{n^2(n+1)^2}{4}$$

$$1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$$

$$\sum_{i=1}^n i^m = \frac{1}{m+1} \left[(n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m) \right]$$

$$\sum_{i=1}^{n-1} i^m = \frac{1}{m+1} \sum_{k=0}^m \binom{m+1}{k} B_k n^{m+1-k}$$

$$\sum_{k=0}^n kx^k = (x - (n+1)x^{n+1} + nx^{n+2}) / (x-1)^2$$

7.6 Series

$$e^x = 1 + x + \frac{x^2}{2!} + \frac{x^3}{3!} + \dots, (-\infty < x < \infty)$$
$$\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots, (-1 < x \leq 1)$$
$$\sqrt{1+x} = 1 + \frac{x}{2} - \frac{x^2}{8} + \frac{2x^3}{32} - \frac{5x^4}{128} + \dots, (-1 \leq x \leq 1)$$
$$\sin x = x - \frac{x^3}{3!} + \frac{x^5}{5!} - \frac{x^7}{7!} + \dots, (-\infty < x < \infty)$$
$$\cos x = 1 - \frac{x^2}{2!} + \frac{x^4}{4!} - \frac{x^6}{6!} + \dots, (-\infty < x < \infty)$$
$$(x+a)^{-n} = \sum_{k=0}^{\infty} (-1)^k \binom{n+k-1}{k} x^k a^{-n-k}$$

7.7 Pythagorean Triples

The Pythagorean triples are uniquely generated by

$$a = k \cdot (m^2 - n^2), \quad b = k \cdot (2mn), \quad c = k \cdot (m^2 + n^2),$$

with $m > n > 0$, $k > 0$, $m \perp n$, and either m or n even.

7.8 Number Theory

7.8.1 Primes

$p = 962592769$ is such that $2^{21} \mid p-1$, which may be useful. For hashing use 970592641 (31-bit number), 31443539979727 (45-bit), 3006703054056749 (52-bit). There are 78498 primes less than 1 000 000.

Primitive roots exist modulo any prime power p^a , except for $p = 2, a > 2$, and there are $\phi(\phi(p^a))$ many. For $p = 2, a > 2$, the group $\mathbb{Z}_{2^a}^\times$ is instead isomorphic to $\mathbb{Z}_2 \times \mathbb{Z}_{2^{a-2}}$.

7.8.2 Estimates

$\sum_{d|n} d = O(n \log \log n)$.

The number of divisors of n is at most around 100 for $n < 5e4$, 500 for $n < 1e7$, 2000 for $n < 1e10$, 200 000 for $n < 1e19$.

7.8.3 Perfect numbers

$n > 1$ is called perfect if it equals sum of its proper divisors and 1. Even n is perfect iff $n = 2^{p-1}(2^p - 1)$ and $2^p - 1$ is prime (Mersenne's). No odd perfect numbers are yet found.

7.8.4 Carmichael numbers

A positive composite n is a Carmichael number ($a^{n-1} \equiv 1 \pmod n$) for all a : $\gcd(a, n) = 1$, iff n is square-free, and for all prime divisors p of n , $p-1$ divides $n-1$.

7.8.5 Mobius function

$\mu(1) = 1$. $\mu(n) = 0$, if n is not squarefree. $\mu(n) = (-1)^s$, if n is the product of s distinct primes. Let f, F be functions on positive integers. If for all $n \in \mathbb{N}$, $F(n) = \sum_{d|n} f(d)$, then $f(n) = \sum_{d|n} \mu(d) F(\frac{n}{d})$, and vice versa.

$$\phi(n) = \sum_{d|n} \mu(d) \frac{n}{d}. \quad \sum_{d|n} \mu(d) = 1.$$

If f is multiplicative, then $\sum_{d|n} \mu(d) f(d) = \prod_{p|n} (1 - f(p))$,

$$\sum_{d|n} \mu(d)^2 f(d) = \prod_{p|n} (1 + f(p)).$$

7.8.6 Legendre symbol

If p is an odd prime, $a \in \mathbb{Z}$, then $\left(\frac{a}{p}\right)$ equals 0, if $p|a$; 1 if a is a quadratic residue modulo p ; and -1 otherwise. Euler's criterion:

$$\left(\frac{a}{p}\right) = a^{\left(\frac{p-1}{2}\right)} \pmod p.$$

7.8.7 Jacobi symbol

If $n = p_1^{a_1} \cdots p_k^{a_k}$ is odd, then $\left(\frac{a}{n}\right) = \prod_{i=1}^k \left(\frac{a}{p_i}\right)^{a_i}$.

7.8.8 Primitive roots

If the order of g modulo m ($\min n > 0$: $g^n \equiv 1 \pmod m$) is $\phi(m)$, then g is called a primitive root. If \mathbb{Z}_m has a primitive root, then it has $\phi(\phi(m))$ distinct primitive roots. \mathbb{Z}_m has a primitive root iff m is one of 2, 4, p^k , $2p^k$, where p is an odd prime. If \mathbb{Z}_m has a primitive root g , then for all a coprime to m , there exists unique integer $i = \text{ind}_g(a)$

modulo $\phi(m)$, such that $g^i \equiv a \pmod m$. $\text{ind}_g(a)$ has logarithm-like properties: $\text{ind}(1) = 0$, $\text{ind}(ab) = \text{ind}(a) + \text{ind}(b)$.

If p is prime and a is not divisible by p , then congruence $x^n \equiv a \pmod p$ has $\gcd(n, p-1)$ solutions if $a^{(p-1)/\gcd(n, p-1)} \equiv 1 \pmod p$, and no solutions otherwise. (Proof sketch: let g be a primitive root, and $g^i \equiv a \pmod p$, $g^u \equiv x \pmod p$. $x^n \equiv a \pmod p$ iff $g^{nu} \equiv g^i \pmod p$ iff $nu \equiv i \pmod p$.)

7.8.9 Discrete logarithm problem

Find x from $a^x \equiv b \pmod m$. Can be solved in $O(\sqrt{m})$ time and space with a meet-in-the-middle trick. Let $n = \lceil \sqrt{m} \rceil$, and $x = ny - z$. Equation becomes $a^{ny} \equiv ba^z \pmod m$. Precompute all values that the RHS can take for $z = 0, 1, \dots, n-1$, and brute force y on the LHS, each time checking whether there's a corresponding value for RHS.

7.8.10 Pythagorean triples

Integer solutions of $x^2 + y^2 = z^2$ All relatively prime triples are given by: $x = 2mn, y = m^2 - n^2, z = m^2 + n^2$ where $m > n, \gcd(m, n) = 1$ and $m \not\equiv n \pmod 2$. All other triples are multiples of these. Equation $x^2 + y^2 = 2z^2$ is equivalent to $(\frac{x+y}{2})^2 + (\frac{x-y}{2})^2 = z^2$.

7.8.11 Postage stamps/McNuggets problem

Let a, b be relatively-prime integers. There are exactly $\frac{1}{2}(a-1)(b-1)$ numbers *not* of form $ax + by$ ($x, y \geq 0$), and the largest is $(a-1)(b-1) - 1 = ab - a - b$.

7.8.12 Fermat's two-squares theorem

Odd prime p can be represented as a sum of two squares iff $p \equiv 1 \pmod 4$. A product of two sums of two squares is a sum of two squares. Thus, n is a sum of two squares iff every prime of form $p = 4k + 3$ occurs an even number of times in n 's factorization.

7.9 Permutations

7.9.1 Factorial

$\frac{n}{n!}$	1	2	3	4	5	6	7	8	9	10
$\frac{n}{n!}$	1	2	6	24	120	720	5040	40320	362880	3628800
$\frac{n}{n!}$	11	12	13	14	15	16	17			
$\frac{n}{n!}$	4.0e7	4.8e8	6.2e9	8.7e10	1.3e12	2.1e13	3.6e14			
$\frac{n}{n!}$	20	25	30	40	50	100	150	171		
$\frac{n}{n!}$	2e18	2e25	3e32	8e47	3e64	9e157	6e262	>DBL_MAX		

7.9.2 Cycles

Let $g_S(n)$ be the number of n -permutations whose cycle lengths all belong to the set S . Then

$$\sum_{n=0}^{\infty} g_S(n) \frac{x^n}{n!} = \exp \left(\sum_{n \in S} \frac{x^n}{n} \right)$$

7.9.3 Derangements

Permutations of a set such that none of the elements appear in their original position.

$$D(n) = (n-1)(D(n-1) + D(n-2)) = nD(n-1) + (-1)^n = \left\lfloor \frac{n!}{e} \right\rfloor$$

7.9.4 Burnside's lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|,$$

where X^g are the elements fixed by g ($g.x = x$).

If $f(n)$ counts “configurations” (of some sort) of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k)$$

7.10 Partitions and subsets

7.10.1 Partition function

Number of ways of writing n as a sum of positive integers, disregarding the order of the summands.

$$p(0) = 1, \quad p(n) = \sum_{k \in \mathbb{Z} \setminus \{0\}} (-1)^{k+1} p(n - k(3k-1)/2)$$

$$p(n) \sim 0.145/n \cdot \exp(2.56\sqrt{n})$$

$\frac{n}{p(n)}$	0	1	2	3	4	5	6	7	8	9	20	50	100
$\frac{n}{p(n)}$	1	1	2	3	5	7	11	15	22	30	62	7	~2e5

7.11 General purpose numbers

7.11.1 Stirling numbers of the first kind

Number of permutations on n items with k cycles.

$$c(n, k) = c(n-1, k-1) + (n-1)c(n-1, k), \quad c(0, 0) = 1$$

$$\sum_{k=0}^n c(n, k) x^k = x(x+1) \cdots (x+n-1)$$

$$c(8, k) = 8, 0, 5040, 13068, 13132, 6769, 1960, 322, 28, 1$$

$$c(n, 2) = 0, 0, 1, 3, 11, 50, 274, 1764, 13068, 109584, \dots$$

7.11.2 Eulerian numbers

Number of permutations $\pi \in S_n$ in which exactly k elements are greater than the previous element. k j:s s.t. $\pi(j) > \pi(j+1)$, $k+1$ j:s s.t. $\pi(j) \geq j$, k j:s s.t. $\pi(j) > j$.

$$E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$$

$$E(n, 0) = E(n, n-1) = 1$$

$$E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$$

7.11.3 Stirling numbers of the second kind

Partitions of n distinct elements into exactly k groups.

$$S(n, k) = S(n-1, k-1) + kS(n-1, k)$$

$$S(n, 1) = S(n, n) = 1$$

$$S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$$

7.11.4 Bell numbers

Total number of partitions of n distinct elements. $B(n) = 1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, \dots$ For p prime,

$$B(p^m + n) \equiv mB(n) + B(n+1) \pmod p$$

7.11.5 Bernoulli numbers

$$\sum_{j=0}^m \binom{m+1}{j} B_j = 0. \quad B_0 = 1, B_1 = -\frac{1}{2}, B_n = 0, \text{ for all odd } n \neq 1.$$

7.11.6 Catalan numbers

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, C_{n+1} = \frac{2(2n+1)}{n+2} C_n, C_{n+1} = \sum C_i C_{n-i}$$

$$C_n = 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, \dots$$

- sub-diagonal monotone paths in an $n \times n$ grid.
- strings with n pairs of parenthesis, correctly nested.
- binary trees with with $n+1$ leaves (0 or 2 children).
- ordered trees with $n+1$ vertices.
- ways a convex polygon with $n+2$ sides can be cut into triangles by connecting vertices with straight lines.
- permutations of $[n]$ with no 3-term increasing subseq.

7.12 Inequalities**7.12.1 Titu's Lemma**

For positive reals a_1, a_2, \dots, a_n and b_1, b_2, \dots, b_n ,

$$\frac{a_1^2}{b_1} + \frac{a_2^2}{b_2} + \dots + \frac{a_n^2}{b_n} \geq \frac{a_1 + a_2 + \dots + a_n^2}{b_1 + b_2 + \dots + b_n}$$

Equality holds if and only if $a_i = k b_i$ for a non-zero real constant k .

7.13 Games**7.13.1 Grundy numbers**

For a two-player, normal-play (last to move wins) game on a graph (V, E) : $G(x) = \text{mex}(\{G(y) : (x, y) \in E\})$, where $\text{mex}(S) = \min\{n \geq 0 : n \notin S\}$. x is losing iff $G(x) = 0$.

7.13.2 Sums of games

- *Player chooses a game and makes a move in it* Grundy number of a position is xor of grundy numbers of positions in summed games.
- *Player chooses a non-empty subset of games (possibly, all) and makes moves in all of them* A position is losing iff each game is in a losing position.
- *Player chooses a proper subset of games (not empty and not all), and makes moves in all chosen ones.* A position is losing iff grundy numbers of all games are equal.
- *Player must move in all games, and loses if can't move in some game* A position is losing if any of the games is in a losing position.

7.13.3 Misère Nim

A position with pile sizes $a_1, a_2, \dots, a_n \geq 1$, not all equal to 1, is losing iff $a_1 \oplus a_2 \oplus \dots \oplus a_n = 0$ (like in normal nim.) A position with n piles of size 1 is losing iff n is odd.

7.14 Number Theory

$$\sum_{k=1}^n \frac{1}{\gcd(k, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d) \quad (13)$$

$$\sum_{k=1}^n \frac{k}{\gcd(k, n)} = \frac{n}{2} \cdot \frac{1}{n} \cdot \sum_{d|n} d \cdot \phi(d) \quad (14)$$

$$\sum_{k=1}^n \frac{n}{\gcd(k, n)} = 2 * \sum_{k=1}^n \frac{k}{\gcd(k, n)} - 1, \text{ for } n > 1 \quad (15)$$

$$\sum_{i=1}^n \sum_{j=1}^n [\gcd(i, j) = 1] = \sum_{d=1}^n \mu(d) \left\lfloor \frac{n}{d} \right\rfloor^2 \quad (16)$$

$$\sum_{i=1}^n \sum_{j=1}^n \gcd(i, j) = \sum_{d=1}^n \phi(d) \left\lfloor \frac{n}{d} \right\rfloor^2 \quad (17)$$

$$\sum_{i=1}^n \sum_{j=1}^n i \cdot j [\gcd(i, j) = 1] = \sum_{i=1}^n \phi(i) i^2 \quad (18)$$

$$\sum_{i=1}^n \sum_{j=1}^n \text{lcm}(i, j) = \sum_{l=1}^n \left(\frac{\left(1 + \left\lfloor \frac{n}{l} \right\rfloor\right) \left(\left\lfloor \frac{n}{l} \right\rfloor\right)}{2} \right)^2 = \sum_{d|l} \mu(d) l d \quad (19)$$

7.15 troubleshoot**General:**

Write down most of your thoughts, even **if** you're not sure whether they're useful.
Give your variables (and files) meaningful names.
Stay organized and don't leave papers all over the place!
You should know what your code is doing ...

Pre-submit:

Write a few simple test cases **if** sample is not enough.
Are time limits close? If so, generate max cases.
Is the memory usage fine?
Could anything overflow?
Remove debug output.
Make sure to submit the right file.

Wrong answer:

Print your solution! Print debug output as well.
Read the full problem statement again.
Have you understood the problem correctly?
Are you sure your algorithm works?
Try writing a slow (but correct) solution.
Can your algorithm handle the whole range of input?
Did you consider corner cases (ex. $n=1$)?
Is your output format correct? (including whitespace)
Are you clearing all data structures between test cases?
Any uninitialized variables?
Any undefined behavior (array out of bounds)?
Any overflows or NaNs (or shifting ll by ≥ 64 bits)?
Confusing N and M, i and j, etc.?
Confusing $++i$ and $i++$?
Return vs **continue** vs **break**?

Are you sure the STL functions you use work as you think?

Add some assertions, maybe resubmit.
Create some test cases to run your algorithm on.

Go through the algorithm **for** a simple **case**.

Go through this list again.

Explain your algorithm to a teammate.

Ask the teammate to look at your code.

Go for a small walk, e.g. to the toilet.

Rewrite your solution from the start or let a teammate do it.

Geometry:

Work with ints **if** possible.

Correctly account **for** numbers close to (but not) zero.

Related:

for functions like acos make sure absolute val of input is not (slightly) greater than one.

Correctly deal with vertices that are collinear, concyclic,

coplanar (in 3D), etc.

Subtracting a point from every other (but not itself)?

Runtime error:

Have you tested all corner cases locally?

Any uninitialized variables?

Are you reading or writing outside the range of any vector?

Any assertions that might fail?

Any possible division by 0? (mod 0 **for** example)

Any possible infinite recursion?

Invalidated pointers or iterators?

Are you **using** too much memory?

Debug with resubmits (e.g. remapped signals, see Various).

Time limit exceeded:

Do you have any possible infinite loops?

What's your complexity? Large TL does not mean that something

simple (like $N \log N$) isn't intended.

Are you copying a lot of unnecessary data? (References)

Avoid vector, map. (use arrays/unordered map)

How big is the input and output? (consider FastIO)

What **do** your teammates think about your algorithm?

Calling count() on multiset?

Memory limit exceeded:

What is the max amount of memory your algorithm should need?

Are you clearing all data structures between test cases?

If **using** pointers **try** BumpAllocator.

8 String**8.1 aho_corasick**

```
using namespace std;
const int N = ?;
const int A = ?;
struct AC {
    int nd, pt;
    int next[N][A], link[N], out_link[N], cnt[N], ans[N];
    vector<int> ed[N], out[N];
    AC(): nd(0), pt(0) { node(); }
    int node() {
        memset(next[nd], 0, sizeof next[nd]);
        link[nd] = out_link[nd] = cnt[nd] = 0;
        ed[nd].clear(), out[nd].clear();
        return nd++;
    }
    void clear() {
        nd = pt = 0;
        node();
    }
    inline int get(char c) { return c - 'a'; }
    void insert(const string &T) {
        int u = 0;
        for (char c : T) {
            if (!next[u][get(c)]) next[u][get(c)] = node();
            u = next[u][get(c)];
        }
        ans[pt] = 0;
        out[u].push_back(pt++);
    }
    void build() {
        queue<int> q;
        for (q.push(0); !q.empty(); ) {
            int u = q.front();
            q.pop();
            for (int c = 0; c < A; ++c) {
                int v = next[u][c];
                if (!v) next[u][c] = next[link[u]][c];
                else {
                    link[v] = u ? next[link[u]][c] : 0;
                    out_link[v] = out[link[v]].empty() ?
                        out_link[link[v]] : link[v];
                    ed[link[v]].push_back(v);
                    q.push(v);
                }
            }
        }
    }
};
```

```

}
}
void dfs(int s) {
    for(int x : ed[s]) dfs(x), cnt[s] += cnt[x];
    for(int e : out[s]) ans[e] = cnt[s];
}
void traverse(const string &S) {
    int u = 0;
    for(char c : S) {
        u = next[u][get(c)];
        cnt[u]++;
    }
    dfs(0);
}
};
char str[1000010], pat[505];
int main() {
    // freopen("in.txt", "r", stdin);
    AC aho;
    int t, T;
    scanf("%d", &T);
    for(int t=1; t<=T; t++) {
        int n;
        scanf("%d", &n);
        scanf("%s", str);
        for(int i=1; i<=n; i++) {
            scanf("%s", pat);
            aho.insert(pat);
        }
        aho.build();
        aho.traverse(str);
        printf("Case %d:\n", t);
        for(int i=0; i<n; i++) {
            printf("%d\n", aho.ans[i]);
        }
        aho.clear();
    }
    return 0;
}

```

8.2 fft match

```

using ld = double;
using cd = complex<ld>;
const ld PI = acos(-1.0);
const ld eps = 1e-6;
void fft(vector<cd>& a, bool invert)
{
    int n = (int)a.size();
    for(int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for(; j & bit; bit >>= 1) j ^= bit;
        j ^= bit;
        if(i < j) swap(a[i], a[j]);
    }
    for(int len = 2; len <= n; len <<= 1) {
        ld ang = 2 * PI / len * (invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for(int i = 0; i < n; i += len) {
            cd w(1);
            for(int j = 0; j < len / 2; j++) {
                cd u = a[i + j], v = a[i + j + len/2];
                u *= w;
                a[i + j] = u + v;
                a[i + j + len/2] = u - v;
                w *= wlen;
            }
        }
    }
    if(invert) {
        for(cd& x : a) {
            x /= n;
        }
    }
}

```

```

}
}
vector<i64> multiply(vector<cd> const& a, vector<cd>
    const& b) {
    vector<cd> fa(a.begin(), a.end()), fb(b.begin(),
        b.end());
    int n = 1;
    while(n < (int)a.size() + b.size()) {
        n <<= 1;
    }
    fa.resize(n);
    fb.resize(n);
    fft(fa, false);
    fft(fb, false);
    for(int i = 0; i < n; i++) fa[i] *= fb[i];
    fft(fa, true);
    vector<i64> res(n);
    for(int i = 0; i < n; i++) {
        if(abs(fa[i].imag()) < eps) {
            res[i] = round(fa[i].real());
            if(abs(res[i] - fa[i].real()) > eps) {
                res[i] = -1;
            }
        } else {
            res[i] = -1;
        }
    }
    return res;
}
int main()
{
    /*
    |t| <= |s|
    Want to check if t occurs as a substring of s
    */
    string s, t; cin >> s >> t;
    vector<cd> sa(s.size()), ta(t.size());
    for(int i = 0; i < s.size(); ++i) {
        ld ang = 2 * PI * (s[i] - 'a' + 1) / 27;
        sa[i] = cd(cos(ang), sin(ang));
    }
    for(int i = 0; i < t.size(); ++i) {
        ld ang = 2 * PI * (t[i] - 'a' + 1) / 27;
        ta[i] = cd(cos(ang),
            -sin(ang));
    }
    vector<i64> mul = multiply(sa, ta);
    for(int i = 0; i < sa.size(); ++i) {
        if(mul[i] == ta.size()) {
            cout << i - ta.size() + 1 << ' ';
        }
    }
    cout << '\n';
}

```

8.3 hash

```

struct Hash {
    struct base {
        string s; int b, mod;
        vector<int> hash, p;
        void init(string &s, int _b, int _mod) { // b >
            26, prime.
            s = s; b = _b, mod = _mod;
            hash.resize(s.size());
            p.resize(s.size());
            hash[0] = s[0] - 'A' + 1; p[0] = 1;
            for(int i = 1; i < s.size(); ++i) {
                hash[i] = ((ll) hash[i-1] * b % mod;
                hash[i] += s[i] - 'A' + 1;
                if(hash[i] >= mod) hash[i] -= mod;
                p[i] = ((ll) p[i-1] * b % mod;
            }
        }
    }
}

```

```

int get(int l, int r) {
    int ret = hash[r];
    if(l) ret -= (ll) hash[l-1] * p[r-l+1] %
        mod;
    if(ret < 0) ret += mod;
    return ret;
}
h[2];
void init(string &s) {
    h[0].init(s, 29, 1e9+7);
    h[1].init(s, 31, 1e9+9);
}
pair<int, int> get(int l, int r) {
    return { h[0].get(l, r), h[1].get(l, r) };
}
}
H;

```

8.4 hash_segtree

```

#define INVALID_CHAR -1
namespace strhash {
    int n;
    const int MAX = 1000010;
    int ara[MAX];
    const int MOD[] = {1067737007, 1069815139};
    const int BASE[] = {982451653, 984516781};
    int BP[2][MAX], CUM[2][MAX];
    void init(char *str) {
        n = strlen(str);
        for(int i=0; i<n; i++) ara[i] = str[i] - '0' + 1;
    }
    void precal() {
        BP[0][0] = BP[1][0] = 1;
        CUM[0][0] = CUM[1][0] = 1;
        for(int i=1; i<MAX; i++) {
            BP[0][i] = ( BP[0][i-1] * (long long) BASE[0] )
                % MOD[0];
            BP[1][i] = ( BP[1][i-1] * (long long) BASE[1] )
                % MOD[1];
            CUM[0][i] = ( CUM[0][i-1] + (long long) BP[0][i] )
                % MOD[0];
            CUM[1][i] = ( CUM[1][i-1] + (long long) BP[1][i] )
                % MOD[1];
        }
    }
    struct node {
        int sz;
        int h[2];
        node() {}
    } tree[4*MAX];
    int lazy[4*MAX];
    inline void lazyUpdate(int n, int st, int ed) {
        if(lazy[n] != INVALID_CHAR) {
            tree[n].h[0] = (lazy[n] * (long long)
                CUM[0][ed-st]) % MOD[0];
            tree[n].h[1] = (lazy[n] * (long long)
                CUM[1][ed-st]) % MOD[1];
            if(st != ed) {
                lazy[2*n] = lazy[n];
                lazy[2*n+1] = lazy[n];
            }
            lazy[n] = INVALID_CHAR;
        }
    }
    inline node Merge(node a, node b) {
        node ret;
        ret.h[0] = ( ( a.h[0] * (long long) BP[0][b.sz] )
            + b.h[0] ) % MOD[0];
    }
}

```

```

ret.h[1] = ( ( a.h[1] * (long long) BP[1][b.sz] )
    + b.h[1] ) % MOD[1];
ret.sz = a.sz + b.sz;
return ret;
}

inline void build(int n, int st, int ed) {
    lazy[n] = INVALID_CHAR;
    if(st==ed) {
        tree[n].h[0] = tree[n].h[1] = ara[st];
        tree[n].sz = 1;
        return;
    }
    int mid = (st+ed)>>1;
    build(n+n, st, mid);
    build(n+n+1, mid+1, ed);
    tree[n] = Merge(tree[n+n], tree[n+n+1]);
}

inline void update(int n, int st, int ed, int i, int
    j, int v) {
    lazyUpdate(n, st, ed);
    if(st>j or ed<=j) return;
    if(st>=i and ed<=j) {
        lazy[n] = v;
        lazyUpdate(n, st, ed);
        return;
    }
    int mid = (st+ed)>>1;
    update(n+n, st, mid, i, j, v);
    update(n+n+1, mid+1, ed, i, j, v);
    tree[n] = Merge(tree[n+n], tree[n+n+1]);
}

inline node query(int n, int st, int ed, int i, int j) {
    lazyUpdate(n, st, ed);
    if(st>=i and ed<=j) return tree[n];
    int mid = (st+ed)/2;
    if(mid<i) return query(n+n+1, mid+1, ed, i, j);
    else if(mid>=j) return query(n+n, st, mid, i, j);
    else return Merge(query(n+n, st, mid, i, j), query(n+n+1,
        mid+1, ed, i, j));
}
}

```

8.5 kmp

// returns the longest proper prefix array of pattern p
 // where lps[i]=longest proper prefix which is also
 // suffix of p[0...i]

```

vector<int> build_lps(string p) {
    int sz = p.size();
    vector<int> lps;
    lps.assign(sz + 1, 0);
    int j = 0;
    lps[0] = 0;
    for(int i = 1; i < sz; i++) {
        while(j >= 0 && p[i] != p[j]) {
            if(j >= 1) j = lps[j - 1];
            else j = -1;
        }
        j++;
        lps[i] = j;
    }
    return lps;
}

```

```

vector<int> ans;
// returns matches in vector ans in 0-indexed
void kmp(vector<int> lps, string s, string p) {
    int psz = p.size(), sz = s.size();
    int j = 0;
    for(int i = 0; i < sz; i++) {
        while(j >= 0 && p[j] != s[i])
            if(j >= 1) j = lps[j - 1];
    }
}

```

```

    else j = -1;
    j++;
    if(j == psz) {
        j = lps[j - 1];
        // pattern found in string s at position i-psz+1
        ans.push_back(i - psz + 1);
    }
    // after each loop we have j=longest common suffix
    // of s[0..i] which is also prefix of p
}
}

```

8.6 manachar

```

vector<int> d1(n); // maximum odd length palindrome
// centered at i
// here d1[i]=the palindrome has
// d1[i]-1 right characters from i
// e.g. for aba, d1[1]=2;
for(int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 1 : min(d1[l + r - i], r - i);
    while(0 <= i - k && i + k < n && s[i - k] == s[i + k]) {
        k++;
    }
    d1[i] = k--;
    if(i + k > r) {
        l = i - k;
        r = i + k;
    }
}

vector<int> d2(n); // maximum even length palindrome
// centered at i
// here d2[i]=the palindrome has
// d2[i]-1 right characters from i
// e.g. for abba, d2[2]=2;
for(int i = 0, l = 0, r = -1; i < n; i++) {
    int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
    while(0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k]) {
        k++;
    }
    d2[i] = k--;
    if(i + k > r) {
        l = i - k - 1;
        r = i + k;
    }
}
}

```

8.7 palindromic tree

```

const int A = 26;
const int N = 300010;
char s[N]; long long ans;
int last, ptr, nxt[N][A], link[N], len[N], occ[N];
void feed(int at) {
    while(s[at - len[last] - 1] != s[at]) last =
        link[last];
    int ch = s[at] - 'a', temp = link[last];
    while(s[at - len[temp] - 1] != s[at]) temp =
        link[temp];
    if(!nxt[last][ch]) {
        nxt[last][ch] = ++ptr, len[ptr] = len[last] + 2;
        link[ptr] = len[ptr] == 1 ? 2 : nxt[temp][ch];
    }
    last = nxt[last][ch], ++occ[last];
}

int main() {
    len[1] = -1, len[2] = 0, link[1] = link[2] = 1, last
        = ptr = 2;
    scanf("%s", s + 1);
    for(int i = 1, n = strlen(s + 1); i <= n; ++i)
        feed(i);
}

```

```

for(int i = ptr; i > 2; --i) ans = max(ans, len[i]
    * 1LL * occ[i]), occ[link[i]] += occ[i];
printf("%lld\n", ans);
return 0;
}

```

8.8 persistent trie

```

const int MAX = 200010;
const int B = 19;
int root[MAX], ptr = 0;
struct node {
    int ara[2], sum;
    node() {}
} tree[MAX * (B + 1)];
void insert(int prevnode, int &curRoot, int val) {
    curRoot = ++ptr;
    int curnode = curRoot;
    for(int i = B; i >= 0; i--) {
        bool bit = val & (1 << i);
        tree[curnode] = tree[prevnode];
        tree[curnode].ara[bit] = ++ptr;
        tree[curnode].sum += 1;
        prevnode = tree[prevnode].ara[bit];
        curnode = tree[curnode].ara[bit];
    }
    tree[curnode] = tree[prevnode];
    tree[curnode].sum += 1;
}

int find_xor_max(int prevnode, int curnode, int x) {
    int ans = 0;
    for(int i = B; i >= 0; i--) {
        bool bit = x & (1 << i);
        if(tree[tree[curnode].ara[bit ^ 1]].sum >
            tree[tree[prevnode].ara[bit ^ 1]].sum) {
            curnode = tree[curnode].ara[bit ^ 1];
            prevnode = tree[prevnode].ara[bit ^ 1];
            ans = ans | (1 << i);
        }
        else {
            curnode = tree[curnode].ara[bit];
            prevnode = tree[prevnode].ara[bit];
        }
    }
    return ans;
}

void solve() {
    int n, q, L, R, K;
    cin >> n;
    for(int i = 1; i <= n; i++) cin >> ara[i];
    for(int i = 1; i <= q; i++) {
        cin >> L >> R >> K;
        cout << find_xor_max(root[L - 1], root[R], K) << endl;
    }
}

```

8.9 suffix_array

```

// Everything is 0-indexed
char s[N]; // Suffix array will be built for this
// string
int SA[N], isa[N]; // SA is the suffix array, isa[i]
// stores the rank of the i'th suffix
int cnt[N], nxt[N]; // Internal stuff
bool bh[N], b2h[N]; // Internal stuff
int lcp[N]; // Stores lcp of SA[i] and SA[i + 1];
// lcp[n - 1] = 0
int lcpSparse[LOGN][N]; // lcpSparse[i][j] =
// min(lcp[j], ..., lcp[j - 1 + (1 << i)])

```



```

void buildSA(int n) {
    for (int i = 0; i < n; i++) SA[i] = i;
    sort(SA, SA + n, [](int i, int j) { return s[i] < s[j]; });
    for (int i = 0; i < n; i++) {
        bh[i] = i == 0 || s[SA[i]] != s[SA[i - 1]];
        b2h[i] = 0;
    }
    for (int h = 1; h < n; h <= 1) {
        int tot = 0;
        for (int i = 0, j; i < n; i = j) {
            j = i + 1;
            while (j < n && !bh[j]) j++;
            nxt[i] = j; tot++;
        } if (tot == n) break;
        for (int i = 0; i < n; i = nxt[i]) {
            for (int j = i; j < nxt[i]; j++) iSA[SA[j]] = i;
            cnt[i] = 0;
        }
        cnt[iSA[n - h]]++;
        b2h[iSA[n - h]] = 1;
        for (int i = 0; i < n; i = nxt[i]) {
            for (int j = i; j < nxt[i]; j++) {
                int s = SA[j] - h;
                if (s < 0) continue;
                int head = iSA[s];
                iSA[s] = head + cnt[head]++;
                b2h[iSA[s]] = 1;
            }
            for (int j = i; j < nxt[i]; j++) {
                int s = SA[j] - h;
                if (s < 0 || !b2h[iSA[s]]) continue;
                for (int k = iSA[s] + 1; !bh[k] && b2h[k]; k++) b2h[k] = 0;
            }
        }
        for (int i = 0; i < n; i++) {
            SA[iSA[i]] = i;
            bh[i] = b2h[i];
        }
    }
    for (int i = 0; i < n; i++) iSA[SA[i]] = i;
}

void buildLCP(int n) {
    for (int i = 0, k = 0; i < n; i++) {
        if (iSA[i] == n - 1) {
            k = 0;
            lcp[n - 1] = 0;
            continue;
        }
        int j = SA[iSA[i] + 1];
        while (i + k < n && j + k < n && s[i + k] == s[j + k]) k++;
        lcp[iSA[i]] = k;
        if (k) k--;
    }
}

void buildLCPSparse(int n) {
    for (int i = 0; i < n; i++) lcpSparse[0][i] = lcp[i];
    for (int i = 1; i < LOGN; i++) {
        for (int j = 0; j < n; j++) {
            lcpSparse[i][j] = min(lcpSparse[i - 1][j],
                                lcpSparse[i - 1][min(n - 1, j + (1 << (i - 1)))]);
        }
    }
}

pair<int, int> minLCPRange(int n, int from, int to) {
    int r = from;

```

```

    for (int i = LOGN - 1; i >= 0; i--) {
        int jump = 1 << i;
        if (r + jump < n and lcpSparse[i][r] >= minLCP) r += jump;
    }
    int l = from;
    for (int i = LOGN - 1; i >= 0; i--) {
        int jump = 1 << i;
        if (l - jump >= 0 and lcpSparse[i][l - jump] >= minLCP) l -= jump;
    }
    return make_pair(l, r);
}

```

8.10 suffix automata

```

namespace sa {
    const int MAXN = 100005 << 1;
    const int MAXC = 26;
    char str[MAXN];
    int n, sz, last;
    int len[MAXN], link[MAXN], ed[MAXN][MAXC], cnt[MAXN];
    bool terminal[MAXN];
    vector<int> G[MAXN];
    void init() {
        SET(ed[0]);
        len[0] = 0, link[0] = -1, sz = 1, last = 0,
        terminal[0] = false;
    }
    inline int scale(char c) { return c - 'a'; }
    void extend(char c) {
        int cur = sz++;
        terminal[cur] = false;
        cnt[cur] = 1;
        SET(ed[cur]);
        len[cur] = len[last] + 1;
        int p = last;
        while (p != -1 && ed[p][c] == -1) {
            ed[p][c] = cur;
            p = link[p];
        }
        if (p == -1) link[cur] = 0;
        else {
            int q = ed[p][c];
            if (len[p] + 1 == len[q]) link[cur] = q;
            else {
                int clone = sz++;
                len[clone] = len[p] + 1;
                memcpy(ed[clone], ed[q], sizeof(ed[q]));
                link[clone] = link[q];
                while (p != -1 && ed[p][c] == q) {
                    ed[p][c] = clone;
                    p = link[p];
                }
                link[q] = link[cur] = clone;
                cnt[clone] = 0;
                terminal[clone] = false;
            }
        }
        last = cur;
    }
    void dfs(int s) {
        for (auto x : G[s]) dfs(x), cnt[s] += cnt[x];
    }
    void build() {
        init();
        int n = strlen(str);
        for (int i = 0; i < n; i++) extend(scale(str[i]));
        for (int i = 1; i < sz; i++) G[link[i]].pb(i);
        dfs(0);
        for (int i = 0; i < sz; i++) G[i].clear();
    }
}

```

```

    }
    for (int i = last; i != -1; i = link[i]) terminal[i] = true;
}

```

8.11 trie

```

#define N 200000
#define S 26
int root, now;
int nxt[N][S], cnt[N];
void init() {
    root = now = 1;
    CLR(nxt), CLR(cnt);
}
inline int scale(char ch) { return (ch - 'a'); }
inline void Insert(char s[], int sz) {
    int cur = root, to;
    for (int i = 0; i < sz; i++) {
        to = scale(s[i]);
        if (!nxt[cur][to]) nxt[cur][to] = ++now;
        cur = nxt[cur][to];
    }
    cnt[cur]++;
}
inline bool Find(char s[], int sz) {
    int cur = root, to;
    for (int i = 0; i < sz; i++) {
        to = scale(s[i]);
        if (!nxt[cur][to]) return false;
        cur = nxt[cur][to];
    }
    return (cnt[cur] != 0);
}
inline void Delete(char s[], int sz) {
    int cur = root, to;
    for (int i = 0; i < sz; i++) {
        to = scale(s[i]);
        cur = nxt[cur][to];
    }
    cnt[cur]--;
}

```

8.12 z_algo

```

const int N = 100010;
char s[N];
int t, n, z[N];
int main() {
    scanf("%s", s);
    n = strlen(s), z[0] = n;
    int L = 0, R = 0;
    for (int i = 1; i < n; ++i) {
        if (i > R) {
            L = R = i;
            while (R < n && s[R - L] == s[R]) ++R;
            z[i] = R - L; --R;
        } else {
            int k = i - L;
            if (z[k] < R - i + 1) z[i] = z[k];
            else {
                L = i;
                while (R < n && s[R - L] == s[R]) ++R;
                z[i] = R - L; --R;
            }
        }
    }
}

```