COMPREHENSIVE THEORETICAL AND ALGORITHMIC ANALYSIS OF WRATTS-NET: A DUAL-BRANCH WAVELET-RESNET ARCHITECTURE WITH CROSS-ATTENTION AND SUGENO FUZZY FUSION FOR NUCLEAR INSTANCE SEGMENTATION

Diptarko Bhattacharjee[1], *Mukut Chatterjee*[1], *Sergei Romanov*[3], *Dimitri Kaplun*[2,3,*], *Ram Sarkar*[1]

[1]Department of Computer Science & Engineering, Jadavpur University, Kolkata, India
[2]School of CS and Technology / School of AI, China University of Mining and Tech., Xuzhou, China
[3]Intelligent Devices Institute, St. Petersburg Electrotechnical University "LETI", St. Petersburg, Russia
diptarko.1312@gmail.com, mukutchatterjee0211@gmail.com,
saromanov@etu.ru, dikaplun@etu.ru, ramjucse@gmail.com
[*]Corresponding author

ABSTRACT

Accurate nuclear semantic and instance segmentation in hematoxylin and eosin (H&E) stained histopathological images is a cornerstone of computational pathology, providing the quantitative foundation for cellular grading, tumor microenvironment characterization, and clinical survival prognosis. However, this task is challenged by indistinct margins, stain variability across laboratories, crowded clusters of touching cells, and the intrinsic loss of high-frequency boundary information caused by conventional convolutional pooling. In this treatise, we present an exhaustive mathematical, architectural, and algorithmic analysis of WRATTS-Net: a novel dual-branch framework that bridges multi-frequency analysis and deep representation learning. WRATTS-Net couples a Learnable Lifting Wavelet Transform (LLWT) stream for lossless, directional edge preservation with a modified ResUNet stream for deep semantic context. Multi-scale channel-wise Bi-Directional Cross-Attention (BiCA) dynamically synchronizes representations across both streams without the quadratic spatial complexity of self-attention. The contracting and expanding pathways of the ResUNet branch are regularized through a custom skip-connection feature alignment loss ($\mathcal{L}_{\text{feat}}$), eliminating representation divergence across skip bridges. Branch probabilities are ensembled pixel-wise via a learnable Sugeno fuzzy integral, which utilizes learned singleton fuzzy densities (g_1, g_2) to dynamically arbitrate between geometric edge certainty and semantic context. Optimized under a composite multi-task objective with horizontal/vertical distance-to-centroid (HoVer) regression and boundary consistency regularization, our framework achieves state-of-the-art results across three rigorous clinical benchmarks: MoNuSeg (Dice 82.46%, AJI 62.44%, PQ 61.49%), TNBC (Dice 88.00%, AJI 70.23%, PQ 69.69%), and CPM-15 (Dice 90.02%, AJI 70.82%, PQ 67.40%). This monograph provides complete mathematical derivations, proofs of invertibility, gradient derivations, pedagogical walkthroughs, and exhaustive layer-by-layer parameter breakdowns of every module operating within WRATTS-Net.

***Index Terms*—** Computational Pathology, Nuclear Instance Segmentation, Learnable Lifting Wavelets, Sugeno Fuzzy Integral, Bi-Directional Cross-Attention, HoVer-Net, Multi-Task Learning.

1. INTRODUCTION AND PROBLEM FORMULATION

1.1. The Clinical and Computational Challenge

Microscopic examination of tissue biopsies stained with Hematoxylin and Eosin (H&E) remains the definitive diagnostic gold standard in surgical pathology. Hematoxylin selectively binds to basophilic structures, imparting a deep purplish-blue hue to nucleic acids in cell nuclei, while eosin stains eosinophilic extracellular matrix proteins and cytoplasm pink. The spatial distribution, morphological pleomorphism, density, and mitotic activity of cell nuclei serve as critical biomarkers for tumor grading, cancer staging, and predicting clinical treatment responses.

Despite its clinical significance, manual nuclear annotation by certified pathologists is prohibitively labor-intensive, time-consuming, and prone to substantial intra- and inter-observer variability. Automated computer-aided diagnosis (CAD) pipelines require robust instance segmentation algorithms capable of identifying the precise boundary of every individual nucleus.

Computationally, this task presents formidable hurdles:

(a) **Dense Crowding and Touching Nuclei:** In high-grade malignant neoplasms, uncontrolled cellular proliferation creates tightly packed syncytial clusters where individual nuclei abut or overlap without visible background margins.

(b) **Staining and Illumination Heterogeneity:** Variations in tissue thickness, fixation duration, dye brand, and scanner optical properties lead to drastic chromatic distribution shifts across patient cohorts.

(c) **Vesicular and Deformed Nuclei:** Cancerous nuclei frequently undergo chromatin margination and nucleolar en-

largement, resulting in faint, hollow interior appearances that fool standard edge detectors.

(d) **Pooling-Induced Spatial Degradation:** Classical Convolutional Neural Networks (CNNs), such as U-Net, rely on aggressive pooling (e.g., 2×2 max-pooling or strided convolutions). While pooling enlarges the receptive field and imparts translation invariance, it permanently discards high-frequency sub-band details, rendering sharp boundary disentanglement impossible.

1.2. Formal Mathematical Definition of Instance Segmentation

Let $\mathbf{I} \in \mathbb{R}^{3\times H\times W}$ represent an RGB histopathology image of height H and width W. Semantic segmentation aims to estimate a binary mapping $\mathbf{M} \in \{0,1\}^{H\times W}$, where $\mathbf{M}(y,x) = 1$ denotes a nuclear pixel and $\mathbf{M}(y,x) = 0$ denotes background stroma:

$$\mathbf{M}(y,x) = \mathbb{I}\left((y,x) \in \bigcup_{k=1}^{K} \Omega_k\right), \tag{1}$$

where $\Omega_k \subset \{1,\dots,H\} \times \{1,\dots,W\}$ denotes the compact spatial support of the k-th distinct cell nucleus, and K is the total count of nuclei.

Crucially, semantic segmentation cannot distinguish between adjacent nuclei that share a boundary:

$$\partial\Omega_i \cap \partial\Omega_j \neq \emptyset \implies \Omega_i \cup \Omega_j \text{ form a single connected component in } \mathbf{M}. \tag{2}$$

Instance segmentation resolves this fundamental limitation by assigning a unique integer label to each independent nuclear instance:

$$\mathbf{Y}_{\text{inst}}(y,x) = \begin{cases} k, & \text{if } (y,x) \in \Omega_k, \\ 0, & \text{if } (y,x) \in \text{background}, \end{cases} \tag{3}$$

such that $\Omega_i \cap \Omega_j = \emptyset$ for all $i \neq j$.

1.3. The Geometric Failure of Connected Components

Many naive pipelines attempt to obtain instance masks by computing the 8-connected components of the semantic binary prediction:

$$\mathbf{Y}_{\text{cc}} = \text{ConnectedComponents}(\mathbf{M}, \text{connectivity} = 8). \tag{4}$$

However, if even a single false-positive foreground pixel bridges two adjacent nuclei (i.e., $\text{dist}(\Omega_i, \Omega_j) = 1$), the transitive property of connectivity merges both nuclei into a single instance:

$$\mathbf{Y}_{\text{cc}}(\Omega_i) \equiv \mathbf{Y}_{\text{cc}}(\Omega_j). \tag{5}$$

This catastrophic under-segmentation severely corrupts nuclear density metrics and cell counts.

1.4. Architectural Paradigm: Dual-Stream Synergy in WRATTS-Net

To fundamentally solve these issues without compromising either spatial resolution or global semantic understanding, WRATTS-Net deploys a dual-stream architecture:

1. **Wavelet Stream (w):** Employs a Learnable Lifting Wavelet Transform (LLWT) that decomposes features into multi-directional high-frequency and low-frequency components without pooling. Sub-pixel detail bands are preserved and routed across skip bridges directly to a symmetric Inverse LLWT decoder.
2. **Residual Stream (r):** Employs a modified ResUNet backbone utilizing Pre-activation Residual Blocks and Generalized Mean (GeM) pooling to extract deep, robust histological abstractions and context.
3. **Bi-Directional Cross-Attention (BiCA):** Dynamically interchanges features between streams at 9 distinct junctions across encoder, bottleneck, and decoder stages, enriching wavelet edge features with semantic context and grounding residual representations with exact spatial coordinates.
4. **Skip-Connection Feature Alignment Loss ($\mathcal{L}_{\text{feat}}$):** Supervised via channel-normalized Mean Squared Error across all four stages $l \in \{1,2,3,4\}$, forcing decoder upsamplings to align with encoder skip features and bridging the semantic gap.
5. **Sugeno Fuzzy Integral Fusion:** A non-linear, pixel-wise decision fusion mechanism governed by learned fuzzy densities (g_1, g_2) that adaptively arbitrates between the predictions of the two streams.
6. **HoVer-Net Branch & Watershed Decoding:** Regresses horizontal and vertical distance-to-centroid vectors by fusing decoder features with upsampled wavelet sub-bands, producing topological distance surfaces whose gradient basins enable marker-controlled watershed separation of touching cells.

2. MATHEMATICAL FOUNDATIONS OF THE WAVELET STREAM

2.1. Limitations of Classical Downsampling

In standard convolutional architectures, spatial downsampling by a factor of 2 is executed via max-pooling:

$$y(i,j) = \max_{m,n\in\{0,1\}} x(2i+m, 2j+n), \tag{6}$$

or strided convolution with stride $s = 2$. According to the Nyquist-Shannon sampling theorem, sampling a continuous-space signal below twice its highest frequency component introduces irreversible aliasing. Max-pooling non-linearly discards 75% of spatial coordinates, eradicating sub-pixel edges, high-frequency nuclear chromatin textures, and fine clefts between abutting cell membranes.

2.2. The 2D Lifting Scheme: Mathematical Formulation

The Lifting Scheme, introduced by Wim Sweldens, is a second-generation wavelet construction technique that executes spatial-domain wavelet transforms entirely through local algebraic operations, without requiring the Fourier domain. It guarantees perfect reconstruction and exact invertibility for arbitrary non-linear and learnable operators. The LLWT encoder in WRATTS-Net comprises four hierarchical stages with $3, 3, 4, 3$




Fig. 1. Comprehensive architectural blueprint of the proposed WRATTS-Net architecture, illustrating the polyphase LLWT decomposition, modified ResUNet stream, Bi-Directional Cross-Attention bridging, skip feature alignment loss ($\mathcal{L}_{\text{feat}}$), Sugeno fuzzy integral fusion, and multi-task HoVer distance regression.

Pre-activation Residual Blocks operating on $64, 128, 256, 512$ channels.

2.2.1. *Polyphase Decomposition (Split Step)*

Let $\mathbf{X} \in \mathbb{R}^{C\times H\times W}$ represent an incoming feature tensor at stage l, where H and W are even integers. The polyphase decomposition splits $\mathbf{X}$ into four non-overlapping sub-grids sampled at even and odd spatial coordinates:

$$x_{00}(c,i,j) = \mathbf{X}(c,2i,2j), \quad \text{(Even rows, Even columns - Reference)} \tag{7}$$

$$x_{01}(c,i,j) = \mathbf{X}(c,2i,2j+1), \quad \text{(Even rows, Odd columns - Horizontal)} \tag{8}$$

$$x_{10}(c,i,j) = \mathbf{X}(c,2i+1,2j), \quad \text{(Odd rows, Even columns - Vertical)} \tag{9}$$

$$x_{11}(c,i,j) = \mathbf{X}(c,2i+1,2j+1), \quad \text{(Odd rows, Odd columns - Diagonal)} \tag{10}$$

for $c \in \{1,\dots,C\}$, $i \in \{0,\dots,\frac{H}{2}-1\}$, and $j \in \{0,\dots,\frac{W}{2}-1\}$. Each polyphase component has spatial dimension $\mathbb{R}^{C\times\frac{H}{2}\times\frac{W}{2}}$.

2.2.2. *Stain-Adaptive Spatial Calibration (`StainAdapt`)*

Because histological slides exhibit substantial chromatic and photometric variance due to variable tissue staining, the correlation between adjacent polyphase components fluctuates across tissue sections. To normalize this variability prior to prediction, we design a calibration operator $\mathrm{StainAdapt}(\cdot)$ operating on the reference coset x_{00}:

$$\begin{aligned}\mathbf{y}_{\text{gap}} &= \mathrm{GAP}(x_{00}) \\ &= \frac{4}{HW}\sum_{i=0}^{\frac{H}{2}-1}\sum_{j=0}^{\frac{W}{2}-1} x_{00}(c,i,j) \in \mathbb{R}^{C\times1\times1}.\end{aligned} \tag{11}$$

The global descriptor $\mathbf{y}_{\text{gap}}$ is processed by a multi-layer perceptron with bottleneck reduction ratio $r = 4$:

$$\mathbf{s} = \sigma\Big(\mathbf{W}_2 \cdot \mathrm{ReLU}(\mathbf{W}_1\mathbf{y}_{\text{gap}} + \mathbf{b}_1) + \mathbf{b}_2\Big) \in \mathbb{R}^{C\times1\times1}, \tag{12}$$

where $\mathbf{W}_1 \in \mathbb{R}^{(\frac{C}{4}+1)\times C}$, $\mathbf{W}_2 \in \mathbb{R}^{C\times(\frac{C}{4}+1)}$, and $\sigma(z) = \frac{1}{1+e^{-z}}$ is the element-wise sigmoid function. The calibrated prediction is then computed as the Hadamard product:

$$S(x_{00}, f) = f \odot \mathbf{s}, \tag{13}$$

where $\odot$ denotes channel-wise broadcasting multiplication. This dynamically scales feature intensities according to global stain density.

2.2.3. *Learnable Directional Predict Step*

In the classical Haar wavelet, an odd sample is approximated by its adjacent even sample ($x_{01} \approx x_{00}$). In our learnable framework, we parameterize three dedicated depthwise convolutional operators $\mathcal{P}_h, \mathcal{P}_v, \mathcal{P}_d$ (one for each spatial orientation):

$$\begin{aligned}\mathcal{P}_k(x) = \mathrm{PReLU}\Big(\mathrm{BN}\big(\mathrm{DWConv}^{(k)}_{3\times3}(x)\big)\Big), \\ k \in \{h,v,d\},\end{aligned} \tag{14}$$

where $\mathrm{DWConv}_{3\times3}$ denotes a depthwise convolution with kernel size 3×3, padding 1, and groups equal to C.

The high-frequency detail sub-bands $d_h, d_v, d_d \in \mathbb{R}^{C\times\frac{H}{2}\times\frac{W}{2}}$ represent the prediction errors (residuals) along horizontal, vertical, and diagonal trajectories:

$$d_h = x_{01} - S_h\big(x_{00}, \mathcal{P}_h(x_{00})\big), \tag{15}$$

$$d_v = x_{10} - S_v\big(x_{00}, \mathcal{P}_v(x_{00})\big), \tag{16}$$

$$d_d = x_{11} - S_d\big(x_{00}, \mathcal{P}_d(x_{00})\big). \tag{17}$$

By design, if the local neighborhood is smooth and uniform, $\mathcal{P}(x_{00})$ accurately predicts the adjacent samples, yielding $d_k \approx \mathbf{0}$. Conversely, when a cellular border traverses the receptive field, d_k captures the sharp gradient discontinuity.

2.2.4. Learnable Directional Update Step

The reference component x_{00} alone is an aliased representation of the input. To maintain the running average energy and prevent aliasing, the update step modifies x_{00} by incorporating detail sub-bands through update operators $\mathcal{U}_h, \mathcal{U}_v, \mathcal{U}_d$ and learnable scalars $k_h, k_v, k_d \in \mathbb{R}$:

$$c_l = x_{00} + k_h \mathcal{U}_h(d_h) + k_v \mathcal{U}_v(d_v) + k_d \mathcal{U}_d(d_d), \tag{18}$$

where $\mathcal{U}_k(y) = \mathrm{PReLU}\left(\mathrm{BN}(\mathrm{DWConv}^{(k)}_{3\times3}(y))\right)$ and k_h, k_v, k_d are initialized to 1.0.

The resulting low-frequency coarse approximation $c_l \in \mathbb{R}^{C\times\frac{H}{2}\times\frac{W}{2}}$ retains generalized morphological structure. The complete sub-band representation is formed by concatenation:

$$\mathbf{X}_{\text{subbands}} = [c_l \,\|\, d_h \,\|\, d_v \,\|\, d_d] \in \mathbb{R}^{4C\times\frac{H}{2}\times\frac{W}{2}}, \tag{19}$$

which is projected to the next stage channel dimension via a 1×1 convolution:

$$\begin{aligned}\mathbf{X}_{\text{pooled}} &= \mathrm{ReLU}\left(\mathrm{BN}\left(\mathrm{Conv}_{1\times1}(\mathbf{X}_{\text{subbands}})\right)\right)\\ &\in \mathbb{R}^{2C\times\frac{H}{2}\times\frac{W}{2}}.\end{aligned} \tag{20}$$

Crucially, the detail sub-bands $\mathbf{D} = [d_h \,\|\, d_v \,\|\, d_d] \in \mathbb{R}^{3C\times\frac{H}{2}\times\frac{W}{2}}$ are preserved and routed across skip bridges directly to the decoder.

2.3. Mathematical Proof of Exact Invertibility

Theorem 1 (Exact Invertibility of the LLWT)**.** *Let $\mathbf{X}$ be decomposed into coarse approximation c_l and detail sub-bands d_h, d_v, d_d via the lifting equations (13)–(16). Then $\mathbf{X}$ can be reconstructed exactly, with zero numerical information loss, irrespective of the non-linearity, complexity, or parameterization of $\mathcal{P}_k$ and $\mathcal{U}_k$.*

Proof. Assume the detail sub-bands d_h, d_v, d_d and the approximation c_l are available at the decoder. From Equation (16), the reference polyphase component x_{00} can be isolated algebraically:

$$x_{00} = c_l - \Big(k_h \mathcal{U}_h(d_h) + k_v \mathcal{U}_v(d_v) + k_d \mathcal{U}_d(d_d)\Big). \tag{21}$$

Notice that the update terms $k_k \mathcal{U}_k(d_k)$ depend strictly on d_k, which are known constants during reconstruction. Thus, x_{00} is recovered with exact mathematical precision.

Having recovered x_{00}, the predict operators $\mathcal{P}_h, \mathcal{P}_v, \mathcal{P}_d$ and calibration functions S_h, S_v, S_d can be evaluated deterministically on x_{00}. From Equations (13)–(15), the remaining polyphase components are recovered by simple addition:

$$x_{01} = d_h + S_h\big(x_{00}, \mathcal{P}_h(x_{00})\big), \tag{22}$$

$$x_{10} = d_v + S_v\big(x_{00}, \mathcal{P}_v(x_{00})\big), \tag{23}$$

$$x_{11} = d_d + S_d\big(x_{00}, \mathcal{P}_d(x_{00})\big). \tag{24}$$

Finally, the original full-resolution tensor $\mathbf{X}$ is synthesized by interlacing the recovered components back onto the 2D Cartesian spatial lattice:

$$\mathbf{X}(c, 2i+m, 2j+n) = x_{mn}(c, i, j), \quad m, n \in \{0, 1\}. \tag{25}$$

Because no division by zero or non-invertible matrix operations occur, the reconstruction error $\left\|\mathbf{X} - \hat{\mathbf{X}}\right\|_\infty = 0$ up to standard machine floating-point precision. □

2.4. The Inverse Learnable Lifting Wavelet Transform (ILLWT) Decoder

In the wavelet decoder, an Inverse Learnable Lifting Wavelet Transform (`InverseLearnableLiftingWavelet2D`) acts as the exact adjoint operator. When upsampling from stage l to stage $l-1$, the decoder takes the coarse approximation feature map $\mathbf{x}_{\text{dec}} \in \mathbb{R}^{C_{\text{in}}\times H\times W}$ and projects it to match the skip channel width:

$$c_l = \mathrm{Conv}_{1\times1}(\mathbf{x}_{\text{dec}}) \in \mathbb{R}^{C_{\text{skip}}\times H\times W}. \tag{26}$$

The preserved detail sub-bands $\mathbf{D}_{l-1} = [d_h \,\|\, d_v \,\|\, d_d] \in \mathbb{R}^{3C_{\text{skip}}\times H\times W}$ are retrieved from the skip connection. The inverted update and predict equations are executed via learned parameters l_h, l_v, l_d:

$$x_{00} = c_l - \big(l_h \mathcal{U}'_h(d_h) + l_v \mathcal{U}'_v(d_v) + l_d \mathcal{U}'_d(d_d)\big), \tag{27}$$

$$x_{01} = d_h + \mathcal{P}'_h(x_{00}), \tag{28}$$

$$x_{10} = d_v + \mathcal{P}'_v(x_{00}), \tag{29}$$

$$x_{11} = d_d + \mathcal{P}'_d(x_{00}). \tag{30}$$

The reconstructed polyphase components are interlaced into a feature map of spatial size $2H\times2W$, which is added directly to the encoder skip feature $\mathbf{s}^w_{l-1}$:

$$\tilde{\mathbf{s}}^w_{l-1} = \mathbf{s}^w_{l-1} + \mathrm{ILLWT}(c_l, \mathbf{D}_{l-1}). \tag{31}$$

The decoder features $\mathbf{x}_{\text{dec}}$ are bilinearly interpolated to size $2H\times2W$, concatenated with $\tilde{\mathbf{s}}^w_{l-1}$, merged via a 1×1 convolution, and processed by residual blocks.

3. MATHEMATICAL FOUNDATIONS OF THE RESIDUAL STREAM

3.1. Pre-Activation Residual Blocks and Gradient Propagation

The residual stream leverages Pre-activation Residual Blocks (`ResBlock`). In conventional residual networks, the activation function (ReLU) is applied after the residual addition:

$$\mathbf{x}_{l+1} = f(\mathbf{x}_l + \mathcal{F}(\mathbf{x}_l)). \tag{32}$$

In our pre-activation configuration, Batch Normalization and ReLU precede the convolutional layers:

$$\mathbf{x}_{l+1} = \mathbf{x}_l + \mathcal{F}_{\text{pre}}(\mathbf{x}_l), \tag{33}$$

where $\mathcal{F}_{\text{pre}}(\mathbf{x}) = \mathbf{W}_2 * \mathrm{ReLU}\Big(\mathrm{BN}_2\big(\mathbf{W}_1 * \mathrm{ReLU}(\mathrm{BN}_1(\mathbf{x}))\big)\Big)$.

Lemma 1 (Clean Gradient Propagation in Pre-Activation Blocks)**.** *Under the formulation $\mathbf{x}_{l+1} = \mathbf{x}_l + \mathcal{F}(\mathbf{x}_l)$, the gradient of the total objective $\mathcal{L}$ with respect to an arbitrary early layer $\mathbf{x}_l$ decomposes into:*

$$\begin{aligned}\frac{\partial\mathcal{L}}{\partial\mathbf{x}_l} &= \frac{\partial\mathcal{L}}{\partial\mathbf{x}_L}\frac{\partial\mathbf{x}_L}{\partial\mathbf{x}_l}\\ &= \frac{\partial\mathcal{L}}{\partial\mathbf{x}_L}\left(\mathbf{I} + \frac{\partial}{\partial\mathbf{x}_l}\sum_{i=l}^{L-1}\mathcal{F}(\mathbf{x}_i)\right),\end{aligned} \tag{34}$$

where L denotes the deepest layer and $\mathbf{I}$ is the identity matrix.

Proof. By recursive expansion of the identity connection:

$$\mathbf{x}_L = \mathbf{x}_l + \sum_{i=l}^{L-1} \mathcal{F}(\mathbf{x}_i). \tag{35}$$

Differentiating with respect to $\mathbf{x}_l$ via the multivariate chain rule directly yields the term $\mathbf{I}$. Even if the term $\frac{\partial}{\partial \mathbf{x}_l} \sum_{i=l}^{L-1} \mathcal{F}(\mathbf{x}_i)$ vanishes or exhibits extreme gradient decay, the identity term $\mathbf{I}$ ensures that gradients backpropagate unimpeded directly from layer L to layer l, eliminating vanishing gradients. □

3.2. Modified ResUNet 4-Stage Hierarchy and GeM Pooling

The ResUNet stream (r) is structured into four hierarchical encoder stages with $3, 3, 4, 3$ pre-activation residual blocks per stage (operating across $64, 128, 256, 512$ feature channels). Spatial downsampling at each stage is performed by a dedicated Generalized Mean (GeM) downsampling block (`GeMDownsample`), which executes 2×2 GeM pooling followed by a 1×1 convolution that projects the feature dimension from C to $2C$:

$$f_{\text{GeM}}(\mathbf{x}) = \left(\frac{1}{|\Omega|} \sum_{i \in \Omega} x_i^p \right)^{1/p}, \quad p \geq 1. \tag{36}$$

where Ω represents a 2×2 spatial pooling window, $x_i = \max(x_i', \epsilon)$ with $\epsilon = 10^{-6}$ to prevent numerical instability, and $p \geq 1$ is an unconstrained learnable parameter initialized to 3.0.

3.2.1. Theoretical Limiting Behaviors of GeM

The GeM operator provides continuous, differentiable interpolation between arithmetic mean and maximum operations:

- When $p = 1$:

$$\lim_{p \to 1} f_{\text{GeM}}(\mathbf{x}) = \frac{1}{|\Omega|} \sum_{i \in \Omega} x_i = f_{\text{avg}}(\mathbf{x}). \tag{37}$$

- When $p \to \infty$:

$$\begin{aligned} \lim_{p \to \infty} f_{\text{GeM}}(\mathbf{x}) &= \lim_{p \to \infty} \left(\frac{1}{|\Omega|} \sum_{i \in \Omega} x_i^p \right)^{1/p} \\ &= x_{\max} \cdot \lim_{p \to \infty} \left(\frac{1}{|\Omega|} \sum_{i \in \Omega} \left(\frac{x_i}{x_{\max}} \right)^p \right)^{1/p} \\ &= x_{\max} = \max_{i \in \Omega} x_i. \end{aligned} \tag{38}$$

3.2.2. Gradient Derivation with Respect to the Learnable Parameter p

Because p is optimized via gradient descent, we derive its exact analytical derivative. Let $S = \frac{1}{|\Omega|} \sum_{i \in \Omega} x_i^p$. Then $f = S^{1/p}$. Taking the natural logarithm:

$$\ln f = \frac{1}{p} \ln S. \tag{39}$$

Differentiating with respect to p:

$$\frac{1}{f} \frac{\partial f}{\partial p} = -\frac{1}{p^2} \ln S + \frac{1}{p} \frac{1}{S} \frac{\partial S}{\partial p}. \tag{40}$$

Since $\frac{\partial S}{\partial p} = \frac{1}{|\Omega|} \sum_{i \in \Omega} x_i^p \ln x_i$:

$$\frac{\partial f_{\text{GeM}}}{\partial p} = \frac{f_{\text{GeM}}}{p} \left[\frac{\sum_{i \in \Omega} x_i^p \ln x_i}{\sum_{i \in \Omega} x_i^p} - \frac{\ln \left(\frac{1}{|\Omega|} \sum_{i \in \Omega} x_i^p \right)}{p} \right]. \tag{41}$$

This derivative enables the network to automatically adjust pooling sharpness per channel: learning high p values for sharp nuclear boundary channels and low p values for smooth stromal context channels.

3.3. Skip-Connection Feature Alignment Loss ($\mathcal{L}_{\text{feat}}$)

In classical U-Net architectures, an inherent semantic discrepancy exists between the high-resolution, low-level features of early encoder stages and the upsampled, high-level features of the decoder. Directly concatenating them introduces representational conflict.

To bridge this semantic gap, the ResUNet decoder features four stages with $3, 4, 3, 3$ residual blocks. Each decoder block (`DecoderBlockRes`) executes 2×2 transposed convolution upsampling:

$$\mathbf{u}_l^r = \text{ConvTranspose2d}_{2\times2}(\mathbf{x}_{l+1}^r) \in \mathbb{R}^{C_l \times H_l \times W_l}, \tag{42}$$

prior to concatenation with the encoder skip feature $\mathbf{s}_l^r$. We formulate a dedicated normalized MSE feature alignment objective across all four stages $l \in \{1, 2, 3, 4\}$:

$$\mathcal{L}_{\text{feat}} = \sum_{l=1}^{4} \text{MSE} \left(\frac{\mathbf{u}_l^r}{\|\mathbf{u}_l^r\|_2 + \epsilon}, \frac{\mathbf{s}_l^r}{\|\mathbf{s}_l^r\|_2 + \epsilon} \right), \tag{43}$$

where the L_2 norm is computed along the channel dimension at each spatial coordinate (i, j):

$$\|\mathbf{v}(i,j)\|_2 = \sqrt{\sum_{c=1}^{C} v(c,i,j)^2}. \tag{44}$$

3.3.1. Theoretical Analysis of Feature Alignment

Let $\hat{\mathbf{u}} = \mathbf{u}/\|\mathbf{u}\|_2$ and $\hat{\mathbf{s}} = \mathbf{s}/\|\mathbf{s}\|_2$ be unit-norm channel vectors. Expanding the squared Euclidean norm:

$$\begin{aligned} \|\hat{\mathbf{u}} - \hat{\mathbf{s}}\|_2^2 &= \|\hat{\mathbf{u}}\|_2^2 + \|\hat{\mathbf{s}}\|_2^2 - 2\langle \hat{\mathbf{u}}, \hat{\mathbf{s}} \rangle \\ &= 1 + 1 - 2\cos(\theta) = 2\big(1 - \cos(\theta)\big), \end{aligned} \tag{45}$$

where $\cos(\theta)$ is the cosine similarity between the encoder skip feature and the decoder upsampled feature. Minimizing $\mathcal{L}_{\text{feat}}$ is mathematically identical to maximizing directional alignment in the feature latent space while remaining invariant to arbitrary magnitude scaling. This forces the decoder to reconstruct representations that preserve the semantic subspace spanned by the encoder.

4. ATROUS SPATIAL PYRAMID POOLING (ASPP) BOTTLENECK

4.1. Receptive Field and Dilated Convolutions

At the deepest layer of both branches, feature maps reach a spatial dimension of $\frac{H}{16} \times \frac{W}{16}$ with 1024 channels. To capture long-range contextual relationships (e.g., global tissue architecture, glandular orientation) without further reducing spatial

Table 1. Exhaustive layer-by-layer architectural tensor dimension tracing, kernel specifications, and exact parameter allocations across all modules of WRATTS-Net for an input patch of shape $[B, 3, 256, 256]$ (Total Parameters: 133,013,984).

Module / Layer	Input Tensor Shape	Output Tensor Shape	Kernel (K)	Stride (S)	Pad (P)	Dil (D)	Parameters
Wavelet Multi-Resolution Stream (LLWT Encoder)							
Stage 1: `enc1_w.blocks` (3 ResBlocks)	$[B, 3, 256, 256]$	$[B, 64, 256, 256]$	$3 \times 3, 1 \times 1$	1	1	1	186,886
Stage 1: `enc1_w.downsample` (LLWT 64)	$[B, 64, 256, 256]$	$[B, 128, 128, 128]$	3×3 (DW), 1×1	1	1	1	43,785
↪ Detail Bypass $\mathbf{D}_1$	–	$[B, 192, 128, 128]$	–	–	–	–	(Routed to Skip/HV)
Stage 2: `enc2_w.blocks` (3 ResBlocks)	$[B, 128, 128, 128]$	$[B, 128, 128, 128]$	3×3	1	1	1	886,272
Stage 2: `enc2_w.downsample` (LLWT 128)	$[B, 128, 128, 128]$	$[B, 256, 64, 64]$	3×3 (DW), 1×1	1	1	1	165,385
↪ Detail Bypass $\mathbf{D}_2$	–	$[B, 384, 64, 64]$	–	–	–	–	(Routed to Skip)
Stage 3: `enc3_w.blocks` (4 ResBlocks)	$[B, 256, 64, 64]$	$[B, 256, 64, 64]$	3×3	1	1	1	4,722,688
Stage 3: `enc3_w.downsample` (LLWT 256)	$[B, 256, 64, 64]$	$[B, 512, 32, 32]$	3×3 (DW), 1×1	1	1	1	642,057
↪ Detail Bypass $\mathbf{D}_3$	–	$[B, 768, 32, 32]$	–	–	–	–	(Routed to Skip)
Stage 4: `enc4_w.blocks` (3 ResBlocks)	$[B, 512, 32, 32]$	$[B, 512, 32, 32]$	3×3	1	1	1	14,161,920
Stage 4: `enc4_w.downsample` (LLWT 512)	$[B, 512, 32, 32]$	$[B, 1024, 16, 16]$	3×3 (DW), 1×1	1	1	1	2,529,289
↪ Detail Bypass $\mathbf{D}_4$	–	$[B, 1536, 16, 16]$	–	–	–	–	(Routed to Skip)
Modified ResUNet Semantic Stream (Encoder)							
Stage 1: `enc1_r.blocks` (3 ResBlocks)	$[B, 3, 256, 256]$	$[B, 64, 256, 256]$	$3 \times 3, 1 \times 1$	1	1	1	186,886
Stage 1: `enc1_r.downsample` (GeM 64)	$[B, 64, 256, 256]$	$[B, 128, 128, 128]$	2×2 (GeM), 1×1	2	0	1	8,193
Stage 2: `enc2_r.blocks` (3 ResBlocks)	$[B, 128, 128, 128]$	$[B, 128, 128, 128]$	3×3	1	1	1	886,272
Stage 2: `enc2_r.downsample` (GeM 128)	$[B, 128, 128, 128]$	$[B, 256, 64, 64]$	2×2 (GeM), 1×1	2	0	1	32,769
Stage 3: `enc3_r.blocks` (4 ResBlocks)	$[B, 256, 64, 64]$	$[B, 256, 64, 64]$	3×3	1	1	1	4,722,688
Stage 3: `enc3_r.downsample` (GeM 256)	$[B, 256, 64, 64]$	$[B, 512, 32, 32]$	2×2 (GeM), 1×1	2	0	1	131,073
Stage 4: `enc4_r.blocks` (3 ResBlocks)	$[B, 512, 32, 32]$	$[B, 512, 32, 32]$	3×3	1	1	1	14,161,920
Stage 4: `enc4_r.downsample` (GeM 512)	$[B, 512, 32, 32]$	$[B, 1024, 16, 16]$	2×2 (GeM), 1×1	2	0	1	524,289
Bottlenecks and Multi-Scale Bi-Directional Cross-Attention (BiCA)							
Encoder BiCA 1 (`att_e1`)	$[B, 128, 128, 128] \times 2$	$[B, 128, 128, 128] \times 2$	1×1	1	0	1	133,120
Encoder BiCA 2 (`att_e2`)	$[B, 256, 64, 64] \times 2$	$[B, 256, 64, 64] \times 2$	1×1	1	0	1	528,384
Encoder BiCA 3 (`att_e3`)	$[B, 512, 32, 32] \times 2$	$[B, 512, 32, 32] \times 2$	1×1	1	0	1	2,105,344
Encoder BiCA 4 (`att_e4`)	$[B, 1024, 16, 16] \times 2$	$[B, 1024, 16, 16] \times 2$	1×1	1	0	1	8,404,992
ASPP Bottleneck (Wavelet Stream, `bot_w`)	$[B, 1024, 16, 16]$	$[B, 1024, 16, 16]$	$\{1, 3, 3, 3\}$	1	$\{0, 1, 4, 7\}$	$\{1, 1, 4, 7\}$	10,525,696
ASPP Bottleneck (ResNet Stream, `bot_r`)	$[B, 1024, 16, 16]$	$[B, 1024, 16, 16]$	$\{1, 3, 3, 3\}$	1	$\{0, 1, 4, 7\}$	$\{1, 1, 4, 7\}$	10,525,696
Bottleneck BiCA (`att_b`)	$[B, 1024, 16, 16] \times 2$	$[B, 1024, 16, 16] \times 2$	1×1	1	0	1	8,404,992
Symmetrical Decoders and Intermediate Cross-Attention Bridges							
Wavelet Decoder Stage 4 (`dec4_w`)	$[B, 1024, 16, 16]$	$[B, 512, 32, 32]$	ILLWT, $1 \times 1, 3 \times 3$	1	1	1	15,507,465
ResUNet Decoder Stage 4 (`dec4_r`)	$[B, 1024, 16, 16]$	$[B, 512, 32, 32]$	2×2 (T), $1 \times 1, 3 \times 3$	2	0	1	16,784,896
Decoder BiCA 4 (`att_d4`)	$[B, 512, 32, 32] \times 2$	$[B, 512, 32, 32] \times 2$	1×1	1	0	1	2,105,344
Wavelet Decoder Stage 3 (`dec3_w`)	$[B, 512, 32, 32]$	$[B, 256, 64, 64]$	ILLWT, $1 \times 1, 3 \times 3$	1	1	1	5,067,785
ResUNet Decoder Stage 3 (`dec3_r`)	$[B, 512, 32, 32]$	$[B, 256, 64, 64]$	2×2 (T), $1 \times 1, 3 \times 3$	2	0	1	5,378,816
Decoder BiCA 3 (`att_d3`)	$[B, 256, 64, 64] \times 2$	$[B, 256, 64, 64] \times 2$	1×1	1	0	1	528,384
Wavelet Decoder Stage 2 (`dec2_w`)	$[B, 256, 64, 64]$	$[B, 128, 128, 128]$	ILLWT, $1 \times 1, 3 \times 3$	1	1	1	976,905
ResUNet Decoder Stage 2 (`dec2_r`)	$[B, 256, 64, 64]$	$[B, 128, 128, 128]$	2×2 (T), $1 \times 1, 3 \times 3$	2	0	1	1,050,496
Decoder BiCA 2 (`att_d2`)	$[B, 128, 128, 128] \times 2$	$[B, 128, 128, 128] \times 2$	1×1	1	0	1	133,120
Wavelet Decoder Stage 1 (`dec1_w`)	$[B, 128, 128, 128]$	$[B, 64, 256, 256]$	ILLWT, $1 \times 1, 3 \times 3$	1	1	1	246,793
ResUNet Decoder Stage 1 (`dec1_r`)	$[B, 128, 128, 128]$	$[B, 64, 256, 256]$	2×2 (T), $1 \times 1, 3 \times 3$	2	0	1	263,104
Decoder BiCA 1 (`att_d1`)	$[B, 64, 256, 256] \times 2$	$[B, 64, 256, 256] \times 2$	1×1	1	0	1	33,792
Multi-Task Prediction Heads and Sugeno Fuzzy Fusion							
Wavelet Segmentation Head (`head_w`)	$[B, 64, 256, 256]$	$[B, 1, 256, 256]$	1×1	1	0	1	2,113
ResUNet Segmentation Head (`head_r`)	$[B, 64, 256, 256]$	$[B, 1, 256, 256]$	1×1	1	0	1	2,113
Sugeno Fuzzy Integral Fusion (`sugeno`)	$[B, 1, 256, 256] \times 2$	$[B, 1, 256, 256]$	Element-wise	–	–	–	2 (θ_1, θ_2)
Deep Supervision Auxiliary Head 3 (`aux_head3`)	$[B, 512, 64, 64]$	$[B, 1, 256, 256]$	$1 \times 1 +$ Bilinear	1	0	1	131,585
Deep Supervision Auxiliary Head 2 (`aux_head2`)	$[B, 256, 128, 128]$	$[B, 1, 256, 256]$	$1 \times 1 +$ Bilinear	1	0	1	33,025
HoVer-Net Distance Regression Head (`hv_head`)	$[B, 256, 256, 256]$	$[B, 2, 256, 256]$	$3 \times 3, 1 \times 1$	1	1	1	147,650
Total Network Parameters	**WRATTS-Net Dual-Branch End-to-End System**						**133,013,984**

resolution, we deploy an Atrous Spatial Pyramid Pooling module on both streams.

A 2D dilated convolution with dilation rate r is defined over input $\mathbf{x}$ as:

$$\mathbf{y}(i,j) = \sum_{m=-1}^{1} \sum_{n=-1}^{1} \mathbf{x}(i + r \cdot m,\ j + r \cdot n) \cdot \mathbf{W}(m,n). \tag{46}$$

The effective kernel size K_{eff} of a $K \times K$ filter dilated by rate r is:

$$K_{\text{eff}} = K + (K-1)(r-1). \tag{47}$$

For $K = 3$ and rates $r \in \{1, 4, 7\}$, the effective receptive fields span 3×3, 9×9, and 15×15, respectively.

4.2. Depthwise-Separable Efficiency (`DWSepConvBNReLU`)

Standard 3×3 convolutions on a 1024-channel tensor incur prohibitive computational expense:

$$\text{FLOPs}_{\text{std}} = 2 \cdot H \cdot W \cdot K^2 \cdot C_{\text{in}} \cdot C_{\text{out}} = 18 \cdot C^2 \cdot H \cdot W. \tag{48}$$

We replace standard convolutions in the dilated branches with Depthwise-Separable Convolutions (`DWSepConvBNReLU`):

1. **Depthwise Convolution:** Applies a single 3×3 spatial filter per channel (groups $= C$):

$$\text{FLOPs}_{\text{dw}} = 2 \cdot H \cdot W \cdot K^2 \cdot C = 18 \cdot C \cdot HW. \tag{49}$$

2. **Pointwise Convolution:** Applies a 1×1 convolution across all channels:

$$\text{FLOPs}_{\text{pw}} = 2 \cdot H \cdot W \cdot 1 \cdot C \cdot C = 2 \cdot C^2 \cdot HW. \tag{50}$$

The computational reduction ratio $\mathcal{R}$ is given by:

$$\begin{aligned}\mathcal{R} &= \frac{\text{FLOPs}_{\text{dw}} + \text{FLOPs}_{\text{pw}}}{\text{FLOPs}_{\text{std}}} \\ &= \frac{18 \cdot C \cdot HW + 2 \cdot C^2 \cdot HW}{18 \cdot C^2 \cdot HW} = \frac{1}{C} + \frac{1}{9} \approx \frac{1}{9}.\end{aligned} \tag{51}$$

This achieves an $\approx 8.9\times$ reduction in computational burden, preventing memory saturation on NVIDIA T4 GPUs.

The ASPP bottleneck incorporates:

(i) One 1×1 convolutional branch ($\text{Conv}_{1\times1} \rightarrow \text{BN} \rightarrow \text{ReLU}$),

(ii) Three depthwise-separable branches with dilation rates $r \in \{1, 4, 7\}$,

(iii) One Image Global Average Pooling branch ($\text{AdaptiveAvgPool2D}(1) \rightarrow \text{Conv}_{1\times1} \rightarrow \text{BN} \rightarrow \text{ReLU} \rightarrow \text{BilinearInterpolate}$),

(iv) Feature concatenation and projection with 2D spatial dropout ($p = 0.1$):

$$\mathbf{x}_{\text{bot}} = \text{Dropout2D}_{0.1}\left(\text{Conv}_{1\times1}\left([\mathbf{b}_0 \parallel \mathbf{b}_1 \parallel \mathbf{b}_2 \parallel \mathbf{b}_3 \parallel \mathbf{b}_{\text{pool}}]\right)\right). \tag{52}$$

5. MULTI-SCALE BI-DIRECTIONAL CROSS-ATTENTION (BICA)

5.1. Why Channel Cross-Attention Over Spatial Self-Attention?

Standard spatial self-attention operates over spatial tokens $N = HW$. For an input crop of 256×256, the number of tokens is $N = 65,536$. Constructing the spatial attention map requires an affinity matrix of size $N \times N$, entailing $(65,536)^2 \approx 4.29 \times 10^9$ elements per attention head, exceeding 16 GB of GPU memory for a single matrix.

To eliminate this quadratic bottleneck, we formulate an efficient channel-wise cross-attention mechanism where spatial coordinates act as sample instances and channels act as features. The attention affinity matrix operates in channel space:

$$\mathbf{A} \in \mathbb{R}^{C\times C}, \tag{53}$$

which is entirely invariant to spatial resolution and requires minimal memory ($C \leq 1024$).

5.2. Mathematical Formulation

Let $\mathbf{x}_q \in \mathbb{R}^{C\times H\times W}$ represent the query stream tensor and $\mathbf{x}_{kv} \in \mathbb{R}^{C\times H\times W}$ represent the key-value stream tensor. Both tensors are flattened along spatial dimensions into matrices of dimension $\mathbb{R}^{C\times N}$, where $N = HW$.

5.2.1. Projections

Queries $\mathbf{Q}$, Keys $\mathbf{K}$, and Values $\mathbf{V}$ are generated using 1×1 convolutions followed by Batch Normalization to stabilize activation variance:

$$\mathbf{Q} = \text{BN}\left(\text{Conv}_{1\times1}(\mathbf{x}_q)\right) \in \mathbb{R}^{C\times N}, \tag{54}$$

$$\mathbf{K} = \text{BN}\left(\text{Conv}_{1\times1}(\mathbf{x}_{kv})\right) \in \mathbb{R}^{C\times N}, \tag{55}$$

$$\mathbf{V} = \text{Conv}_{1\times1}(\mathbf{x}_{kv}) \in \mathbb{R}^{C\times N}. \tag{56}$$

5.2.2. Scaled Channel Affinity and Aggregation

The channel affinity matrix $\mathbf{A} \in \mathbb{R}^{C\times C}$ measures the cross-covariance between channel i of the query stream and channel j of the key stream:

$$\mathbf{A}_{i,j} = \frac{\sum_{k=1}^{N} \mathbf{Q}_{i,k}\mathbf{K}_{j,k}}{\sqrt{N}} = \frac{1}{\sqrt{N}}\langle \mathbf{Q}_{i,:}, \mathbf{K}_{j,:}\rangle, \tag{57}$$

where scaling by $\frac{1}{\sqrt{N}}$ stabilizes the variance across varying spatial token counts. Applying the Softmax activation row-wise:

$$\tilde{\mathbf{A}}_{i,j} = \frac{\exp(\mathbf{A}_{i,j})}{\sum_{m=1}^{C}\exp(\mathbf{A}_{i,m})}, \quad \sum_{j=1}^{C}\tilde{\mathbf{A}}_{i,j} = 1. \tag{58}$$

The attended representation is formed by multiplying the affinity matrix with the value matrix:

$$\mathbf{O} = \tilde{\mathbf{A}}\mathbf{V} \in \mathbb{R}^{C\times N}. \tag{59}$$

Reshaping $\mathbf{O}$ back to spatial dimension $C \times H \times W$, the output is passed through an output projection module:

$$\hat{\mathbf{x}}_q = \mathbf{x}_q + \mathbf{W}_{\text{out}}(\mathbf{O}), \tag{60}$$

where $\mathbf{W}_{\text{out}}$ consists of a 1×1 convolution followed by Batch Normalization.

5.3. Zero-Initialized Identity Mapping Proof

Theorem 2 (Training Stability via Zero-Initialized Identity Mapping)**.** *If the weight parameter γ and bias β of the Batch Normalization layer in $\mathbf{W}_{out}$ are initialized to zero:*

$$\gamma_{init} = 0, \quad \beta_{init} = 0, \tag{61}$$

then the cross-attention module acts as an exact identity operator at initialization:

$$\hat{\mathbf{x}}_q^{(0)} \equiv \mathbf{x}_q^{(0)}, \tag{62}$$

guaranteeing that early gradient updates do not destabilize feature representations.

Proof. Let $\mathbf{z} = \text{Conv}_{1\times1}(\mathbf{O})$ be the pre-normalization features. The Batch Normalization transform is:

$$\text{BN}(\mathbf{z}) = \gamma\left(\frac{\mathbf{z} - \mu}{\sqrt{\sigma^2 + \epsilon}}\right) + \beta. \tag{63}$$

Setting $\gamma = 0$ and $\beta = 0$:

$$\text{BN}(\mathbf{z}) = 0 \cdot \left(\frac{\mathbf{z} - \mu}{\sqrt{\sigma^2 + \epsilon}}\right) + 0 = \mathbf{0}. \tag{64}$$

Substituting into Equation (48):

$$\hat{\mathbf{x}}_q = \mathbf{x}_q + \mathbf{0} = \mathbf{x}_q. \tag{65}$$

Thus, at step $t = 0$, each branch processes features independently as if cross-attention were absent. As training progresses, backpropagation gracefully tunes γ away from zero, smoothly injecting cross-stream interactions. □

5.4. Bi-Directional Exchange Scheme

The BiCrossAttention module executes mutual queries simultaneously:

$$\hat{\mathbf{x}}_w = \text{CrossAttention}(\mathbf{x}_q = \mathbf{x}_w, \mathbf{x}_{kv} = \mathbf{x}_r), \tag{66}$$

$$\hat{\mathbf{x}}_r = \text{CrossAttention}(\mathbf{x}_q = \mathbf{x}_r, \mathbf{x}_{kv} = \mathbf{x}_w). \tag{67}$$

This exchange is deployed across 9 distinct junction points in WRATTS-Net:

- Encoder stages 1, 2, 3, 4 ($C \in \{128, 256, 512, 1024\}$),
- ASPP Bottleneck ($C = 1024$),
- Decoder stages 4, 3, 2, 1 ($C \in \{512, 256, 128, 64\}$).

6. THEORY OF FUZZY MEASURES AND SUGENO FUZZY INTEGRAL FUSION

6.1. Why Linear or Gated Fusion Fails

Conventional multi-stream segmentation networks combine output logits via concatenation ($\mathrm{Conv}_{1\times1}([\mathbf{z}_1 \parallel \mathbf{z}_2])$), element-wise addition, or simple averaging ($p = \frac{p_1+p_2}{2}$). These operations assume:

1. **Spatial Homogeneity:** The reliability of stream 1 versus stream 2 is assumed constant across the image.
2. **Additive Independence:** The joint information of both streams is assumed to equal the sum of their individual contributions.

In histopathology, these assumptions are invalid. In smooth nuclear centers, deep residual features are highly reliable while wavelet high-frequency bands contain zero energy. At nuclear boundaries, high-frequency wavelet sub-bands are precise while residual representations suffer spatial blur. Non-additive fuzzy integrals model these non-linear interactions explicitly.

6.2. Mathematical Formulation of Fuzzy Measures

Let $X = \{x_1, x_2\}$ be the set of information sources (branch 1: Wavelet stream, branch 2: ResNet stream). The power set $\mathcal{P}(X) = \{\emptyset, \{x_1\}, \{x_2\}, \{x_1, x_2\}\}$ represents all possible subsets of criteria.

Definition 1 (Fuzzy Measure)**.** *A fuzzy measure $g : \mathcal{P}(X) \to [0, 1]$ satisfies:*

(i) Boundary conditions: $g(\emptyset) = 0$ and $g(X) = 1$.

(ii) Monotonicity: If $A \subseteq B \subseteq X$, then $g(A) \leq g(B)$.

The values $g_1 = g(\{x_1\})$ and $g_2 = g(\{x_2\})$ are termed *fuzzy densities*. In Sugeno λ-fuzzy measures:

$$g(A \cup B) = g(A) + g(B) + \lambda g(A)g(B), \quad \lambda > -1. \tag{68}$$

When $\lambda = 0$, the measure is additive (standard probability). When $\lambda > 0$, the sources exhibit synergistic reinforcement; when $\lambda < 0$, they exhibit redundant overlap.

6.3. Derivation of the Sugeno Fuzzy Integral for $N = 2$

Let $h : X \to [0, 1]$ be the evidence function corresponding to predicted probabilities: $h(x_1) = p_w \in [0, 1]$ and $h(x_2) = p_r \in [0, 1]$.

Definition 2 (Sugeno Fuzzy Integral)**.** *The Sugeno fuzzy integral of h with respect to fuzzy measure g is defined as:*

$$\mathcal{S}_g(h) = \sup_{\alpha\in[0,1]} \Big[\alpha \wedge g\big(\{x \in X \mid h(x) \geq \alpha\}\big)\Big], \tag{69}$$

where $\wedge$ denotes the minimum operator ($\min$).

Theorem 3 (Closed-Form Representation for Two Branches)**.** *For two information sources $X = \{x_1, x_2\}$ with predicted probabilities $p_1, p_2 \in [0, 1]$ and singleton fuzzy densities $g_1, g_2 \in [0, 1]$, the Sugeno fuzzy integral admits the closed-form analytical expression:*

$$p_{\mathit{fused}} = \max\Big(\min\big(\max(p_1, p_2),\, g_{\max}\big),\, \min(p_1, p_2)\Big), \tag{70}$$

where $g_{\max} = g_1$ if $p_1 \geq p_2$, and $g_{\max} = g_2$ if $p_2 > p_1$.

Proof. Sort the evidence values in descending order:

$$h_{(1)} = \max(p_1, p_2), \quad h_{(2)} = \min(p_1, p_2). \tag{71}$$

Let $x_{(1)}$ denote the index of the dominant stream such that $h(x_{(1)}) = h_{(1)}$. The evaluation sets $F_i = \{x \in X \mid h(x) \geq h_{(i)}\}$ are:

$$F_1 = \{x_{(1)}\}, \tag{72}$$

$$F_2 = \{x_{(1)}, x_{(2)}\} = X. \tag{73}$$

By the boundary condition of fuzzy measures, $g(F_2) = g(X) = 1$. The fuzzy measure of F_1 is the singleton density corresponding to the dominant stream:

$$g(F_1) = g(\{x_{(1)}\}) = g_{\max} = \begin{cases} g_1, & \text{if } p_1 \geq p_2, \\ g_2, & \text{if } p_2 > p_1. \end{cases} \tag{74}$$

In discrete form, the Sugeno integral simplifies to:

$$\mathcal{S}_g(h) = \max_{i=1,2} \Big[h_{(i)} \wedge g(F_i)\Big]. \tag{75}$$

Evaluating the terms inside the maximum:

Term 1: $h_{(1)} \wedge g(F_1) = \min(h_{(1)}, g_{\max}) = \min\big(\max(p_1, p_2), g_{\max}\big)$, (76)

Term 2: $h_{(2)} \wedge g(F_2) = \min(h_{(2)}, 1) = h_{(2)} = \min(p_1, p_2)$. (77)

Taking the supremum over both terms:

$$\mathcal{S}_g(h) = \max\Big(\min\big(\max(p_1, p_2), g_{\max}\big),\, \min(p_1, p_2)\Big). \tag{78}$$

This completes the proof. □

6.4. Differentiable Parameterization and Logit Reconstruction

To learn the optimal fuzzy densities end-to-end via gradient descent, g_1 and g_2 are parameterized as unconstrained real-valued logits $\theta_1, \theta_2 \in \mathbb{R}$:

$$g_1 = \sigma(\theta_1) = \frac{1}{1 + e^{-\theta_1}}, \quad g_2 = \sigma(\theta_2) = \frac{1}{1 + e^{-\theta_2}}. \tag{79}$$

Both logits are initialized to $\theta_1 = 0.0, \theta_2 = 0.0$, ensuring initial densities $g_1 = 0.5, g_2 = 0.5$.

Because the downstream loss function (`BCEWithLogitsLoss`) accepts raw un-activated logits to leverage log-sum-exp numerical stabilization, the fused probability $p_{\text{fused}} \in [0, 1]$ is transformed back to logit space via the clamped inverse sigmoid:

$$\begin{aligned} \mathbf{z}_{\text{fused}} &= \mathrm{logit}(p_{\text{fused}}, \epsilon) \\ &= \ln(p_{\text{fused}} + \epsilon) - \ln(1 - p_{\text{fused}} + \epsilon). \end{aligned} \tag{80}$$

6.5. Pedagogical Walkthrough: How Sugeno Fusion Works in Practice

To understand this intuitively, consider three distinct physical scenarios in histopathology:

1. **Unambiguous Foreground (Cell Center):** Both streams output high probability: $p_w = 0.95, p_r = 0.90$.
   - $h_1 = 0.95, h_2 = 0.90$.
   - $g_{\max} = g_1 \approx 0.6$.
   - Term 1: $\min(0.95, 0.6) = 0.6$.
   - Term 2: $\min(p_w, p_r) = 0.90$.
   - $p_{\text{fused}} = \max(0.6, 0.90) = 0.90$.
   - *Outcome:* When both branches agree that a pixel is cell, the fused prediction retains the high probability regardless of $g_{\max}$.
2. **Unambiguous Background (Stroma):** Both streams output low probability: $p_w = 0.02, p_r = 0.05$.
   - $h_1 = 0.05, h_2 = 0.02$.
   - Term 1: $\min(0.05, g_{\max}) = 0.05$.
   - Term 2: 0.02.
   - $p_{\text{fused}} = \max(0.05, 0.02) = 0.05$.
   - *Outcome:* Background noise remains suppressed.
3. **Ambiguous Boundary Pixel (Disagreement):** The ResNet stream suffers boundary blur and predicts background ($p_r = 0.20$), but the Wavelet stream detects a sharp edge ($p_w = 0.85$).
   - $h_1 = 0.85, h_2 = 0.20$. Dominant stream is Wavelet ($g_{\max} = g_1$).
   - Term 1: $\min(0.85, g_1) = g_1$.
   - Term 2: $\min(0.85, 0.20) = 0.20$.
   - $p_{\text{fused}} = \max(g_1, 0.20) = g_1$.
   - *Outcome:* The learned fuzzy density g_1 acts as an adaptive confidence gate. If the network has learned that the Wavelet branch is highly trustworthy along boundaries ($g_1 = 0.80$), the fused probability jumps to 0.80, preserving the sharp border.

7. MULTI-TASK LEARNING AND COMPOSITE LOSS FORMULATION

7.1. Composite Objective

WRATTS-Net is optimized end-to-end under a composite objective:

$$\mathcal{L}_{\text{total}} = \mathcal{L}_{\text{seg}} + \lambda_f \mathcal{L}_{\text{feat}} + \lambda_{\text{hv}} \mathcal{L}_{\text{hv}} + \lambda_b \mathcal{L}_{\text{boundary}}, \tag{81}$$

with loss balancing hyper-parameters $\lambda_f = 0.1$, $\lambda_{hv} = 1.0$, and $\lambda_b = 0.15$.

7.2. Focal Tversky Loss with Weighted BCE

Nuclear segmentation exhibits severe class imbalance: in typical biopsy images, background stroma occupies 70–85% of pixels, while nuclei occupy only 15–30%.

7.2.1. Tversky Index Formulation

The Tversky index generalizes the Dice coefficient (F_1) by decoupling penalties assigned to False Positives (FP) and False Negatives (FN):

$$TI(\mathbf{p}, \mathbf{y}) = \frac{\sum_i p_i y_i + 1.0}{\sum_i p_i y_i + \alpha \sum_i p_i (1 - y_i) + \beta \sum_i (1 - p_i) y_i + 1.0}. \tag{82}$$

where $p_i = \sigma(z_i)$ is the predicted foreground probability, $y_i \in \{0, 1\}$ is the ground truth, and smoothing is set to 1.0. Setting $\alpha = 0.7$ and $\beta = 0.3$ penalizes False Negatives more heavily, preventing missed nuclear regions.

7.2.2. Focal Exponent

To prevent well-classified background pixels from dominating the gradient update, we apply a focal modulation exponent $\gamma = 0.75$:

$$\mathcal{L}_{\text{FT}} = \big(1 - TI(\mathbf{p}, \mathbf{y})\big)^{0.75}. \tag{83}$$

7.2.3. Weighted Binary Cross-Entropy

The Focal Tversky loss is combined with positive-weighted Binary Cross-Entropy:

$$\mathcal{L}_{\text{BCE}}(\mathbf{z}, \mathbf{y}) = -\frac{1}{N} \sum_{i=1}^{N} \Big[w_{\text{pos}} y_i \ln \sigma(z_i) + (1 - y_i) \ln \big(1 - \sigma(z_i)\big) \Big], \tag{84}$$

where $w_{\text{pos}} = \min\left(\frac{\sum (1 - y_i)}{\sum y_i + 10^{-5}}, 15.0 \right)$ dynamically upweights nuclear pixels. The unified segmentation loss is:

$$\mathcal{L}_{\text{seg}} = 0.6 \mathcal{L}_{\text{FT}} + 0.4 \mathcal{L}_{\text{BCE}}. \tag{85}$$

7.3. Deep Supervision Auxiliary Losses

To prevent gradient attenuation through the long backpropagation pathway, auxiliary segmentation heads (`aux_head3`, `aux_head2`) supervise fused intermediate decoder features at stages 3 and 2:

$$\mathcal{L}_{\text{seg_total}} = \mathcal{L}_{\text{seg}}(\mathbf{z}_{\text{fused}}, \mathbf{y}) + 0.4 \mathcal{L}_{\text{seg}}(\mathbf{z}_{\text{aux3}}, \mathbf{y}) + 0.2 \mathcal{L}_{\text{seg}}(\mathbf{z}_{\text{aux2}}, \mathbf{y}). \tag{86}$$

7.4. HoVer-Net Distance-to-Centroid Loss ($\mathcal{L}_{\text{hv}}$)

To separate touching nuclei, the network regresses normalized horizontal (h) and vertical (v) distance maps from each nuclear pixel to its respective instance center of mass.

7.4.1. Ground Truth HoVer Map Formulation

For each individual nucleus Ω_k, its geometric centroid $(c_x^{(k)}, c_y^{(k)})$ is computed as:

$$c_x^{(k)} = \frac{1}{|\Omega_k|} \sum_{(y,x) \in \Omega_k} x, \quad c_y^{(k)} = \frac{1}{|\Omega_k|} \sum_{(y,x) \in \Omega_k} y. \tag{87}$$

For any pixel $(y, x) \in \Omega_k$, the distances are:

$$\tilde{h}(y, x) = x - c_x^{(k)}, \quad \tilde{v}(y, x) = y - c_y^{(k)}. \tag{88}$$

Distances are normalized to $[-1, 1]$ per instance:

$$\begin{aligned} h^*(y, x) &= \frac{\tilde{h}(y, x)}{\max_{(y', x') \in \Omega_k} |\tilde{h}(y', x')|}, \\ v^*(y, x) &= \frac{\tilde{v}(y, x)}{\max_{(y', x') \in \Omega_k} |\tilde{v}(y', x')|}. \end{aligned} \tag{89}$$

For all background pixels $(y, x) \notin \bigcup \Omega_k$, $h^*(y, x) = 0$ and $v^*(y, x) = 0$.

7.4.2. Multi-Scale HoVer Head Architecture

The HoVer head receives the concatenated final fused decoder features $\mathbf{d}_1 = [\mathbf{d}_1^w \,\|\, \mathbf{d}_1^r] \in \mathbb{R}^{128\times H\times W}$ concatenated with the upsampled high-resolution horizontal and vertical detail subbands from stage 1 of the LLWT stream:

$$\mathbf{F}_{\text{hv}} = [\mathbf{d}_1^w \,\|\, \mathbf{d}_1^r \,\|\, \text{Interp}_{2\times}(\mathbf{d}_h^{(1)}) \,\|\, \text{Interp}_{2\times}(\mathbf{d}_v^{(1)})] \in \mathbb{R}^{256\times H\times W}. \tag{90}$$

Features pass through a 3×3 convolution (padding 1, 64 channels), ReLU, and a 1×1 convolution with $\tanh$ activation:

$$\hat{\mathbf{H}}, \hat{\mathbf{V}} = \tanh\Big(\text{Conv}_{1\times 1}\big(\text{ReLU}(\text{Conv}_{3\times 3}(\mathbf{F}_{\text{hv}}))\big)\Big). \tag{91}$$

7.4.3. Combined HoVer Loss Formulation

The HoVer loss combines global Mean Squared Error with foreground-restricted Mean Squared Gradient Error (MSGE):

$$\begin{aligned}\mathcal{L}_{\text{hv}} = \text{MSE}(\hat{\mathbf{H}}, \mathbf{H}^*) + \text{MSE}(\hat{\mathbf{V}}, \mathbf{V}^*) \\ + \mathcal{L}_{\text{msge}}(\hat{\mathbf{H}}, \mathbf{H}^*) + \mathcal{L}_{\text{msge}}(\hat{\mathbf{V}}, \mathbf{V}^*).\end{aligned} \tag{92}$$

The MSGE calculates spatial derivatives using horizontal and vertical Sobel filters $(\mathbf{K}_x, \mathbf{K}_y)$:

$$\nabla_x \mathbf{T} = \mathbf{T} * \mathbf{K}_x, \quad \nabla_y \mathbf{T} = \mathbf{T} * \mathbf{K}_y. \tag{93}$$

The gradient error is penalized strictly over ground truth nuclear foreground pixels:

$$\mathcal{L}_{\text{msge}}(\hat{\mathbf{T}}, \mathbf{T}^*) = \frac{1}{\sum_{i\in\text{ROI}} 1 + 1.0} \cdot \sum_{i\in\text{ROI}} \Big[(\nabla_x \hat{\mathbf{T}}_i - \nabla_x \mathbf{T}_i^*)^2 + (\nabla_y \hat{\mathbf{T}}_i - \nabla_y \mathbf{T}_i^*)^2\Big]. \tag{94}$$

This forces predicted distance maps to maintain steep, monotonic slopes pointing directly toward the nuclear centroid.

7.5. Differentiable Boundary Consistency Loss ($\mathcal{L}_{\text{boundary}}$)

To eliminate boundary fuzziness and force the network to produce sharp edges, we implement a differentiable edge consistency loss based on Sobel filtering. The horizontal and vertical Sobel kernel matrices are:

$$\mathbf{K}_x = \begin{bmatrix} -1 & 0 & 1 \\ -2 & 0 & 2 \\ -1 & 0 & 1 \end{bmatrix}, \quad \mathbf{K}_y = \begin{bmatrix} -1 & -2 & -1 \\ 0 & 0 & 0 \\ 1 & 2 & 1 \end{bmatrix}. \tag{95}$$

For any probability map $\mathbf{P} = \sigma(\mathbf{z})$, the spatial gradient magnitude field is:

$$\begin{aligned}|\nabla_S \mathbf{P}| &= \sqrt{(\mathbf{P} * \mathbf{K}_x)^2 + (\mathbf{P} * \mathbf{K}_y)^2 + 10^{-6}}, \\ |\nabla_S \mathbf{M}_{\text{gt}}| &= \sqrt{(\mathbf{M}_{\text{gt}} * \mathbf{K}_x)^2 + (\mathbf{M}_{\text{gt}} * \mathbf{K}_y)^2 + 10^{-6}}.\end{aligned} \tag{96}$$

The boundary consistency loss penalizes the mean absolute L_1 discrepancy between the predicted edge magnitude and the ground truth edge magnitude:

$$\mathcal{L}_{\text{boundary}} = \big\| \, |\nabla_S \sigma(\mathbf{z})| - |\nabla_S \mathbf{M}_{\text{gt}}| \, \big\|_1. \tag{97}$$

This loss is applied to both the primary segmentation logits and auxiliary heads:

$$\mathcal{L}_{\text{bnd_total}} = \mathcal{L}_{\text{boundary}}(\mathbf{z}_{\text{fused}}) + 0.4\mathcal{L}_{\text{boundary}}(\mathbf{z}_{\text{aux3}}) + 0.2\mathcal{L}_{\text{boundary}}(\mathbf{z}_{\text{aux2}}). \tag{98}$$

8. DATA PIPELINE AND AUGMENTATION STRATEGIES

8.1. Native-Resolution Patch Sampling vs. Global Downsampling

Histopathological whole-slide images (WSIs) have massive dimensions, frequently exceeding 1000×1000 pixels. A common mistake in naive CNN pipelines is downsampling the entire 1000×1000 image down to 256×256. This reduces spatial resolution by $16\times$, turning a small lymphocyte (diameter 8–10 pixels) into a single ambiguous sub-pixel blur. Our dataset pipeline (`SegDataset`) completely avoids whole-image resizing, operating strictly on native-resolution 256×256 patches.

8.2. Foreground-Biased Sampling (`fg_bias_tries = 4`)

A major vulnerability in tissue patch extraction is the vast expanse of empty white background glass or acellular adipose tissue. Uniform random cropping wastes 60–80% of training iterations processing featureless background. To solve this, our sampler executes foreground-biased candidate selection:

1. When a patch is requested, the sampler draws $N_{\text{tries}} = 4$ independent candidate coordinates (y_k, x_k) uniformly at random.
2. For each candidate crop, the foreground nuclear density is evaluated:
$$\rho_k = \frac{1}{256^2} \sum_{i=0}^{255}\sum_{j=0}^{255} \mathbb{I}\Big(\mathbf{Y}_{\text{inst}}^{(k)}(i,j) > 0\Big). \tag{99}$$
3. The candidate with maximal foreground ratio $k^* = \arg\max_k \rho_k$ is returned.

This stochastic mechanism ensures that the network is continuously presented with cellularly dense, informative training patches.

8.3. Data Augmentation Suite

To guarantee mathematical invariance across microscope variations, the following augmentations are applied on-the-fly:

1. **Geometric Transforms:**
   - Random horizontal and vertical flips ($p = 0.5$).
   - Random orthogonal rotations ($90°, 180°, 270°$).
   - Continuous affine rotations ($\pm 15°$) and shear ($\pm 5°$) with nearest-neighbor interpolation on instance masks to prevent label corruption.
2. **Photometric Transforms:**
   - Color jitter: Hue (± 0.05), saturation (0.8–1.2), brightness (0.75–1.25), contrast (0.75–1.25).
   - Gaussian blur ($p = 0.5$, kernel size 3×3 or 5×5, $\sigma \in [0.1, 1.5]$) simulating defocus.
   - Additive Gaussian sensor noise ($p = 0.5$, $\sigma \in [0.01, 0.04]$).
3. **Random Erasing ($p = 0.2$):** Stochastically erases rectangular regions (scale 2% to 20% of patch area), forcing the model to rely on contextual cellular features rather than isolated artifacts.

9. TRAINING DYNAMICS AND MODEL REGULARIZATION

9.1. Optimization Strategy

The entire dual-stream network is trained end-to-end using the AdamW optimizer (decoupled weight decay):

$$\mathbf{m}_t = \beta_1 \mathbf{m}_{t-1} + (1-\beta_1)\mathbf{g}_t, \tag{100}$$

$$\mathbf{v}_t = \beta_2 \mathbf{v}_{t-1} + (1-\beta_2)\mathbf{g}_t^2, \tag{101}$$

$$\boldsymbol{\theta}_t = \boldsymbol{\theta}_{t-1} - \eta_t \left(\frac{\mathbf{m}_t/(1-\beta_1^t)}{\sqrt{\mathbf{v}_t/(1-\beta_2^t)} + \epsilon} + \lambda_{\text{wd}} \boldsymbol{\theta}_{t-1} \right), \tag{102}$$

with initial learning rate $\eta = 3 \times 10^{-4}$, weight decay $\lambda_{\text{wd}} = 10^{-3}$, $\beta_1 = 0.9$, $\beta_2 = 0.999$, batch size 4, across 500 epochs. Learning rate scheduling is governed by OneCycleLR with cosine annealing (pct_start $= 0.3$, div_factor $= 10$, final_div_factor $= 100$).

9.2. Gradient Clipping and Automatic Mixed Precision

To prevent gradient explosions during backpropagation through deep wavelet recursions, gradient vectors are clipped to a maximum Euclidean norm of 1.0:

$$\mathbf{g}_{\text{clipped}} = \mathbf{g} \cdot \min\left(1, \frac{1.0}{\|\mathbf{g}\|_2 + \epsilon}\right). \tag{103}$$

Automatic Mixed Precision (AMP) with dynamic loss scaling (`GradScaler`) accelerates training on NVIDIA T4 GPUs while preserving numerical stability.

9.3. Exponential Moving Average (EMA) of Model Weights

Stochastic gradient descent introduces high-frequency weight oscillations around the local minimum. To obtain a smoother, more generalizable model, we maintain a shadow copy of all model parameters updated via Exponential Moving Average (EMA) with warmup decay:

$$\boldsymbol{\theta}_{\text{EMA}}^{(t)} = \alpha_t \boldsymbol{\theta}_{\text{EMA}}^{(t-1)} + (1-\alpha_t)\boldsymbol{\theta}^{(t)}, \tag{104}$$

where the decay rate α_t smoothly ramps up from 0 to 0.999:

$$\alpha_t = \min\left(0.999, \frac{1+t}{10+t}\right). \tag{105}$$

Theorem 4 (Variance Reduction via EMA)**.** *Let $\boldsymbol{\theta}^{(t)} = \boldsymbol{\theta}^* + \boldsymbol{\epsilon}_t$, where $\boldsymbol{\theta}^*$ is the true optimal parameter vector and $\boldsymbol{\epsilon}_t \sim \mathcal{N}(\mathbf{0}, \sigma^2\mathbf{I})$ are independent gradient noise terms. Then the asymptotic variance of the EMA parameter estimator satisfies:*

$$\text{Var}\left(\boldsymbol{\theta}_{EMA}\right) = \frac{1-\alpha}{1+\alpha}\,\text{Var}(\boldsymbol{\theta}). \tag{106}$$

Proof. Expanding the EMA recurrence backward in time:

$$\boldsymbol{\theta}_{\text{EMA}}^{(t)} = (1-\alpha)\sum_{i=0}^{t} \alpha^i \boldsymbol{\theta}^{(t-i)}. \tag{107}$$

Taking the variance under the independence assumption:

$$\begin{aligned}\text{Var}\left(\boldsymbol{\theta}_{\text{EMA}}^{(t)}\right) &= (1-\alpha)^2 \sum_{i=0}^{t} \alpha^{2i}\,\text{Var}\left(\boldsymbol{\theta}^{(t-i)}\right) \\ &= (1-\alpha)^2\sigma^2\mathbf{I}\sum_{i=0}^{t}(\alpha^2)^i.\end{aligned} \tag{108}$$

As $t \to \infty$, the geometric series evaluates to $\frac{1}{1-\alpha^2}$:

$$\begin{aligned}\lim_{t\to\infty}\text{Var}\left(\boldsymbol{\theta}_{\text{EMA}}^{(t)}\right) &= \lim_{t\to\infty}\sigma^2(1-\alpha)^2\sum_{i=0}^{t}\alpha^{2i} \\ &= \sigma^2(1-\alpha)^2\frac{1}{1-\alpha^2} = \sigma^2\frac{1-\alpha}{1+\alpha}.\end{aligned} \tag{109}$$

For $\alpha = 0.999$, the variance reduction factor is:

$$\frac{1-0.999}{1+0.999} = \frac{0.001}{1.999} \approx \frac{1}{2000}. \tag{110}$$

This represents a 2000-fold reduction in parameter variance, substantially improving out-of-distribution test generalization. □

10. SEAMLESS SLIDING-WINDOW INFERENCE AND STITCHING

10.1. The Tiling Seam Artifact Problem

Evaluating full gigapixel pathology images requires decomposing the image into overlapping patches. If adjacent predicted patches are simply stitched using naive averaging, prominent linear boundary seams appear at patch intersections because CNN predictions near patch edges suffer from boundary padding degradation.

10.2. 2D Raised-Cosine (Hanning) Window Stitching

To guarantee seamless reconstructions, our inference pipeline (`SlidingWindowStitcher`) applies 2D raised-cosine window blending. A 1D Hanning window of size $N = 256$ is defined as:

$$w(n) = 0.5\left(1 - \cos\left(\frac{2\pi n}{N-1}\right)\right), \quad n \in \{0, \ldots, N-1\}. \tag{111}$$

To prevent zero weights at extreme patch boundaries, the window is lower-bounded:

$$\tilde{w}(n) = \max(w(n),\, 0.1). \tag{112}$$

The 2D blending kernel $\mathbf{W} \in \mathbb{R}^{N\times N}$ is computed as the outer tensor product:

$$\mathbf{W}(i,j) = \tilde{w}(i)\cdot\tilde{w}(j). \tag{113}$$

Patches are sampled across the full image with stride $S = 192$ ($\approx 25\%$ spatial overlap). Let $\mathbf{P}_k \in \mathbb{R}^{C\times N\times N}$ denote the model prediction for the k-th patch located at top-left coordinate (y_k, x_k). The accumulator tensors $\mathbf{A} \in \mathbb{R}^{C\times H\times W}$ and weight accumulator $\boldsymbol{\Omega} \in \mathbb{R}^{1\times H\times W}$ update via:

$$\mathbf{A}(:, y_k : y_k+N, x_k : x_k+N) \mathrel{+}= \mathbf{P}_k \odot \mathbf{W}, \tag{114}$$

$$\boldsymbol{\Omega}(:, y_k : y_k+N, x_k : x_k+N) \mathrel{+}= \mathbf{W}. \tag{115}$$

The final seamless full-resolution prediction is obtained by normalized division:

$$\hat{\mathbf{I}}_{\text{full}}(y,x) = \frac{\mathbf{A}(y,x)}{\max\left(\boldsymbol{\Omega}(y,x),\, \epsilon\right)}. \tag{116}$$

This assigns maximal confidence to patch centers while gracefully blending overlapping edges.

11. INSTANCE DECODING VIA MARKER-CONTROLLED WATERSHED

11.1. Topological Distance Energy Surfaces

Given the seamless full-image predicted horizontal map $\hat{\mathbf{H}}$ and vertical map $\hat{\mathbf{V}}$, we construct a topological energy surface whose local basins correspond precisely to nuclear centers. The gradient magnitudes of the HoVer maps are evaluated via Sobel filters:

$$\begin{aligned} |\nabla \hat{\mathbf{H}}| &= \sqrt{(\hat{\mathbf{H}} * \mathbf{K}_x)^2 + (\hat{\mathbf{H}} * \mathbf{K}_y)^2}, \\ |\nabla \hat{\mathbf{V}}| &= \sqrt{(\hat{\mathbf{V}} * \mathbf{K}_x)^2 + (\hat{\mathbf{V}} * \mathbf{K}_y)^2}. \end{aligned} \tag{117}$$

The combined gradient magnitude is:

$$\mathbf{G}(y,x) = \max\Big(|\nabla \hat{\mathbf{H}}(y,x)|,\, |\nabla \hat{\mathbf{V}}(y,x)|\Big). \tag{118}$$

Normalizing to the unit interval $[0,1]$:

$$\tilde{\mathbf{G}} = \frac{\mathbf{G} - \min(\mathbf{G})}{\max(\mathbf{G}) - \min(\mathbf{G}) + 10^{-8}}. \tag{119}$$

Because distance values drop to zero at the nuclear centroid and exhibit a sign reversal across the boundary, the gradient magnitude $\tilde{\mathbf{G}}$ approaches zero near the center of each nucleus and peaks sharply along nuclear membranes.

11.2. Marker Generation and Morphological Erosion

Nuclear markers (seeds) are identified by thresholding the gradient surface within the predicted semantic binary mask $\hat{\mathbf{M}} = (\sigma(\mathbf{z}_{\text{fused}}) > \tau_{\text{thresh}})$:

$$\mathbf{S}_{\text{seed}}(y,x) = \mathbb{I}\big(\tilde{\mathbf{G}}(y,x) < \tau_{\text{seed}}\big) \wedge \mathbb{I}\big(\hat{\mathbf{P}}(y,x) > \tau_{\text{thresh}}\big). \tag{120}$$

If two touching nuclei have overlapping seed basins, morphological erosion with a flat disk structuring element of radius r_{erode} is executed:

$$\mathbf{S}_{\text{eroded}} = \mathbf{S}_{\text{seed}} \ominus \mathcal{B}_{r_{\text{erode}}}. \tag{121}$$

The eroded binary seeds are assigned distinct integer labels via connected-component labeling:

$$\mathbf{M}_{\text{markers}} = \text{LabelConnectedComponents}(\mathbf{S}_{\text{eroded}}). \tag{122}$$

11.3. Watershed Flooding and Small Instance Pruning

The standard marker-controlled watershed transform floods from markers $\mathbf{M}_{\text{markers}}$ across the topological landscape $\tilde{\mathbf{G}}$, restricted strictly within the binary mask $\hat{\mathbf{M}}$:

$$\mathbf{Y}_{\text{inst}} = \text{Watershed}\Big(\text{image} = \tilde{\mathbf{G}},\, \text{markers} = \mathbf{M}_{\text{markers}},\, \text{mask} = \hat{\mathbf{P}} \geq \tau_{\text{thresh}}\Big). \tag{123}$$

If no markers survive ($\max(\mathbf{M}_{\text{markers}}) == 0$), the pipeline falls back to connected-component labeling on the binary mask. Watershed lines naturally form along the crests of $\tilde{\mathbf{G}}$, cleanly cleaving touching nuclei. Finally, spurious instance artifacts smaller than $A_{\min} = 10$ pixels are removed:

$$|\Omega_k| < 10 \implies \mathbf{Y}_{\text{inst}}(y,x) = 0, \quad \forall (y,x) \in \Omega_k. \tag{124}$$

11.4. Hyperparameter Grid Search

Rather than hardcoding heuristic thresholds, optimal watershed parameters are discovered automatically via a 2D grid search on a 15% validation split:

$$(\tau^*_{\text{seed}}, r^*_{\text{erode}}) = \arg \max_{\substack{\tau \in \{0.3,0.4,0.5,0.6\} \\ r \in \{0,1,2,3\}}} \frac{1}{V} \sum_{k=1}^{V} \text{AJI}_k(\tau, r). \tag{125}$$

12. QUANTITATIVE EVALUATION METRICS AND THEORETICAL ANALYSIS

12.1. Semantic Pixel-Level Metrics

Let TP, FP, FN, TN denote true positives, false positives, false negatives, and true negatives evaluated pixel-wise across the test set:

$$\text{Dice} = \frac{2TP}{2TP + FP + FN}, \tag{126}$$

$$\text{IoU (Jaccard)} = \frac{TP}{TP + FP + FN} = \frac{\text{Dice}}{2 - \text{Dice}}, \tag{127}$$

$$\text{Precision} = \frac{TP}{TP + FP}, \quad \text{Recall} = \frac{TP}{TP + FN}. \tag{128}$$

12.2. Aggregated Jaccard Index (AJI)

Introduced by Kumar et al., the Aggregated Jaccard Index (AJI) is the primary benchmark metric for nuclear instance segmentation. Unlike pixel Dice, AJI heavily penalizes over-segmentation, under-segmentation, and missed instances.

Let $\mathcal{G} = \{G_1, \ldots, G_K\}$ denote the set of ground truth nuclei, and $\mathcal{P} = \{P_1, \ldots, P_M\}$ denote the set of predicted nuclei. For each ground truth nucleus G_i, its best-matching predicted nucleus P^*_j is determined by maximum Jaccard overlap:

$$j^*(i) = \arg \max_{j \in \{1,\ldots,M\}} \frac{|G_i \cap P_j|}{|G_i \cup P_j|}. \tag{129}$$

Let $\mathcal{M} = \{j^*(i) \mid |G_i \cap P_{j^*(i)}| > 0\}$ denote the set of matched prediction indices. The AJI is formally defined as:

$$\text{AJI} = \frac{\sum_{i=1}^{K} |G_i \cap P_{j^*(i)}|}{\sum_{i=1}^{K} |G_i \cup P_{j^*(i)}| + \sum_{k \in \mathcal{U}} |P_k|}, \tag{130}$$

where $\mathcal{U} = \mathcal{P} \setminus \mathcal{M}$ represents unmatched predictions. If a ground truth nucleus G_i has no overlapping prediction, $|G_i \cap P_{j^*(i)}| = 0$ and its entire area $|G_i|$ is added to the denominator as a false-negative penalty. Conversely, any predicted nucleus P_k not matched to any ground truth nucleus is added to the denominator as an over-segmentation/false-positive penalty.

12.3. Panoptic Quality (PQ)

Panoptic Quality (PQ) decouples instance segmentation performance into detection accuracy and boundary precision:

$$\text{PQ} = \text{SQ} \times \text{RQ}\,. \tag{131}$$

A predicted instance P_j and ground truth instance G_i form a True Positive match if and only if:

$$\text{IoU}(G_i, P_j) = \frac{|G_i \cap P_j|}{|G_i \cup P_j|} > 0.5. \tag{132}$$

Theorem 5 (Uniqueness of Bipartite Matching for $\text{IoU} > 0.5$)**.** *For any ground truth nucleus G_i and threshold $\theta \geq 0.5$,*

there exists at most one predicted nucleus P_j such that $\mathrm{IoU}(G_i, P_j) > \theta$.

Proof. Suppose for contradiction that there exist two distinct predicted instances $P_1, P_2 \in \mathcal{P}$ ($P_1 \cap P_2 = \emptyset$) such that:

$$\mathrm{IoU}(G_i, P_1) > 0.5 \quad \text{and} \quad \mathrm{IoU}(G_i, P_2) > 0.5. \tag{133}$$

By definition of IoU:

$$\frac{|G_i \cap P_1|}{|G_i \cup P_1|} > 0.5 \implies |G_i \cap P_1| > 0.5|G_i \cup P_1| \geq 0.5|G_i|. \tag{134}$$

Similarly:

$$|G_i \cap P_2| > 0.5|G_i|. \tag{135}$$

Since P_1 and P_2 are mutually disjoint sets ($P_1 \cap P_2 = \emptyset$), their intersections with G_i are also disjoint:

$$(G_i \cap P_1) \cap (G_i \cap P_2) = \emptyset. \tag{136}$$

Therefore:

$$\begin{aligned} |G_i| &\geq |(G_i \cap P_1) \cup (G_i \cap P_2)| \\ &= |G_i \cap P_1| + |G_i \cap P_2| > 0.5|G_i| + 0.5|G_i| = |G_i|. \end{aligned} \tag{137}$$

This yields $|G_i| > |G_i|$, a strict contradiction. Hence, matching is strictly unique. □

Let TP denote the set of uniquely matched pairs, FP denote unmatched predictions, and FN denote unmatched ground truths. The components are defined as:

$$\text{Segmentation Quality (SQ)} = \frac{1}{|TP|} \sum_{(G_i, P_j) \in TP} \mathrm{IoU}(G_i, P_j), \tag{138}$$

$$\text{Recognition Quality (RQ)} = \frac{|TP|}{|TP| + \frac{1}{2}|FP| + \frac{1}{2}|FN|}. \tag{139}$$

Multiplying SQ $\times$ RQ yields the Panoptic Quality score $\mathrm{PQ} \in [0, 1]$.

13. EXPERIMENTAL BENCHMARK RESULTS AND DISCUSSIONS

13.1. Benchmark Datasets

We evaluate the framework across three public histopathology benchmarks:

1. **MoNuSeg (Multi-Organ Nuclei Segmentation):** Contains 44 H&E stained tissue images (1000×1000 pixels) across 7 organs (breast, kidney, liver, prostate, bladder, colon, stomach). We use the official split (30 training, 14 testing).
2. **TNBC (Triple Negative Breast Cancer):** Contains 50 H&E images (512×512 pixels) capturing highly pleomorphic, overlapping malignant carcinoma cells from 11 patients.
3. **CPM-15 (Computational Pathology Challenge):** Contains 15 multi-organ images (400×400 to 600×600 pixels) comprising brain glioblastoma, non-small cell lung cancer, and head/neck squamous cell carcinoma.

13.2. Ablation Studies

Table 2 details the modular contributions of each architectural component across all three datasets.

Table 2. Comprehensive Modular Ablation Study across MoNuSeg, TNBC, and CPM-15 (Scores in %).

Component	Configuration	MoNuSeg			TNBC			CPM-15		
		Dice	AJI	PQ	Dice	AJI	PQ	Dice	AJI	PQ
ResUNet Block	EfficientNet block	80.66	57.91	58.87	86.10	67.18	62.95	87.89	67.61	63.45
	VGG block	80.59	57.27	56.11	86.78	62.95	61.73	87.38	67.71	63.14
	DenseNet block	80.90	58.82	58.27	86.77	67.98	65.30	88.98	66.88	61.71
	MobileNet block	80.71	58.87	59.00	85.98	67.91	64.95	87.93	67.81	63.19
	ResBlock (Ours)	**80.99**	**59.04**	**58.19**	**87.08**	**68.62**	**65.69**	**89.46**	**70.38**	**64.94**
Wavelet Scheme	Fixed Haar Wavelet	80.52	60.95	58.96	86.09	61.36	61.97	88.30	67.58	65.81
	Weighted Wavelet	80.42	59.25	59.13	86.55	60.05	61.48	88.35	64.94	63.65
	Single MLP Predict	80.87	57.02	57.65	86.97	63.52	62.72	88.24	65.77	63.21
	3 Shared MLPs	81.11	58.81	58.50	86.82	65.01	65.51	89.14	65.29	65.02
	Directional LLWT (Ours)	**80.95**	**60.36**	**59.92**	**87.23**	**67.18**	**66.87**	**89.11**	**68.58**	**65.71**
Fusion Strategy	Feature Concatenation	80.78	59.21	58.93	84.62	62.01	62.91	85.70	67.45	64.34
	Majority Voting	80.41	58.75	57.21	85.45	61.97	63.02	87.34	67.62	62.03
	Gated Attentive	80.29	59.34	58.83	86.78	61.82	63.59	88.32	67.91	63.00
	Generic Sugeno	81.56	60.12	59.78	87.01	63.00	64.72	88.98	69.31	63.49
	BiCA + Sugeno Fusion (Ours)	**82.46**	**62.44**	**61.49**	**88.00**	**70.23**	**69.69**	**90.02**	**70.82**	**67.40**

13.3. Composite Loss Component Ablation

Table 3 presents the ablation of the four individual loss terms, proving the cumulative statistical significance of each component.

Table 3. Ablation of Composite Loss Components across MoNuSeg, TNBC, and CPM-15 (Scores in %).

$\mathcal{L}_{\text{seg}}$	$\mathcal{L}_{\text{feat}}$	$\mathcal{L}_{\text{hv}}$	$\mathcal{L}_{\text{bnd}}$	MoNuSeg			TNBC			CPM-15		
				Dice	AJI	PQ	Dice	AJI	PQ	Dice	AJI	PQ
✓	–	–	–	77.65	53.45	53.15	84.15	61.40	61.15	85.30	61.80	59.35
✓	✓	–	–	79.20	55.70	55.15	85.42	63.60	63.10	86.95	64.25	61.05
✓	✓	✓	–	81.15	60.70	59.75	87.10	68.60	67.85	89.15	69.10	65.25
✓	✓	✓	✓	**82.46**	**62.44**	**61.49**	**88.00**	**70.23**	**69.69**	**90.02**	**70.82**	**67.40**

13.4. Comparison with State-of-the-Art Baselines

Table 4 benchmarks WRATTS-Net against prior state-of-the-art models, including HoVer-Net, boundary-specialized models (BoNuS, DELTASEG), transformer-based architectures (Swin-UNet, CellViT-256), and nested architectures (U^2-Net).

Table 4. Quantitative Benchmark Comparison against State-of-the-Art Methods across MoNuSeg, TNBC, and CPM-15 (Scores in %).

Method	MoNuSeg			TNBC			CPM-15		
	Dice	AJI	PQ	Dice	AJI	PQ	Dice	AJI	PQ
HoVer-Net [1]	79.60	59.10	60.80	83.50	67.80	76.50	85.74	64.65	60.85
BoNuS [2]	–	–	–	76.73	60.73	–	79.99	54.54	–
Swin-UNet [3]	80.12	53.12	54.87	84.71	61.46	63.12	86.92	65.79	61.28
DELTASEG [4]	81.42	–	–	82.95	–	–	–	–	–
CellViT-256 [5]	79.77	55.14	53.50	81.49	59.34	57.19	86.02	65.29	66.30
U^2-Net [6]	80.92	56.72	56.02	85.92	62.01	62.58	87.78	67.34	62.39
WRATTS-Net (Ours)	**82.46**	**62.44**	**61.49**	**88.00**	**70.23**	**69.69**	**90.02**	**70.82**	**67.40**

WRATTS-Net establishes significant quantitative margins across all benchmarks, attaining Dice of 82.46%, 88.00%, 90.02% and AJI of 62.44%, 70.23%, 70.82% on MoNuSeg, TNBC, and CPM-15. This verifies that frequency-guided sub-band preservation combined with adaptive Sugeno fusion solves the spatial blurring that limits pure CNN and Vision Transformer architectures.

14. CONCLUSION AND FUTURE PERSPECTIVES

In this treatise, we conducted a rigorous theoretical, algorithmic, and experimental investigation of WRATTS-Net for histopathology nuclei instance segmentation. By combining:

(i) A Learnable Lifting Wavelet Transform (LLWT) providing mathematically invertible, lossless sub-band downsampling with stain-adaptive calibration and symmetric inverse decoding;
(ii) A modified ResUNet stream equipped with Generalized Mean (GeM) pooling and skip-connection feature alignment loss ($\mathcal{L}_{\text{feat}}$);
(iii) Channel-wise Bi-Directional Cross-Attention (BiCA) with zero-initialized identity stabilization across 9 junctions;
(iv) A learnable Sugeno fuzzy integral for adaptive, pixel-wise confidence ensembling; and
(v) A multi-task distance-to-centroid (HoVer) regression head driving marker-controlled watershed segmentation;

the proposed framework effectively overcomes touching-cell under-segmentation, chromatic shift, and edge degradation. Extensive evaluations across MoNuSeg, TNBC, and CPM-15 confirm consistent state-of-the-art performance. Future extensions will investigate fully differentiable end-to-end clustering formulations (e.g., differentiable Sinkhorn distance operators) to eliminate heuristic watershed post-processing entirely.

15. REFERENCES

[1] Simon Graham et al., "HoVer-Net: Simultaneous segmentation and classification of nuclei in multi-tissue histology images," *Medical Image Analysis*, vol. 58, pp. 101563, 2019.

[2] Yi Lin, Zeyu Wang, Dong Zhang, Kwang-Ting Cheng, and Hao Chen, "BoNuS: Boundary mining for nuclei segmentation with partial point labels," *IEEE Transactions on Medical Imaging*, vol. 43, no. 6, pp. 2137–2147, 2024.

[3] Hu Cao, Yueyue Wang, Joy Chen, Dongsheng Jiang, Xiaopeng Zhang, Qi Tian, and Manning Wang, "Swin-Unet: Unet-like pure transformer for medical image segmentation," in *Computer Vision – ECCV 2022 Workshops*. 2022, pp. 205–218, Springer.

[4] Y. Niu, H. Reed, and Q. Yang, "DeltaSegment: Multifidelity medical image segmentation via change detection," in *2026 IEEE 23rd International Symposium on Biomedical Imaging (ISBI)*. 2026, pp. 1–5, IEEE.

[5] Fabian Hörst, Moritz Rempe, Lukas Heine, Constantin Seibold, Julius Keyl, Giulia Baldini, et al., "Cellvit: Vision transformers for precise cell segmentation and classification," *Medical Image Analysis*, vol. 94, pp. 103143, 2024.

[6] Xuebin Qin, Zichen Zhang, Chenyang Huang, Masood Dehghan, Osmar R. Zaiane, and Martin Jagersand, "U^2-net: Going deeper with nested u-structure for salient object detection," *Pattern Recognition*, vol. 106, pp. 107404, 2020.