



## NITTE MEENAKSHI INSTITUTE OF TECHNOLOGY

An Autonomous Institution Approved by UGC/AICTE/Govt. of Karnataka  
Accredited by NBA (Tier-I) and NAAC 'A+' Grade  
Affiliated to Visvesvaraya Technological University, Belagavi  
Post Box No. 6429, Yelahanka, Bengaluru-560064, Karnataka, INDIA



KNOWLEDGE • CHARACTER • UNITY

# DEPARTMENT OF ARTIFICIAL INTELLIGENCE AND DATA SCIENCE

## 21ADA581 WEB APPLICATION DEVELOPMENT

NAME	:	_____
USN	:	_____
YEAR/SEM	:	_____
SECTION	:	_____
BRANCH	:	_____

1. Write a HTML program for the demonstration of Lists.
2. Write a HTML program for time-table using tables.
3. Write HTML for demonstration of cascading stylesheets.
4. Write a JavaScript to design a simple calculator to perform the following operations: sum, product, difference and quotient.
5. Develop and demonstrate a HTML5 file that includes JavaScript script that uses functions for the following problems:
  - Parameter: A string
  - Output: The position in the string of the left-most vowel
  - Parameter: A number
  - Output: The number with its digits in the reverse order
6. a. Write a Javascript program for validating REGISTRATION FORM.  
b. Write a Javascript program to validate USER LOGIN page.
7. Write an XML for student information and access second students data using DOM.
8. Write a Javascript program for implementing constructor
9. Write a Javascript to add items in a blank array and display the items
10. Write a Javascript program for implementing pattern matching.

<b>Lab Exercises</b>	
1.	Write a HTML program for the demonstration of Lists. <ul style="list-style-type: none"> <li>a. Unordered List</li> <li>b. Ordered List</li> <li>c. Definition List</li> <li>d. Nested List</li> </ul>
2.	Write a HTML program for demonstrating Hyperlinks. <ul style="list-style-type: none"> <li>a. Navigation from one page to another.</li> <li>b. Navigation within the page.</li> </ul>
3.	Write a HTML program for time-table using tables.
4.	Write a HTML program to develop a static Home Page using frames.
5.	Write a HTML program to develop a static Registration Form.
	Write a HTML program to develop a static Login Page.
6.	Write HTML for demonstration of cascading stylesheets. <ul style="list-style-type: none"> <li>a. Embedded stylesheets.</li> <li>b. External stylesheets.</li> <li>c. Inline styles.</li> </ul>
7.	Write a javascript program to validate USER LOGIN page.
	Write a javascript program for validating REGISTRATION FORM
8.	a. Write a program for implementing XML document for CUSTOMER DETAILS.
	b. Write an internal Document Type Definition to validate XML for CUSTOMERDETAILS?
	c. Write an external Document Type Definition to validate XML for CUSTOMERDETAILS?
9.	Write an XML for person information and access the data using XSL.
10.	Write an XML for student information and access second students data using DOM.

## 1. Write a HTML program for the demonstration of Lists.

a. Unordered List

b. Ordered List

c. Definition List

d. Nested List

Unordered List:

```
<html>
<head>
    <title> Creating Unorder List </title>
</head>
<body bgcolor="pink">
    <h1 align="center"> Creating Unorder List</h1>
    <h1 align="center">List of Colleges in Karnataka</h1>
    <ul type="square">
        <li>CIT Gubbi</li>
        <li>SIT Tumkur</li>
        <li>NITTE MEENAKSHI Banglore</li>
    </ul>
</body>
</html>
```

---

---

### **Ordered List:**

```
<html>
<head>
<title> Creating Order List </title>
</head>
<body bgcolor="pink">
<h1 align="center"> Creating Order List</h1>
<h1 align="center">List of branches in CIT GUBBI</h1>
<ol type="A">
    <li>CSE</li>
    <li>ISE</li>
    <li>ECE</li>
    <li>EEE</li>
    <li>CIVIL</li>
    <li>ME</li>
    <li>AIDS</li>
</ol>
</body>
</html>
```

---

---

### Definition List:

```
<html>
<head>
<title>Creating Definition List</title>
</head>
<body bgcolor="pink">
  <h1 align="center">Definition List</h1>
  <dl>
    <dt>CSE<dd>Computer Science & Engineering
    <dt>ECE<dd>Electronics & Communication Engineering
    <dt>IT<dd>Information Technology
    <dt>EEE<dd>Electrical & Electronics Engineering
    <dt>CE<dd>Civil Engineering
  </dl>
</body>
</html>
```

---

### **Nested List:**

```
<html>
<head>
<title>Nested Lists</title>
</head>
<body bgcolor="pink">
<h1 align="center">List of Colleges in Karnataka</h1>
<ol>
<li>Karnataka</li>
<ul>
<li>CIT Gubbi</li>
<li>SIT Tumkur</li>
<li>SSIT Tumkur</li>
</ul>
<li>Bangalore</li>
<ul>
<li>BMS</li>
<li>NITTE</li>
</ul>
</ol>
</body>
</html>
```

## 2. Write a HTML program for time-table using tables.

```
<html>
<head>
  <title>Time Table</title>
</head>
<body bgcolor="skyblue">
<H1><FONT COLOR="DARKCYAN"><CENTER>V SEMESTER TIME
TABLE<br>AI&DS</FONT></H1>
<table border="2" cellspacing="3" align="center">
<tr>
  <td align="center">TIME/DAY</td>
  <td>9:00AM-10:00AM
  <td>10:00AM-11:00AM
  <td>11:15AM-12:15PM
  <td>12:15PM-1:15PM
  <td>2:00PM-3:00PM
  <td>3:00PM-4:00PM
  <td>4:00PM-5:00PM
</tr>
<tr align="center">
  <td>MONDAY</td>
  <td>21AD581</td>
  <td>21AD54</td>
  <td>21ADL581</td>
  <td>21AD51</td>
  <td colspan="2">21CSL46</td>
  <td></td>
</tr>
<tr>
  <td align="center">
  <td>TUESDAY</td>
  <td>21ADL581</td>
  <td>21AD52</td>
  <td>21AD51</td>
  <td>21AD53</td>
  <td colspan="2">21CS42</td>
  <td></td>
</tr>
<tr align="center">
  <td>WEDNESDAY</td>
  <td>21AD51</td>
  <td>21AD52</td>
  <td>21AD54</td>
  <td>21AD52</td>
```



```

<td colspan="2">21AD53</td>
<td></td>
</tr>
<tr align="center">
<td>THURSDAY</td>
<td>21AD53</td>
<td>21AD45</td>
<td>21AD54</td>
<td>21UH59</td>
<td>21AD51</td>
<td>PROCTOR MEETING</td>
<td>Scheduled Activity<br>4:30PM to 6:00PM</td>
</tr>
<tr align="center">
<td>FRIDAY</td>
<td>21AD54</td>
<td>21AD55</td>
<td>21CIP57</td>
<td>21AD53</td>
<td></td>
<td></td>
<td></td>
</tr>
<tr align="center">
<td>SATURDAY</td>
<td colspan="7"></td>
</tr>
</body>
</html>

```

### 3. Write HTML for demonstration of cascading stylesheets.

d. Embedded stylesheets.

e. External stylesheets.

f. Inline styles.

#### Embedded stylesheets:

```
<!DOCTYPE html>
<html>
<head>
<title>Embedded Style sheets</title>
<style type="text/css">
  body {
    background-color: pink;
  }

  h1 {
    color: orange;
    text-align: center;
  }

  p {
    font-family: "Times New Roman";
    font-size: 20px;
  }
</style>
</head>
<body>
  <h1>Embedded Style Sheets</h1>
  <p>This is a paragraph</p>
</body>
</html>
```

## **External Stylesheets:**

### **extern.css:**

```
body {  
    background-color: #d0e4fe;  
}  
  
h1 {  
    color: orange;  
    text-align: center;  
}  
  
p {  
    font-family: "Times New Roman";  
    font-size: 20px;  
}
```

### **extern.html:**

```
<!DOCTYPE html>  
<html>  
<head>  
<title>External Style Sheets</title>  
<link rel="stylesheet" type="text/css" href="extern.css">  
</head>  
<body>  
<h1>External Style Sheets</h1>  
<p>This is a paragraph</p>  
</body>  
</html>
```

**Inline styles:**

```
<!DOCTYPE html>
<html>
<head>
  <title>External Style Sheets</title>
</head>
<body style="background-color: pink;">
  <h1 style="color: orange; text-align: center;">Inline Style Sheets</h1>
  <p style="font-family: 'Times New Roman'; font-size: 20px;">This is a paragraph</p>
</body>
</html>
```

#### 4. Write a JavaScript to design a simple calculator to perform the following operations: sum, product, difference and quotient.

```
<html>
<head>
<title>My calculator</title>
<script type="text/javascript">
function call(click_id)
{
var v1=parseFloat(document.getElementById("ip1").value);
var v2=parseFloat(document.getElementById("ip2").value);
if(isNaN(v1) || isNaN(v2))
alert("enter a valid number");
else if(click_id=="add")
document.getElementById("output").value=v1+v2;
else if(click_id=="sub")
document.getElementById("output").value=v1-v2;
else if(click_id=="mul")
document.getElementById("output").value=v1*v2;
else if(click_id=="div")
document.getElementById("output").value=v1/v2;
}
</script>
</head>
<body>
<center>
<h1> A SIMPLE CALCULATOR PROGRAM</h1>
<table style="background-color:yellow" align=="center">
<tr>
<td>
<form method="get" action="">
<div width=50% align="center">
<label>OP1<input type="text" id="ip1"/></label>
<label>op2<input type="text" id="ip2"/></label>
<label>total<input type="text" id="output"/></label>
</div>
<br>
<div width=50% align="center">
<input type="button" value="+" id="add" onclick="call(this.id)"/>
<input type="button" value="-" id="sub" onclick="call(this.id)"/>
<input type="button" value="*" id="mul" onclick="call(this.id)"/>
<input type="button" value="/" id="div" onclick="call(this.id)"/>
<input type="reset" value="clear"/>
</div>
</form>
</td>
</tr>
</table>
</center>
</body>
</html>
```

**5. Develop and demonstrate a HTML5 file that includes JavaScript script that uses functions for the following problems:**

**a. Parameter: A string**

**b. Output: The position in the string of the left-most vowel**

```
<!DOCTYPE html>
<html>

<head>
  <title>vowel & reverse</title>
</head>

<body>

  <script type="text/javascript">
    var str = prompt("Enter the input", "");

    if (!isNaN(str)) {
      alert("No vowel found in the entered string");
      var num = parseInt(str);
      var rev = 0, remainder;

      while (num !== 0) {
        remainder = num % 10;
        num = parseInt(num / 10);
        rev = rev * 10 + remainder;
      }

      alert("Reverse of " + str + " is " + rev);
    } else {
      str = str.toUpperCase();

      for (var i = 0; i < str.length; i++) {
        var ch = str.charAt(i);
        if (ch === 'A' || ch === 'E' || ch === 'I' || ch === 'O' || ch === 'U') {
          break;
        }
      }

      if (i < str.length) {
        alert("The position of the leftmost vowel is " + (i + 1));
      } else {
        alert("No vowel found in the entered string");
      }
    }
  </script>

</body>

</html>
```

## 6. Write a javascript program for validating REGISTRATION FORM.

```
<!DOCTYPE html>
<html lang="en">

<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Registration Form Validation</title>
  <style>
    body {
      font-family: Arial, sans-serif;
      margin: 20px;
    }

    label {
      display: block;
      margin-bottom: 8px;
    }

    input {
      width: 100%;
      padding: 8px;
      margin-bottom: 16px;
    }

    button {
      padding: 10px;
      background-color: #4CAF50;
      color: white;
      border: none;
      cursor: pointer;
    }

    button:hover {
      background-color: #45a049;
    }

    .error {
      color: red;
      margin-top: 5px;
    }
  </style>
</head>

<body>

  <h2>Registration Form</h2>

  <form id="registrationForm">
    <label for="username">Username:</label>
    <input type="text" id="username" name="username">
```

```
<label for="email">Email:</label>
<input type="email" id="email" name="email">
```

```
<label for="password">Password:</label>
<input type="password" id="password" name="password">
```

```
<div class="error" id="usernameError"></div>
<div class="error" id="emailError"></div>
<div class="error" id="passwordError"></div>
```

```
<button type="button" onclick="validateForm()">Register</button>
</form>
```

```
<script>
function validateForm() {
    // Reset errors
    document.getElementById("usernameError").innerHTML = "";
    document.getElementById("emailError").innerHTML = "";
    document.getElementById("passwordError").innerHTML = "";

    // Get form values
    var username = document.getElementById("username").value.trim();
    var email = document.getElementById("email").value.trim();
    var password = document.getElementById("password").value.trim();

    // Validation checks
    if (username === "") {
        document.getElementById("usernameError").innerHTML = "Username is required";
    }

    if (email === "") {
        document.getElementById("emailError").innerHTML = "Email is required";
    } else if (!isValidEmail(email)) {
        document.getElementById("emailError").innerHTML = "Invalid email format";
    }

    if (password === "") {
        document.getElementById("passwordError").innerHTML = "Password is required";
    } else if (password.length < 6) {
        document.getElementById("passwordError").innerHTML = "Password must be at least 6
characters";
    }

    // Additional validation checks can be added
}
```



```
// If all checks pass, the form is considered valid
if (username !== "" && email !== "" && isValidEmail(email) && password !== "" &&
password.length >= 6) {
    alert("Registration successful!");
    // You can submit the form or perform other actions here
}
}
```

```
function isValidEmail(email) {
    // Basic email format validation
    var emailRegex = /^[^\s@]+@[^\s@]+\.[^\s@]+$/;
    return emailRegex.test(email);
}
```

```
</script>
```

```
</body>
```

```
</html>
```

**7. Write an XML for student information and access second students data using DOM.**

**Schl.xml:**

```
<?xml version="1.0"?>
<school>
  <class>
    <class_title>XML</class_title>
    <students>
      <student>
        <firstname>aaa</firstname>
        <lastname>bbb</lastname>
      </student>
      <student>
        <firstname>aaa</firstname>
        <lastname>bbb</lastname>
      </student>
    </students>
  </class>
</school>
```

**School.html:**

```
<html>
<head>
  <title>Accessing XML data</title>
  <script type="text/javascript">
function getStudentData()
{
  var xmldoc;
  xmldoc=new ActiveXObject("Microsoft.XMLDOM");
  xmldoc.load("school.xml");
  nodeSchool=xmldoc.documentElement;
```

---

---

```
nodeClass=nodeSchool.firstChild;
nodeStudents=nodeClass.lastChild;
nodeStudent=nodeStudents.lastChild;
nodeFirstname=nodeStudent.firstChild;
nodeLastname=nodeFirstname.nextSibling;
message.innerHTML="Name:"+nodeFirstname.firstChild.nodeValue+"
"+nodeLastname.firstChild.nodeValue;
}
</script>
</head>
<body bgcolor="pink">
<center>
<h1>Accessing XML Data</h1>
<div id="message"></div>
<input type="button" value="GET DATA" onClick="getStudentData()">
</center>
</body>
</html>
```

## 8. Write a Javascript program for implementing constructor

```
<!DOCTYPE html>

<html>

<body>

<script>

class CompanyName

{

    constructor()

    {

        this.company="NMIT";

    }

}

class Employee extends CompanyName {

    constructor(id,name) {

        super();

        this.id=id;

        this.name=name;

    }

}

var emp = new Employee(1,"Ram");

document.writeln(emp.id+" "+emp.name+" "+emp.company);

</script>

</body>

</html>
```

## 9. Write a Javascript to add items in a blank array and display the items

```
<!DOCTYPE html>
<html>

<head>

  <meta charset="utf-8" />

  <title>Arrays</title>

  <style>

    body {
      padding-top: 50px
    }

  </style>

</head>

<body>

  <input type="text" id="text1"></input>

  <input type="button" id="button1" value="Add" onclick="add_element_to_array();"></input>

  <input type="button" id="button2" value="Display" onclick="display_array();"></input>

  <div id="Result"></div>

  <script>
    var x = 0;
    var array = Array();

    function add_element_to_array() {
      array[x] = document.getElementById("text1").value;
      alert("Element: " + array[x] + " Added at index " + x);
      x++;
      document.getElementById("text1").value = "";
    }

    function display_array() {
      var e = "<hr/>";
      for (var y = 0; y < array.length; y++) {
        e += "Element " + y + " = " + array[y] + "<br/>";
      }
      document.getElementById("Result").innerHTML = e;
    }
  </script>
</body>
</html>
```

</script>

</body>

</html>

## 10. Write a Javascript program for implementing pattern matching.

```
<!DOCTYPE html>
<html lang="en">

<head>

  <meta charset="utf-8">

  <title>JavaScript Match Words Starts or Ends with a Pattern Using Regular
Expression</title>

</head>

<body>

<script>

  var regex = /(\\bcar\\w*)/g;

  var str = "Words beginning with car: cart, carrot, cartoon. Words ending with car: oscar,
supercar.";
  var replacement = '<b>$1</b>';

  // Highlights the words beginning with car in bold
  var result = str.replace(regex, replacement);
  document.write(result);

</script>

</body>

</html>
```