## Expressions: Abstract Syntax

$$X = \{x, y, z, \dots\}$$
 — variables

$$\otimes = \{\texttt{+, -, *, /, \%, <, <=, >, >=, ==, !=, \&\&, ||} - \text{binary operators}$$

$$\mathcal{E} = \mathbb{Z} \mid X \mid \mathcal{E} \otimes \mathcal{E}$$

## Small-Step Operational Semantics (Strict)

 $s:X\to\mathbb{Z}$  — partial function from variables to integers (state)

$$s \xrightarrow{\mathbf{X}} s \mathbf{x}, \mathbf{x} \in X$$
 [VAR]

$$s \xrightarrow{z} z, z \in \mathbb{Z}$$
 [Const]

$$\frac{s \xrightarrow{A} A'}{s \xrightarrow{A \otimes B} A' \otimes B}, \ A \notin \mathbb{Z}$$
 [BINOP\_LEFT]

$$\frac{s \xrightarrow{B} B'}{s \xrightarrow{a \otimes B} a \otimes B'}, \ a \in \mathbb{Z}, \ B \notin \mathbb{Z}$$
 [BINOP\_RIGHT]

$$s \xrightarrow{a \otimes b} a \oplus b, \ a, b \in \mathbb{Z}$$
 [BINOP]

$$\begin{array}{|c|c|c|} \hline \otimes & a \oplus b \\ \hline + & a+b \\ - & a-b \\ * & a \times b \\ / & a/b, b \neq 0 \\ \% & a \mod b, b \neq 0 \\ \leqslant & \begin{cases} 1 & , & a \leq b \\ 0 & , & a > b \end{cases} \\ \leqslant & \begin{cases} 1 & , & a \leq b \\ 0 & , & a > b \end{cases} \\ 0 & , & a \leq b \end{cases} \\ > = & \begin{cases} 1 & , & a \leq b \\ 0 & , & a \leq b \end{cases} \\ > = & \begin{cases} 1 & , & a \leq b \\ 0 & , & a \leq b \end{cases} \\ 0 & , & a \leq b \end{cases} \\ = & \begin{cases} 1 & , & a \geq b \\ 0 & , & a \leq b \end{cases} \\ 1 & , & a = b \\ 0 & , & a \neq b \end{cases} \\ \vdots \\ \begin{cases} 1 & , & a \neq b \\ 0 & , & a = b \end{cases} \\ \frac{1}{a} \vee \overline{b} \\ \vdots \\ \frac{1}{a} \wedge \overline{b} \end{aligned}$$

$$\overline{x} = \left\{ \begin{array}{ll} true & , & x = 1 \\ false & , & x = 0 \end{array} \right.$$

## Semantic Function

$$\llbracket \bullet \rrbracket : \mathcal{E} \mapsto (X \to \mathbb{Z}) \to \mathbb{Z}$$

$$[\![E]\!] \ s = z \iff s \xrightarrow{E} z$$