CC3100 SLS Get Weather Application

Overview and application details



This sample application demonstrates how to connect to **openweathermap.org** server and request for weather details of a city. The application opens a TCP socket w/ the server and sends a HTTP **Get** request to get the weather details. The received data is processed and displayed on the console

For information on how to use Visual-Studio or Eclipse to compile and run this application, refer to cc3100_getting_started_guide_swru375 [1] in '<cc3100/>docs' folder.

By default, this application communicates w/ CC3100 over SPI. The SDK has UART-Drivers as well for 'SimpleLink Studio' platform. For using the UART interface to communicate w/ CC3100, macro SL_IF_TYPE_UART has to be defined in the application-project's properties. Also, 'COMM_PORT_NUM' in main.c needs to be changed to the first com-port that gets enumerated for 'J6' of 'CC31xxEMUBOOST Brd'. In case four ports are getting enumerated, user should use the third com-port.

Note: This wiki page is only applicable for **CC3100-SDK v1.0.0** and upward releases. For documentation on older SDKs' examples, refer corresponding file in <cc3100-sdk-installation-location>\cc3100-sdk\docs\examples\

Source Files briefly explained

i. main - Initializes the device, connects to an AP, opens a TCP socket, requests and displays the weather information.

Usage

Prerequisite: Internet connectivity is required to work w/ this application

- Build and launch the application using Visual-Studio or Eclipse.
- The application requests user for the AP's SSID and security parameters for establishing the connection. It also
 requests user for the city's name for getting the weather information. Enter the required information on the
 console

The application connects to the weather-server and opens an TCP socket to communicate w/ it. It receives and processes the weather-information and displays it on the console

On success, below message will be displayed on the terminal

```
CC3100 Get weather App
1.2.0
Device is configured in default state
Device is configured in default state
Device started as STATION
Please input the SSID you wish to connect to:
TP-LINK-152
Encryption Types:
1: Open
2: WEP
     WPA
Please enter the corresponding number for the encryption type:
Connecting to AP TP-LINK-152...
Connection established w/ AP and IP is acquired
Enter the city name or "QUIT" to quit#:
Bangalore
*****************************
City:
Bangalore
Temperature:
84.25 F
Weather Condition:
Sky is Clear
<del>***************</del>
Enter the city name or "QUIT" to quit#:
```

Limitations/Known Issues

None

References

[1] http://www.ti.com/lit/pdf/swru375

Article Sources and Contributors

CC3100 SLS Get Weather Application Source: http://processors.wiki.ti.com/index.php?oldid=227234 Contributors: A0131814, A0132173, A0221015, Codycooke, Malokyle, Raghshenoy, SarahP

Image Sources, Licenses and Contributors

File: Cc31xx_cc32xx_return_home.png Source: http://processors.wiki.ti.com/index.php?title=File: Cc31xx_cc32xx_return_home.png License: unknown Contributors: A0221015

Image: Scrshot_sls_get_weather.png Source: http://processors.wiki.ti.com/index.php?title=File: Scrshot_sls_get_weather.png License: unknown Contributors: Raghshenoy