

Индивидуальный проект

Часть 4

Калашникова Дарья

Содержание

1	Цель	5
2	Задачи	6
3	Выводы	10

Список иллюстраций

2.1	Открытие	6
2.2	Проверка	6
2.3	Проверка	7
2.4	Игнорирование	7
2.5	Порт	8
2.6	Ускорение	8
2.7	Проверка	9
2.8	Сканирование	9

Список таблиц

1 Цель

Использовать nikto

2 Задачи

Для начала откроем терминал и установим nikto

```
(dvkalashnikova@dvkalashnikova)-[~]  
$ nikto -Version  
Nikto 2.5.0 (LW 2.5)
```

Рис. 2.1: Открытие

После чего проверим сканирование веб-сервера

```
(dvkalashnikova@dvkalashnikova)-[~]  
$ nikto -h http://example.com  
- Nikto v2.5.0  
  
+ Multiple IPs found: 8.47.69.0, 8.6.112.0, 2a06:98c1:3123:8000::, 2a06:98c1:  
3122:8000::  
+ Target IP: 8.47.69.0  
+ Target Hostname: example.com  
+ Target Port: 80  
+ Start Time: 2026-05-01 19:52:47 (GMT3)  
  
+ Server: cloudflare  
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https:  
//developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options  
+ /: The X-Content-Type-Options header is not set. This could allow the user  
agent to render the content of the site in a different fashion to the MIME ty  
pe. See: https://www.netsparker.com/web-vulnerability-scanner/vulnerabilities  
/missing-content-type-header/
```

Рис. 2.2: Проверка

Далее проверим детальное сканирование с выводом в файл

```
(dvkalashnikova@dvkalashnikova)-[~]
$ nikto -h http://example.com -o result_nikto.txt -Format txt
- Nikto v2.5.0

+ Multiple IPs found: 8.6.112.0, 8.47.69.0, 2a06:98c1:3123:8000::, 2a06:98c1:3123:8000::
+ Target IP: 8.6.112.0
+ Target Hostname: example.com
+ Target Port: 80
+ Start Time: 2026-05-01 19:56:29 (GMT3)

+ Server: cloudflare
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type. See: https://www.netsparker.com/web-vulnerability-scanner/vulnerabilities/missing-content-type-header/
+ ERROR: Error limit (20) reached for host, giving up. Last error:
+ Scan terminated: 0 error(s) and 2 item(s) reported on remote host
+ End Time: 2026-05-01 19:59:55 (GMT3) (206 seconds)

+ 1 host(s) tested
```

Рис. 2.3: Проверка

Затем сделаем сканирование с игнорированием ошибок SSL

```
(dvkalashnikova@dvkalashnikova)-[~]
$ nikto -h https://example.com -ssl -nointeractive
- Nikto v2.5.0

+ Multiple IPs found: 8.6.112.0, 8.47.69.0, 2a06:98c1:3122:8000::, 2a06:98c1:3123:8000::
+ Target IP: 8.6.112.0
+ Target Hostname: example.com
+ Target Port: 443

+ SSL Info: Subject: /CN=example.com
           Ciphers: TLS_AES_256_GCM_SHA384
           Issuer: /C=US/O=CLOUDFLARE, INC./CN=Cloudflare TLS Issu
ng ECC CA 1
+ Start Time: 2026-05-01 20:01:04 (GMT3)

+ Server: cloudflare
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The site uses TLS and the Strict-Transport-Security HTTP header is not d
efined. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Strict-Transport-Security
+ /: The X-Content-Type-Options header is not set. This could allow the user
```

Рис. 2.4: Игнорирование

После чего сделаем сканирование конкретного порта, например 8080

```
(dvkalashnikova@dvkalashnikova)-[~]
$ nikto -h http://example.com -p 8080
- Nikto v2.5.0

- ERROR: The -port option cannot be used with a full URI
```

Рис. 2.5: Порт

Далее сделаем ускоренное сканирование

```
(dvkalashnikova@dvkalashnikova)-[~]
$ nikto -h http://example.com -maxtime 60
- Nikto v2.5.0

+ Multiple IPs found: 8.47.69.0, 8.6.112.0, 2a06:98c1:3123:8000::, 2a06:98c1:3122:8000::
+ Target IP: 8.47.69.0
+ Target Hostname: example.com
+ Target Port: 80
+ Start Time: 2026-05-01 20:07:25 (GMT3)

+ Server: cloudflare
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type. See: https://www.netsparker.com/web-vulnerability-scanner/vulnerabilities/missing-content-type-header/
+ ERROR: Host maximum execution time of 60 seconds reached
+ Scan terminated: 0 error(s) and 2 item(s) reported on remote host
+ End Time: 2026-05-01 20:08:26 (GMT3) (61 seconds)

+ 1 host(s) tested
```

Рис. 2.6: Ускорение

Затем сделаем проверку конкретной уязвимости или файла


```
(dvkalashnikova@dvkalashnikova)-[~]
$ nikto -h http://example.com -Tuning 4
- Nikto v2.5.0

+ Multiple IPs found: 8.47.69.0, 8.6.112.0, 2a06:98c1:3123:8000::, 2a06:98c1:3122:8000::
+ Target IP: 8.47.69.0
+ Target Hostname: example.com
+ Target Port: 80
+ Start Time: 2026-05-01 20:08:48 (GMT3)

+ Server: cloudflare
+ /: The anti-clickjacking X-Frame-Options header is not present. See: https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/X-Frame-Options
+ /: The X-Content-Type-Options header is not set. This could allow the user agent to render the content of the site in a different fashion to the MIME type. See: https://www.netsparker.com/web-vulnerability-scanner/vulnerabilities/missing-content-type-header/
+ No CGI Directories found (use '-C all' to force check all possible dirs)
+ ERROR: Error limit (20) reached for host, giving up. Last error:
+ Scan terminated: 0 error(s) and 2 item(s) reported on remote host
+ End Time: 2026-05-01 20:12:13 (GMT3) (205 seconds)

+ 1 host(s) tested
```

Рис. 2.7: Проверка

И в последней проверке отсканируем конкретный сервер, сохраним отчет в формате html и максимально время 120

```
(dvkalashnikova@dvkalashnikova)-[~]
$ nikto -h http://192.168.1.100 -o project_scan.html -Format html -maxtime 120
- Nikto v2.5.0

+ 0 host(s) tested
```

Рис. 2.8: Сканирование

3 Выводы

В результате выполнения лабораторной работы я получила навыки работы с
nikto