NST21022 - Practical for Network Switching and Routing

Department of Information and Communication Technology

Faculty of Technology

Lab sheet :18E1&E2
Reg. Number: SEU/IS/20/ICT/084
Academic Year :2020/2021
Practical No :18

Title: Configure a Wireless LAN

Aim:

- Getting familiar with Wireless Network
- Getting familiar with WPA2 Enterprise WLAN on the WLC

Task:

- Configure wireless router
- Connect wireless devices to the wireless router
- Add an access point to extend wireless coverage
- Configure a new VLAN interface on a WLC.
- Configure a new WLAN on a WLC.
- Configure a new scope on the WLC internal DHCP server.
- Configure the WLC with SNMP settings.
- Configure the WLC to user a RADIUS server to authenticate WLAN users.
- Secure a WLAN with WPA2-Enterprise.
- Connect hosts to the new WLC.

Activities

Exercise 01: Configure Personal Wireless LAN

Use "NST21022 Lab sheet 18E1.pka" file



1. Configure **Admin** to use DHCP



2. Connect to the WR Web Interface (192.168.0.1)

    a. In Web Browser



b. Use **admin** for both username and password



.

c. Under the Network Setup heading on the **Basic Setup** page, notice the IP address rang for the DHCP server.



3. Configure the Internet Port of WR

a. Under **the Internet Setup** at the top of the **Basic Setup** page, change the Internet IP address method to **Static IP**



b. Following IP address have to be assigned to the **Internet interface**:

Internet IP address : 10.1.2.10
Subnet Mask : 255.255.255.0
Default Gateway : 10.1.2.1
DNS Server : 10.1.1.10



c. Save Settings and verity connectivity through access www.cisco.com





4. Configure Wireless Settings
    a. Connect to the WR web interface



b. Navigate to **Wireless ➔ Basic Wireless Settings**



c. Change **Network Name (SSID)** to **Home** for only 2.4GHz. tice that SSIDs are case sensitive



d. Chane the Standard Channel to **6 – 2.437GHz**



e. Disable 5GHz frequencies.



f. **Save Settings**



5. Configure wireless security settings

a. Navigate to **Wireless ➔Wireless Security**



b. Under the **2.4 GHz** heading, **select WPA2 Personal** for the security mode.



c. Keep the default **AES** encryption settings



d. Enter **cisco@123** as the passphrase



e. **Save Settings**



6. Connect the Wireless Clients

a. Turn on wireless interface in **LP1**



b. Navigate to **PC Wireless** on **LP1**



c. Select **Connect** tab and refresh as necessary, select the wireless network name **Home**



d. Enter passphrase and click connect.



e. Open browser and try to access www.cisco.com



7. Connect wireless clients to an Access Point

a. Connect **Port 0** of **AP** with **WR**



b. In the **config** tab select **Port 1**



c. Enter SSID as **Home**



d. Keep **channel 1** if it is not change to **channel 1**



e. Select **WPA2-PSK** and enter the passphrase **cisco@123**



f. Keep **AES** as the default encryption type.



8. Connect the wireless clients

a. On **LP2** turn on wireless interface and go to **PC Wireless**



b. Select **Connect** and **refresh**

c. Select **Home** with the strong single and connect



d. Open web browser and try to access www.cisco.com



9. Change the WR access password

a. Connect to the **WR** web interface



b. Navigate to **Administration** ➔ **Management** and change the current router password to **cisco**



c. **Save Settings**



c. Use **admin** as the username and new password when prompted to log in to the wireless router.



10. Change the DHCP address range in WR

a. Navigate to **Setup ➔ Basic Setup**



b. Scroll down the page to **Network Setup**



c. Change **Router IP** to **192.168.20.1**



d. Add **10.1.1.10** as the **DNS Server** with the DHCP settings

e. Save Settings



f. Navigate to Admin PC's **Command Prompt**



g. Type **ipconfig /renew** to force Admin to re-acquire its IP information via DHCP



h. Verity that you can still navigate to www.cisco.com



Exercise 02:

Configure a WPA2 Enterprise WLAN on the WLC

Use “NST21022 Lab sheet 18E2.pka” file



Addressing Table

Device	Interface	IP Address
R1	G0/0/0.5	192.168.5.1/24
	G0/0/0.200	192.168.200.1/24
	G0/0/1	172.31.1.1/24
SW1	VLAN 200	192.168.200.100/24
LAP-1	G0	DHCP
WLC-1	Management	192.168.200.254/24
RADIUS/SNMP Server	NIC	172.31.1.254/24
Admin PC	NIC	192.168.200.200/24

Part 1: Create a new WLAN

Step 1: Create a new VLAN interface.

Each WLAN requires a virtual interface on the WLC. These interfaces are known as dynamic interfaces. The virtual interface is assigned a VLAN ID and traffic that uses the interface will be tagged as VLAN traffic. This is why connections between the

APs, the WLC, and the router are over trunk ports. For the traffic from multiple WLANs to be transported through the network, traffic for the WLAN VLANs must be trunked.

1. Open the browser from the desktop of Admin PC. Connect to the IP address of the WLC over HTTPS.



http → https **change**

2. Login with the username **admin** and password **Cisco123**.



3. Click the **Controller** menu and then click **Interfaces** from the menu on the left. You will see the default virtual interface and the management interface to which you are connected.



4. Click the **New** button in the upper right-hand corner of the page. You may need to scroll the page to the right to see it.



5. Enter the name of the new interface. We will call it **WLAN-5**. Configure the **VLAN ID** as **5**. This is the VLAN that will carry traffic for the WLAN that we create later. Click **Apply**. This leads to a configuration screen for the VLAN interface.



6. First, configure the interface to use physical port number **1**. Multiple VLAN interfaces can use the same physical port because the physical interfaces are like dedicated trunk ports.



7. Address the interface as follows:

IP Address: 192.168.5.254

Netmask: 255.255.255.0

Gateway: 192.168.5.1

Primary DHCP server: 192.168.5.1



User traffic for the WLAN that uses this VLAN interface will be on the 192.168.5.0/24 network. The default gateway is the address of an interface on router R-1. A DHCP pool has been configured on the router. The address that we configure here for DHCP tells the WLC to forward all DHCP requests that it receivesfrom hosts on the WLAN to the DHCP server on the router.

8. Be sure to click **Apply** to enact your changes and click **OK** to respond to the warning message.

Click **Save Configuration** so that your configuration will be in effect when the WLC restarts.



Step 2: Configure the WLC to use a RADIUS server.

WPA2-Enterprise uses an external RADIUS server to authenticate WLAN users. Individual user accounts with unique usernames and passwords can be configured on the RADIUS server. Before the WLC can use the services of the RADIUS server, the WLC must be configured with the server address.

1. Click the **Security** menu on the WLC.

2. Click the **New** button and enter the IP address of the RADIUS server in the





Server IP Address field.

3. The RADIUS server will authenticate the WLC before it will allow the WLC to access the user account information that is on the server. This requires a shared secret value. Use **Cisco123**. Confirm the shared secret and click **Apply**.

Note: It is not a good practice to reuse passwords. This activity reuses passwords only to make the activity easier for you to complete and review.



Step 3: Create a new WLAN.

Create a New WLAN. Use the newly created VLAN interface for the new WLAN.

1. Click the **WLANs** entry in the menu bar. Locate the dropdown box in the upper right-had corner of the WLANs screen. It will say **Create New**. Click **Go** to create a new WLAN.



2. Enter the **Profile Name** of the new WLAN. Use the profile name **Floor 2 Employees**. Assign an SSID of **SSID-5** to the WLAN. Change the ID drop down to **5**. Hosts will need to use this SSID to join the network. When you are done, click **Apply** to accept your settings.



Note: The ID is an arbitrary value that is used as a label for the WLAN. In this case, we configured it as 5 to be consistent with VLAN for the WLAN. It could be any available value.

3. Click **Apply** so that the settings go into effect.



4. Now that the WLAN has been created you can configure features of the network. Click **Enabled** to make the WLAN functional. It is a common mistake to accidentally skip this step.



5. Choose the VLAN interface that will be used for the new WLAN. The WLC will use this interface for user traffic on the network. Click the drop-down box for Interface/Interface Group (G). Select the interface that we created in Step 1.



6. Go to the Advanced tab. Scroll to **FlexConnect** section of the interface.



7. Click to enable **FlexConnect Local Switching** and **FlexConnect Local Auth**.



8. Click **Apply** to enable the new WLAN. If you forget to do this, the WLAN will not operate.



Step 4: Configure WLAN security.

Instead of WPA2-PSK, we will configure the new WLAN to use WPA2-Enterprise.

1. Click the WLAN ID of the newly created WLAN to continue configuring it, if necessary.



2. Click the Security tab. Under the Layer 2 tab, select **WPA+WPA2** from the dropdown box.



3. Under WPA+WPA2 Parameters, enable **WPA2 Policy**. Click **802.1X** under Authentication Key Management. This tells the WLC to use the 802.1X protocol to authenticate users externally.



4. Click the **AAA Servers** tab. Open the drop-down next to Server 1 in the Authentication Servers column and select the server that we configured in Step 2.



5. Click **Apply** to enact this configuration. You have now configured the WLC to use the RADIUS sever to authenticate users that attempt to connect to the WLAN.



Part 2: Configure a DHCP Scope and SNMP Step 1:

Configure a DHCP Scope.

The WLC offers its own internal DHCP server. Cisco recommends that the WLAN DHCP server not be used for high-volume DHCP services, such as that required by larger user WLANs. However, in smaller networks, the DHCP server can be used to provide IP addresses to LAPs that are connected to the wired management network.

1. Should be connected to the WLC GUI from Admin PC.



2. Click the **Controller** menu and then click **Interfaces**.



3. Click the **management** Interface. Record its addressing information here.

IP address:

Netmask:

Gateway:

Primary DHCP server:



4. We want the WLC to use its own DHCP sever to provide addressing to devices on the wireless management network, such as lightweight APs. For this reason, enter the IP address of the WLC management interface as the primary DHCP server address. Click **Apply**. Click **OK** to acknowledge any warning messages that appear.



5. In the left-hand menu, expand the **Internal DHCP Server** section. Click **DHCP Scope**.



6. To create a DHCP scope, click the **New...** button.



7. Name the scope **Wired Management**. You will configure this DHCP scope to provide addresses to the wired infrastructure network that connects the Admin PC, WLC-1, and LAP-1.



8. Click **Apply** to create the new DHCP scope.

9. Click the new scope in the DHCP Scopes table to configure addressing information for the scope. Enter the following information.

Scope Name	Address Pool
Wired Management	0.0.0.0 - 0.0.0.0

Pool Start Address: 192.168.200.240

Pool End Address: 192.168.200.249

Status: Enabled

Provide the values for **Network, Netmask,** and **Default Routers** from the information you gathered in Step 1.3. **(Step 1 . 3 eke Netmask add krnna)**



10. Click **Apply** to activate the configuration. Click **Save Configuration** in the upper-right-hand corner of the WLC interface to save your work so that it is available when the WLC restarts.



The internal DHCP server will now provide an address to LAP-1 after a brief delay. When LAP-1 has its IP address, the CAPWAP tunnel will be established and LAP-1 will be able to provide access to the Floor 2 Employees (SSID-5) WLAN. If you move the mouse over LAP-1 in the topology, you should see its IP address, the status of the CAPWAP tunnel, and the WLAN that LAP-1 is providing access to.

Step 2: Configure SNMP.

1. Click the **Management** menu in the WLC GUI and expand the entry for **SNMP** in the left-hand menu.



2. Click **Trap Receivers** and then **New...**



3. Enter the community string as **WLAN_SNMP** and the IP address of the server at

172.31.1.254.



3. Click **Apply** to finish the configuration.

Part 3: Connect Hosts to the Network

Step 1: Configure a host to connect to the enterprise network.

In the Packet Tracer PC Wireless client app, you must configure a WLAN Profile in order to attach to a WPA2-Enterprise WLAN.

1. Click Wireless Host and open the **PC Wireless** app.



2. Click the **Profiles** tab and then click **New** to create a new profile. Name the profile **WLC NET**.





3. Highlight the Wireless Network Name for the WLAN that we created earlier and click **Advanced Setup**.

4. Verify that the SSID for the wireless LAN is present and then click Next. Wireless Host should see SSID-5. If it does not, move the mouse over LAP-1 to verify that it is communicating with the WLC. The popup box should indicate that LAP-1 is aware of SSID-5. If it is not, check the WLC configuration. You can also manually enter the SSID.


Creating a Profile
Wireless Mode
Please choose the Wireless Mode that best suits your needs.
Infrastructure Mode
Ad-Hoc Mode
Select Infrastructure Mode if you want to connect to a wireless router or access point.
Select Ad-Hoc Mode if you want to connect to another wireless device directly without using a wireless router or access point.
Please enter the wireless network name (SSID) for your wireless network.
The wireless network name is shared by all devices in a wireless network and is case-sensitive.
Wireless Network Name
SSID-5
Back
Next
Wireless-N Notebook Adapter
Wireless Network Monitor v1.0
Model No. WPC300N


Creating a Profile
Network Settings
Obtain network settings automatically (DHCP)
Select this option to have your network settings assigned automatically.
Specify network settings
Select this option to specify the network settings for the adapter.
IP Address
Subnet Mask
Default Gateway
DNS 1
DNS 2
Back
Next
Wireless-N Notebook Adapter
Wireless Network Monitor v1.0
Model No. WPC300N

5. Verify that the DHCP network setting is selected and click **Next**.

6. In the Security drop down box, select **WPA2-Enterprise**. Click **Next**.



7. Enter login name **user1** and the password **User1Pass** and click **Next**.

8. Verify the Profile Settings and click **Save**.



9. Select the **WLC NET** profile and click the **Connect to Network** button. After a brief delay, you should see the Wireless Host connect to LAP-1. You can click the Fast Forward Time button to speed up the process if it seems to be taking too long.





Select and Click Connect Refresh and select wireless network and connect



10. Confirm that Wireless Host has connected to the WLAN. Wireless Host should receive an IP address from the DHCP server that is configured for hosts on R1. The address will be in the 192.168.5.0/24 network. You may need to click the Fast Forward Time button speed up the process.

Step 2: Test Connectivity.

1. Close the PC Wireless app.



2. Open a command prompt and confirm that Wireless Host laptop has obtained an IP address from the WLAN network.



3. Ping the default gateway, SW1, and the RADIUS server. Success indicates full connectivity within this topology.



Discussion

- In this lab session, we focused on configuring and securing a wireless network using a wireless router and Wireless LAN Controller (WLC). First, we set up a wireless router and

connected wireless devices to it, ensuring basic wireless connectivity. To extend coverage, we added an access point to expand the network's reach. On the WLC, we configured a new VLAN interface to segment network traffic, then created a new WLAN for wireless clients. We also set up a new DHCP scope on the WLC's internal DHCP server to automatically assign IP addresses to wireless clients. To improve monitoring, we configured SNMP settings on the WLC, followed by integrating a RADIUS server for secure user authentication. Finally, we secured the WLAN using WPA2-Enterprise and connected hosts to the new WLAN, ensuring both security and smooth wireless access across the network.