

LibraryService.wsdl

```
<definitions name="LibraryService"
  targetNamespace="http://example.com/wsdl/LibraryService"
  xmlns="http://schemas.xmlsoap.org/wsdl/"
  xmlns:soap="http://schemas.xmlsoap.org/wsdl/soap/"
  xmlns:tns="http://example.com/wsdl/LibraryService"
  xmlns:xsd="http://www.w3.org/2001/XMLSchema">

  <message name="AddBookRequest">
    <part name="bookId" type="xsd:int"/>
    <part name="title" type="xsd:string"/>
    <part name="author" type="xsd:string"/>
  </message>

  <message name="GetBookDetailsRequest">
    <part name="bookId" type="xsd:int"/>
  </message>

  <message name="GetBookDetailsResponse">
    <part name="title" type="xsd:string"/>
    <part name="author" type="xsd:string"/>
    <part name="availability" type="xsd:boolean"/>
  </message>

  <portType name="LibraryPortType">
    <operation name="addBook">
      <input message="tns:AddBookRequest"/>
    </operation>

    <operation name="getBookDetails">
      <input message="tns:GetBookDetailsRequest"/>
      <output message="tns:GetBookDetailsResponse"/>
    </operation>
  </portType>

  <binding name="LibraryBinding" type="tns:LibraryPortType">
    <soap:binding style="rpc"
      transport="http://schemas.xmlsoap.org/soap/http"/>
  </binding>

  <service name="LibraryService">
    <port name="LibraryPort" binding="tns:LibraryBinding">
      <soap:address location="http://localhost:8080/LibraryService"/>
    </port>
  </service>
</definitions>
```

```
</service>
```

```
</definitions>
```