



Experiment 4

Student Name: Vaibhav Kumar

Branch: CSE

Semester: 5th

Subject Name: ADBMS

UID: 23BCS13386

Section/Group: KRG_2B

Date of Performance: 8/09/2025

Subject Code: 23CSP-333

Q1. Consider a relation R having attributes as R(ABCD), functional dependencies are given below:

AB→C, C→D, D→A

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.

Solution : To find the candidate keys, let us compute closures:

- $(AB)^+ = \{A, B, C, D\}$
- $(BC)^+ = \{A, B, C, D\}$
- $(BD)^+ = \{A, B, C, D\}$

Hence, the possible candidate keys are AB, BC, and BD.

Since all attributes (A, B, C, D) are part of at least one candidate key, they are prime attributes. Thus, there are no non-prime attributes (\emptyset).

Normal Form Check

- **BCNF: Not satisfied.**
 - Rule: For each functional dependency $X \rightarrow Y$, the left-hand side must be a superkey.
 - $C \rightarrow D$: C alone is not a superkey → violates.
 - $D \rightarrow A$: D alone is not a superkey → violates.
- **3NF: Satisfied.**
 - Rule: For every FD $X \rightarrow Y$, either X is a superkey or Y is a prime attribute.
 - $AB \rightarrow C$: AB is a key → valid.



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

- $C \rightarrow D$: C is not a key, but D is prime \rightarrow valid.
- $D \rightarrow A$: D is not a key, but A is prime \rightarrow valid.

Therefore, the relation is in 3NF but not in BCNF.

Q2. Relation R(ABCDE) having functional dependencies as :

$A \rightarrow D, B \rightarrow A, BC \rightarrow D, AC \rightarrow BE$

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.

Solution: For relation R(A, B, C, D, E) with the given dependencies:

- $A \rightarrow D$
- $B \rightarrow A$
- $BC \rightarrow D$
- $AC \rightarrow BE$

Candidate Keys

Let's compute closures:

- $(BC)^+ = \{A, B, C, D, E\} \rightarrow$ covers all attributes.
- $(AC)^+ = \{A, B, C, D, E\} \rightarrow$ covers all attributes.

Thus, the candidate keys are {BC, AC}.

Here, attributes A, B, and C are part of at least one candidate key, so they are prime attributes.

Attributes D and E are not in any candidate key \rightarrow they are non-prime attributes.

Normal Form Check

- **BCNF: Not satisfied.**
 - Rule: Every determinant should be a superkey.
 - $A \rightarrow D$: A alone is not a key \rightarrow violates.
 - $B \rightarrow A$: B alone is not a key \rightarrow violates.
- **3NF: Also not satisfied.**
 - Condition: Either the left side is a key or the right side contains only prime attributes.
 - $A \rightarrow D$: A is not a key, and D is non-prime \rightarrow violation.
- **2NF: Not satisfied** as well, since partial dependencies exist on candidate keys.

Hence, the relation is only in 1NF.

Q3. Consider a relation R having attributes as R(ABCDE), functional dependencies are given below:

$B \rightarrow A, A \rightarrow C, BC \rightarrow D, AC \rightarrow BE$

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Given: $R(A,B,C,D,E)$ with FDs

- $B \rightarrow A$
- $A \rightarrow C$
- $BC \rightarrow D$
- $AC \rightarrow BE$

Closures:

- ☐ $(A)^+ = \{A, C, B, E, D\} = \{A,B,C,D,E\}$
- ☐ $(B)^+ = \{B, A, C, E, D\} = \{A,B,C,D,E\}$
- ☐ $(C)^+ = \{C\}$
- ☐ $(D)^+ = \{D\}$
- ☐ $(E)^+ = \{E\}$

Candidate Keys: $\{A, B\}$

Prime attributes: $\{A, B\}$

Non-prime attributes: $\{C, D, E\}$

BCNF: Yes

- $B \rightarrow A$: B is a superkey \rightarrow Ok
- $A \rightarrow C$: A is a superkey \rightarrow Ok

So on.. all LHS are superkeys

Normal Form: BCNF

Q4. Consider a relation R having attributes as $R(ABCDEF)$, functional dependencies are given below:

$A \rightarrow BCD, BC \rightarrow DE, B \rightarrow D, D \rightarrow A$

Identify the set of candidate keys possible in relation R. List all the set of prime and non prime attributes.

Given: $R(A,B,C,D,E,F)$ with FDs

- $A \rightarrow B C D$
- $BC \rightarrow D E$
- $B \rightarrow D$



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

- $D \rightarrow A$

Closures:

- $(A)^+ = \{A, B, C, D, E\}$
- $(B)^+ = \{A, B, C, D, E\}$
- $(D)^+ = \{A, B, C, D, E\}$
- $(F)^+ = \{F\}$
- $(AF)^+ = \{A, B, C, D, E, F\} \rightarrow \text{key}$
- $(BF)^+ = \{A, B, C, D, E, F\} \rightarrow \text{key}$
- $(DF)^+ = \{A, B, C, D, E, F\} \rightarrow \text{key}$

Candidate Keys: $\{AF, BF, DF\}$

Prime attributes: $\{A, B, D, F\}$

Non-prime attributes: $\{C, E\}$

BCNF: No

- $A \rightarrow BCD$: A is not a superkey \rightarrow violates.

3NF: No

- $A \rightarrow C$ (part of $A \rightarrow BCD$): A not a superkey and C is non-prime \rightarrow violates.

2NF: No

- AF is a key, but $A \rightarrow C$ (C non-prime) is a partial dependency on part of key AF \rightarrow violates.

1NF: Yes — attributes assumed atomic.

Normal Form: 1NF

Q5. Designing a student database involves certain dependencies which are listed below:

$X \rightarrow Y$

$WZ \rightarrow X$

$WZ \rightarrow Y$

$Y \rightarrow W$

$Y \rightarrow X$

$Y \rightarrow Z$



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

Identify the set of candidate keys possible in student database. List all the set of prime and non prime attributes.

Given: attributes {W, X, Y, Z} with FDs

- $X \rightarrow Y$
- $WZ \rightarrow X$
- $WZ \rightarrow Y$
- $Y \rightarrow W$
- $Y \rightarrow X$
- $Y \rightarrow Z$

Closures:

- $(Y)^+ = \{Y, W, X, Z\} = \text{all attributes} \rightarrow Y \text{ is a key.}$
- $(X)^+ = \{X, Y, W, Z\} = \text{all attributes} \rightarrow X \text{ is a key.}$
- $(WZ)^+ = \{W, Z, X, Y\} = \text{all attributes} \rightarrow WZ \text{ is a key.}$

Candidate Keys: { X, Y, WZ }

Prime attributes: { W, X, Y, Z }

Non-prime attributes: \emptyset

BCNF: Yes

- Every FD has LHS that is a superkey (X, Y, WZ) \rightarrow satisfies BCNF.

Normal Form: BCNF

Q6. Debix Pvt Ltd needs to maintain database having dependent attributes ABCDEF. These attributes are functionally dependent on each other for which functional dependency set F given as:

{A \rightarrow BC, D \rightarrow E, BC \rightarrow D, A \rightarrow D} Consider a universal relation R1(A, B, C, D, E, F) with functional dependency set F, also all attributes are simple and take atomic values only. Find the highest normal form along with the candidate keys with prime and non-prime attribute.

Given: R(A,B,C,D,E,F) with FDs

- $A \rightarrow B C$
- $D \rightarrow E$
- $BC \rightarrow D$



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING

Discover. Learn. Empower.

- $A \rightarrow D$

Closures:

- $(A)^+ = \{A, B, C, D, E\}$
- $(AF)^+ = \{A, B, C, D, E, F\} \rightarrow \text{key}$
- $(BC)^+ = \{B, C, D, E\}$
- $(D)^+ = \{D, E\}$
- $(F)^+ = \{F\}$

Candidate Keys: $\{AF\}$

Prime attributes: $\{A, F\}$

Non-prime attributes: $\{B, C, D, E\}$

BCNF: No

- $A \rightarrow BC / A \rightarrow D$: A not a superkey \rightarrow violates.

3NF: No

- $A \rightarrow BC$: A not a superkey and B,C are non-prime \rightarrow violates.

2NF: No

- AF is a key, $A \rightarrow BC$ (BC non-prime) is a partial dependency on part of the key \rightarrow violates.

1NF: Yes — attributes atomic.

Normal Form: 1NF