

# Grouping the aggregated rows and using sub queries

- The learning objectives for this week are:
  - Knowing how the `GROUP BY` clause operates and how it is related to the aggregate functions
  - Knowing how to use the aggregate functions in filtering with the `HAVING` clause
  - Knowing what are subqueries and how they can be used in a `SELECT` statement
  - Knowing different kind of use-cases for subqueries, including row filter criteria, correlated subqueries, in the `SELECT` list, in the `HAVING` clause, and in the `FROM` clause

# Grouping the aggregated rows

- Aggregate function (such as `COUNT` and `SUM` ) performs a calculation for **multiple rows so that the end result is a single value**
- However, in many cases we want to get a certain summarized information for specific **groups of rows**, for example *"what's the average grade from each course?"* or *"what is the average grade of each student"*
- To achieve this, we need to **group** the rows based on a specific column (such as `course_code` or `student_number` ) and **perform the aggregate function for each group separately**
- This can be done using the `GROUP BY` clause

# The GROUP BY clause

```
GROUP BY column_list [ HAVING group_filtering_condition ]
```

- The `GROUP BY` clause uses a column or a group of columns in a `SELECT` statement to form **groups of rows which the aggregate function operators on:**

```
-- what's the average grade from each course?  
SELECT course_code, AVG(grade) as average_grade FROM CourseGrade  
-- form the groups based on the course_code  
GROUP BY course_code
```

# The GROUP BY clause

- The result table will have a row for **each distinct column value** of the `GROUP BY` column
- Each row has the corresponding aggregate function result for that group
- In the example's case the result table would contain the average grade for each distinct `course_code` :

<code>course_code</code>	<code>average_grade</code>
a290	2.5
a450	3.0
...	...

# The GROUP BY clause

- As mentioned, the `GROUP BY` clause can have multiple columns
- In this case the result table will have a row for **each distinct combination of column values** of the `GROUP BY` columns

```
-- what's the average grade from each course instance?  
SELECT course_code, instance_number, AVG(grade) as average_grade FROM CourseGrade  
-- form the groups based on the course_code and instance_number  
GROUP BY course_code, instance_number
```

# The GROUP BY clause

- In the example's case the result table would contain the average grade for each distinct combination of `course_code` and `instance_number` :

```
-- what is the average grade of each course instance?  
SELECT course_code, instance_number, AVG(grade) as average_grade FROM CourseGrade  
GROUP BY course_code, instance_number
```

course_code	instance_number	average_grade
a290	1	4.5
a290	2	3.0
a450	1	2.9
...	...	...

# The GROUP BY clause

- It is worth noting that in the `SELECT` statement we can only select columns that are either aggregate functions or columns used in the `GROUP BY` clause:

```
-- ✗ student_number is not an aggregate function, nor it is in the GROUP BY clause.  
-- This will lead into an error  
SELECT course_code, student_number, AVG(grade) as average_grade FROM CourseGrade  
GROUP BY course_code
```

- This causes the following error:

*"Column 'CourseGrade.student\_number' is invalid in the select list because it is not contained in either an aggregate function or the GROUP BY clause"*

# Combining with the WHERE clause

- We can use the `WHERE` clause to apply filtering **before the grouping is done** by the `GROUP BY` clause:

```
-- how many employees whose salary is above 10000 there are in each department?  
SELECT deptno, COUNT(*) AS number_of_employees  
FROM Employee  
WHERE salary > 10000 -- The WHERE clause is applied before grouping is done  
GROUP BY deptno  
ORDER BY deptno
```



# Using aggregate functions in filtering

- The `WHERE` clause can't use aggregate functions because it is **applied before** the `GROUP BY` clause while the query is executed
- Instead, we can use the `HAVING` clause to filter rows based on aggregate function results:

```
-- which departments have more than 10 employees?  
-- ❌ can't use aggregate functions with the WHERE clause, this won't work  
SELECT deptno, COUNT(*) AS number_of_employees  
FROM Employee  
WHERE COUNT(*) > 10  
GROUP BY deptno  
  
-- ✅ we should use the HAVING clause instead  
SELECT deptno, COUNT(*) AS number_of_employees  
FROM Employee  
GROUP BY deptno  
HAVING COUNT(*) > 10
```

# Examples of GROUP BY clause

- What do we get from the following queries?

```
-- ? what do we get from this query?  
SELECT campus_code, COUNT(campus_code) AS number_of_teachers  
FROM Teacher  
GROUP BY campus_code
```

```
-- ? what do we get from this query?  
SELECT course_code, AVG(grade) AS average_grade  
FROM CourseGrade  
WHERE grade_date BETWEEN '2024-01-01' AND '2024-12-31'  
GROUP BY course_code  
HAVING COUNT(grade) > 10
```

# Subqueries

- A **subquery** is a query within another query, which is used to retrieve data that will be processed by the outer query
- The most common use case for a subquery is to use subquery result in a filtering condition in a `WHERE` clause
- There is now maximum depth in subqueries, so a subquery can also contain another subquery
- Most of our examples will cover usage of subqueries with the `SELECT` statement, but they can be used with e.g. `INSERT INTO` and `UPDATE` statements as well

```
--- who are the teachers with a above average salary?  
SELECT first_name, surname, salary  
FROM Teacher  
WHERE salary > (  
    -- subquery for calculating the average salary  
    SELECT AVG(salary) FROM Teacher  
)
```

# Subqueries in a SELECT statement

- The subquery is placed inside brackets ( ) and its result will be passed to the outer query
- In a SELECT statement, we can nest a subquery within:
  - WHERE clause as a row filter criteria to be used in the condition
  - WHERE clause as a correlated subquery
  - SELECT list as a column expression or as a part of a column expression
  - HAVING clause as a group filter criteria within a GROUP BY clause
  - FROM clause to create a temporary derived table
  - WITH clause to create a temporary named result set, known as common table expression (CTE)

# Subquery as a row filter criteria

- The most common use of the subquery is to use it as a row filter criteria similarly as e.g. literals:

```
-- using literal 5000 as a filter criteria
WHERE salary > 5000

-- using a subquery as a filter criteria (note the brackets wrapping the subquery)
WHERE salary > (
  -- the result of the subquery will be used in the comparison
  SELECT AVG(salary) FROM Teacher
)
```

# Subquery as a row filter criteria

```
-- which countries have larger population than Australia?
SELECT country_name, population
FROM Country
WHERE population > (
    -- subquery for getting the population of Australia
    SELECT population
    FROM Country
    WHERE country_name = 'Australia'
)
```

```
-- ? what do we get from this query?
SELECT country_name, population
FROM Country
WHERE population = (SELECT MAX(population) FROM Country)
```

```
-- ? what do we get from this query?
SELECT empno, empname
FROM Employee
WHERE empno NOT IN (SELECT empno FROM Project_Employee)
```

# Correlated subqueries

- A **correlated subquery** (inner query) uses one or more values from the outer query
- The correlated subquery is executed once for each row that is selected by the outer query

```
-- which students are from a city where there is a campus?  
SELECT city, surname, given_name, student_number  
FROM Student  
-- using a correlated subquery  
WHERE EXISTS (  
    -- does any such row EXIST in the Campus table where Campus.city = Student.city  
    SELECT * FROM Campus  
    WHERE Campus.city = Student.city  
)
```

# Performance of correlated subqueries

- 🍌 In the example, the **correlated subquery is executed once per each student**, which will degrade the query performance
- 🚀 If possible, it is usually better to use a non-correlated subquery to improve readability and performance:

```
-- 🚀 same result using a non-correlated subquery
SELECT city, surname, given_name, student_number
FROM Student
-- we aren't using any information from the outer query in the subquery
WHERE city IN (SELECT city FROM Campus)
```



# Subqueries within a SELECT list

- A subquery can be used in the `SELECT` list to **compute a value for a column** that will be displayed in the result table:

```
-- what is the percentage of red cars?
SELECT (SELECT 100.0 * COUNT(*) FROM Car WHERE colour = 'red') / COUNT(*)
  AS percentage_of_red_cars
FROM Car

-- what is the average grade for each student?
SELECT
student_number, (
  SELECT AVG(grade) FROM CourseGrade
  WHERE CourseGrade.student_number = Student.student_number
) AS average_grade
FROM Student
```

# Subqueries within a HAVING clause

- Similarly as in the `WHERE` clause, a subquery can be used in the `HAVING` clause to filter the groups based on the aggregate function result:

```
-- in which departments the average salary is higher than the average salary of all employees?  
SELECT deptno, AVG(salary) AS average_salary  
FROM Employee  
GROUP BY deptno HAVING AVG(salary) > (SELECT AVG(salary) FROM Employee)
```

# Subqueries within a FROM clause

- A subquery can be used in the `FROM` clause to **create a temporary derived table** that can be used in the outer query
- The subquery **must have an alias name** ( `FROM (subquery) AS alias_name` )
- The subquery's result set can be used in the `FROM` clause similarly to a normal table
- Let's consider the following example:

*"What is the minimum and the maximum grade point average (GPA) of such students who have passed more than 20 courses?"*

# Subqueries within a FROM clause

- First, we define a query for the grade point average of students who have passed more than 20 courses:

```
SELECT student_number, AVG(grade) AS gpa
FROM CourseGrade
WHERE grade > 0
GROUP BY student_number
HAVING COUNT(*) > 20
```

# Subqueries within a FROM clause

- Then, we use this query as a subquery in the FROM clause:

```
-- what is the minimum and the maximum grade point average (GPA)
-- of such students who have passed more than 20 courses?
SELECT MIN(gpa) AS min_gpa, MAX(gpa) AS max_gpa
FROM (
  -- our subquery from the previous slide
  SELECT student_number, AVG(grade) AS gpa
  FROM CourseGrade
  WHERE grade > 0
  GROUP BY student_number
  HAVING COUNT(*) > 20
) AS StudentGpa -- ⚠ alias name for the subquery is required
```

# Subqueries within a WITH clause

- A subquery can be used in the `WITH` clause to **create a temporary named result table**, known as common table expression (CTE)
- CTEs can be queried just like "regular" tables, but they **only exist while the query is executed**
- CTEs are useful for improving the readability of the query and can be used multiple times in the query

```
-- common table expression containing the number of grades from each course
WITH CourseGradeCount (course_code, grade_count) AS (
    SELECT course_code, COUNT(*) AS grade_count
    FROM CourseGrade
    GROUP BY course_code
)

SELECT MAX(grade_count) AS most_grades FROM CourseGradeCount
```

# WITH clause example

- Let's consider the previous `StudentGpa` example using a common table expression:

```
-- common table expression containing
-- the GPA of each student who has passed more than 20 courses
WITH StudentGpa (student_number, gpa) AS (
    SELECT student_number, AVG(grade) AS gpa
    FROM CourseGrade
    WHERE grade > 0
    GROUP BY student_number
    HAVING COUNT(*) > 20
)

-- which students have passed more than 20 courses with above 4.5 GPA?
SELECT student_number, first_name, surname
FROM Student
-- here we use StudentGpa just like a "regular" table
WHERE student_number IN (SELECT student_number FROM StudentGpa WHERE gpa > 4.5)
```

# Summary

- The `GROUP BY` clause is used to group the rows based on a specific column or columns
- The `HAVING` clause is used to filter the groups based on the aggregate function result
- Subqueries are queries within another query
- Subqueries can be used in a `SELECT` statement in the `WHERE` clause, `SELECT` list, `HAVING` clause, `FROM` clause, and `WITH` clause
- The `WITH` clause is used to create a temporary named result table, known as common table expression (CTE)